

STATE OF SOUTH DAKOTA  
DEPARTMENT OF TRANSPORTATION

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	NH 0037(164)24	1	63


Plotting Date: 01/08/2024

PLANS FOR PROPOSED  
**PROJECT NH 0037(164)24**  
**SD HIGHWAY 37**  
**BON HOMME COUNTY**

COLD MILLING ASPHALT CONCRETE,  
ASPHALT CONCRETE RESURFACING,  
BLEND, HAUL & STOCKPILE GRANULAR MATERIAL,  
CULVERT WORK, PAVEMENT MARKING & GUARDRAIL  
PCN 06PN

INDEX OF SHEETS

Sheet 1	Layout Map & Index of Sheets
Sheet 2	Estimate of Quantities
Sheets 3-5	Environmental Commitments
Sheet 6	Typical Section
Sheet 7	Rates of Materials
Sheet 8	Table of Additional Quantities
Sheet 9	Summary of Asphalt Concrete
Sheet 10	Table for Guardrail
Sheets 11-14	Table for Mainline Culvert Work
Sheets 15-25	Plan Notes & SWPPP
Sheets 26-30	Pavement Marking & Traffic Control
Sheet 31	Layout of Embankment and Surfacing for Culvert Replacement
Sheet 32	Layout for Pipe Insert in Existing RC Cattle Pass
Sheets 33-35	Details for Cold Milling Tapers
Sheet 36	Layout for Installation of Guardrail
Sheets 37-61	Standard Plates
Sheets 62-63	Cross Sections



PROJECT

**BEGIN PROJECT**  
STA. 0+00 - 60'  
MRM 36.00 +0.397  
MILEAGE 32.509  
(60' N of  $\odot$  Jct 291 St)


**DESIGN DESIGNATION**

ADT(2022)	1,308
ADT(2042)	1,922
DHV	222
D	51%
T DHV	14.2%
T ADT	31.2%
V	65 MPH


**STORM WATER PERMIT**  
Receiving Waters:  
Tributaries to Emanuel Creek  
Area Disturbed: 2.5 Acres  
Total Project Area: 290 Acres  
Latitude: 43.1687 (Google Maps)  
Longitude: -97.9714 (Google Maps)

**PROJECT LENGTH**

Gross Length:	63,082.0'	11.947 Miles
Bridge Length:	223.5'	0.042 Mile
Net Length:	62,858.5'	11.905 Miles



IDENTICAL POINTS



**END PROJECT**  
STA. 630+22  
110' S of MRM 24.48  
MILEAGE 20.571  
(Edgeline of SD50W)

**STRUCTURE 05-100-104**  
543+97.25 to 545+02.75  
Continuous Concrete Bridge  
105'-6"=0.020 Mile  
MRM 26.08

**STRUCTURE 05-100-118**  
616+81.5 to 617+99.5  
Continuous Concrete Bridge  
118'-0"=0.022 Mile  
MRM 24.70

9

March 20, 2024

PLOT SCALE - 1"=7000'

PLOTTED FROM - TRM111118

FILE - ... \PRJ2024\BONH06PN\TTL06PN.DGN

# ESTIMATE OF QUANTITIES

STATE OF SOUTH DAKOTA	PROJECT <b>NH 0037(164)24</b>	SHEET <b>2</b>	TOTAL SHEETS <b>63</b>
-----------------------------	----------------------------------	-------------------	------------------------------

Rev. 01/12/24 GAW

BID ITEM NUMBER	ITEM	QUANTITY	UNIT
009E0010	Mobilization	Lump Sum	LS
110E0135	Remove Delineator	47	Each
110E0500	Remove Pipe Culvert	68	Ft
110E0510	Remove Pipe End Section	2	Each
110E0595	Remove Cattle Pass End Section	2	Each
110E0600	Remove Fence	174	Ft
110E0730	Remove Beam Guardrail	350.0	Ft
110E0800	Remove W Beam Guardrail End Terminal	8	Each
110E1010	Remove Asphalt Concrete Pavement	1,827.0	SqYd
110E7500	Remove Pipe for Reset	90	Ft
110E7510	Remove Pipe End Section for Reset	16	Each
120E0010	Unclassified Excavation	1,229	CuYd
120E0100	Unclassified Excavation, Digouts	595	CuYd
120E0600	Contractor Furnished Borrow Excavation	1,332	CuYd
260E1010	Base Course	2,624.0	Ton
* 260E6000	Granular Material, Furnish	7,682.0	Ton
* 270E0200	Blend, Haul, and Stockpile Granular Material	15,364.0	Ton
320E0005	PG 58-34 Asphalt Binder	1,443.1	Ton
320E1200	Asphalt Concrete Composite	346.0	Ton
320E1203	Class Q3R Hot Mixed Asphalt Concrete	28,163.0	Ton
320E1800	Asphalt Concrete Blade Laid	1,786.0	Ton
320E4000	Hydrated Lime	296.6	Ton
320E7008	Grind 8" Rumble Strip or Stripe in Asphalt Concrete	23.9	Mile
320E7040	Grind 6" Transverse Rumble Strip in Asphalt Concrete	408.0	Ft
330E0100	SS-1h or CSS-1h Asphalt for Tack	136.1	Ton
330E0210	SS-1h or CSS-1h Asphalt for Flush Seal	2.4	Ton
332E0010	Cold Milling Asphalt Concrete	247,461	SqYd
421E0100	Pipe Culvert Undercut	26	CuYd
450E0182	36" RCP Class 2, Furnish	74	Ft
450E0190	36" RCP, Install	74	Ft
450E2028	36" RCP Flared End, Furnish	2	Each
450E2029	36" RCP Flared End, Install	2	Each
450E3052	48" RCP Arch Class 2, Furnish	62	Ft
450E3060	48" RCP Arch, Install	62	Ft
450E4520	48" RCP Arch Flared End, Furnish	2	Each
450E4521	48" RCP Arch Flared End, Install	2	Each
450E8300	Culvert Joint Cleaning	308.0	Ft
450E8305	Repair Culvert Joint	308.0	Ft
450E8310	Chemical Grout Void Fill	22.0	Gal
* 450E8900	Cleanout Pipe Culvert	1	Each
450E9000	Reset Pipe	90	Ft
450E9001	Reset Pipe End Section	16	Each
464E0100	Controlled Density Fill	14.0	CuYd

BID ITEM NUMBER	ITEM	QUANTITY	UNIT
600E0300	Type III Field Laboratory	1	Each
620E0020	Type 2 Right-of-Way Fence	142	Ft
620E1020	2 Post Panel	4	Each
620E1030	3 Post Panel	2	Each
630E0500	Type 1 MGS	750.0	Ft
630E1501	Type 1 Retrofit Guardrail Transition	8	Each
630E2017	MGS MASH Flared End Terminal	8	Each
632E2220	Guardrail Delineator	36	Each
632E2510	Type 2 Object Marker Back to Back	74	Each
633E1200	High Build Waterborne Pavement Marking Paint, White	542	Gal
633E1205	High Build Waterborne Pavement Marking Paint, Yellow	204	Gal
634E0010	Flagging	670.0	Hour
634E0020	Pilot Car	310.0	Hour
634E0110	Traffic Control Signs	1,023.6	SqFt
634E0120	Traffic Control, Miscellaneous	Lump Sum	LS
634E0275	Type 3 Barricade	2	Each
634E0630	Temporary Pavement Marking	35.7	Mile
720E1015	Bank and Channel Protection Gabion	74.0	CuYd
730E0204	Type C Permanent Seed Mixture	45	Lb
732E0100	Mulching	5.0	Ton
734E0102	Type 2 Erosion Control Blanket	1,783	SqYd
734E0103	Type 3 Erosion Control Blanket	1,800	SqYd
734E0510	Shaping for Erosion Control Blanket	1,105	Ft
831E0110	Type B Drainage Fabric	206	SqYd
900E0010	Refurbish Single Mailbox	6	Each
900E1980	Storage Unit	1	Each

\* - Denotes Non-Participating

## SPECIFICATIONS

Standard Specifications for Roads and Bridges, 2015 Edition and Required Provisions, Supplemental Specifications and Special Provisions as included in the Proposal.

# ENVIRONMENTAL COMMITMENTS

## ENVIRONMENTAL COMMITMENTS

The SDDOT is committed to protecting the environment and uses Environmental Commitments as a communication tool for the Engineer and Contractor to ensure that attention is given to avoid, minimize, and/or mitigate an environmental impact. Environmental commitments to various agencies and the public have been made to secure approval of this project. An agency with permitting authority can delay a project if identified environmental impacts have not been adequately addressed. Unless otherwise designated, the Contractor's primary contact regarding matters associated with these commitments will be the Project Engineer. During construction, the Project Engineer will verify that the Contractor has met Environmental Commitment requirements. These environmental commitments are not subject to change without prior written approval from the SDDOT Environmental Office.

Additional guidance on SDDOT's Environmental Commitments can be accessed through the Environmental Procedures Manual found at: <https://dot.sd.gov/media/documents/EnvironmentalProceduresManual.pdf> >

For questions regarding change orders in the field that may have an effect on an Environmental Commitment, the Project Engineer will contact the Environmental Engineer at 605-773-3180 or 605-773-4336 to determine whether an environmental analysis and/or resource agency coordination is necessary.

Once construction is complete, the Project Engineer will review all environmental commitments for the project and document their completion.

## COMMITMENT A: AQUATIC RESOURCES

### COMMITMENT A: WETLANDS

All efforts to avoid and minimize wetland impacts from the project have resulted in approximately 0.12 acres of wetlands (includes temporary and permanent) becoming impacted. Refer to plans for location and boundaries of the impacted wetlands.

#### Table of Impacted Wetlands

Wetland No.	Station	Perm. Impact Left (Acres)	Perm. Impact Right (Acres)	Temp. Impact Left (Acres)	Temp. Impact Right (Acres)	Total Impact (Acres)
1	0+60	0.00	0.00	0.001	0.001	0.002
2	18+66	0.008	0.003	0.00	0.00	0.011
3	39+63	0.005	0.00	0.00	0.00	0.005
4	65+74	0.002	0.00	0.00	0.00	0.002
5	73+84	0.015	0.00	0.00	0.00	0.015
6	87+79	0.00	0.00	0.002	0.002	0.004
7	104+53	0.00	0.00	0.001	0.00	0.001
8	122+59	0.00	0.00	0.001	0.00	0.001
9	133+00	0.00	0.00	0.042	0.00	0.042
10	149+51	0.00	0.00	0.001	0.00	0.001
11	190+95	0.00	0.00	0.001	0.00	0.001
12	208+63	0.00	0.00	0.001	0.00	0.001
13	238+27	0.00	0.00	0.001	0.001	0.002
14	289+29	0.00	0.00	0.00	0.001	0.001
15	294+85	0.00	0.00	0.003	0.003	0.006
16	302+00	0.00	0.00	0.001	0.001	0.002
17	313+00	0.00	0.00	0.001	0.00	0.001
18	338+50	0.00	0.00	0.002	0.00	0.002
19	350+25	0.003	0.00	0.00	0.00	0.003
20	368+29	0.00	0.00	0.00	0.001	0.001
21	370+19	0.00	0.00	0.001	0.001	0.002
22	468+06	0.00	0.00	0.001	0.00	0.001
23	495+00	0.00	0.00	0.00	0.001	0.001
24	529+12	0.00	0.003	0.00	0.00	0.003
25	557+23	0.00	0.00	0.002	0.00	0.002
26	581+62	0.00	0.00	0.001	0.00	0.001
27	587+04	0.00	0.00	0.00	0.001	0.001
28	594+39	0.00	0.00	0.00	0.001	0.001
29	623+10	0.00	0.00	0.001	0.001	0.002
30	628+38	0.00	0.00	0.00	0.001	0.001

## COMMITMENT A: WETLANDS (CONTINUED)

### Action Taken/Required:

Mitigation is required in accordance with the "Statewide Finding Regarding Wetlands for South Dakota Federal-Aid Highway Projects (February 2018)". Replacement of 0.04 acres of permanent wetland impacts will be completed through another wetland mitigation opportunity in a manner which considers FHWA's program-wide goal of 'net gain' of wetlands through enhancement, creation, and preservation.

Temporary impacts identified in the Table of Impacted Wetlands will not be mitigated as original contours and elevations will be re-established as designated in the plans. Prior to initiating temporary work in wetlands, the Contractor will submit a plan to the Project Engineer in accordance with Section 7.21 D of the Specifications.

The Contractor will notify the Project Engineer if additional easement is needed to complete work adjacent to any wetland. The Project Engineer will obtain an appropriate course of action from the Environmental Office before proceeding with construction activities that affect any wetlands beyond the work limits and easements shown in the plans.

## COMMITMENT B: FEDERALLY THREATENED, ENDANGERED, AND PROTECTED SPECIES

### COMMITMENT B2: WHOOPING CRANE

The Whooping Crane is a spring and fall migratory bird in South Dakota that is about 5 feet tall and typically stops on wetlands, rivers, and agricultural lands along their migration route. An adult Whooping Crane is white with a red crown and a long, dark, pointed bill. Immature Whooping Cranes are cinnamon brown. While in flight, their long necks are kept straight and their long dark legs trail behind. Adult Whooping Cranes' black wing tips are visible during flight.

### Action Taken/Required:

Harassment or other measures to cause the Whooping Crane to leave the site is a violation of the Endangered Species Act. If a Whooping Crane is sighted roosting in the vicinity of the project, borrow pits, or staging areas associated with the project, cease construction activities in the affected area until the Whooping Crane departs and immediately contact the Project Engineer. The Project Engineer will contact the Environmental Office so that the sighting can be reported to USFWS.

# ENVIRONMENTAL COMMITMENTS

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	NH 0037(164)24	4	63

## **COMMITMENT C: WATER SOURCE**

The Contractor will not withdraw water with equipment previously used outside the State of South Dakota or previously used in aquatic invasive species (AIS) positive waters within South Dakota without prior approval from the SDDOT Environmental Office. To prevent and control the introduction and spread of invasive species into the project vicinity, all equipment will be power washed with hot water ( $\geq 140$  °F) and completely dried for a minimum of 7 days prior to subsequent use. South Dakota administrative rule 41:10:04:02 forbids the possession and transport of AIS; therefore, all attached dirt, mud, debris and vegetation must be removed and all compartments and tanks capable of holding standing water must be drained. This includes, but is not limited to, all equipment, pumps, lines, hoses and holding tanks.

### **Action Taken/Required:**

The Contractor will obtain the necessary permits from the regulatory agencies such as the South Dakota Department of Agriculture and Natural Resources (DANR) and the United States Army Corps of Engineers (USACE) prior to water extraction activities.

Additional information and mapping of water sources impacted by Aquatic Invasive Species in South Dakota can be accessed at:

< <https://sdleastwanted.sd.gov/maps/default.aspx> >

< [South Dakota Administrative Rule 41:10:04 Aquatic Invasive Species: https://sdlegislature.gov/rules/DisplayRule.aspx?Rule=41:10:04](https://sdlegislature.gov/rules/DisplayRule.aspx?Rule=41:10:04) >

## **COMMITMENT D: WATER QUALITY STANDARDS**

### **COMMITMENT D1: SURFACE WATER QUALITY**

This project may be in the vicinity of multiple streams and wetlands. These waters are considered waters of the state and are protected under Administrative Rules of South Dakota (ARSD) Chapter 74:51. Special construction measures may have to be taken to ensure that this water body is not impacted.

### **Action Taken/Required:**

The Contractor is advised that the South Dakota Surface Water Quality Standards, administered by the South Dakota Department of Agriculture and Natural Resources (DANR), apply to this project. Special construction measures will be taken to ensure the above standard(s) of the surface waters are maintained and protected.

## **COMMITMENT E: STORM WATER**

Construction activities constitute 1 acre or more of earth disturbance and/or work in a waterway.

### **Action Taken/Required:**

The DANR General Permit for Stormwater Discharges Associated with Construction Activities is required for construction activity disturbing one or more acres of earth and work in a waterway. The SDDOT is the owner of this permit and will submit the NOI to DANR 15 days prior to project start in order to obtain coverage under the General Permit. Work can begin once the DANR letter of approval is received.

The Contractor must adhere to the "Special Provision Regarding Storm Water Discharges to Waters of the State."

The Contractor will complete the DANR Contractor Certification Form prior to the pre-construction meeting. The form certifies under penalty of law that the Contractor understands and will comply with the terms and conditions of the permit for this project. Work may not begin on this project until this form is signed and submitted to DANR.

The form can be found at:

<[https://danr.sd.gov/OfficeOfWater/SurfaceWaterQuality/docs/DANR\\_CGPAppe ndixCCA2018Fillable.pdf](https://danr.sd.gov/OfficeOfWater/SurfaceWaterQuality/docs/DANR_CGPAppe ndixCCA2018Fillable.pdf)>

The Contractor is advised that permit coverage may also be required for off-site activities, such as borrow and staging areas, which are the responsibility of the Contractor.

### **Storm Water Pollution Prevention Plan**

The Storm Water Pollution Prevention Plan (SWPPP) will be developed prior to the submittal of the NOI and will be implemented for all construction activities for compliance with the permit. The SWPPP must be kept on-site and updated as site conditions change. Erosion control measures and best management practices will be implemented in accordance with the SWPPP.

The DOT 298 Form will be used for site inspections and to document changes to the SWPPP. A copy of the completed inspection form will be filed with the SWPPP documents and retained for a minimum of three years.

The inspection will include disturbed areas of the construction site that have not been finally stabilized, areas used for storage materials, structural control measures, and locations where vehicles enter or exit the site. These areas will be inspected for evidence of, or the potential for, pollutants entering the drainage system. Erosion and sediment control measures identified in the SWPPP will be observed to ensure that they are operating correctly, and sediment is not tracked off the site.

Information on storm water permits and SWPPPs are available on the following websites:

SDDOT: < <https://dot.sd.gov/doing-business/environmental/stormwater> >

DANR: <<https://danr.sd.gov/OfficeOfWater/SurfaceWaterQuality/stormwater/default.aspx>>

EPA: < <https://www.epa.gov/npdes> >

## **COMMITMENT H: WASTE DISPOSAL SITE**

The Contractor will furnish a site(s) for the disposal of construction and/or demolition debris generated by this project.

### **Action Taken/Required:**

Construction and/or demolition debris may not be disposed of within the Public ROW.

The waste disposal site(s) will be managed and reclaimed in accordance with the following from the General Permit for Construction/Demolition Debris Disposal Under the South Dakota Waste Management Program issued by the Department of Agriculture and Natural Resources.

The waste disposal site(s) will not be located in a wetland, within 200 feet of surface water, or in an area that adversely affects wildlife, recreation, aesthetic value of an area, or any threatened or endangered species, as approved by the Environmental Office and the Project Engineer.

If the waste disposal site(s) is located such that it is within view of any ROW, the following additional requirements will apply:

1. Construction and/or demolition debris consisting of concrete, asphalt concrete, or other similar materials will be buried in a trench separate from wood debris. The final cover over the construction and/or demolition debris will consist of a minimum of 1 foot of soil capable of supporting vegetation. Waste disposal sites provided outside of the Public ROW will be seeded in accordance with Natural Resources Conservation Service recommendations. The seeding recommendations may be obtained through the appropriate County NRCS Office. The Contractor will control the access to waste disposal sites not within the Public ROW with fences, gates, and placement of a sign or signs at the entrance to the site stating, "No Dumping Allowed".
2. Concrete and asphalt concrete debris may be stockpiled within view of the ROW for a period not to exceed the duration of the project. Prior to project completion, the waste will be removed from view of the ROW or buried, and the waste disposal site reclaimed as noted above.

The above requirements will not apply to waste disposal sites that are covered by an individual solid waste permit as specified in SDCL 34A-6-58, SDCL 34A-6-1.13, and ARSD 74:27:10:06.

Failure to comply with the requirements stated above may result in civil penalties in accordance with South Dakota Solid Waste Law, SDCL 34A-6-1.31.

All costs associated with furnishing waste disposal site(s), disposing of waste, maintaining control of access (fence, gates, and signs), and reclamation of the waste disposal site(s) will be incidental to the various contract items.

# ENVIRONMENTAL COMMITMENTS

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	NH 0037(164)24	5	63

## **COMMITMENT I: HISTORIC PRESERVATION OFFICE CLEARANCES**

The SDDOT has obtained concurrence with the State Historic Preservation Office (SHPO or THPO) for all work included within the project limits and all department designated sources and designated option material sources, stockpile sites, storage areas, and waste sites provided within the plans.

### **Action Taken/Required:**

All earth disturbing activities not designated within the plans require a cultural resource review prior to scheduling the pre-construction meeting. This work includes but is not limited to: Contractor furnished material sources, material processing sites, stockpile sites, storage areas, plant sites, and waste areas.

The Contractor will arrange and pay for a record search and when necessary, a cultural resource survey. The Contractor has the option to contact the state Archaeological Research Center (ARC) at 605-394-1936 or another qualified archaeologist, to obtain either a records search or a cultural resources survey. A record search might be sufficient for review if the site was previously surveyed; however, a cultural resources survey may need to be conducted by a qualified archaeologist.

The Contractor will provide ARC with the following: a topographical map or aerial view in which the site is clearly outlined, site dimensions, project number, and PCN. If applicable, provide evidence that the site has been previously disturbed by farming, mining, or construction activities with a landowner statement that artifacts have not been found on the site.

The Contractor will submit the cultural resources survey report to SDDOT Environmental Office, 700 East Broadway Avenue, Pierre, SD 57501-2586. SDDOT will submit the information to the appropriate SHPO/THPO. Allow **30 Days** from the date this information is submitted to the Environmental Engineer for SHPO/THPO review.

In the event of an inadvertent discovery of human remains, funerary objects, or if evidence of cultural resources is identified during project construction activities, then such activities within 100 feet of the inadvertent discovery will immediately cease and the Project Engineer will be immediately notified. The Project Engineer will contact the SDDOT Environmental Office, who will contact the appropriate SHPO/THPO within 48 hours of the discovery to determine an appropriate course of action.

SHPO/THPO review does not relieve the Contractor of the responsibility for obtaining any additional permits and clearances for Contractor furnished material sources, material processing sites, stockpile sites, storage areas, plant sites, and waste areas that affect wetlands, threatened and endangered species, or waterways. The Contractor will not utilize a site known or suspected of having contaminated soil or water. The Contractor will provide the required permits and clearances to the Project Engineer at the preconstruction meeting.

## **COMMITMENT N: SECTION 404 PERMIT**

The SDDOT has obtained a Section 404 Permit from the USACE for the permanent actions associated with this project.


### **Action Taken/Required:**

The Contractor will comply with all requirements contained in the Section 404 Permit.

The Contractor will also be responsible for obtaining a Section 404 Permit for any dredge, excavation, or fill activities associated with material sources, storage areas, waste sites, and Contractor work sites outside the plan work limits that affect wetlands, floodplains, or waters of the United States.

# TYPICAL COLD MILLING SECTION


0+00 - 60' to 630+22



\*Transition:  
 310+05 to 313+35 (12' to 18')  
 313+35 to 315+55 (18')  
 315+55 to 318+85 (18' to 12')

# TYPICAL RESURFACING SECTION

0+00 - 60' to 630+22



\*Transition:  
 310+05 to 313+35 (12' to 18')  
 313+35 to 315+55 (18')  
 315+55 to 318+85 (18' to 12')

# RATES OF MATERIALS

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	NH 0037(164)24	7	63

-0+60.00 to 630+22.00 (less 223.5' for two bridges)

The Estimate of quantities is based on the following quantities of materials per mile.

## 2" CLASS Q3R HOT MIXED ASPHALT CONCRETE

Salvaged Asphalt Concrete	416 Tons
Crushed Aggregate	1663 Tons
PG 58-34 Asphalt Binder	103 Tons
	<hr/>
	<b>TOTAL: 2182 Tons</b>
Hydrated Lime	22 Tons
	<hr/>
	<b>TOTAL: 2204 Tons</b>

The exact proportions of these materials will be determined on construction.

SS-1h or CSS-1h Asphalt for Tack at the rate of 5.4 tons applied 36 feet wide (Rate = 0.06 gallon per square yard).

## FLUSH SEAL

SS-1h or CSS-1h Asphalt for Flush Seal at the rate of 0.2 ton applied 2.4 feet wide (1.2 feet wide each shoulder) (Rate = 0.05 gallon per square yard).

## TABLE OF ADDITIONAL QUANTITIES

LOCATION	REMOVE ASPHALT CONCRETE PAVEMENT	CONTRACTOR FURNISHED BORROW EXCAVATION	BASE COURSE	COLD MILLING ASPHALT CONCRETE	ASPHALT CONCRETE COMPOSITE 1ST LIFT	ASPHALT CONCRETE COMPOSITE 2ND LIFT	CLASS Q3R HOT MIXED ASPHALT CONCRETE	PG 58-34 ASPHALT BINDER	HYDRATED LIME	SALV. MAT'L.  N.A.B.I.	SS-1h/ CSS-1h ASPH. FOR FLUSH SEAL
	SqYd	CuYd	Ton	SqYd	Ton	Ton	Ton	Ton	Ton	Ton	Ton
N.A.B.I. = Not A Bid Item											
Mainline Transitions											
310+05 to 313+35	-	-	-	220	-	-	25	1.2	0.2	5	-
313+35 to 315+55	-	-	-	293	-	-	33	1.5	0.3	6	-
315+55 to 318+85	-	-	-	220	-	-	25	1.2	0.2	5	-
Other Locations											
Mainline Cross Pipe Replacement	168	-	236	-	24	24	-	-	-	-	-
Rumble Strips at SD37/SD50 Intersection	-	-	-	-	-	-	-	-	-	-	0.02
Radii at intersection of SD37 & SD50	-	-	-	304	-	-	34	1.6	0.3	6	-
Guardrail Locations											
See Guardrail Table	766	835	67	-	-	-	104	4.8	1.0	20	-
Turnouts											
5 Mailbox Turnouts	-	-	-	178	-	-	20	0.9	0.2	4	-
Resurface to ROW											
3 Intersecting Roads	-	-	-	504	-	-	174	8.1	1.7	33	-
Resurface to End of Radius											
20 Intersecting Roads	-	-	300	1292	-	-	318	14.8	3.1	60	-
Pads											
8 Double Approaches	-	-	160	-	-	-	-	-	-	-	-
11 Farm Entrances	-	-	110	-	-	-	-	-	-	-	-
56 Field Entrances	-	-	560	-	-	-	-	-	-	-	-
<b>TOTALS:</b>	<b>934</b>	<b>835</b>	<b>1433</b>	<b>3011</b>	<b>24</b>	<b>24</b>	<b>733</b>	<b>34.1</b>	<b>7.0</b>	<b>139</b>	<b>0.02</b>

NOTES: 2.0 tons of SS-1h or CSS-1h Asphalt for Tack are included in the Estimate of Quantities and will be applied at the rate shown on the plans as directed by the Engineer.

The tonnage shown above for Base Course is based on a compacted depth of 4 inches for Guardrail Locations and 2 inches for other locations.

The tonnage shown above for Asphalt Concrete Composite - 1st Lift is based on a compacted depth of 2.5 inches.  
The tonnage shown above for Asphalt Concrete Composite - 2nd Lift is based on a compacted depth of 2.5 inches.  
The tonnage shown above for Class Q3R Hot Mixed Asphalt Concrete is based on a compacted depth of 2 inches.

The above quantities are included in the Estimate of Quantities.



## SUMMARY OF ASPHALT CONCRETE

	ASPHALT CONCRETE COMPOSITE 1ST LIFT COMPACTION WITHOUT SPECIFIED DENSITY TONS	ASPHALT CONCRETE COMPOSITE 2ND LIFT COMPACTION WITHOUT SPECIFIED DENSITY TONS	ASPHALT CONCRETE BLADE LAID COMPACTION WITHOUT SPECIFIED DENSITY TONS	CLASS Q3R HOT MIXED ASPHALT CONCRETE COMPACTION WITH SPECIFIED DENSITY TONS	CLASS Q3R HOT MIXED ASPHALT CONCRETE COMPACTION WITHOUT SPECIFIED DENSITY TONS
Finished Roadway Surface	-	-	-	18798	-
Shoulders	-	-	-	-	7441
Backfilling Dugouts	-	298	-	-	-
<b>Additional Quantities for spot leveling and tight blading totals</b>	-	-	1786	-	1191

<b>Table of Additional Quantities</b>					
Mainline Transitions	-	-	-	83	-
Other Locations	24	24	-	-	-
Miscellaneous Nondensity Locations	-	-	-	-	138
Turnouts, Int Roads, Ents & Pads	-	-	-	-	512
<b>Additional Totals:</b>	<b>24</b>	<b>24</b>	<b>-</b>	<b>83</b>	<b>650</b>
<b>Totals:</b>	<b>24</b>	<b>322</b>	<b>1786</b>	<b>18881</b>	<b>9282</b>

18881 TONS ASPHALT CONCRETE COMPACTION WITH SPECIFIED DENSITY
11414 TONS ASPHALT CONCRETE COMPACTION WITHOUT SPECIFIED DENSITY
30295 TONS TOTAL

### TABLE FOR REMOVAL AND INSTALLATION OF GUARDRAIL AND RELATED ITEMS

LOCATION	REMOVE BEAM GUARDRAIL	REMOVE W BEAM GUARDRAIL END TERMINAL	REMOVE ASPHALT CONCRETE PAVEMENT	CONTRACTOR BASE FURNISHED BORROW EXCAVATION	BASE COURSE	CLASS Q3R HOT MIXED ASPHALT CONCRETE	TYPE 1 MGS	TYPE 1 RETROFIT GUARDRAIL TRANSITION	MGS MASH FLARED END TERMINAL
BRIDGE CORNER	Ft	Each	SqYd	CuYd	Ton	Ton	Ft	Each	Each
<b>STRUCTURE 05-100-104</b> <b>MRM 26.08</b>									
Begin Bridge L	43.75	1	83	105	7	11	25	1	1
Begin Bridge R	43.75	1	115	45	12	15	162.5	1	1
End Bridge L	43.75	1	115	75	9	15	162.5	1	1
End Bridge R	43.75	1	72	15	6	11	25	1	1
<b>STRUCTURE 05-100-118</b> <b>MRM 24.70</b>									
Begin Bridge L	43.75	1	75	325	10	11	25	1	1
Begin Bridge R	43.75	1	120	190	8	15	162.5	1	1
End Bridge L	43.75	1	117	45	7	15	162.5	1	1
End Bridge R	43.75	1	69	35	8	11	25	1	1
<b>TOTALS:</b>	<b>350</b>	<b>8</b>	<b>766</b>	<b>835</b>	<b>67</b>	<b>104</b>	<b>750</b>	<b>8</b>	<b>8</b>

\* Quantities for these guardrail work items are also included in the Table of Additional Quantities.

### TABLE OF GUARDRAIL DELINEATORS & OBJECT MARKERS

LOCATION	TYPE 2 OBJECT MARKER BACK TO BACK	TYPE 2 OBJECT MARKER	GUARDRAIL TERMINAL END OBJECT MARKER (ADHESIVE)	GUARDRAIL DELINEATOR			
			N.A.B.I.	BEAM		CABLE	
	(M) #	(M) #	(E) #	(B) #	(C) #		
BRIDGE CORNER				Yellow	White	Yellow	White
<b>STRUCTURE 05-100-104</b> <b>MRM 26.08</b>							
Begin Bridge L			1		4		
Begin Bridge R			1		5		
End Bridge L			1		5		
End Bridge R			1		4		
<b>STRUCTURE 05-100-118</b> <b>MRM 24.70</b>							
Begin Bridge L			1		4		
Begin Bridge R			1		5		
End Bridge L			1		5		
End Bridge R			1		4		
<b>TOTALS</b>	-	-	<b>8</b>	-	<b>36</b>	-	-

# - For KEY, Refer to Standard Plate 632.40 - Sheet 1 of 4.

N.A.B.I. = Not A Bid Item - Cost is incidental to the contract unit prices for the various items.

36









### UTILITIES

The Contractor will contact the involved utility companies through South Dakota One Call (1-800-781-7474) prior to starting work. It will be the responsibility of the Contractor to coordinate work with the utility owners to avoid damage to existing facilities.

If utilities are identified near the improvement area through the SD One Call Process as required by South Dakota Codified Law 49-7A and Administrative Rule Article 20:25, the Contractor will contact the Engineer to determine modifications that will be necessary to avoid utility impacts.

### SURFACING/SUBGRADE INVESTIGATION

A copy of the surfacing/subgrade investigation for this project is available from the Yankton Area and the Mitchell Region Offices.

### SURFACING THICKNESS DIMENSIONS

The plans shown spread rates will be applied even though the thickness may vary from that shown on the plans.

At those locations where material must be placed to achieve a required elevation, the depth/quantity may be varied to achieve the required elevation.

### COORDINATION BETWEEN CONTRACTORS

A separate contract for Project PH 0037(173)30 - PCN 09C9 will be awarded to another Contractor for changing the intersection of SD37 & SD46 to an all way stop. The project will also include adding transverse rumble strips to SD37.

The Contractor will schedule work so as not to interfere with or hinder the progress of the work performed by other Contractors on the intersection control, lighting and signing improvement project.

### TYPE III FIELD LABORATORY

The lab will be equipped with an internet connection such as DSL, cable modem, or other approved service. The internet connection will be provided with a multi-port wireless router. The internet connection will be a minimum speed of 5 Mbps unless limited by job location and approved by the DOT. Prior to installing the wireless router, the Contractor will submit the wireless router's technical data to the Area Office to check for compatibility with the State's computer equipment. The internet connection is intended for State personnel usage only. The Contractor's personnel are prohibited from using the internet connection unless pre-approved by the Project Engineer.

Reimbursement will not be made for fees associated with the purchase, installation, maintenance, monthly line charges, and incidentals involved with the internet connection (including attachments). These items will be incidental to the contract unit price per each for Type III Field Laboratory.

### STORAGE UNIT

The Contractor will provide a storage unit such as a portable storage container or a semi-trailer meeting the minimum size requirements from the table below:

Project Total Asphalt Concrete Tonnage	Minimum Internal Size (Cu Ft)	Minimum External Size (L x W x H)
Less than 50,000 ton	1,166	20' x 8' x 8.6' std
More than 50,000 ton	2,360	40' x 8' x 8.6' std
All Gyratory Controlled QC/QA Projects	2,360	40' x 8' x 8.6' std

The storage unit is intended for use only by the Engineer for the duration of the project. The QC lab personnel or the Contractor will not be allowed to use the storage container while it is on the project, without permission of the Engineer.

The storage unit will be on site and operational prior to asphalt concrete production. Upon completion of asphalt concrete production, the Engineer will notify the Contractor when the storage unit can be removed from the project. The storage unit use will not exceed 30 calendar days from the completion of asphalt concrete production. The storage unit will remain the property of the Contractor.

The storage unit will be weather proof and will be set in a level position. The storage unit will be able to be locked with a padlock.

The storage unit will be placed adjacent to the QA lab, as approved by the Engineer.

The following will apply when the storage unit provided on the project is a portable storage container:

1. The portable storage container will be constructed of steel.
2. The portable storage container will be set such that it is raised above the surrounding ground level to keep water from ponding under or around the storage container.

The following will apply when the storage unit provided on the project is a semi-trailer:

1. A set of steps and hand railings will be provided at the exterior door.
2. If the floor of the semi-trailer is 18 inches or more above the ground, a landing will be constructed at the exterior door. The minimum dimensions for the landing will be 4 feet by 5 feet. The top of the landing will be level with the threshold or opening of the doorway.
3. The semi-trailer may be connected to the QA lab by a stable elevated walkway. The walkway will be a minimum of 48 inches wide and contain handrails installed at 32 inches above the deck of the walkway. The walkway will be constructed such that it is stable and the deck does not deform during use and allows for proper door operation. Walkway construction will be approved by the Engineer.

All cost for furnishing, maintaining, and removing the storage unit including labor, equipment, and materials including any necessary walkways, landings, stairways, and handrails will be included in the contract unit price per each for "Storage Unit".

### INTERSECTING ROADS AND ENTRANCES

Intersecting roads and entrances will be satisfactorily cleared of vegetation, shaped and compacted prior to placement of mainline surfacing. This work will be considered incidental to other contract items. Separate measurement and payment will not be made.

### SHOULDER WORK

Prior to construction, Department of Transportation maintenance forces will spray the shoulders to kill existing vegetation. It is the Contractor's responsibility to notify the State a minimum of 30 days prior to starting work on the surface of the highway. The State assumes no responsibility for the effectiveness of the herbicide applied.

Vegetation and accumulated material on or adjacent to the existing roadway edge will be removed by the Contractor, to the satisfaction of the Engineer, prior to asphalt concrete resurfacing. Any remaining windrow of accumulated material will be spread evenly on the inslope adjacent to the asphalt shoulder, to the satisfaction of the Engineer, following application of the flush seal.

Cost for shoulder work including removal and replacement of topsoil will be incidental to the contract unit prices for the various items. Separate measurement and payment will not be made.

### CONTRACTOR FURNISHED BORROW EXCAVATION

The Contractor will provide a suitable site for Contractor furnished borrow excavation material. The Contractor is responsible for obtaining required permits and clearances for the borrow site. The borrow material will be approved by the Engineer. The plans quantity for Contractor Furnished Borrow Excavation as shown in the Estimate of Quantities will be the basis of payment for this item.

Prior to placement or removal of fill material, the Contractor will be required to remove four inches of topsoil and replace it following the placement of the new fill material. Removing and replacing topsoil will not be measured for payment but will be incidental to the contract unit price per cubic yard for Contractor Furnished Borrow Excavation.

The Contractor will be allowed to place topsoil in lieu of fill material if the fill depth is one foot or less. By doing this the Contractor will not be required to remove and replace the four inches of in place topsoil.

It is not anticipated that water for compaction will be required; however, if in the opinion of the Engineer the fill material is extremely dry, water may be ordered and placed to the satisfaction of the Engineer. Cost for water will be incidental to the contract unit price per cubic yard for Contractor Furnished Borrow Excavation.

Restoration of the Contractor furnished borrow excavation site will be the responsibility of the Contractor.

### UNCLASSIFIED EXCAVATION

The plan shown quantity will be the basis of payment. No measurement will be made.

### WATER FOR EMBANKMENT

Water for compaction of earth embankment will be applied at the rate of 10 gallons per cubic yard of Unclassified Excavation. Cost for water will be incidental to the contract unit price per cubic yard for Unclassified Excavation.

### REMOVE ASPHALT CONCRETE PAVEMENT

Where existing asphalt concrete is to be removed at guardrail installations, the Contractor will remove enough material so that a 2" lift of new guardrail surfacing can be placed. This material will become the property of the Contractor for disposal.

**UNCLASSIFIED EXCAVATION, DIGOUTS**

The locations and extent of digout areas will be determined in the field by the Engineer. The backfilling material for the digouts will be Asphalt Concrete Composite and Base Course. The depth of asphalt will match the in-place thickness.

Included in the Estimate of Quantities are 50 cubic yards of Unclassified Excavation, Digouts and 75 square yards of Remove Asphalt Concrete Pavement per mile for the removal of asphalt and unstable material throughout the project.

Included in the Estimate of Quantities are 100 tons of Base Course and 25 tons of Asphalt Concrete Composite per mile for backfill of Unclassified Excavation, Digouts.

The digouts will be extended to the shoulder and backfilled with granular material that will daylight to the inslope to allow water to escape the subsurface.

**WATER FOR COMPACTION**

Cost for water for compaction of the Base Course will be incidental to the contract unit prices for the various contract items. The moisture required at the time of compaction will be 6%± unless otherwise directed by the Engineer.

**COLD MILLING ASPHALT CONCRETE**

Cold milling will be done according to the typical sections. At intersecting roads, entrances, turnouts, pads and in areas where maintenance patches have raised and/or widened the road, additional milling will be done to provide a uniform typical section. Milling will be daylighted to the outside edge of the roadway. Quantities for milling additional width are included in the Table of Additional Quantities.

The Los Angeles Abrasion Loss value on the aggregate used for the in place asphalt concrete was 27. This value was obtained from testing during construction of the in place asphalt concrete.

Cold milling is estimated to produce 12997 tons of cold milled asphalt concrete material. An estimated 5315 tons of cold milled asphalt concrete material will be used on this project as RAP in the Class Q3R Hot Mixed Asphalt Concrete mixture. The Contractor is responsible to assure that enough cold milled asphalt concrete material is available for use as RAP in the Class Q3R Hot Mixed Asphalt Concrete.

RAP not reused on the project (estimated at 7682 tons) will be blended, hauled and stockpiled.

Cold milling operations ahead of asphalt concrete laydown will be limited by particular job conditions and will be subject to approval of the Engineer. In no case will cold milling operations ahead of asphalt concrete laydown operations exceed seven calendar days.

If resurfacing as per the typical section cannot be placed immediately after cold milling at project ends, bridge approaches, etc., then temporary asphalt mix ramps will be placed as directed by the Engineer. Cost for placing and removing the temporary ramps will be incidental to the contract unit prices for the various items.

Intersecting roads and entrances will be milled back for approximately ten feet from the shoulder edge so that additional surfacing may be placed at these locations.

Asphalt concrete intersecting roads will be milled-in for approximately ten feet at the ROW line so that additional surfacing may be placed at these locations.

**COLD MILLING TAPERS**

In order to construct the new surfacing flush with the asphalt concrete, it will be necessary to taper the depth of milling according to the details for Cold Milling Tapers.

The surface will be milled full roadway width.

Cost for this work will be incidental to the contract unit price per square yard for Cold Milling Asphalt Concrete.

Taper depth of Cold Milling at locations shown below:

<u>STA</u>	<u>LOCATION</u>	<u>SIZE</u>
0+00 -60'	Begin Project	80' long X 35' wide
543+97.25	Begin Bridge	240' long X 35' wide
545+02.75	End Bridge	240' long X 35' wide
616+81.5	Begin Bridge	240' long X 35' wide
617+99.5	End Bridge	240' long X 35' wide
630+22	End Project	60' long X 35' wide

**GRANULAR MATERIAL, FURNISH**

Granular Material for blending stockpile material will be Base Course meeting the requirements of Section 882 of the specifications except that if ledge rock is used, the Plastic Index will be between 2 and 6.

**BLEND, HAUL AND STOCKPILE GRANULAR MATERIAL**

Cold milled asphalt concrete material not reused on the project will be hauled to the State stockpile site located in Tripp in the NE ¼ of the SW ¼ of Section 17, T 97 N, R 60 W. The Contractor will have approval from the Engineer of the stockpile location prior to stockpiling the material.

A computerized scale, portable platform scale, stationary commercial scale, stationary commercial plant, portable plant scale, or a belt scale along with a scale operator will be provided by the Contractor at the stockpile site to weigh the milled material prior to blending.

The milled asphalt concrete material will be crushed to meet the requirements of Section 884.2 D.2 prior to blending into the stockpile.

Cold milled asphalt concrete material will be blended with Granular Material, Furnish at a rate of 50% milled material and 50% Granular Material, Furnish to obtain stockpile material. Material will be uniformly blended to the satisfaction of the Engineer.

No further gradation testing of the blended material will be required.

Cost for hauling, weighing, stockpiling, and blending milled material with Granular Material, Furnish will be included in the contract unit price per ton for Blend, Haul and Stockpile Granular Material.

**ASPHALT CONCRETE COMPOSITE**

Section 324 will apply except that Class Q3R Hot Mixed Asphalt Concrete as specified elsewhere in the plans may be used as Asphalt Concrete Composite.

Plans specified locations for Asphalt Concrete Composite will be paid for at the contract unit price per ton for Asphalt Concrete Composite regardless of the class of asphalt concrete used at such locations.

Asphalt Concrete Composite will include MC-70 Asphalt for Prime placed at the rate of 0.30 gallons per square yard. The Asphalt for Prime will be applied to the Base Course for the full width of the bottom layer of Asphalt Concrete Composite plus one foot additional on the outside shoulder.

Asphalt for tack SS-1h or CSS-1h will be applied prior to each lift of Asphalt Concrete Composite. Asphalt for tack will be applied at a rate of 0.09 gallons per square yard on existing pavement or milled asphalt concrete surfaces and at a rate of 0.06 gallons per square yard on primed base course or new asphalt concrete pavement. The Asphalt for tack will be applied for the full width of the bottom layer of Asphalt Concrete Composite plus one-half foot additional on the outside shoulder.

**ASPHALT CONCRETE BLADE LAID**

Included in the Estimate of Quantities are 150 tons of Asphalt Concrete Blade Laid, 11.1 tons of PG 58-34 Asphalt Binder, 1.5 tons of Hydrated Lime and 5.6 tons of SS-1h or CSS-1h Emulsified Asphalt for Tack (Rate = 0.09 gallon per square yard) per mile and will be tight bladed on the existing surface 25' wide prior to the overlay.

A sufficient amount of material will be kept in front of the blade to fill and level all joints, cracks and other surface irregularities.

Mineral Aggregate for tight bladed material will use only the fine aggregate components combined in the same proportions as the Class Q3R Hot Mixed Asphalt Concrete mix. Quality testing is not required on the coarse aggregate (+No. 4 sieve) in this mixture.

The Asphalt Concrete Blade Laid Lift will be designed using an N<sub>design</sub> Gyrotory Compactive Effort of 65. The asphalt binder content will be determined so that the air voids of Asphalt Concrete Blade Laid Lift are between 3.0% and 5.0%.

**CLASS Q3R HOT MIXED ASPHALT CONCRETE**

Mineral Aggregate:

Asphalt concrete aggregate will consist of reclaimed asphalt pavement (RAP) and virgin aggregate.

Virgin mineral aggregate for Class Q3R Hot Mixed Asphalt Concrete will conform to the requirements of Class Q3.

The Class Q3R Hot Mixed Asphalt Concrete will include 20% percent RAP in the mixture. RAP will be obtained from the material produced by cold milling.

Mix Design Criteria:

Gyrotory Controlled QC/QA Mix Design requirements for the Class Q3R Hot Mixed Asphalt Concrete will conform to the requirements of Class Q3 except as modified by the following:

Gyrotory Compactive Effort:

	N <sub>initial</sub>	N <sub>design</sub>	N <sub>maximum</sub>
Class Q3R	6	50	75

All remaining requirements for Class Q3 will apply.



**ADDITIONAL QUANTITIES**

Included in the Estimate of Quantities are 100 tons of Class Q3R Hot Mixed Asphalt Concrete, 4.7 tons of PG 58-34 Asphalt Binder and 1.0 tons of Hydrated Lime per mile for spot leveling, strengthening and repair of the existing surface and/or shoulders throughout the project.

Included in the Estimate of Quantities are 3 tons of SS-1h or CSS-1h Asphalt for Tack for surface repair and leveling areas throughout the project. (Rate = 0.09 gallon per square yard).

**FLUSH SEAL**

Application of the flush seal will be applied to cover the Rumble Stripes on each shoulder.

**EDGELINE RUMBLE STRIPES**

**INSTALLATION:**

Edgeline rumble stripes will be constructed according to Standard Plate 320.20.

Rumble stripes will be completed prior to application of the flush seal and permanent pavement marking.

Rumble stripes will be installed in rural areas with posted speeds greater than 50 mph and are not required in urban areas. The rumble stripes will begin at the location of the Speed Limit 65 sign as traffic is departing the built up area of a community, unless otherwise specified in the plans. The Engineer will provide the exact start and stop locations.

**ROADWAY CLEANING:**

The Contractor will be required to remove loose material from the driving surface and/or asphalt shoulders of the roadway. Loose material may be broomed to the edge of shoulders. It will be the Contractor's responsibility to ensure the loose material does not enter any vegetated areas or waterways.

Cost for this work will be incidental to the contract unit price per mile for Grind 8" Rumble Strip or Stripe in Asphalt Concrete.

**RUMBLE STRIPS AT SD37 & SD50 INTERSECTION**

Rumble strips in the SBL will be grooved into the asphalt concrete surface prior to the flush seal application. The Contractor will remove excess aggregate from the rumble strips upon completion of the flush seal.

Refer to Standard Plate 320.45 for details.

Payment for rumble strips will be at the contract unit price per foot for Grind 6" Transverse Rumble Strip in Asphalt Concrete.

**INSTALLING 36" RCP IN EXISTING RC CATTLE PASS**

The Contractor will install 36" RCP through the existing 4' x 6' RC Cattle Pass at the location shown on the Layout for Pipe Insert in Existing RC Cattle Pass and in the Table for Mainline Culvert Work.

The 36" RCP, Controlled Density Fill and Contractor Furnished Borrow Excavation will be placed as shown in the Layout for Pipe Insert in Existing RC Cattle Pass.

Contractor Furnished Borrow Excavation will be placed and compacted to eliminate settlement and voids at the ends of the existing RC Cattle Pass End Section.

**MAINLINE CROSS PIPE REPLACEMENT**

All pipe culvert replacements will be installed one half at a time under traffic control conditions outlined in these plans and in accordance with the following notes and as shown on the Layout of Embankment and Surfacing for Culvert Replacement.

This work will be completed prior to beginning cold milling on the project.

After the existing pipe has been removed, the new pipe culvert will be undercut to a minimum depth of 1 foot. The depth of undercut is an estimate and the actual depth necessary will be determined during construction. The Engineer will determine how much undercut will be done in accordance with Section 421 of the specifications but will not reduce the undercut to less than 1 foot in depth.

Select fill material for backfilling the undercut area will conform to the gradation requirements of Base Course in Section 882. If groundwater is encountered during construction, the select fill material for backfilling the undercut area and Class B Bedding will conform to the gradation requirements of Section 421.2 A. until backfill placement is above the groundwater level. The Engineer will process a CCO to provide for compensation to the Contractor for the added cost of the changed material. All other requirements of Section 421 will apply.

Pipe culverts will be bedded in accordance with Section 450.3 F.2, Class B Bedding with the following exceptions. The excavated area will extend 2 feet from the outermost diameter on both sides of the pipe with the back of the excavated area being sloped 2:1 upward to the top of the roadway surface. Select fill material for Class B Bedding will conform to the gradation requirements of Base Course in Section 882.

After the minimum testing requirements of M.S.T.R Section 4.1.F.3.a.1 (SDDOT Materials Manual) have been met, the minimum density testing requirements will be one test per zone. Each zone from the top of the pipe to the top of the subgrade will be 2 feet in depth. Moisture testing will remain as per M.S.T.R.

The remainder of the pipe culvert excavation will be backfilled with soils taken from the pipe removal excavation or other suitable material as approved by the Engineer. The backfill will be benched into 2:1 excavation slope. Compaction of the backfill material will be governed by the Specified Density Method.

After the new pipe has been backfilled to the top of the subgrade, a 12" depth of Base Course and 5" (2-2.5" lifts) depth of asphalt concrete composite will be placed as a patch matching the existing asphalt concrete.

**MAINLINE CROSS PIPE REPLACEMENT (CONTINUED)**

All costs to remove and dispose of asphalt concrete pavement, including full depth saw cutting of the asphalt concrete pavement, will be incidental to the contract unit price per square yard to Remove Asphalt Concrete Pavement. All excavation necessary for Class B Bedding and the pipe installation will be incidental to the contract unit price per foot for the corresponding pipe installation contract items. The excavation of material for pipe culvert undercut will be paid for at the contract unit price per cubic yard for Pipe Culvert Undercut.

The select fill material used for backfilling the pipe culvert undercut and Class B Bedding will be paid for at the contract unit price per ton for Base Course. The 3" layer of bedding material to form the cradle in the pipe foundation will be incidental to the corresponding pipe installation contract items. The cost for asphalt concrete composite installed over the pipe replacement will be paid for at the contract unit price per ton for Asphalt Concrete Composite.

**TABLE FOR MAINLINE CROSS PIPE REPLACEMENT**

LOCATION	REMOVE ASPHALT CONCRETE (Sq.Yds)	SELECT FILL MATERIAL (Tons)	BASE COURSE (Tons)	1 <sup>ST</sup> LIFT ASPHALT CONCRETE COMPOSITE (Tons)	2 <sup>ND</sup> LIFT ASPHALT CONCRETE COMPOSITE (Tons)
18+66	168	103	133	24	24
<b>Totals:</b>	<b>168</b>	<b>103</b>	<b>133</b>	<b>24</b>	<b>24</b>

Quantities are included in the Table of Additional Quantities for Mainline Cross Pipe Replacement. The quantity for Select Fill Material will be added/included in the quantity for Base Course.

**PIPE EXTENSIONS**

For pipe extensions that are outside the new surfaced shoulder as shown in the typical sections, acceptance tests for pipe culvert backfill of pipe 48" or less in diameter may be performed by visual inspection to the satisfaction of the Engineer. All other MSTR pipe density testing requirements will apply.

**REINFORCED CONCRETE PIPE JOINT REPAIR AND VOID GROUTING**

The Contractor will provide a notarized statement, from the Manufacturer, that the products used for culvert joint repair meet the specified requirements, along with the Manufacturer's current product specification and installation instructions.

The Contractor will be an Approved Contractor of the Manufacturer of the specified product and will provide written certification from the Manufacturer attesting to their Approved Contractor status.

All product documentation and Contractor submittals must be submitted to the Engineer prior to or at the preconstruction conference. The Contractor must have the Engineer's approval prior to commencing any of this work.

The Contractor will follow the Manufacturer's installation instructions and specifications throughout the repair process.

Temperature of the specified products is critical from the point of pumping to the point of injection. All polyurethanes react faster at higher temperatures. Drum heaters and heated hoses are required when ambient or ground temperatures are below 70 degrees Fahrenheit. The optimum hose temperature will vary with the weather conditions and the particular job site conditions with the minimum hose temperature being 75 degrees Fahrenheit and the maximum hose temperature being 95 degrees Fahrenheit and the drum temperature not to exceed 90 degrees Fahrenheit.

The Contractor will provide worker and inspector safety protective gear in accordance with the manufacturer, including but not limited to chemical goggles, face shields, eye wash system and NBR gloves.

The Contractor will provide safe storage and handling of materials prior to delivery and at the project site. All material installation, handling and storage will be in accordance with the Manufacturer's recommendations.

The Contractor will visit the project to determine the extent of culvert joints to be cleaned and filled, prior to bidding.

Culvert Joint Cleaning and Repair Culvert Joint quantities will be based upon the following table showing circumference of joints based upon culvert size and shape.

Pipe Diameter	Round Pipe Circumference per Joint	Arch Pipe Circumference per Joint
(In)	(Ft)	(Ft)
36	9.4	
42	11.0	11.0
48	12.6	
54	14.1	
60	15.7	
66	17.3	
72	18.8	19.0
78	20.4	
84	22.0	

**CULVERT JOINT CLEANING**

This work will consist of cleaning of the culvert joints, washing the entire culvert and joints with a high-pressure washer, and if needed, wire brush cleaning of each joint to be repaired as directed by the Engineer. The entire culvert will be clean and dry and most notably the specified joints will be thoroughly cleaned to the satisfaction of the Engineer using a power washer with water pressure of at least 2500 psi. The culvert must be in a clean condition so that no deleterious material is trapped in the joints that are being repaired. The Contractor will dispose of all debris removed from the culverts during the cleaning operation as approved by the Engineer.

**REINFORCED CONCRETE PIPE JOINT REPAIR AND VOID GROUTING (CONTINUED)**

All costs for equipment, material and labor for the culvert joint cleaning work will be incidental to the contract unit price per foot for Culvert Joint Cleaning. Culvert Joint Cleaning will be measured to the nearest 0.1 foot of joint which is cleaned for joint repair.

**REPAIR CULVERT JOINT**

The culvert joints will be repaired in accordance with the Chemical Grout Manufacturer's directions to prevent future infiltration/exfiltration of soils and water and to keep the chemical grout from expanding back into the structure during injection.

The culvert joint will be repaired with a sealant comprised of water reactive hydrophilic polyurethane resin and dry oil free oakum. All grout will be injected under such pressure so as not to damage the existing drainage structure or roadway structure.

The Contractor will submit to the Engineer for approval a detailed procedure for the installation of the polyurethane grout.

The work will include, but is not limited to sealing each pipe joint with a hydrophilic polyurethane grout meeting the following specifications:

GEL FOAM II (Saturated Oakum Rope Joint Packing) as manufactured by Green Mountain International, LLC or equal.

ULTRA (Single Component Grout for Joint Injection) as manufactured by Green Mountain International, LLC or equal.

Excess grout and oakum will be trimmed from the interior face of the joint prior to applying the UV Protection (Gel Coat). The epoxy gel coat compound will be as recommended by the Manufacturer for both surface sealing and protecting the hydrophilic grout from UV exposure. The epoxy gel compound will be mixed and handled in accordance with the Manufacturer's recommendations and will meet the following requirements:

Epoxy gel sealant compounds manufactured by Green Mountain Grouts, LLC or equal.

All costs for all equipment, material and labor required to complete the work will be incidental to the contract unit price per foot for Repair Culvert Joint. Completion of the work includes initial saturated oakum rope packing of each joint, follow up injection of grout into the back side of each joint, trimming the excess grout and oakum from the interior face of the joint, application of the epoxy gel coat and site clean-up. Payment will be made per 0.1 foot of culvert joint repaired.

**DUAL COMPONENT CHEMICAL GROUT FOR VOID FILLING**

The external voids surrounding the culvert will be filled with an injected high expansion chemical grout compound. Holes will be strategically drilled as required and grout injected throughout the structure to effectively fill all voids that have developed outside of the structure due to the infiltration of external soils and materials into the culvert and "piping" (water running outside and under the structure due to separated joints). It is the Contractor's responsibility to locate reinforcing bars and conduit prior to drilling any grout holes. All grout will be injected under such pressure so as not to damage the existing drainage structure or roadway structure. All joints will be appropriately cleaned and sealed, with appropriate recommended cure time, prior to the injection of the void grouting. After completion of the void filling, all holes will be properly sealed.

**REINFORCED CONCRETE PIPE JOINT REPAIR AND VOID GROUTING (CONTINUED)**

The typical method consists of placing a layer of chemical grout behind or around the structure. The Contractor will submit for approval by the Engineer a detailed grouting plan showing the spacing, orientation and depth of the grout holes, as well as type of polyurethane grout to be used, range of gel times, equipment, mixing procedures, recommended injection pressure, technique for monitoring grout travel and any other pertinent information. The grouting plan should address the prevention of overfilling and prevention of damage to structures or roadway. The Contractor will submit this detailed procedure for the installation of the expansion grout to the Engineer for approval. The holes are drilled with a rotary percussion hammer drill using a sharp masonry bit with a minimum diameter of 3/8 inch to a maximum diameter of 5/8 inch. Care must be taken to prevent holes from causing damage to reinforcing bars or utility conduits. Drilled holes should be vacuumed and flushed. Use injection grout and methods as recommended by Manufacturer.

Injection can be monitored by either applicator's visual inspection or by pumping a specific amount of injection grout into each hole. The work will start at the inlet end of the pipe and proceed downstream to the outlet. Inject bottom row every other hole. When material appears at the adjacent port, discontinue injection at entry port and begin injection at the adjacent port. Continue injection process section by section from bottom of pipe to top of pipe in a continuous manner to next pipe section. Injection pressure will vary from 200 psi to 3000 psi depending on the width of the joint, thickness of the structure, and condition of the concrete.

The Contractor must supply the Engineer with three (3) prior job references of projects where they have successfully injected urethane resin for subgrade void filling applications, or soil stabilization.

In lieu of three (3) prior job references the Contractor will:

- a) Obtain hands on training from the supplier on the installation procedures, and
- b) Have the supplier on site to provide training to Contractor's staff. Supplier will be present for at least two complete pipe culvert repairs and until the Engineer is satisfied that Contractor's staff is competent in performing this work.

The chemical grout will be a dual component hydrophobic polyurethane grout compound which is non-flammable and non-toxic when cured.

The chemical grout mixture will have expansion properties listed in the data sheets of greater than eighteen (18) times its original volume and cure to rigid closed cell polyurethane foam. The grout will expand to fill any voids and must bond to the exterior surface of the structure. The chemical grout will be Mountain Grout U 4.0 dual component polyurethane grouts as manufactured by Green Mountain International LLC or equal.

All costs for equipment, material, and labor required to fill external voids surrounding the culvert will be incidental to the contract unit price per gallon for Chemical Grout Void Fill. Any overfilling of voids that results in damage to overlying pavement, highway user ride quality, or drainage structure integrity will be corrected and paid for by the Contractor. All corrections will be approved by the Engineer. Payment will be to the 0.1 gallon of chemical grout used, prior to expansion of the material.

A calibrated metering device will be used to measure the chemical grout and to assure proper mixing ratio of components.

After the grout cures, excess material will be removed flush with the pipe interior wall and the pipe left clean.

**CULVERT CLEANOUT**

Material in existing culverts as listed in the Table for Mainline Culvert Work will be cleaned out by water flushing or other approved methods.

It is the responsibility of the Contractor to visit the site to determine the extent of culvert cleaning work required.

Cost for this work will be included in the contract unit price per each for Cleanout Pipe Culvert.

The Contractor will implement appropriate sediment control measures prior to water flushing in order to prevent discharges from project boundaries, and to comply with the Storm Water Permit.

**DITCH RESTORATION**

The ditches will be excavated for approximately 50 feet in each direction (or as directed by the Engineer) from the new/reset pipe ends to obtain proper water flow through the pipe. The excavated material may be used as fill material for culvert work, etc. as approved by the Engineer.

Cost for this work will be incidental to the contract unit price per cubic yard for Contractor Furnished Borrow Excavation.

**CORRUGATED METAL PIPE**

Corrugated metal pipes will have 2 2/3-inch x 1/2-inch corrugations for 42-inch and smaller round pipe and 48-inch and smaller arch pipe unless otherwise stated in the plans. Corrugated metal pipes will have 3-inch x 1-inch or 5-inch x 1-inch corrugations for 48-inch and larger round pipe and 54-inch and larger arch pipe unless otherwise stated in the plans.

The gauge of the corrugated metal ends will match the thickest gauge of corrugated metal pipe it is connected to.

**TIE BOLTS FOR RCP/RCP ARCH CULVERTS**

Tie bolts will conform to Standard Plate 450.18.

Tie Bolts will be installed at the inlet and outlet on the first three sections of new/reset culvert and on new/reset culvert ends (requires connection from existing culvert to new culvert / new end section).

For informational purposes:

Field drilling will be required to install the tie bolts on reset culvert, on reset culvert ends and on existing culvert when installing a new/reset end section.

Cost for removing tie bolts, drilling tie bolt holes and furnishing and installing tie bolts will be incidental to the contract unit prices for installing or resetting RCP/RCP Arch Culverts and End Sections. Existing tie bolts may be salvaged and reused if condition is acceptable to the Engineer.

The Contractor will place culvert and end sections such that the installation does not cause existing culvert sections to separate at any of the existing joints. Any joint separation caused by the Contractor's operations will result in removal, resetting and re-tie bolting of said culvert sections at the Contractor's expense.

**INSLOPE TRANSITIONS**

Inslope transitions will be required at various culvert locations. Refer to Standard Plate 120.05 for details.

**TABLE OF INSLOPE TRANSITIONS**

Station	Side
18+66	L & R

**EMBANKMENT ADJACENT TO CULVERTS**

Earth embankment adjacent to the existing culverts/end sections shown in the Table of Mainline Culvert Work will be removed prior to removing the culverts/end sections. Upon installation/reset of the culvert/end sections, the earth embankment will be replaced and compacted adjacent to the culvert/end sections.

Cost for removing, replacing and compacting the earth embankment is included in the contract unit price per cubic yard for Unclassified Excavation.

**REFURBISH SINGLE MAILBOXES**

Existing mailboxes will be removed, turnouts constructed, and mailboxes reset on new posts with the necessary support hardware for single mailbox assemblies. The local Postmaster will determine the recommended mounting height. The Contractor will coordinate with the Engineer on the proper postal representative to contact.

STATION	CLASS Q3R HOT MIXED ASPHALT CONCRETE	REFURBISH SINGLE MAILBOX
	TONS	EACH
45+00 Rt.	-	1
176+50 Lt.	4	1
275+25 Rt.	4	1
358+40 Rt.	4	1
513+35 Rt.	4	1
584+15 Rt.	4	1
<b>TOTALS:</b>	<b>20</b>	<b>6</b>

The Contractor will be responsible for maintaining a temporary mailbox assembly until the refurbished mailbox assembly is complete in place.

Cost for removing existing mailboxes, providing temporary mailbox assemblies, and resetting mailboxes with new posts and necessary support hardware will be incidental to the contract unit price per each for Refurbish Single Mailbox.

**TYPE 2 OBJECT MARKERS AT ROADSIDE OBSTACLES**

At locations shown in the Table for Mainline Culvert Work where Type 2 Object Markers will be removed, cost for removing the existing Type 2 Object Markers will be included in the contract unit price per each for Remove Delineator.

New Type 2 Object Markers and posts will be furnished and installed according to the details of Standard Plates 632.01, 632.03 and 632.04 by the Contractor at the locations shown in the Table for Mainline Culvert Work. Cost for new Type 2 object marker and post installation is included in the contract unit price per each for Type 2 Object Marker Back to Back.

**PERMANENT SEEDING AND MULCHING**

The areas to be seeded and mulched consist of disturbed areas within the right-of-way resulting from the work required by this contract.

Type C Permanent Seed Mixture will consist of the following:

Grass Species	Variety	Pure Live Seed (PLS) (Pounds/Acre)
Western Wheatgrass	Arriba, Flintlock, Rodan, Rosana, Walsh	16
Canada Wildrye	Mandan	2
Total:		18

The areas to be seeded and mulched are estimated at 2.5 acres.

If the Contractor uses a no-till drill, mulch may be applied prior to seeding and the mulch can then be punched into the soil by the no-till drill. If the Contractor uses this process, the no-till drill seeding will be completed immediately following the mulch application and the mulch will be punched into the soil at a 3-inch depth.

**EROSION CONTROL BLANKET**

Erosion control blanket will be installed at the locations noted in the Table for Mainline Culvert Work.

The erosion control blanket provided will be from the approved product list. The approved product list for erosion control blanket may be viewed at the following internet site:

<http://apps.sd.gov/HC60ApprovedProducts/main.aspx>



**TEMPORARY PAVEMENT MARKING (CONTINUED)**

Prior to nightfall, tabs will be required to mark centerline on segments of roadway where existing centerline markings have been removed and new markings have not been installed.

**PERMANENT PAVEMENT MARKING**

The Contractor will be required to repaint all existing pavement markings including centerline, edge line, lane lines, turn arrows and stop bars. This list is approximate. The Contractor will be required to document and be able to relocate for replacement of the existing turn arrows, stop bars, etc. before the markings are obliterated. Additional quantities are included in the estimate of quantities to paint the additional pavement marking. The cost to duplicate the existing marking locations will be incidental to the contract unit prices for the various contract items.

The Contractor will advise the Engineer a minimum of 3 weeks prior to the application of the permanent pavement marking to allow the State to check and mark the location of no passing zones.

The application of permanent pavement marking will begin no sooner than 7 calendar days following completion of the fog or flush seal. Application of permanent pavement marking will be completed within 14 calendar days following completion of the final surfacing.

**HIGH BUILD WATERBORNE PAVEMENT MARKING PAINT**

All materials will be applied as per manufacturer's recommendations. High build waterborne pavement marking paint will conform to the supplemental specifications for Section 980.1 B.

Reflective media will consist of glass beads.

**RATES OF MATERIALS FOR HIGH BUILD WATERBORNE PAVEMENT MARKING PAINT**

White Solid 4" line = 22.5 Gals/Mile  
Dashed 4" line = 6.2 Gal/Mile  
Glass Beads = 8 Lbs/Gal

All cost for materials, labor and equipment necessary to furnish and install the pavement markings will be incidental to the contract unit price for the respective High Build Waterborne Pavement Marking Paint items.

**RETROREFLECTIVITY FOR PAVEMENT MARKING PAINT**

The Department may take retro-reflectivity readings on the pavement marking lines after 2 days and within 30 days of the line application using either a portable or mobile retro-reflectometer that conforms to 30-meter geometry. If the Department chooses to take retro-reflectivity readings, three retro-reflectivity readings will be taken on each line at each test location. The three readings will be averaged and become the reading for that test location.

If the Department chooses to take retro-reflectivity readings, three readings will be taken on the edge lines and lane lines in the direction of application. For combination solid yellow and skip yellow lines for turn lanes and for centerline markings on two-way roadways, three readings will be taken in one direction, the reflectometer will be turned 180 degrees and three more readings will be taken. The six readings for the centerline markings will be averaged and become the test reading for that test location.

If the Department chooses to take readings, the minimum retro-reflectivity values will be 275 mc/m<sup>2</sup>/lux for white and 170 mc/m<sup>2</sup>/lux for yellow.

**ITEMIZED LIST FOR TRAFFIC CONTROL SIGNS**

SIGN CODE	SIGN DESCRIPTION	CONVENTIONAL ROAD			
		NUMBER	SIGN SIZE	SQFT PER SIGN	SQFT
W3-4	BE PREPARED TO STOP	6	48" x 48"	16.0	96.0
W8-1	BUMP	6	48" x 48"	16.0	96.0
W8-6	TRUCK CROSSING	4	48" x 48"	16.0	64.0
W8-15	GROOVED PAVEMENT	8	48" x 48"	16.0	128.0
W13-1P	ADVISORY SPEED (plaque)	6	30" x 30"	6.3	37.8
W20-1	ROAD WORK AHEAD	16	48" x 48"	16.0	256.0
W20-4	ONE LANE ROAD AHEAD	6	48" x 48"	16.0	96.0
W20-7	FLAGGER (symbol)	8	48" x 48"	16.0	128.0
SPECIAL	WAIT FOLLOW PILOT CAR	6	30" x 18"	3.8	22.8
G20-1	ROAD WORK NEXT 1 MILE	1	36" x 18"	4.5	4.5
G20-1	ROAD WORK NEXT 6 MILES	2	36" x 18"	4.5	9.0
G20-1	ROAD WORK NEXT 11 MILES	1	36" x 18"	4.5	4.5
G20-1	ROAD WORK NEXT 12 MILES	2	36" x 18"	4.5	9.0
G20-2	END ROAD WORK	16	36" x 18"	4.5	72.0
<b>CONVENTIONAL ROAD TRAFFIC CONTROL SIGNS SQFT</b>					<b>1023.6</b>

**STORMWATER POLLUTION PREVENTION PLAN CHECKLIST**

(The numbers left of the title headings are **reference numbers** to the GENERAL PERMIT FOR STORM WATER DISCHARGES ASSOCIATED WITH CONSTRUCTION ACTIVITIES (Stormwater Permit))

**5.3 (2): STAFF TRAINING/SWPPP IMPLEMENTATION**

To promote stormwater management awareness specific for this project, the Contractor's Erosion Control Supervisor should provide correspondence of how the SWPPP will be implemented. The Contractor's Erosion Control Supervisor is responsible for providing this information at the preconstruction meeting, and subsequently completing an attendance log, which should identify site-specific implementation of the SWPPP and the names of the personnel who attended the preconstruction meeting. Documentation of the preconstruction meeting will be filed with the SWPPP documents.

**5.3 (3): DESCRIPTION OF CONSTRUCTION ACTIVITIES**

- **5.3 (3a): Project Limits** (See Title Sheet)
- **5.3 (3a): Project Description** (See Title Sheet)
- **5.3 (4): Site Map(s)** (See Title Sheet and Plans)
- **Major Soil Disturbing Activities** (check all that apply)
  - Clearing and grubbing
  - Excavation/borrow
  - Grading and shaping
  - Filling
  - Other (describe):
- **5.3 (3b): Total Project Area** 290 Acres
- **5.3 (3b): Total Area to be Disturbed** 2.5 Acres
- **5.3 (3c): Maximum Area Disturbed at One Time** 2.5 Acres
- **5.3 (3d): Existing Vegetative Cover (%)**
- **5.3 (3d): Description of Vegetative Cover**
  
- **5.3 (3e): Soil Properties:** AASHTO Soil or USDA-NRCS Soil Series Classification
- **5.3 (3f): Name of Receiving Water Body/Bodies** Tributaries to Emanuel Creek
- **5.3 (3g): Location of Construction Support Activity Areas**

**5.3 (3h): ORDER OF CONSTRUCTION ACTIVITIES**

The Contractor will enter the Estimated Start Date.

Description	Estimated Start Date
Install Mainline Pipe Replacement.	
Place temporary surfacing at Mainline Pipe Replacement.	
Perform remaining Pipe work.	
Perform Cold Milling operations.	
Perform surfacing operations.	
Install Guardrail.	
Reseed disturbed areas.	

**5.3 (5): DESCRIPTION AND MAINTENANCE OF CONTROL MEASURES**

All controls will be maintained in good working order. Necessary repairs will be initiated within 24 hours of the site inspection report. Include the technical reasoning for selecting each control. (check all that apply)

**Perimeter Controls (See Detail Plan Sheets)**

Description	Estimated Start Date
<input type="checkbox"/> Natural Buffers (within 50 ft of Waters of State)	
<input type="checkbox"/> Silt Fence	
<input type="checkbox"/> Erosion Control Wattles	
<input type="checkbox"/> Temporary Berm / Windrow	
<input type="checkbox"/> Floating Silt Curtain	
<input type="checkbox"/> Stabilized Construction Entrances	
<input type="checkbox"/> Entrance/Exit Equipment Tire Wash	
<input type="checkbox"/> Other:	

**Structural Erosion and Sediment Controls**

Description	Estimated Start Date
<input type="checkbox"/> Silt Fence	
<input type="checkbox"/> Temporary Berm/Windrow	
<input type="checkbox"/> Erosion Control Wattles	
<input type="checkbox"/> Temporary Sediment Barriers	
<input type="checkbox"/> Erosion Bales	
<input type="checkbox"/> Temporary Slope Drain	
<input type="checkbox"/> Turf Reinforcement Mat	
<input type="checkbox"/> Riprap	
<input checked="" type="checkbox"/> Gabions	
<input type="checkbox"/> Rock Check Dams	
<input type="checkbox"/> Sediment Traps/Basins	
<input type="checkbox"/> Culvert Inlet Protection	
<input type="checkbox"/> Transition Mats	
<input type="checkbox"/> Median/Area Drain Inlet Protection	
<input type="checkbox"/> Curb Inlet Protection	
<input type="checkbox"/> Interceptor Ditch	
<input type="checkbox"/> Concrete Washout Facility	
<input type="checkbox"/> Work Platform	
<input type="checkbox"/> Temporary Water Barrier	
<input type="checkbox"/> Temporary Water Crossing	
<input type="checkbox"/> Permanent Stormwater Ponds	
<input type="checkbox"/> Permanent Open Vegetated Swales	
<input type="checkbox"/> Natural Depressions to allow for Infiltration	
<input type="checkbox"/> Sequential Systems that combine several practices	
<input type="checkbox"/> Other:	

**Dust Controls**

Description	Estimated Start Date
<input type="checkbox"/> Tarps & Wind impervious fabrics	
<input type="checkbox"/> Watering	
<input type="checkbox"/> Stockpile location/orientation	
<input type="checkbox"/> Dust Control Chlorides	
<input type="checkbox"/> Other	

**Dewatering BMPs**

Description	Estimated Start Date
<input type="checkbox"/> Sediment Basins	
<input type="checkbox"/> Dewatering bags	
<input type="checkbox"/> Weir tanks	
<input type="checkbox"/> Temporary Diversion Channel	
<input type="checkbox"/> Other:	

**Stabilization Practices (See Detail Plan Sheets)**

(Stabilization measures will begin the following work day whenever earth disturbing activity on any portion of the site has temporarily or permanently ceased. Temporary stabilization will be completed as soon as practicable but no later than 14 days after initiating soil stabilization activities (3.18))

Description	Estimated Start Date
<input type="checkbox"/> Vegetation Buffer Strips	
<input type="checkbox"/> Temporary Seeding (Cover Crop Seeding)	
<input checked="" type="checkbox"/> Permanent Seeding	
<input type="checkbox"/> Sodding	
<input type="checkbox"/> Planting (Woody Vegetation for Soil Stabilization)	
<input checked="" type="checkbox"/> Mulching (Grass Hay or Straw)	
<input type="checkbox"/> Fiber Mulching (Wood Fiber Mulch)	
<input type="checkbox"/> Soil Stabilizer	
<input type="checkbox"/> Bonded Fiber Matrix	
<input type="checkbox"/> Fiber Reinforced Matrix	
<input type="checkbox"/> Erosion Control Blankets	
<input type="checkbox"/> Surface Roughening (e.g. tracking)	
<input type="checkbox"/> Other:	

**Wetland Avoidance**

Will construction and/or erosion and sediment controls impinge on regulated wetlands? Yes  No  If yes, the structural and erosion and sediment controls have been included in the total project wetland impacts and have been included in the 404 permit process with the USACE.

### 5.3 (6): PROCEDURES FOR INSPECTIONS

- Inspections will be conducted at least once every 7 days.
- All controls will be maintained in good working order. Necessary repairs will be initiated within 24 hours of the site inspection report.
- Silt fence will be inspected for depth of sediment and for tears to ensure the fabric is securely attached to the posts and that the posts are well anchored. Sediment buildup will be removed from the silt fence when it reaches  $\frac{1}{3}$  of the height of the silt fence.
- Sediment basins and traps will be checked. Sediment will be removed when depth reaches approximately 50 percent of the structure's capacity, and at the conclusion of the construction.
- Check dams will be inspected for stability. Sediment will be removed when depth reaches  $\frac{1}{2}$  the height of the dam.
- All seeded areas will be checked for bare spots, washouts, and vigorous growth free of significant weed infestations.
- Inspection and maintenance reports will be prepared on form DOT 298 for each site inspection, this form will also be used to document changes to the SWPPP. A copy of the completed inspection form will be filed with the SWPPP documents.
- The SDDOT Project Engineer and Contractor's Erosion Control Supervisor are responsible for inspections. Maintenance and repair activities are the responsibility of the Contractor. The SDDOT Project Engineer will complete the inspection and maintenance reports and distribute copies per the distribution instructions on DOT 298.

### 5.3 (7): POST CONSTRUCTION STORMWATER MANAGEMENT

Stormwater management will be handled by temporary controls outlined in "DESCRIPTION AND MAINTENANCE OF CONTROL MEASURES" above, and any permanent controls needed to meet permanent stormwater management needs in the post construction period will be shown in the plans and noted as permanent.

### 5.3 (8): POLLUTION PREVENTION PROCEDURES

#### 5.3 (8a): Spill Prevention and Response Procedures

##### ➤ Material Management

##### ▪ Housekeeping

- Only needed products will be stored on-site by the Contractor.
- Except for bulk materials the contractor will store all materials under cover and/or in appropriate containers.
- Products must be stored in original containers and labeled.
- Material mixing will be conducted in accordance with the manufacturer's recommendations.
- When possible, all products will be completely used before properly disposing of the container off-site.
- The manufacturer's directions for disposal of materials and containers will be followed.
- The Contractor's site superintendent will inspect materials storage areas regularly to ensure proper use and disposal.
- Dust generated will be controlled in an environmentally safe manner.

##### ▪ Hazardous Materials

- Products will be kept in original containers unless the container is not resealable and provide secondary containment as applicable.
- Original labels and material safety data sheets will be retained in a safe place to relay important product information.
- If surplus product must be disposed of, manufacturer's label directions for disposal will be followed.
- Maintenance and repair of all equipment and vehicles involving oil changes, hydraulic system drain down, de-greasing operations, fuel tank drain down and removal, and other activities which may result in the accidental release of contaminants will be conducted on an impervious surface and under cover during wet weather to prevent the release of contaminants onto the ground.
- Wheel wash water will be collected and allowed to settle out suspended solids prior to discharge. Wheel wash water will not be discharged directly into any stormwater system or stormwater treatment system.
- Potential pH-modifying materials such as: bulk cement, cement kiln dust, fly ash, new concrete washings, concrete pumping, residuals from concrete saw cutting (either wet or dry), and mixer washout waters will be collected on site and managed to prevent contamination of stormwater runoff.

##### ➤ Spill Control Practices

In addition to the previous housekeeping and management practices, the following practices will be followed for spill prevention and cleanup if needed.

- For all hazardous materials stored on site, the manufacturer's recommended methods for spill cleanup will be clearly posted. Site personnel will be made aware of the procedures and the locations of the information and cleanup supplies.
- Appropriate cleanup materials and equipment will be maintained by the Contractor in the materials storage area on-site. As appropriate, equipment and materials may include items such as brooms, dust pans, mops, rags, gloves, goggles, kitty litter, sand, sawdust, and plastic and metal trash containers specifically for cleanup purposes.
- All spills will be cleaned immediately after discovery and the materials disposed of properly.
- The spill area will be kept well ventilated and personnel will wear appropriate protective clothing to prevent injury from contact with a hazardous substance.
- After a spill a report will be prepared describing the spill, what caused it, and the cleanup measures taken. The spill prevention plan will be adjusted to include measures to prevent this type of spill from reoccurring, as well as clean up instructions in the event of reoccurrences.
- The Contractor's site superintendent, responsible for day-to-day operations, will be the spill prevention and cleanup coordinator.

##### ➤ Spill Response

The primary objective in responding to a spill is to quickly contain the material(s) and prevent or minimize migration into stormwater runoff and conveyance systems. If the release has impacted on-site stormwater, it is critical to contain the released materials on-site and prevent their release into receiving waters. If a spill of pollutants threatens stormwater or surface water at the site, the spill response procedures outlined below must be implemented in a timely manner to prevent the release of pollutants.

- The Contractor's site superintendent will be notified immediately when a spill or the threat of a spill is observed. The superintendent will assess the situation and determine the appropriate response.
- If spills represent an imminent threat of escaping erosion and sediment controls and entering receiving waters, personnel will be directed to respond immediately to contain the release and notify the superintendent after the situation has been stabilized.
- Spill kits containing appropriate materials and equipment for spill response and cleanup will be maintained by the Contractor at the site.
- If oil sheen is observed on surface water (e.g. settling ponds, detention ponds, swales), action will be taken immediately to remove the material causing the sheen. The Contractor will use appropriate materials to contain and absorb the spill. The source of the oil sheen will also be identified and removed or repaired as necessary to prevent further releases.
- If a spill occurs the superintendent or the superintendent's designee will be responsible for completing the spill reporting form and for reporting the spill to SDDANR.
- Personnel with primary responsibility for spill response and cleanup will receive training by the Contractor's site superintendent or designee. The training must include identifying the location of the spill kits and other spill response equipment and the use of spill response materials.
- Spill response equipment will be inspected and maintained as necessary to replace any materials used in spill response activities.

### 5.3 (8b): WASTE MANAGEMENT PROCEDURES

##### ➤ Waste Disposal

- All liquid waste materials will be collected and stored in approved sealed containers. All trash and construction debris from the site will be deposited in the approved containers. Containers will be serviced as necessary, and the trash will be hauled to an approved disposal site or licensed landfill. All onsite personnel will be instructed in the proper procedures for waste disposal and notices stating proper practices will be posted. The Contractor is responsible for ensuring waste disposal procedures are followed.

##### ➤ Hazardous Waste

- All hazardous waste materials will be disposed of in a manner specified by local or state regulations or by the manufacturer. Site personnel will be instructed in these practices, and the Contractor will be responsible for seeing that these practices are followed.

##### ➤ Sanitary Waste

- Portable sanitary facilities will be provided on all construction sites. Sanitary waste will be collected from the portable units which must be secured to prevent tipping and serviced in a timely manner by a licensed waste management Contractor or as required by any local regulations.

### 5.3 (9): CONSTRUCTION SITE POLLUTANTS

The following materials or substances are expected to be present on the site during the construction period. These materials will be handled as noted under the heading "POLLUTION PREVENTION PROCEDURES" (check all that apply).

- Concrete and Portland Cement
- Detergents
- Paints
- Metals
- Bituminous Materials
- Petroleum Based Products
- Diesel Exhaust Fluid
- Cleaning Solvents
- Wood
- Cure
- Texture
- Chemical Fertilizers
- Other:

#### Product Specific Practices

##### ▪ **Petroleum Products**

All on-site vehicles will be monitored for leaks and receive regular preventive maintenance to reduce the chance of leakage. Petroleum products will be stored in tightly sealed containers which are clearly labeled.

##### ▪ **Fertilizers**

Fertilizers will be applied only in the amounts specified by the SDDOT. Once applied, fertilizers will be worked into the soil to limit the exposure to stormwater. Fertilizers will be stored in an enclosed area. The contents of partially used fertilizer bags will be transferred to sealable containers to avoid spills.

##### ▪ **Paints**

All containers will be tightly sealed and stored when not required for use. The excess will be disposed of according to the manufacturer's instructions and any applicable state and local regulations.

##### ▪ **Concrete Trucks**

Contractors will provide designated truck washout facilities on the site. These areas must be self-contained and not connected to any stormwater outlet of the site. Upon completion of construction, the area at the washout facility will be properly stabilized.

### 5.3 (10): NON-STORMWATER DISCHARGES

The following non-stormwater discharges are anticipated during the course of this project (check all that apply).

- Discharges from water line flushing.
- Pavement wash-water, where no spills or leaks of toxic or hazardous materials have occurred.
- Uncontaminated ground water associated with dewatering activities.

### 5.3 (11): INFEASIBILITY DOCUMENTATION

If it is determined to be infeasible to comply with any of the requirements of the Stormwater Permit, the infeasibility determination must be thoroughly documented in the SWPPP.

### 7.0: SPILL NOTIFICATION

In the event of a spill, the Contractor's site superintendent will make the appropriate notification(s), consistent with the following procedures:

- A release or spill of a regulated substance (includes petroleum and petroleum products) must be reported to SDDANR immediately **if any one of the following** conditions exists:
  - The release or spill threatens or is able to threaten waters of the state (surface water or ground water)
  - The release or spill causes an immediate danger to human health or safety
  - The release or spill exceeds 25 gallons
  - The release or spill causes a sheen on surface water
  - The release or spill of any substance that exceeds the ground water quality standards of ARSD Chapter 74:54:01
  - The release or spill of any substance that exceeds the surface water quality standards of ARSD Chapter 74:51:01
  - The release or spill of any substance that harms or threatens to harm wildlife or aquatic life
  - The release or spill is required to be reported according to Superfund Amendments and Reauthorization Act (SARA) Title III List of Lists, Consolidated List of Chemicals Subject to Reporting Under the Emergency Planning and Community Right to Know Act, US Environmental Protection Agency.
- To report a release or spill, call SDDANR at 605-773-3296 during regular office hours (8 a.m. to 5 p.m. Central Standard Time). To report the release after hours, on weekends or holidays, call South Dakota Emergency Management at 605-773-3231. Reporting the release to SDDANR does not meet any obligation for reporting to other state, local, or federal agencies. Therefore, you must also contact local authorities to determine the local reporting requirements for releases. A written report of the unauthorized release of any regulated substance, including quantity discharged, and the location of the discharge will be sent to SDDANR within 14 days of the discharge.



#### 5.4: SWPPP CERTIFICATIONS

##### ➤ Certification of Compliance with Federal, State, and Local Regulations

The Storm Water Pollution Prevention Plan (SWPPP) for this project reflects the requirements of all local municipal jurisdictions for storm water management and sediment and erosion control as established by ordinance, as well as other state and federal requirements for sediment and erosion control plans, permits, notices or documentation as appropriate.

##### ➤ South Dakota Department of Transportation

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.



\_\_\_\_\_  
Authorized Signature (See the General Permit, Section 7.4 (1))

##### ➤ Prime Contractor

This section is to be executed by the General Contractor after the award of the contract. This section may be executed any time there is a change in the Prime Contractor of the project.

I certify under penalty of law that this document and all attachments will be revised or maintained under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

\_\_\_\_\_  
Authorized Signature

#### CONTACT INFORMATION

The following personnel are duly authorized representatives and have signatory authority for modifications made to the SWPPP:

##### ➤ Contractor Information:

- Prime Contractor Name: \_\_\_\_\_
- Contractor Contact Name: \_\_\_\_\_
- Address: \_\_\_\_\_
- \_\_\_\_\_
- City: \_\_\_\_\_ State: \_\_\_\_\_ Zip: \_\_\_\_\_
- Office Phone: \_\_\_\_\_ Field: \_\_\_\_\_
- Cell Phone: \_\_\_\_\_ Fax: \_\_\_\_\_

##### ➤ Erosion Control Supervisor

- Name: \_\_\_\_\_
- Address: \_\_\_\_\_
- \_\_\_\_\_
- City: \_\_\_\_\_ State: \_\_\_\_\_ Zip: \_\_\_\_\_
- Office Phone: \_\_\_\_\_ Field: \_\_\_\_\_
- Cell Phone: \_\_\_\_\_ Fax: \_\_\_\_\_

##### ➤ SDDOT Project Engineer

- Name: \_\_\_\_\_
- Business Address: \_\_\_\_\_
- Job Office Location: \_\_\_\_\_
- City: \_\_\_\_\_ State: \_\_\_\_\_ Zip: \_\_\_\_\_
- Office Phone: \_\_\_\_\_ Field: \_\_\_\_\_
- Cell Phone: \_\_\_\_\_ Fax: \_\_\_\_\_

##### ➤ SDDANR Contact Spill Reporting

- Business Hours Monday-Friday (605) 773-3296
- Nights and Weekends (605) 773-3231

##### ➤ SDDANR Contact for Hazardous Materials.

- (605) 773-3153

##### ➤ National Response Center Hotline

- (800) 424-8802.

##### ➤ SDDANR Stormwater Contact Information

- SDDANR Stormwater (800) 737-8676
- Surface Water Quality Program (605) 773-3351

#### 5.5: REQUIRED SWPPP MODIFICATIONS

##### ➤ 5.5 (1): Conditions Requiring SWPPP Modification

The SWPPP must be modified, including the site map(s), in response to any of the following conditions:

- When a new operator responsible for implementation of any part the SWPPP begins work on the site.
- When changes to the construction plans, sediment and erosion control measures, or any best management practices on site that are no longer accurately reflected in the SWPPP. This includes changes made in response to corrective actions triggered by inspections.
- To reflect areas on the site map where operational control has been transferred (including the date of the transfer) or has been covered under a new permit since initiating coverage under this general permit.
- If inspections by site staff, local officials, SDDANR, or U.S. EPA determine that SWPPP modifications are necessary for compliance with the Stormwater Permit.
- To reflect any revisions to applicable federal, state, or local requirements that affect the control measures implemented at the site.
- If approved by the Secretary, to reflect any changes in chemical water treatment systems or controls, including the use of a different water treatment chemical, age rates, different areas, or methods of application.

##### ➤ 5.5 (2): Deadlines for SWPPP Modification

Any required revisions to the SWPPP must be completed within 7 calendar days following any of the items listed above.

##### ➤ 5.5 (3): Documentation of Modifications to the Plan

All SWPPP modification records are required to be maintained showing the dates of when the modification occurred. The records must include the name of the person authorizing each change and a brief summary of all changes.

##### ➤ 5.5 (4): Certification Requirements

All modifications made to the SWPPP must be signed and certified as required in Section 7.4.

##### ➤ 5.5 (5): Required Notice to Other Operators

If there are multiple operators at the site, the Contractor's Erosion Control Supervisor must notify each operator that may be impacted by the change to the SWPPP within 24 hours.

When modifications as described above occur, the SWPPP will be modified to provide appropriate protection to disturbed areas, all storm water structures, and adjacent waters. The SDDOT Project Engineer will modify the SWPPP using the DOT 298 form and drawings on the plan will be modified to reflect the needed changes. Copies of the DOT 298 forms and the SWPPP will be retained on site in a designated place for review throughout the course of the project. A copy of the DOT 298 form will be given to the Contractor Erosion Control Supervisor and a copy will be emailed to the SDDOT Environmental Section in accordance with the DOT 298 Form.

**PAVEMENT MARKING**

**TWO LANE ROADWAY**

Typical pavement marking as shown on this sheet will be applied throughout the entire length of two lane roadway.

Traffic Control will be incidental to the cost of application. The striper and advance or trailing warning vehicle will be equipped with flashing amber lights and advance warning arrow board.


Application rates will be as follows:

Two Lane Roadway (Rates for one line)	
Dashed Yellow Centerline	Rate = 6.2 Gals./Pass-Mile
Solid Yellow Centerline	Rate = 22.5 Gals./Pass-Mile
Solid White Edgeline	Rate = 22.5 Gals./Pass-Mile


4" Yellow Skip Centerline (when not adjacent to a 4" Yellow No Passing Zone) will be placed consistently to the south or east side of centerline.

ESTIMATED QUANTITIES (BASED ON ONE APPLICATION)	
HIGH BUILD	QUANTITY
WHITE	542 GALLONS
YELLOW	204 GALLONS

Included in the above quantities are:			
Additional White (1 Application)		Additional Yellow (1 Application)	
Description	Gallons	Description	Gallons
4" Lines	240'	Transitions 2 Ea	1560'
8" Lines	-	4" Skip Lines	-
12" Gore Lines	-	8" Lines	-
Crosswalks	-	12" Lines	-
24" Stop Lines	-	24" Hatches	360'
24" Hatches	-	Solid Areas	-
Solid Areas	-	Additional Yellow: 27	
<b>Arrows</b>			
Left Arrows	4 Ea	Additional Quantities	
Right Arrows	-	<u>Rates of Coverage:</u> SqFt/Gal	
Straight Arrows	-	4", 8" & 12" Lines	60
Combo Arrows	-	24" Lines & Hatches	40
Lane Drop Arrows	-	Arrows, Messages and Solid Areas	25
<u>Messages</u>			
STOP	-	All pavement marking dimensions are based on 12' driving lanes.	
STOP AHEAD	-		
R X R w/ Stop Lines	-		
SCHOOL X-ING	-		
Additional White: 4			



## TRAFFIC CONTROL Fixed Location Signs (Ground Mounted Support)



**NOTES:**

- All fixed location signs will remain in place until permanent pavement marking is complete.
- Signs will be placed 200' to 300' from intersections. Exact location to be determined by the Engineer.
- Construction signs cannot obscure existing signs and must be installed a minimum of 200' from existing sign.
- Construction signs will not be installed on the same post as an existing highway sign or light pole.

PLOT SCALE - 1:7000

PLOTTED FROM - TRM113318

PLOT NAME - 2

FILE - ... \BONHOMME\TC\TTL06PN.DGN

Plot Scale - 1:200

\* Messages on signs will vary depending on the operation being conducted.

Vehicle-mounted signs will be mounted in a manner such that they are not obscured by equipment or supplies. Sign legends on vehicle-mounted signs will be covered or turned from view when work is not in progress.


Shadow and Work vehicles will display high-intensity rotating, flashing, oscillating, or strobe lights, flags, signs, or arrow boards.

Vehicle hazard warning signals will not be used instead of the vehicle's high-intensity rotating, flashing, oscillating, or strobe lights.

When an arrow board is used, it will be used in the caution mode. Marching Diamonds are acceptable.

Arrow boards will, as a minimum, be Type B, with a size of 60" x 30".

All costs associated with the traffic control for mobile operation including signs, arrow boards and equipment will be incidental to the contract lump sum price for "Traffic Control, Miscellaneous".



January 22, 2021

<b>S D D O T</b>	<b>MOBILE OPERATIONS ON 2-LANE ROAD</b>	PLATE NUMBER <b>634.06</b>
		Sheet 1 of 1

Published Date: 2024

Posted Speed Prior to Work (M.P.H.)	Spacing of Advance Warning Signs (Feet) (A)	Spacing of Channelizing Devices (Feet) (G)
0 - 30	200	25
35 - 40	350	25
45	500	25
50	500	50
55	750	50
60 - 65	1000	50

Flagger  
 Channelizing Device

For low-volume traffic situations with short work zones on straight roadways where the flagger is visible to road users approaching from both directions, a single flagger may be used.


The ROAD WORK AHEAD and the END ROAD WORK signs may be omitted for short duration operations (1 hour or less).

For tack and/or flush seal operations, when flaggers are not being used, the FRESH OIL sign (W21-2) will be displayed in advance of the liquid asphalt areas.

Flashing warning lights and/or flags may be used to call attention to the advance warning signs.

The channelizing devices will be drums or 42" cones.


Channelizing devices are not required along the centerline adjacent to work area when pilot cars are utilized for escorting traffic through the work area.



Channelizing devices and flaggers will be used at intersecting roads to control intersecting road traffic as required.

The buffer space should be extended so that the two-way traffic taper is placed before a horizontal or vertical curve to provide adequate sight distance for the flagger and queue of stopped vehicles.

The length of A may be adjusted to fit field conditions.




January 22, 2021

<b>S D D O T</b>	<b>LANE CLOSURE WITH FLAGGER PROVIDED</b>	PLATE NUMBER <b>634.23</b>
		Sheet 1 of 1

Published Date: 2024

File - ...abom08PNIctitc-Sid-Plates.dgn

Plot Scale - 1:200




Conditions represented are for work that requires closings during daytime hours only.

This application is intended for a planned temporary closing not to exceed 15 to 20 minutes.

<b>S D D O T</b>	<b>TEMPORARY ROAD WORK</b>	PLATE NUMBER <b>634.30</b>
	Published Date: 2024	Sheet 1 of 1

January 22, 2021



- Flagger
- \*\* Need and safe speed to be determined on site by the Engineer.
- \* Need for flagger to be determined at the site by the Engineer. When flagger is used, the W20-7 sign will be installed.
- ☒ Need for BUMP sign to be determined at the site.

The signing shown is applicable during that period when construction operations are in progress in the vicinity of the crossroad. Need for such signing at specific crossroad locations will be determined at the site by the Engineer.


<b>S D D O T</b>	<b>PROJECT OPEN TO TRAFFIC FROM CROSSROAD</b>	PLATE NUMBER <b>634.38</b>
	Published Date: 2024	Sheet 1 of 1

January 22, 2021

File - ...abom06PNIctitc:Std:Plates.dgn


Plotted From - TRM113318

Plot Scale - 1:200



**RURAL DISTRICT**

**RURAL DISTRICT WITH SUPPLEMENTAL PLATE**




**URBAN DISTRICT**

**RURAL DISTRICT 3 DAY MAXIMUM**  
(Not applicable to regulatory signs)


\* If the bottom of supplemental plate is mounted lower than 7 feet above a pedestrian walkway, the supplemental plate should not project more than 4" into the pedestrian facility.

January 22, 2021

Published Date: 2024	S D D O T	CRASHWORTHY SIGN SUPPORTS (Typical Construction Signing)	PLATE NUMBER 634.85
			Sheet 1 of 1



**PLAN VIEW**  
(Examples of stub height clearance checks)



**ELEVATION VIEW**

**GENERAL NOTES:**

- The top of anchor posts and slip bases WILL NOT extend above a 60" chord line within a 120" diameter circle around the post with ends 4" above the ground.
- At locations where there is curb and gutter adjacent to the breakaway sign support, the stub height will be a maximum of 4" above the ground line at the localized area adjacent to the breakaway support stub.
- The 4" stub height clearance is not necessary for U-channel lap splices where the support is designed to yield (bend) at the base.

January 22, 2021

Published Date: 2024	S D D O T	BREAKAWAY SUPPORT STUB CLEARANCE	PLATE NUMBER 634.99
			Sheet 1 of 1


Plotted From: TRM113318

File: ...abom06P\Nct\Std Plates.dgn

# LAYOUT OF EMBANKMENT AND SURFACING FOR CULVERT REPLACEMENT

PLOT SCALE - 1:6.5

PLOT NAME - 3






\* Quantity is included in the Table of Additional Quantities.

PLOTTED FROM - TRM111118

FILE - ... \PRJ2024\BONH06PN\PIPEXC.DGN

# LAYOUT FOR PIPE INSERT IN EXISTING RC CATTLE PASS

-  Contractor Furnished Borrow
-  Controlled Density Fill




**TABLE FOR EXISTING RC CATTLE PASS PIPE INSERTS**

Project	Station	New RCP Size In	Contractor Furnished Borrow CuYd	Controlled Density Fill CuYd
NH 0037(164)24	87+79	36	^ 273	^ 13.7

^ Quantities are included in the Table for Mainline Culvert Work for NH 0037(164)24.

**SECTION A-A**






# DETAIL FOR COLD MILLING TAPER AT BEGIN PROJECT

PLOT SCALE - 1:1.008


PLOT NAME - 5



# DETAIL FOR RESURFACING TAPER AT BEGIN PROJECT

PLOTTED FROM - TRM111118

FILE - ... \PRJ2024\BONH06PN\MILL06PN.DGN






# DETAIL FOR COLD MILLING TAPER AT END PROJECT

STATE OF SOUTH DAKOTA	PROJECT <b>NH 0037(164)24</b>	SHEET 35	TOTAL SHEETS 63
-----------------------------	----------------------------------	-------------	-----------------------


Plotting Date: 01/04/2024

PLOT SCALE - 1:1.008

PLOT NAME - 7



# DETAIL FOR RESURFACING TAPER AT END PROJECT



PLOTTED FROM - TRM111118

FILE - ... \PRJ2024\BONH06PN\MILL06PN.DGN

# INSTALLATION OF GUARDRAIL

STR. NO. 05-100-104 SD37 MRM 26.08 &  
STR. NO. 05-100-118 SD37 MRM 24.70


STATE OF SOUTH DAKOTA	PROJECT NH 0037(164)24	SHEET 36	TOTAL SHEETS 63
-----------------------	---------------------------	-------------	--------------------




Plotting Date: 01/04/2024

- # Inslope:
- Str. No. 05-100-104 Begin Bridge Left = 4:1
  - Str. No. 05-100-104 Begin Bridge Right = 4:1
  - Str. No. 05-100-104 End Bridge Left = 4:1
  - Str. No. 05-100-104 End Bridge Right = 4:1
  - Str. No. 05-100-118 Begin Bridge Left = 4:1 to 27' from centerline and 3:1 thereafter
  - Str. No. 05-100-118 Begin Bridge Right = 4:1 to 27' from centerline and 3:1 thereafter
  - Str. No. 05-100-118 End Bridge Left = 4:1
  - Str. No. 05-100-118 End Bridge Right = 4:1

PLOT SCALE - 1:20

PLOT NAME - 8



-  Remove Asphalt Concrete Pavement
-  Remove Asphalt Concrete Pavement. Place 2" Class Q3R Hot Mixed Asphalt Concrete.
-  Place Contractor Furnished Borrow Excavation, 4" Base Course and 2" Class Q3R Hot Mixed Asphalt Concrete.

\* 2'-1 1/4" of guardrail overlaps onto structure.

PLOTTED FROM - TRM111118

FILE - ... \PRJ2024 \BONH06PN\T1GR06PN.DGN

Published Date: 2024


**S D D O T**

**INSLOPE TRANSITIONS AT PIPE CULVERTS OR REINFORCED CONCRETE BOX CULVERTS**

September 14, 2018

PLATE NUMBER  
120.05

Sheet 1 of 2



**TYPE 1 INSLOPE TRANSITION**

**GENERAL NOTES:**

This Type 1 Inslope Transition is used when the specified inslope at the drainage structure is flatter than the typical inslope and the inslope at the drainage structure is between a 4:1 slope and 6:1 slope.

Line B-B represents the clear zone line, the location where soil intercepts the parapet on an RCBC, the location where the soil intercepts the top of the pipe adjacent to the opening of the pipe end section, or may represent a change in slope.

\* Transition from the typical inslope to the inslope at the drainage structure. Within the clear zone (area from edge of subgrade shoulder to line B-B) use 100' length for each 1:1 slope change. Example: transition from a 4:1 to a 6:1 would require a 200' length transition. The typical inslope outside of the clear zone will be transitioned gradually to the slope necessary adjacent to the RCBC wing wall or pipe culvert end section within the transition length necessary for the transition within the clear zone.

Published Date: 2024


**S D D O T**

**INSLOPE TRANSITIONS AT PIPE CULVERTS OR REINFORCED CONCRETE BOX CULVERTS**

September 14, 2018

PLATE NUMBER  
120.05

Sheet 2 of 2



**TYPE 2 INSLOPE TRANSITION**

**GENERAL NOTES:**

This Type 2 Inslope Transition is used when the specified inslope at the pipe or RCBC is flatter than a 6:1 slope.

Line B-B represents the clear zone line, the location where soil intercepts the parapet on an RCBC, the location where the soil intercepts the top of the pipe adjacent to the opening of the pipe end section, or may represent a change in slope.

\* Transition from Inslope at drainage structure to a 6 : 1 inslope and 3:1 inslope.  
\*\* Transition from typical inslope to the inslopes adjacent to the drainage structure. Within the clear zone (area from edge of subgrade shoulder to line B-B) use 100' length for each 1:1 slope change. Example: transition from a 4:1 to a 6:1 would require a 200' length transition. The typical inslope outside of the clear zone will be transitioned to a 3:1 inslope within the transition length necessary for the transition within the clear zone.

STATE OF SOUTH DAKOTA


PROJECT  
NH 0037(164)24

SHEET  
37

TOTAL SHEETS  
63

Plotting Date: 01/04/2024

PLOT SCALE - 1:200



**PLAN VIEW**  
(Intersecting Road)  
(No Asphalt Concrete Surfacing  
Beyond Right of Way)

**PLAN VIEW**  
(Intersecting Road)  
(Asphalt Concrete Surfacing  
Beyond Right of Way)

**GENERAL NOTES:**

The precise construction limits for situations other than shown above will be determined by the Engineer during construction.

\* For new construction, 35' radius typical or as specified in the plans. For resurfacing projects, radius is variable depending on existing conditions.


\*\* The Contractor may adjust the screed of the paver during mainline paving operations to provide the 2-foot asphalt concrete pad or the Contractor may provide the 2-foot asphalt concrete pad during paving of the intersecting roads as shown above. The Engineer may eliminate the 2-foot asphalt concrete pads if the Engineer, in the Engineer's sole discretion, determines the pads are infeasible to construct due to site specific reasons including, but not limited to; existing inslope configuration, borrow and material availability, and right-of-way constraints.

August 27, 2020

<b>Published Date: 2024</b>	<b>S D D O T</b>	<b>SURFACING OR RESURFACING OF INTERSECTING ROADS AND ENTRANCES (MAINLINE AND SHOULDERS: PCC OR AC PAVEMENT)</b>	PLATE NUMBER <b>320.04</b>
			Sheet 1 of 2


PLOT NAME - 2

FILE - ... \STANDARDPLATES\_06PN.DGN



**DETAIL A**  
(Typ. for Projects with PCC Pavement on Shoulder)

**DETAIL B**  
(Typ. for Projects with AC Pavement on Shoulder)




**PLAN VIEW**  
(Entrance)

\*\*\* Not required if finished shoulder width is 4' or greater.

August 27, 2020

<b>Published Date: 2024</b>	<b>S D D O T</b>	<b>SURFACING OR RESURFACING OF INTERSECTING ROADS AND ENTRANCES (MAINLINE AND SHOULDERS: PCC OR AC PAVEMENT)</b>	PLATE NUMBER <b>320.04</b>
			Sheet 2 of 2

PLOTTED FROM - TRM111118



**GENERAL NOTES:**

**SECTION A-A**

A rumble stripe will be constructed on all of the asphalt concrete shoulders by grinding alternating patterns of 40' continuous indentations in the asphalt concrete. The rumble stripe will receive a flush seal or asphalt surface treatment as specified in the plans.


A rumble stripe will not be constructed through intersecting roads, entrances, turnouts, bridge decks, bridge approach slabs, and railroad crossings. The lengths of the 40' segments with continuous indentations and the 12' segments without a rumble stripe adjacent to the intersecting roads, entrances, turnouts, bridge decks, bridge approach slabs, and railroad crossings will be adjusted as approved by the Engineer.

Prior to constructing the rumble stripe the Contractor will submit to the Engineer, for approval, the proposed method of constructing the rumble stripe.

Measurement of the rumble stripe will be to the nearest 0.1 of a mile for each shoulder. Measurement and payment of the rumble stripe will include the 12' long segments without rumble stripes and the segments adjacent to intersecting roads, entrances, turnouts, bridge decks, bridge approach slabs, and railroad crossings without rumble stripes. Payment for constructing the rumble stripe will be at the contract unit price per mile for "Grind 8" Rumble Strip or Stripe in Asphalt Concrete".

September 14, 2019

<b>Published Date: 2024</b>	<b>S D D O T</b>	<b>8" RUMBLE STRIPE IN ASPHALT CONCRETE ON NONDIVIDED HIGHWAY SHOULDERS</b>	<b>PLATE NUMBER 320.20</b>
			Sheet 1 of 1



**GENERAL NOTES:**

Transverse rumble strips will be constructed by grinding, routing, or cutting recessed indentations into the asphalt concrete as approved by the Engineer. The transverse rumble strips will receive a flush seal or fog seal as specified in the plans.

\* The transverse rumble strips will extend into the finished shoulder as approved by the Engineer.

Measurement of the recessed transverse rumble strips will be to the nearest foot. Payment for constructing the recessed transverse rumble strips will be at the contract unit price per foot for "Grind 6" Transverse Rumble Strip in Asphalt Concrete".

January 22, 2021

<b>Published Date: 2024</b>	<b>S D D O T</b>	<b>TRANSVERSE RUMBLE STRIP IN ASPHALT CONCRETE HIGHWAY ADJACENT TO STOP CONTROLLED INTERSECTION</b>	<b>PLATE NUMBER 320.45</b>
			Sheet 1 of 1

PLOT SCALE - 1:200

PLOTTED FROM - TRM111118


PLOT NAME - 3

FILE - ... \STANDARDPLATES\_06PN.DGN

PLOT SCALE - 1:200

**TOLERANCES IN DIMENSIONS**

Diameter:  $\pm 1.5\%$  for 24" Dia. or less and  $\pm 1\%$  or  $\frac{3}{8}$ " whichever is more for 27" Dia. or greater.  
 Diameters at joints:  $\pm \frac{3}{16}$ " for 30" Dia. or less and  $\pm \frac{1}{4}$ " for 36" or greater.  
 Length of joint (j):  $\pm \frac{1}{4}$ ".  
 Wall thickness (T): not less than design T by more than 5% or  $\frac{3}{16}$ ", whichever is greater.  
 Laying length: shall not underrun by more than  $\frac{1}{2}$ ".



**GENERAL NOTES:**

Construction of R. C. P. shall conform to the requirements of Section 990 of the Specifications.

Not more than 2 four-foot sections shall be permitted near the ends of any culvert. Four-foot lengths shall be used only to secure the required length of culvert.

Diam. (in.)	Approx. Wt./Ft. (lb.)	T (in.)	J (in.)	D1 (in.)	D2 (in.)	D3 (in.)	D4 (in.)
12	92	2	1 3/4	13 1/4	13 5/8	13 3/8	14 1/4
15	127	2 1/4	2	16 1/2	16 3/8	17 1/4	17 5/8
18	168	2 1/2	2 1/4	19 5/8	20	20 3/8	20 3/4
21	214	2 3/4	2 1/2	22 1/8	23 1/4	23 3/4	24 1/8
24	265	3	2 3/4	26	26 3/8	27	27 3/8
27	322	3 1/4	3	29 1/4	29 5/8	30 1/4	30 5/8
30	384	3 1/2	3 1/4	32 3/8	32 3/4	33 1/2	33 3/8
36	524	4	3 3/4	38 3/4	39 1/4	40	40 1/2
42	685	4 1/2	4	45 1/8	45 5/8	46 1/2	47
48	867	5	4 1/2	51 1/2	52	53	53 1/2
54	1070	5 1/2	4 1/2	57 1/8	58 3/8	59 3/8	59 7/8
60	1296	6	5	64 1/4	64 3/4	66	66 1/2
66	1542	6 1/2	5 1/2	70 5/8	71 1/8	72 1/2	73
72	1810	7	6	77	77 1/2	79	79 1/2
78	2098	7 1/2	6 1/2	83 3/8	83 3/8	85 5/8	86 1/8
84	2410	8	7	89 3/4	90 1/4	92 1/8	92 5/8
90	2740	8 1/2	7	95 3/4	96 1/4	98 1/8	98 5/8
96	2950	9	7	102 1/8	102 5/8	104 1/2	105
102	3075	9 1/2	7 1/2	109	109 1/2	111 1/2	112
108	3870	10	7 1/2	115 1/2	116	118	118 1/2

June 26, 2015


<b>S D D O T</b>	<b>REINFORCED CONCRETE PIPE</b>	PLATE NUMBER 450.01
		Sheet 1 of 1

Published Date: 2024

PLOT NAME - 4

FILE - ... \STANDARDPLATES\_06PN.DGN

.PLOTTED FROM - TRM111118



**TOLERANCES IN DIMENSIONS**

Radial dimensions at joints:  $\pm \frac{1}{8}$ " for 65" span or less and  $\pm \frac{1}{4}$ " for longer spans.  
 Rise and Span:  $\pm 2\%$  of tabular values.  
 Length of Joint (J):  $\pm \frac{1}{4}$ ".  
 Wall thickness (T): not less than design T by more than 5% or  $\frac{3}{16}$ ", whichever is greater.  
 Laying length: shall not underrun by more than  $\frac{1}{2}$ ".

Gravel Bedding Material shall be supplied for 102" to 169" spans. It shall be placed to a thickness of 6" (Min.) x 85% of the Span x Length of culvert and shall conform to the gradation requirements for gravel surfacing except material may be screened or may be plan provided material.

* Size (in.)	Approx. Wt./Ft. (lb.)	Rise (in.)	Span (in.)	T (in.)	a (in.)	b (in.)	c (in.)	j (in.)	e (in.)	f (in.)	g (in.)	R1 (in.)	R2 (in.)	R3 (in.)
18	170	13 1/2	22	2 1/2	1 3/8	3/8	3/4	2	1 1/8	3/8	1	27 1/2	13 3/4	5 1/4
24	320	18	28 1/2	3 1/2	1 5/8	1/2	1 3/8	3	1 3/8	1/2	1 5/8	40 1/16	14 3/4	4 5/8
30	450	22 1/2	36 1/4	4	1 13/16	5/8	1 9/16	3 1/2	1 9/16	5/8	1 13/16	51	18 3/4	6 1/8
36	600	26 5/8	43 3/4	4 1/2	2	3/4	1 3/4	4	1 3/4	3/4	2	62	22 1/2	6 1/2
42	740	31 5/16	51 1/8	4 1/2	2	3/4	1 3/4	4	1 3/4	3/4	2	73	26 1/4	7 3/4
48	890	36	58 1/2	5	2 1/4	3/4	2	5	2	3/4	2 1/4	84	30	8 7/8
54	1100	40	65	5 1/2	2 1/2	3/4	2 1/4	5	2 1/4	3/4	2 1/2	92 1/2	33 3/8	10
60	1400	45	73 1/2	6	3 5/16	3/4	1 5/16	5	2 3/4	3/4	2 1/2	105	37 1/2	11
72	1900	54	88	7	3 13/16	1	2 3/16	6	3 1/4	1	2 3/4	126	45	13 5/16
84	2500	62	102	8	4 1/8	1	2 7/8	6	3 1/2	1	3 1/2	162 1/2	52	14 1/2
96	3300	78	122 3/8	9	4 1/2	1	3 1/2	7	4	1	4	218	62	20
108	4200	88	138 1/2	10	5	1	4	7	4 1/2	1	4 1/2	269	70	22
120	5100	96 7/8	154	11	5 1/2	1	4 1/2	7	5	1	5	301 3/8	78	24
132	5100	106 1/2	168 3/4	10		1	4	7	4 1/2	1	4 1/2	329	85 5/8	26 1/8

\* Equivalent Diameter of Circular R. C. P.

**GENERAL NOTES:**

Construction of R.C.P. Arch shall conform to the requirements of Section 990 of the Specifications. Not more than 2 four-foot sections shall be permitted near the ends of any culvert. Four-foot lengths shall be used only to secure the required length of culvert.


June 26, 2015

<b>S D D O T</b>	<b>REINFORCED CONCRETE PIPE ARCH</b>	PLATE NUMBER 450.02
		Sheet 1 of 1


Published Date: 2024



Plotting Date: 01/04/2024



**TOP VIEW**




**SLOPE DETAIL**


**GENERAL NOTES:**

Lengths of concrete pipe shown on plan sheets are between flared ends only.

Construction of R.C.P. Flared End shall conform to the requirements of Section 990 of the Specifications.



**LONGITUDINAL SECTION**



**END VIEW**

Dia. (in.)	Approx. Wt. of Section (lbs.)	Approx. Slope (X to Y)	T (in.)	A (in.)	B (in.)	C (in.)	D (in.)	E (in.)	G (in.)	R (in.)
12	530	2.4:1	2	4	24	48 1/8	72 7/8	24	2	1 1/2
15	740	2.4:1	2 1/4	6	27	46	73	30	2 1/4	1 1/2
18	990	2.3:1	2 1/2	9	27	46	73	36	2 1/2	1 1/2
21	1280	2.4:1	2 3/4	9	36	37 1/2	73 1/2	42	2 3/4	1 1/2
24	1520	2.5:1	3	9 1/2	43 1/2	30	73 1/2	48	3	1 1/2
27	1930	2.5:1	3 1/4	10 1/2	49 1/2	24	73 1/2	54	3 1/4	1 1/2
30	2190	2.5:1	3 1/2	12	54	19 3/4	73 3/4	60	3 1/2	1 1/2
36	4100	2.5:1	4	15	63	34 3/4	97 3/4	72	4	1 1/2
42	5380	2.5:1	4 1/2	21	63	35	98	78	4 1/2	1 1/2
48	6550	2.5:1	5	24	72	26	98	84	5	1 1/2
54	8240	2:1	5 1/2	27	65	33 1/4	98 1/4	90	5 1/2	1 1/2
60	8730	1.9:1	6	35	60	39	99	96	5	1 1/2
66	10710	1.7:1	6 1/2	30	72	27	99	102	5 1/2	1 1/2
72	12520	1.8:1	7	36	78	21	99	108	6	1 1/2
78	14770	1.8:1	7 1/2	36	90	21	111	114	6 1/2	1 1/2
84	18160	1.6:1	8	36	90 1/2	21	111 1/2	120	6 1/2	1 1/2
90	20900	1.5:1	8 1/2	41	87 1/2	24	111 1/2	132	6 1/2	6

June 26, 2015


**S  
D  
D  
O  
T**

**R. C. P. FLARED ENDS**


**PLATE NUMBER  
450.10**

Sheet 1 of 1

Published Date: 2024




**TOP VIEW**




**SLOPE DETAIL**

See Standard Plate 450.18 (TIE BOLTS FOR R.C.P. AND R.C.P. ARCH)



**LONGITUDINAL SECTION**



**END VIEW**

**GENERAL NOTES:**

Lengths of concrete pipe shown on plan sheets are between flared ends only.

Construction of R.C.P. Arch Flared End shall conform to the requirements of Section 990 of the Specifications.

* Size (in.)	Approximate Weight of Section (lbs.)	Rise (in.)	Span (in.)	Slope (X:Y)	T (in.)	A (in.)	B (in.)	C (in.)	D (in.)	E (in.)	R (in.)
18	1100	13 1/2	22	3:1	2 1/2	7	27	45	72	36	2
24	1750	18	28 1/2	3:1	3 1/2	8 1/2	39	33	72	48	3
30	3300	22 1/2	36 1/4	3:1	4	9 1/2	50	46	96	60	3
36	4350	26 5/8	43 3/4	3:1	4 1/2	11 1/8	60	36	96	72	6
42	5250	31 5/16	51 1/8	3:1	4 1/2	15 13/16	60	36	96	78	6
48	6400	36	58 1/2	3:1	5	21	60	36	96	84	6
54	7850	40	65	3:1	5 1/2	25 1/2	60	36	96	90	6
60	9500	45	73 1/2	3:1	6	31	60	36	96	96	6
72	13550	54	88	2:1	7	31	60	39	99	120	6
84	17950	62	102	2:1	8	28 1/2	83	19	102	144	6

\*Equivalent Diameter of Circular R. C. P.

June 26, 2015

**S  
D  
D  
O  
T**

**R. C. P. ARCH FLARED ENDS**

**PLATE NUMBER  
450.11**


Sheet 1 of 1

Published Date: 2024

Plotting Date: 01/04/2024

Wall "t" (in.)	Rod Dia. (in.)	Pipe Sleeve Dia. (nominal)
≤ 3/4	5/8	3/4
3/2-6/2	3/4	1
≥ 7	1	1 1/4


**GENERAL NOTES:**  
 Tie bolts shall conform to ASTM F1554 Grade 36 or ASTM A36. Nuts shall be heavy hex conforming to ASTM A563. Washers shall conform to ASTM F436.  
 Pipe Sleeve shall conform to ASTM A500 or A53, Grade B.  
 Galvanize adjustable eye bolt tie assembly in accordance with ASTM A153.



**ADJUSTABLE EYE BOLT TIE**


Pipe Dia. (in.)	"L" (in.)	Bolt Dia. (in.)
≤ 48	4	3/4
> 48	6	1

**GENERAL NOTES:**  
 Angles shall conform to ASTM A36.  
 Bolts shall conform to ASTM A307. Nuts shall be heavy hex conforming to ASTM A563. Washers shall conform to ASTM F436.  
 Galvanize angles, bolts, nuts, and washers in accordance with ASTM A153.



**ANGLE AND BOLT TIE**

**GENERAL NOTES:**  
 In lieu of the tie bolts detailed above other types of tie bolt connections may be installed as approved by the Office of Bridge Design.  
 All pipe sections of R.C.P. and R.C.P. Arch shall be tied with tie bolts except for pipe located between drop inlets, manholes, and junction boxes. All pipe sections of pipes that only enter or exit drop inlets, manhole, and junction boxes shall be tied with tie bolts.  
 There will be no separate measurement or payment for the tie bolts. The cost for furnishing and installing the tie bolts shall be incidental to the contract unit price per foot for the corresponding bid item for R.C.P. or R.C.P. Arch.




**END VIEW "CIRCULAR"      END VIEW "ARCH"**

February 28, 2013

<b>S D D O T</b>	<b>TIE BOLTS FOR R.C.P. AND R.C.P. ARCH</b>	PLATE NUMBER <b>450.18</b>
		Sheet 1 of 1

Published Date: 2024



TYPE	DESCRIPTION	LINE POST SPACING	WIRE GAGE	BARBED WIRE		WOVEN WIRE
				NUMBER AND SHAPE OF BARBS	STYLE OR DESIGN NO.	
1	3 Barbed Wires	16'-6"	12 1/2	2 Point Round	—	—
2	4 Barbed Wires	16'-6"	12 1/2	2 Point Round	—	—
3	5 Barbed Wires	16'-6"	12 1/2	2 Point Round	—	—
4	26" Woven Wire with 2 Barbed Wires	14'-0"	12 1/2	2 Point Round	—	726-6-12 1/2
5	26" Woven Wire with 4 Barbed Wires	14'-0"	12 1/2	2 wires with 2 Pt. Rd. 2 wires with 4 Pt. Rd.	—	726-6-12 1/2
6	32" Woven Wire with 3 Barbed Wires	14'-0"	12 1/2	2 wires with 2 Pt. Rd. 1 wire with 4 Pt. Rd.	—	832-6-12 1/2

**GENERAL NOTES:**  
 Fence types designated on the plans that are followed by the letter S will have smooth (barbless) wires.  
 When type 5S or 6S is designated the bottom wire may be barbed, smooth, or left off.  
 All degrees of curvature stated for fence are at centerline of roadway.

<b>S D D O T</b>	<b>RIGHT-OF-WAY FENCE</b>	PLATE NUMBER <b>620.01</b>
		Sheet 1 of 1


Published Date: 2024

PLOT SCALE - 1:200

PLOTTED FROM - TRM111118

PLOT NAME - 6

FILE - ... \STANDARDPLATES\_06PN.DGN



**STAPLE INSTALLATION**

**GENERAL NOTES:**

The Right-of-Way fence will consist of barbed wire or a combination of woven wire and barbed wire. The barbed wire and/or woven wire will be fastened to all wood posts or fastened to alternating wood and steel posts. Only wood posts will be used for brace panels. Gates will be of the type designated in the plans or as otherwise directed by the Engineer. Fence will be constructed conforming to the details on the standard plates and in the plans unless otherwise directed by the Engineer.

Right-of-Way fence on Interstate Projects will be constructed one foot within the Interstate Right-of-Way lines except at bridge openings, cattle passes, and as otherwise directed by the Engineer.


Right-of-Way fence other than on Interstate Projects will be constructed within one foot of the Right-of-Way on the Landowner's side except at bridge openings, cattle passes, and as otherwise directed by the Engineer.

Barbs will be fabricated from zinc coated 14 ga. wire. Two point barbs will be wrapped twice around one main strand at four-inch spacings and the four point barbs will be interlocked and wrapped around both main strands at five-inch spacings.

The gages of wire and wood post lengths and sizes are the minimum acceptable unless otherwise specified in the plans. The tolerances for steel posts will be as stated in AASHTO M281. Woven wire will conform to design and specifications of ASTM A116 and barbed wire will conform to ASTM A121.


June 26, 2019

<i>Published Date: 2024</i>	<b>S D D O T</b>	<b>STAPLE INSTALLATION AND GENERAL RIGHT-OF-WAY FENCE NOTES</b>	PLATE NUMBER <b>620.02</b>
			Sheet 1 of 1



**ELEVATION VIEW**  
(2 Post Panel)

**DETAIL A**



**ELEVATION VIEW**  
(3 Post Panel)

**DETAIL B**

**GENERAL NOTES:**

Two Post Panels will be installed at least every 1320' between corners.

Two Post Panels will be installed at any sharp vertical angle crest points and as directed by the Engineer.

Horizontal wood braces will consist of 4" dia. x 8' wood posts or rough 4" x 4" x 8' timbers.

Diagonal brace wires will be fabricated with 4 strands of 9 Ga. galvanized wire twisted tight. The diagonal brace wires will be installed in accordance with the direction of the fence pull. Two diagonal brace wires are required if fence pull is in both directions.

January 22, 2023

<i>Published Date: 2024</i>	<b>S D D O T</b>	<b>BRACE PANELS AND APPLICATIONS OF BRACE PANELS</b>	PLATE NUMBER <b>620.03</b>
			Sheet 1 of 3

SPACING OF 2 POST PANELS WITHIN CURVES	
RADIUS OF CURVE	SPACING OF 2 POST PANEL
Greater than 1800 Ft.	** 1320'
Less than 1800 Ft.	** At P.C., P.T., and at every 1320' between P.C. and P.T.

**GENERAL NOTE:**


All degrees of curvature stated for fence are at centerline of roadway.

If fence length is less than 600' to next corner use a 2 post panel.



\* If fence length is greater than 600' to next corner use a 3 post panel.

\*\* Fence lengths greater than 1320' and less than 2640' place 2 Post Panel approximately at midpoint.


① See Detail B on Sheet 1 of 3.







**BEGIN OR END FENCE**  
(Where new fence ties into existing fence)




**SHORT JOGS IN FENCE**




**CROSS FENCE**



**SHARP ANGLES IN CROSS FENCE**



Additional fence panel is NOT required when an angle in the mainline fence is 10° and less.



Additional fence panel is required when an angle in the mainline fence is greater than 10°.



**ANGLES IN MAINLINE FENCE**

January 22, 2023




Published Date: 2024	S D D O T	BRACE PANELS AND APPLICATIONS OF BRACE PANELS	PLATE NUMBER 620.03
			Sheet 2 of 3




**ENTRANCE**  
(Not on corner)



Fence type will be same as adjacent fence type or as directed by the Engineer.



**DOUBLE ENTRANCES**



**ENTRANCES AT CORNERS**

**GATES**

Fence type will be same as adjacent fence type or as directed by the Engineer.


\* If fence length is less than 600' to next corner use a 2 post panel.  
\* If fence length is greater than 600' to next corner use a 3 post panel.

① See Detail B on Sheet 1 of 3.

January 22, 2023

Published Date: 2024	S D D O T	BRACE PANELS AND APPLICATIONS OF BRACE PANELS	PLATE NUMBER 620.03
			Sheet 3 of 3

PLOT SCALE - 1:200



**GENERAL NOTES:**

**TRANSVERSE SECTION**

Asphalt concrete will be the same type used elsewhere on the project or will be as specified in the plans. If asphalt concrete is not specified in the plans, the asphalt concrete will conform to the Specifications for "Asphalt Concrete Composite."

Granular material will be the same type used elsewhere on the project or will be as specified in the plans. If granular material type is not specified in the plans, the material will conform to the Specifications for "Base Course". The granular material will be placed the same thickness as the mainline surfacing or as specified in the plans.

Topsoil is not shown in the transverse section drawing.


☑ The post and blockout illustrated above is typical for single thrie beam guardrail. When other variations of posts and blockouts are specified on other standard plates (e.g. transitions) then the posts and blockouts will be as specified on the other standard plates or as specified in the plans.

Slots in the rails will be provided as specified in the plans and by the manufacturer. A drilled hole through the rail is not allowed as a replacement for a slot. If the Contractor must create a slot, a cutting torch or plasma cutter is not allowed. The slot edges will be smooth and free of burrs or notches.

The top of post and top of block will have a true square cut. The top of block will be a maximum of  $\pm 1/2$  inch from the top of the post.

<b>S D D O T</b>	<b>THRIE BEAM GUARDRAIL</b>	PLATE NUMBER <b>630.01</b>	September 14, 2019
		Sheet 1 of 5	

Published Date: 2024



<b>S D D O T</b>	<b>THRIE BEAM GUARDRAIL</b>	PLATE NUMBER <b>630.01</b>	September 14, 2019
		Sheet 2 of 5	

Published Date: 2024

FILE - ... \STANDARDPLATES\_06PN.DGN PLOT NAME - 9


PLOTTED FROM - TRM111118

Plotting Date: 01/04/2024


PLOT SCALE - 1:200

PLOT NAME - 10

FILE - ... \STANDARDPLATES\_06PN.DGN



<b>Published Date: 2024</b>	<b>S D D O T</b>	<b>THRIE BEAM GUARDRAIL</b>	September 14, 2019
			PLATE NUMBER <b>630.01</b>
			Sheet 3 of 5




<b>Published Date: 2024</b>	<b>S D D O T</b>	<b>THRIE BEAM GUARDRAIL</b>	September 14, 2019
			PLATE NUMBER <b>630.01</b>
			Sheet 4 of 5

PLOTTED FROM - TRM111118

PLOT SCALE - 1:200

PLOT NAME - 11



September 14, 2019

<b>SDDOT</b>	<b>THRIE BEAM GUARDRAIL</b>	PLATE NUMBER 630.01
		Sheet 5 of 5

Published Date: 2024

TYPE AND DETAILS OF MGS						
Type of MGS	W Beam Rail Single or Double (Nested)	Blockout Size	Blockout Material	Post Size	Post Material	Post Spacing
1	Single	6"x12"x14"	Wood	6"x8"x6'-0"	Wood	6'-3"
1C	Single	6"x12"x14"	Wood	6"x8"x7'-6"	Wood	6'-3"
2	Single	6"x12"x14"	Wood	6"x8"x6'-0"	Wood	3'-1 1/2"
3	Single	6"x12"x14"	Wood	6"x8"x6'-0"	Wood	1'-6 3/4"
4	Double	6"x12"x14"	Wood	6"x8"x6'-0"	Wood	6'-3"

STANDARD PLATE REFERENCE	
Type of MGS	See Standard Plate(s)
1	630.20, 630.22
1C	630.20, 630.25
2	630.20
3	630.20
4	630.20

**GENERAL NOTES:**

Asphalt concrete will be the same type used elsewhere on the project or will be as specified in the plans. If asphalt concrete is not specified in the plans, the asphalt concrete will conform to the Specifications for "Asphalt Concrete Composite".

Granular material will be the same type used elsewhere on the project or will be as specified in the plans. If granular material type is not specified in the plans, the material will conform to the Specifications for "Base Course". The granular material will be placed the same thickness as the mainline surfacing or as specified in the plans.

Topsoil is not shown in the transverse section drawing on sheet 2 of 6.

All W beam rail will be Type 1 and Class A (12 Ga.) unless specified otherwise in the plans.

W beam rail section lengths may be 12'-6" and/or 25'-0". The combination of section lengths used will be compatible with the total length of rail per site as shown in the plans.

Slots in the rails will be provided as specified in the plans and by the manufacturer. A drilled hole through the rail is not allowed as a replacement for a slot. If the Contractor must create a slot, a cutting torch or plasma cutter is not allowed. The slot edges will be smooth and free of burrs or notches.

All costs for constructing the MGS including labor, equipment, and materials including all posts, blockouts, steel beam rail, and hardware will be incidental to the contract unit price per foot for the respective MGS contract item.

September 14, 2019


<b>SDDOT</b>	<b>MIDWEST GUARDRAIL SYSTEM (MGS)</b>	PLATE NUMBER 630.20
		Sheet 1 of 6

Published Date: 2024


PLOTTED FROM - TRM111118

FILE - ... \STANDARDPLATES\_06PN.DGN

Plotting Date: 01/04/2024



**TOP VIEW**  
(Type 1, 2, or 3 MGS Installation)




**TRANSVERSE SECTION**  
(Type 1, 2, or 3 MGS Installation)

- \* See Standard Plate 630.99
- \*\* 2" asphalt concrete or as specified in the plans.
- \*\*\* The cross slope will be as specified in the plans; however, the cross slope will not be steeper than a 10:1 slope.


September 14, 2019

<b>S D D O T</b>	<b>MIDWEST GUARDRAIL SYSTEM (MGS)</b>	PLATE NUMBER <b>630.20</b>
		Sheet 2 of 6

Published Date: 2024



**EXPANDED ISOMETRIC VIEW OF TYPE 1 MGS**



**EXPANDED ISOMETRIC VIEW OF DOUBLE (NESTED) RAIL**  
(For Information Only, Not to Scale)

September 14, 2019

<b>S D D O T</b>	<b>MIDWEST GUARDRAIL SYSTEM (MGS)</b>	PLATE NUMBER <b>630.20</b>
		Sheet 3 of 6

Published Date: 2024

PLOT SCALE - 1:200

.PLOTTED FROM - TRM111118

PLOT NAME - 12

FILE - ... \STANDARDPLATES\_06PN.DGN




Plotting Date: 01/04/2024


PLOT SCALE - 1:200

PLOT NAME - 13

FILE - ... \STANDARDPLATES\_06PN.DGN



Published Date: 2024	S D D O T	MIDWEST GUARDRAIL SYSTEM (MGS)	September 14, 2019
			PLATE NUMBER 630.20
			Sheet 4 of 6




Published Date: 2024	S D D O T	MIDWEST GUARDRAIL SYSTEM (MGS)	September 14, 2019
			PLATE NUMBER 630.20
			Sheet 5 of 6

PLOTTED FROM - TRM111118

PLOT SCALE - 1:200

PLOT NAME - 14


FILE - ... \STANDARDPLATES\_06PN.DGN



September 14, 2019

<b>S D D O T</b>	<b>MIDWEST GUARDRAIL SYSTEM (MGS)</b>	PLATE NUMBER <b>630.20</b>
		Sheet 6 of 6

Published Date: 2024



**GENERAL NOTES:**

Thrie Beam Terminal Connectors will be 10 gauge.



When the thrie beam terminal connector is used to connect the rail to the bridge or concrete end block, 1" steel washers will be used at the lap splice and the washers will be in direct contact with the 3" slots of the thrie beam terminal connector. See the drawings above for the typical locations of the 1" steel washers.

There will be no separate payment for furnishing and installing the thrie beam terminal connector. All costs for furnishing and installing the thrie beam terminal connector will be incidental to the contract unit price of the respective guardrail item it is attached to.

September 14, 2019

<b>S D D O T</b>	<b>THRIE BEAM TERMINAL CONNECTOR</b>	PLATE NUMBER <b>630.47</b>
		Sheet 1 of 1

Published Date: 2024



Published Date: 2024

**SD DDT**  
 ASYMMETRICAL W BEAM TO THRIE BEAM GUARDRAIL TRANSITION SECTION

PLATE NUMBER  
 630.49  
 Sheet 1 of 1


Published Date: 2024

**SD DDT**  
 TYPE 1 RETROFIT GUARDRAIL TRANSITION (CONCRETE END BLOCK TO MIDWEST GUARDRAIL SYSTEM (MGS))

PLATE NUMBER  
 630.51  
 Sheet 1 of 3

STATE OF SOUTH DAKOTA	PROJECT NH 0037(164)24	SHEET 51	TOTAL SHEETS 63
-----------------------	---------------------------	-------------	--------------------

Plotting Date: 01/04/2024



**GENERAL NOTES FOR INSTALLING THREADED RODS INTO CONCRETE:**

⊕ The dimensions shown are estimated based on original construction plans of the concrete end block. The special wood blockout will be cut as necessary such that the front face of the special wood blockout will align with the vertical front face of the concrete end block ± 1/2".

The threaded rods will be 1/2" diameter and conform to ASTM F1554, Grade 55. The threaded rods will be embedded a minimum of 5" into the concrete.

The diameter of the drilled holes will not be less than 1/8" greater or more than 3/8" greater than the diameter of the threaded rods or as per the Manufacturer's recommendations. The holes will not be drilled using core bits. The drilled holes will be blown out with compressed air using a device that will reach the back of the hole to ensure that all debris or loose material has been removed prior to the epoxy injection.


The epoxy resin mixture will be of a type for bonding steel to hardened concrete and will conform to AASHTO M235 Type IV, Grade 3 (Equivalent to ASTM C881, Type IV, Grade 3).

Mix epoxy resin as recommended by the Manufacturer and apply by an injection method as approved by the Engineer. Beginning at the back of the drilled holes, fill the holes 1/3 to 1/2 full of epoxy, or as recommended by the Manufacturer, prior to insertion of the steel rod. Rotate the steel rod during installation to eliminate voids and ensure complete bonding of the rod. Insertion of the rods by the dipping or painting methods will not be allowed.

Loads will not be applied to the epoxy grouted threaded rods until the epoxy resin has had sufficient time to cure as specified by the epoxy resin Manufacturer.

September 14, 2019

<b>S D D O T</b>	<b>TYPE 1 RETROFIT GUARDRAIL TRANSITION (CONCRETE END BLOCK TO MIDWEST GUARDRAIL SYSTEM (MGS))</b>	PLATE NUMBER 630.51
		Sheet 2 of 3
Published Date: 2024		



**GENERAL NOTES:**

Throughout the type 1 retrofit guardrail transition, slots in the rails will be provided as specified in the plans and by the Manufacturer. A drilled hole through the rail is not allowed as a replacement for a slot. If the Contractor must create a slot, a cutting torch or plasma cutter is not allowed. The slot edges will be smooth and free of burrs or notches.

All costs for furnishing and installing the type 1 retrofit guardrail transition including labor, equipment, and materials which includes all rail sections, posts and blockouts, special blockout, hardware, and incidentals will be included in the contract unit price per each for "Type 1 Retrofit Guardrail Transition".

September 14, 2019

<b>S D D O T</b>	<b>TYPE 1 RETROFIT GUARDRAIL TRANSITION (CONCRETE END BLOCK TO MIDWEST GUARDRAIL SYSTEM (MGS))</b>	PLATE NUMBER 630.51
		Sheet 3 of 3
Published Date: 2024		

PLOT SCALE - 1:200

PLOTTED FROM - TRM111118


PLOT NAME - 16

FILE - ... \STANDARDPLATES\_06PN.DGN



Plotting Date: 01/04/2024

PLOT SCALE - 1:200



**GENERAL NOTES:**

The W Beam guardrail shown is for illustrative purpose. The guardrail height for all types of guardrail systems except for high tension cable guardrail/barrier will be measured in accordance with this standard plate.

When measuring height of 3 cable guardrail (low tension) the height will be measured to the center of the top cable. See Detail A.


The height of high tension cable guardrail/barrier will be measured in accordance with the Manufacturer's installation instructions.

September 14, 2019

<b>S D D O T</b>	<b>MEASURING GUARDRAIL HEIGHT</b>	PLATE NUMBER <b>630.99</b>
		Sheet 1 of 1

Published Date: 2024

PLOTTED FROM - TRM111118



TYPE 2 OBJECT MARKER POST LENGTHS										
OFFSET (*)	1'	2'	3'	4'	5'	6'	7'	8'	Greater Than 8'	
<b>POST LENGTH (L)</b>										
<b>SLOPE</b>	3:1	8'-6"	8'-9"	9'-3"	9'-6"	9'-9"	10'-3"	10'-6"	10'-9"	8'-0"
	4:1	8'-6"	8'-9"	9'-0"	9'-3"	9'-9"	9'-9"	10'-0"	10'-3"	8'-0"
	5:1	8'-3"	8'-6"	8'-9"	9'-0"	9'-3"	9'-3"	9'-6"	9'-9"	8'-0"
	6:1	8'-3"	8'-6"	8'-9"	8'-9"	9'-0"	9'-3"	9'-3"	9'-6"	8'-0"

**GENERAL NOTES:**

\*\*\* The type 2 object marker may be installed back to back when specified in the plans.  
Post Length L was calculated based on a shoulder width of 6 feet at a crossslope of 4 percent and L was rounded up to the nearest 3 inches.

\*\* Dimension A is 4 feet when the Offset \* is 8 feet and less. Dimension B is 4 feet when Offset \* is greater than 8 feet.

The type 2 object marker and the 1.12 lb/ft flanged channel steel post will be in conformance with Specifications Section 982.2 J.

Payment for the type 2 object marker will be in conformance with Specification Section 632.5 B.

December 23, 2019

<b>S D D O T</b>	<b>TYPE 2 OBJECT MARKER (DIRECT DRIVE)</b>	PLATE NUMBER <b>632.01</b>
		Sheet 1 of 1

Published Date: 2024



PLOT NAME - 18

FILE - ... \STANDARDPLATES\_06PN.DGN

PLOT SCALE - 1:200

PLOT NAME - 19

FILE - ... \STANDARDPLATES\_06PN.DGN





**GENERAL NOTES:**

This standard plate will be used in conjunction with standard plate 632.01.

\* The type 2 object markers will be installed at the locations shown above. The type 2 object markers, single faced or back to back, will be as specified in the plans.

December 23, 2019

<i>Published Date: 2024</i>	S D D O T	<b>TYPE 2 OBJECT MARKER AT PIPE CULVERTS, BOX CULVERTS, AND CATTLE PASSES (Less than 60" Overall Width)</b>	PLATE NUMBER 632.03
			Sheet 1 of 1




**GENERAL NOTES:**

This standard plate will be used in conjunction with standard plate 632.01.

\* The type 2 object markers will be installed at the locations shown above. The type 2 object markers, single faced or back to back, will be as specified in the plans.

December 23, 2019

<i>Published Date: 2024</i>	S D D O T	<b>TYPE 2 OBJECT MARKER AT PIPE CULVERTS, BOX CULVERTS, AND CATTLE PASSES (60" and Greater Overall Width)</b>	PLATE NUMBER 632.04
			Sheet 1 of 1



**DETAIL T**  
(Provide a Type 2 Object Marker if a Trailing End Terminal is installed)

**PLAN VIEW**  
(Typical Guardrail Layouts)


- (B)** Steel Beam Guardrail Delineation
- (E)** Guardrail End Terminal Object Marker
- (C)** 3 Cable Guardrail (Low Tension) Delineation
- (HT)** High Tension Cable Guardrail Delineation
- (M)** Type 2 Object Marker

\*For two-way traffic, install delineation at the opposite end of structure the same as shown. Back-to-back delineation is required for two-way traffic, single-sided delineation for one-way traffic.


December 23, 2019

<b>S D D O T</b>	<b>DELINEATION OF GUARDRAIL</b>	PLATE NUMBER <b>632.40</b>
		Sheet 1 of 4



Published Date: 2024



**(B) STEEL BEAM GUARDRAIL DELINEATION**



**DELINEATOR**  
(For Steel Beam Guardrail)



**ADHESIVE OBJECT MARKER**

**(E) GUARDRAIL END TERMINAL OBJECT MARKER**

Adhesive object marker dimensions may vary due to shape of terminal end. A minimum of 256 square inches of object marker sheeting area is required. The sheeting will be fluorescent yellow.

December 23, 2019

<b>S D D O T</b>	<b>DELINEATION OF GUARDRAIL</b>	PLATE NUMBER <b>632.40</b>
		Sheet 2 of 4


Published Date: 2024



PLOT SCALE - 1:200

PLOT NAME - 21

FILE - ... \STANDARDPLATES\_06PN.DGN



December 23, 2019

<b>S D D O T</b>	<b>DELINEATION OF GUARDRAIL</b>	PLATE NUMBER <b>632.40</b>
		Sheet 3 of 4

Published Date: 2024

**GENERAL NOTES:**

The delineation of high tension cable guardrail will be reflective sheeting placed back to back on every other post cap or cable spacer. The sheeting will be type XI in conformance with ASTM D4956. The color of the reflective sheeting shall be the same as the nearest pavement marking.

The delineators for steel beam guardrail and sheeting on 3 cable guardrail (low tension) posts will be covered with a minimum of 16 square inches of reflective sheeting. The reflective sheeting will be type XI in conformance with ASTM D4956. Along two-way roadways the sheeting will be on both sides of the delineators and guardrail posts and will be white in color. For one-way roadways the sheeting will only be required on the side facing traffic and the color will be the same as the nearest pavement marking, yellow on the left side of the roadway and white on the right side.

When steel beam guardrail is attached to a bridge the first delineator will be attached to the post nearest the bridge.

At bridges with guardrail less than 200 feet in length, a minimum of 4 delineators will be placed in addition to the end terminal yellow object marker. The spacing between the delineators will be approximately one third of the length of the guardrail.

At bridges with guardrail 200 feet and greater in length, including bridges that have steel beam guardrail transitioning to 3 cable guardrail (low tension), the delineators will be placed at a spacing of approximately 50 feet. Delineation will extend throughout the length of the guardrail system.

Steel beam guardrail that is not attached to a bridge and is less than 200 feet in length, a minimum of 4 delineators will be placed in addition to the end terminal yellow object markers. The spacing between the delineators will be approximately one third of the length of the guardrail.

Steel beam guardrail that is not attached to a bridge and is 200 feet and greater in length, including steel beam guardrail transitioning to 3 cable guardrail (low tension), the delineators will be placed at a spacing of approximately 50 feet. Delineation will extend throughout the length of the guardrail system.

All costs for furnishing and installing single or back to back guardrail delineation on 3 cable guardrail and steel beam guardrail will be included in the contract unit price per each for "Guardrail Delineator".

All costs for furnishing and installing the reflective sheeting on the cable spacers or post caps for the high tension cable guardrail will be incidental to the respective high tension cable guardrail contract item.

An adhesive object marker will be placed on the end of the W beam guardrail or MGS end terminal. The adhesive object marker dimensions may vary due to the shape of the terminal end. A minimum of 256 square inches of object marker reflective sheeting area is required. The reflective sheeting will be fluorescent yellow type XI sheeting in conformance with ASTM D4956. All costs for furnishing and installing the adhesive object marker will be incidental to various contract items.


A type 2 object marker will be placed adjacent to the 3 cable guardrail (low tension) anchor, high tension cable guardrail anchor, and trailing end terminal at the location noted on sheet 1 of this standard plate. The type 2 object marker (6" x 12") will have fluorescent yellow type XI sheeting in conformance with ASTM D4956. All costs for furnishing and installing the type 2 object marker including the steel post, 6" x 12" reflective panel, and hardware will be included in the contract unit price per each for "Type 2 Object Marker" for single-sided and "Type 2 Object Marker Back to Back" for back to back type 2 object markers.

December 23, 2019

<b>S D D O T</b>	<b>DELINEATION OF GUARDRAIL</b>	PLATE NUMBER <b>632.40</b>
		Sheet 4 of 4

Published Date: 2024

PLOTTED FROM - TRM111118



**GABION DETAILS**

STANDARD SIZES					
SIZE	LENGTH	WIDTH	HEIGHT	NUMBER OF CELLS	CAPACITY (Cu. Yd.)
A	6'-0"	3'-0"	3'-0"	2	2.0
B	9'-0"	3'-0"	3'-0"	3	3.0
C	12'-0"	3'-0"	3'-0"	4	4.0
D	6'-0"	3'-0"	1'-6"	2	1.0
E	9'-0"	3'-0"	1'-6"	3	1.5
F	12'-0"	3'-0"	1'-6"	4	2.0
G	6'-0"	3'-0"	1'-0"	2	0.7
H	9'-0"	3'-0"	1'-0"	3	1.0
I	12'-0"	3'-0"	1'-0"	4	1.3

**GENERAL NOTES:**

Above dimensions subject to mill tolerances.

Lacing and internal connecting wire will be 0.0866 inch diameter steel wire ASTM A641, Class 3 soft temper measured after galvanizing and for PVC coated gabions will be 0.0866 inch diameter steel wire measured after galvanizing but before PVC coating.

The lacing procedure is as follows:

1. Cut a length of lacing wire approximately 1½ times the distance to be laced but not exceeding 5 feet.
2. Secure the wire terminal at the corner by looping and twisting.
3. Proceed lacing with alternating single and double loops at a spacing not to exceed 6 inches.
4. Securely fasten the other lacing wire terminal.


Wire lacing or interlocking type fasteners will be used for gabion assembly and final construction of gabion structures. Interlocking fasteners for galvanized gabions will be high tensile 0.120 inch diameter galvanized steel wire measured after galvanizing. The galvanizing will conform to ASTM A641-92, Class 3 coating. Fasteners will also be in accordance with ASTM A764, Class II, Type III.

Interlocking fasteners for PVC coated gabions will be high tensile 0.120 inch diameter stainless steel wire conforming to ASTM A313, Type 302, Class 1. The spacing of the interlocking fasteners during all phases of assembly and construction will not exceed 6 inches.

All fasteners will be placed where the mesh weaves around the selvage wire at the vertical and horizontal joints.

February 14, 2020

<b>S D D O T</b>	<b>BANK AND CHANNEL PROTECTION GABIONS</b>	PLATE NUMBER <b>720.01</b>
	Published Date: 2024	Sheet 1 of 1



February 14, 2020

<b>S D D O T</b>	<b>BANK AND CHANNEL PROTECTION GABION PLACEMENT UNDER PIPE END SECTIONS</b>	PLATE NUMBER <b>720.03</b>
	Published Date: 2024	Sheet 1 of 2

* ESTIMATED QUANTITIES			
Detail	Pipe Diameter (Inches)	Gabion (Cu. Yd.)	Type B Drainage Fabric (Sq. Yd.)
1	12, 18, and 24	4.5	15
2	30 and 36	6.0	19
3	42	10.0	29
4	48 and 54	12.0	34
5	60	15.5	43
6	66	17.0	47
7	72	21.5	57
8	78	26.0	68
9	84	27.0	70

RCP, RCP Arch, CMP, and CMP Arch

**GENERAL NOTES:**

Gabions at outlets of CMP and RCP will be placed under the end section a distance of 2 feet from the outlet end. For CMP end section installations, the upper fabric of the gabions will be modified to accommodate the metal end section as approved by the Engineer.


\* Gabion and type B drainage fabric quantities on this standard plate are based on standard gabion sizes D, E, and F as depicted on standard plate 720.01.

Type B drainage fabric will be placed under the gabions and around the exterior sides (perimeter) of the gabions as approved by the Engineer. The type B drainage fabric will be in conformance with Section 831 of the Specifications. Measurement and payment of the type B drainage fabric will be in conformance with Section 720 of the Specifications.


February 14, 2020

<b>S D D O T</b>	<b>BANK AND CHANNEL PROTECTION GABION PLACEMENT UNDER PIPE END SECTIONS</b>	PLATE NUMBER <b>720.03</b>
		Sheet 2 of 2


Published Date: 2024




**STANDARD DITCH SECTION**



**SLOPED DITCH SECTION**




**TRENCH DETAIL**



**MEDIAN SECTION**


The median will be shaped to the limits shown in this detail where the erosion control blanket will be placed.



\* Use a 4" (Min.) overlap wherever two widths of erosion control blanket are applied side by side.

\* Use a 6" (Min.) overlap wherever one roll of erosion control blanket ends and another begins.

**OVERLAP DETAIL**



**PIPE END DETAIL**

**GENERAL NOTES:**

Prior to placement of the erosion control blanket, the areas will be properly prepared, shaped, seeded, and fertilized.

Erosion control blanket will be unrolled in the direction of the flow of water when placed in ditches and on slopes. The upslope end of the erosion control blanket will be buried in a trench 6" wide by 6" deep. There will be at least a 6" overlap wherever one roll of erosion control blanket ends and another begins, with the upslope erosion control blanket placed on top of the downslope erosion control blanket.

The erosion control blanket will be pinned to the ground according to the manufacturer's installation recommendations.

After the placement of the erosion control blanket, the Contractor will fine grade along all edges of the blanket to maintain a uniform slope adjacent to the blanket and level any low spots which might prevent uniform and unrestricted flow of side drainage directly onto the erosion control blanket.

All ditch sections will be shaped when installing the erosion control blanket. All costs for shaping the ditches will be incidental to the contract unit price per foot for "Shaping for Erosion Control Blanket".


February 14, 2020

<b>S D D O T</b>	<b>EROSION CONTROL BLANKET</b>	PLATE NUMBER <b>734.01</b>
		Sheet 1 of 1

Published Date: 2024

Plotting Date: 01/04/2024

PLOT SCALE - 1:200




September 6, 2015

<b>SDDOT</b>	<b>MAILBOX TURNOUT</b>	PLATE NUMBER <b>900.01</b>
		Sheet 1 of 1

Published Date: 2024

PLOTTED FROM - TRM111118



**GENERAL NOTES: SPACING FOR MULTIPLE POST INSTALLATION**

The post support assemblies provided should be consistent throughout the project. Single and double mailboxes may be in any sequence.

Post support assemblies shall be one from the approved products list, a 4"x4" or 4" round wood post, or an alternate post support assembly that meets the test level 3 crash testing requirements of NCHRP 350 or MASH.

Alternate mailbox support assemblies shall be approved by the Engineer prior to installation. The Contractor shall provide the Engineer written certification that the mailbox support assembly has met the crash testing requirements and will be installed in accordance with the manufacturer's installation instructions.

September 6, 2013

<b>SDDOT</b>	<b>SINGLE AND DOUBLE MAILBOX ASSEMBLIES</b>	PLATE NUMBER <b>900.02</b>
		Sheet 1 of 1


Published Date: 2024

PLOT NAME - 24

FILE - ... \STANDARDPLATES\_06PN.DGN

STATE OF SOUTH DAKOTA	PROJECT <b>NH 0037(164)24</b>	SHEET <b>61</b>	TOTAL SHEETS <b>63</b>
-----------------------	----------------------------------	--------------------	---------------------------

Plotting Date: 01/04/2024




March 31, 2000

<b>S D D O T</b>	<b>MAILBOX SUPPORT HARDWARE</b>	PLATE NUMBER <b>900.03</b>
		Sheet 1 of 1


Published Date: 2024

# 18+66



STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	NH 0037(164)24	62	63

# 87+79



Install 36" - 74' RCP  
& 2 Flared Ends

STATE OF SOUTH DAKOTA	PROJECT	TOTAL SHEETS
NH 0037(164)24	87+79	63
	SHEET	63