

ESTIMATE OF QUANTITIES AND ENVIRONMENTAL COMMITMENTS

STATE OF	PROJECT	SHEET	TOTAL SHEETS
SOUTH DAKOTA	NH 0012(323)298	2	92

BID ITEM NUMBER	ITEM	QUANTITY	UNIT
009E0010	Mobilization	Lump Sum	LS
009E4200	Construction Schedule, Category II	Lump Sum	LS
110E1140	Remove Concrete Sidewalk	151.4	SqYd
110E1520	Remove Signal Equipment	Lump Sum	LS
110E1530	Remove Signal Pole Footing	1	Each
110E1570	Remove Pedestrian Push Button Pole	13	Each
250E0010	Incidental Work	Lump Sum	LS
634E0010	Flagging	20.0	Hour
634E0110	Traffic Control Signs	346.6	SqFt
634E0120	Traffic Control, Miscellaneous	Lump Sum	LS
634E0275	Type 3 Barricade	2	Each
634E0420	Type C Advance Warning Arrow Board	2	Each
634E0640	Temporary Pavement Marking	750	Ft
634E2000	Longitudinal Pedestrian Barricade	20	Ft
634E2015	Temporary Pedestrian Access Route	Lump Sum	LS
634E2020	Temporary Curb Ramp	12	Each
634E2025	Longitudinal Pedestrian Barrier	32	Ft
635E2000	Pedestal Signal Pole	1	Each
635E2135	Signal Pole with 35' Mast Arm and Luminaire Arm	1	Each
635E4100	5 Section Directional Vehicle Signal Head	2	Each
635E5030	3' Diameter Footing	24.0	Ft
635E5302	Type 2 Electrical Junction Box	3	Each
635E5303	Type 3 Electrical Junction Box	13	Each
635E5304	Type 4 Electrical Junction Box	6	Each
635E5313	Type 3A Electrical Junction box	2	Each
635E5880	Accessible Pedestrian Signal	104	Each
635E5910	Pedestrian Push Button Pole	13	Each
635E7018	Install Signal Pole with Mast Arm and Luminaire Arm	1	Each
635E7530	Relocate Signal Equipment	Lump Sum	LS
635E7600	Maintenance of Traffic Signal(s)	10	Hour
635E8120	2" Rigid Conduit, Schedule 40	30	Ft
635E9016	1/C #6 AWG Copper Wire	29,985	Ft
635E9502	2/C #14 AWG Copper Tray Cable, K2	13,825	Ft
635E9504	4/C #14 AWG Copper Tray Cable, K2	190	Ft
635E9507	7/C #14 AWG Copper Tray Cable, K2	4,750	Ft
635E9519	19/C #14 AWG Copper Tray Cable, K2	275	Ft
635E9524	24/C #14 AWG Copper Tray Cable, K2	7,475	Ft
635E9600	#16 AWG Copper Twisted Shielded Pair	5,530	Ft
635E9710	2/C #10 AWG Copper Pole and Bracket Cable	130	Ft
635E9800	Preemption Cable	7,020	Ft
651E0040	4" Concrete Sidewalk	1,363	SqFt
651E7000	Type 1 Detectable Warnings	170	SqFt
998E0100	Railroad Protective Insurance	Lump Sum	LS

SPECIFICATIONS

Standard Specifications for Roads and Bridges, 10-1-25 Version, Required Provisions, and Special Provisions as included in the Proposal. The Standard Specifications for Roads and Bridges is available for download and viewing at https://dot.sd.gov/doing-business/contractors/standard-specifications.

ENVIRONMENTAL COMMITMENTS

The SDDOT is committed to protecting the environment and uses Environmental Commitments as a communication tool for the Engineer and Contractor to ensure that attention is given to avoid, minimize, and/or mitigate an environmental impact. Environmental commitments to various agencies and the public have been made to secure approval of this project. An agency with permitting authority can delay a project if identified environmental impacts have not been adequately addressed. Unless otherwise designated, the Contractor's primary contact regarding matters associated with these commitments will be the Project Engineer. During construction, the Project Engineer will verify that the Contractor has met Environmental Commitment requirements. These environmental commitments are not subject to change without prior written approval from the SDDOT Environmental Office.

Additional guidance on SDDOT's Environmental Commitments can be accessed through the Environmental Procedures Manual found at: https://dot.sd.gov/media/documents/EnvironmentalProceduresManual.pdf >

For questions regarding change orders in the field that may have an effect on an Environmental Commitment, the Project Engineer will contact the Environmental Engineer at 605-773-3180 or 605-773-4336 to determine whether an environmental analysis and/or resource agency coordination is necessary.

Once construction is complete, the Project Engineer will review all environmental commitments for the project and document their completion.

COMMITMENT B: FEDERALLY THREATENED, ENDANGERED, AND PROTECTED SPECIES

COMMITMENT B2: WHOOPING CRANE

The Whooping Crane is a spring and fall migratory bird in South Dakota that is about 5 feet tall and typically stops on wetlands, rivers, and agricultural lands along their migration route. An adult Whooping Crane is white with a red crown and a long, dark, pointed bill. Immature Whooping Cranes are cinnamon brown. While in flight, their long necks are kept straight and their long dark legs trail behind. Adult Whooping Cranes' black wing tips are visible during flight.

Action Taken/Required:

Harassment or other measures to cause the Whooping Crane to leave the site is a violation of the Endangered Species Act. If a Whooping Crane is sighted roosting in the vicinity of the project, borrow pits, or staging areas associated with the project, cease construction activities in the affected area until the Whooping Crane departs and immediately contact the Project Engineer. The Project Engineer will contact the Environmental Office so that the sighting can be reported to USFWS.

COMMITMENT C: WATER SOURCE

Revised 6/11/2025 DLM 10/02/2025 MD

The Contractor will not withdraw water with equipment previously used outside the State of South Dakota or previously used in aquatic invasive species (AIS) positive waters within South Dakota without prior approval from the SDDOT Environmental Office. To prevent and control the introduction and spread of invasive species into the project vicinity, all equipment will be power washed with hot water (≥140 °F) and completely dried for a minimum of 7 days prior to subsequent use. South Dakota administrative rule 41:10:04:02 forbids the possession and transport of AIS; therefore, all attached dirt, mud, debris and vegetation must be removed and all compartments and tanks capable of holding standing water must be drained. This includes, but is not limited to, all equipment, pumps, lines, hoses and holding tanks.

Action Taken/Required:

The Contractor will obtain the necessary permits from the regulatory agencies such as the South Dakota Department of Agriculture and Natural Resources (DANR) and the United States Army Corps of Engineers (USACE) prior to water extraction activities.

Additional information and mapping of water sources impacted by Aquatic Invasive Species in South Dakota can be accessed at:

< https://sdleastwanted.sd.gov/maps/default.aspx>

< South Dakota Administrative Rule 41:10:04 Aquatic Invasive Species: https://sdlegislature.gov/rules/DisplayRule.aspx?Rule=41:10:04 >

COMMITMENT D: WATER QUALITY STANDARDS

COMMITMENT D1: SURFACE WATER QUALITY

This project may be in the vicinity of multiple streams and wetlands. These waters are considered waters of the state and are protected under Administrative Rules of South Dakota (ARSD) Chapter 74:51. Special construction measures may have to be taken to ensure that this water body is not impacted.

Action Taken/Required:

The Contractor is advised that the South Dakota Surface Water Quality Standards, administered by the South Dakota Department of Agriculture and Natural Resources (DANR), apply to this project. Special construction measures will be taken to ensure the above standard(s) of the surface waters are maintained and protected.

COMMITMENT E: STORM WATER

Construction activities constitute less than 1 acre of disturbance.

Action Taken/Required:

At a minimum and regardless of project size, appropriate erosion and sediment control measures must be installed to control the discharge of pollutants from the construction site.

COMMITMENT H: WASTE DISPOSAL SITE

The Contractor will furnish a site(s) for the disposal of construction and/or demolition debris generated by this project.

Action Taken/Required:

The waste disposal site(s) will be managed and reclaimed in accordance with the following from the General Permit for Construction/Demolition Debris Disposal Under the South Dakota Waste Management Program issued by the Department of Agriculture and Natural Resources.

The waste disposal site(s) will not be located in a wetland, within 200 feet of surface water, or in an area that adversely affects wildlife, recreation, aesthetic value of an area, or any threatened or endangered species, as approved by the Environmental Office and the Project Engineer.

If the waste disposal site(s) is located such that it is within view of any ROW, the following additional requirements will apply:

- 1. Construction and/or demolition debris consisting of concrete, asphalt concrete, or other similar materials will be buried in a trench separate from wood debris. The final cover over the construction and/or demolition debris will consist of a minimum of 1 foot of soil capable of supporting vegetation. Waste disposal sites provided outside of the Public ROW will be seeded in accordance with Natural Resources Conservation Service recommendations. The seeding recommendations may be obtained through the appropriate County NRCS Office. The Contractor will control the access to waste disposal sites not within the Public ROW with fences, gates, and placement of a sign or signs at the entrance to the site stating, "No Dumping Allowed".
- 2. Concrete and asphalt concrete debris may be stockpiled within view of the ROW for a period not to exceed the duration of the project. Prior to project completion, the waste will be removed from view of the ROW or buried, and the waste disposal site reclaimed as noted above.

The above requirements will not apply to waste disposal sites that are covered by an individual solid waste permit as specified in SDCL 34A-6-58, SDCL 34A-6-1.13, and ARSD 74:27:10:06.

Failure to comply with the requirements stated above may result in civil penalties in accordance with South Dakota Solid Waste Law, SDCL 34A-6-1.31.

All costs associated with furnishing waste disposal site(s), disposing of waste, maintaining control of access (fence, gates, and signs), and reclamation of the waste disposal site(s) will be incidental to the various contract items.

COMMITMENT I: HISTORIC PRESERVATION OFFICE CLEARANCES

The SDDOT has obtained concurrence with the State Historic Preservation Office (SHPO or THPO) for all work included within the project limits and all department designated sources and designated option material sources, stockpile sites, storage areas, and waste sites provided within the plans.

Action Taken/Required:

All earth disturbing activities not designated within the plans require a cultural resource review prior to scheduling the pre-construction meeting. This work includes but is not limited to: Contractor furnished material sources, material processing sites, stockpile sites, storage areas, plant sites, and waste areas.

The Contractor will arrange and pay for a record search and when necessary, a cultural resource survey. The Contractor has the option to contact the state Archaeological Research Center (ARC) at 605-394-1936 or another qualified archaeologist, to obtain either a records search or a cultural resources survey. A record search might be sufficient for review if the site was previously surveyed; however, a cultural resources survey may need to be conducted by a qualified archaeologist.

The Contractor will provide ARC with the following: a topographical map or aerial view in which the site is clearly outlined, site dimensions, project number, and PCN. If applicable, provide evidence that the site has been previously disturbed by farming, mining, or construction activities with a landowner statement that artifacts have not been found on the site.

The Contractor will submit the cultural resources survey report to SDDOT Environmental Office, 700 East Broadway Avenue, Pierre, SD 57501-2586. SDDOT will submit the information to the appropriate SHPO/THPO. Allow **30 Days** from the date this information is submitted to the Environmental Engineer for SHPO/THPO review.

In the event of an inadvertent discovery of human remains, funerary objects, or if evidence of cultural resources is identified during project construction activities, then such activities within 100 feet of the inadvertent discovery will immediately cease and the Project Engineer will be immediately notified. The Project Engineer will contact the SDDOT Environmental Office, who will contact the appropriate SHPO/THPO within 48 hours of the discovery to determine an appropriate course of action.

SHPO/THPO review does not relieve the Contractor of the responsibility for obtaining any additional permits and clearances for Contractor furnished material sources, material processing sites, stockpile sites, storage areas, plant sites, and waste areas that affect wetlands, threatened and endangered species, or waterways. The Contractor will not utilize a site known or suspected of having contaminated soil or water. The Contractor will provide the required permits and clearances to the Project Engineer at the preconstruction meeting.

STATE OF	PROJECT	SHEET	TOTAL SHEETS
SOUTH DAKOTA	NH 0012(323)298	3	92

SUPPLYING AS BUILT PLANS

If the traffic signal systems are constructed differently than what is stated in the plans, the Contractor will supply as built plans to the Engineer and a copy will be sent to the Traffic Design Engineer. The as built plans may include conduit layouts, wiring diagrams, or other drawings depicting the changes from the original plans.

SHOP DRAWING AND CATALOG CUTS SUBMITTALS

The Contractor will submit shop drawings and catalog cuts in accordance with Section 985 of the Specifications.

PDF submittals will be sent to the following email addresses:

Stacy.Bartlett@state.sd.us & Matt.Dorfschmidt@state.sd.us

ON-SITE INSPECTION

An on-site inspection of the traffic signals will be conducted before acceptance of the project once the traffic signals are completed and operational. The on-site inspection will be conducted by the Project Engineer, Region Engineer with the Contractor, City Traffic Control Department, and the Region Traffic Engineer present.

INCIDENTAL WORK

Incidental work includes, but is not limited to, the restoration of all disturbed areas to the satisfaction of the Engineer.

SIGNAL BACKPLATES

All new vehicle signal heads will have backplates with retroreflective border. The vehicle signal head backplates will have a factory applied 3 inch wide yellow retroreflective border. Sheeting for the border will be Type XI or Type IX in conformance with ASTM D4956. Backplates will be polycarbonate, aluminum, or aluminum-composite. Minimum material thicknesses are:

Polycarbonate, 0.10-inch Aluminum, 0.06-inch Aluminum-Composite, 0.08-inch

Signal backplates will extend not less than 5 inches from the edge of the signal head at the top, bottom, and sides. The bottom of the backplate on Vehicle signal faces mounted directly above pedestrian signal indications will be sized to permit the separate adjustment of the vehicle and pedestrian signal indication and may be less than 4 inches.

All costs involved with furnishing and installing backplates with retroreflective border for the new vehicle signal heads will be incidental to the contract unit price per each for "5 Section Vehicle Signal Head.

MULTICONDUCTOR CONTROL CABLE FOR SIGNAL CIRCUITS

The Conductor Jackets for the multiconductor control cables will be color coded in accordance with ICEA S-73-532 Table E2.

ELECTRICAL JUNCTION BOXES

At the locations noted on the plans, the Contractor will remove existing junction boxes and install new junction boxes. Before placing the new junction boxes, the existing base course will be excavated so that the new junction boxes sit flush with the new sidewalk and ramp grades. The new junction boxes will be the type as noted on the plan sheets and will be 36 inch deep.

The Contractor will extend the existing conduit into the new junction boxes as shown on standard plates 635.65.

The Contractor will salvage the covers from the removed junction boxes and deliver them to the city traffic shop. The Contractor will notify the city 5 days before the delivery of the salvaged signal equipment. The city contact is Mike Thomle at 605.626-7022.

All costs associated with removing the existing junction boxes, excavating the base course, extending existing conduit, and salvaging & delivery of the junction box covers will be incidental to the contract unit price per each for "Type 2 Electrical Junction Box," "Type 3 Electrical Junction Box," "Type 3A Electrical Junction Box," and "Type 4 Electrical Junction Box."

SIDEWALK QUANTITIES REMOVAL AND REPLACEMENT

The Contractor will remove sidewalk adjacent to any junction box to be replaced with the project. Removals will extend to the nearest joints in the sidewalk. Any pedestal pole located in the area of the sidewalk removed will be removed and reset in its existing location upon replacement of the sidewalk.

TRAFFIC SIGNAL WIRING

The Contractor will use Buchanan crimp connectors and insulating caps, or approved equal, on all wire terminations in the signal bases.

All costs for this work will be incidental to the electrical cable bid items.

ACCESSIBLE PEDESTRIAN SIGNAL

The work will consist of furnishing and installing accessible pedestrian signals (APS). Each APS will consist of an interactive vibrotactile pedestrian pushbutton with speaker, an informational sign, a latching light emitting diode (LED) indicator light, a solid-state electronic control board, a power supply, wiring, and all necessary mounting hardware. The operation and performance of the APS units will meet the requirements of the current edition of the MUTCD and the applicable sections of NEMA Standards Publication TS-2.

The APS units will be capable of supporting a minimum of 16 push button stations.

The traffic signal cabinet must have four dedicated load switches for the pedestrian phases. If the traffic signal cabinet does not have four dedicated load switches for the pedestrian phases, then the Contractor will furnish and install the necessary number of load switches. All costs associated with furnishing and installing any additional load switches will be incidental to the contract unit price per each for "Accessible Pedestrian Signal".

Revised: 8/13/25 MD

STATE OF	PROJECT	SHEET	TOTAL SHEETS
SOUTH DAKOTA	NH 0012(323)298	4	92

Revised 06/11/2025 DLM

All mounting fasteners will be stainless steel; all threads will be coated with antiseize compound meeting the requirements of USA Dept. of Defense specification MIL-PRF-907F.

The push button component of APS will meet the requirements of Section 985.1 S of the Specifications except that all housings and external hardware will be aluminum, powder coated yellow.

The APS control unit will include capability to monitor the push buttons and pedestrian signal head displays. Conflicts will cause the channel to be powered off. No part of the APS control unit will be installed in the pedestrian signal head.

The APS control unit will include capability to monitor communications with the push buttons. Communication faults will automatically reset the control unit.

Two licensed copies of any APS programming software will be furnished. All software programming, firmware updates, and audio message programming of the APS will be through USB port or Ethernet connection.

The APS will not have any components located in the pedestrian signal head.

All costs for furnishing and installing the accessible pedestrian signal including labor, materials, and equipment, will be incidental to the contract unit price per each for "Accessible Pedestrian Signal".

DETECTOR LOOP WIRE SPLICING

Detector loop wire splices will be made using wire nuts over soldered connections and sealed in 3M Scotchcast 3570G-N connector sealing packs or an approved equal.

The drain wire of the TSP cable will be left unattached to the ground lug in the traffic signal controller.

SEQUENCE OF OPERATIONS

The Contractor will submit a sequence of operations for approval two weeks prior to the preconstruction meeting. If changes to the sequence of operations are proposed during the project, these must be submitted for review a minimum of one week prior to potential implementation. Approval for changes to the sequence of operations will only be allowed when the proposed changes meet with the Department's intent for traffic control and sequencing of the work.

The Contractor will only work on one intersection at a time.

GENERAL TRAFFIC CONTROL

All temporary traffic control sign locations will be set in the field by the Contractor and verified by the Engineer prior to installation.

If there is a discrepancy between the traffic control plans, standard plates, and the MUTCD, whichever is more stringent will be used, as determined by the Engineer.

Unless otherwise stated in these plans, work will not be allowed during hours of darkness.

Fixed location signing placed more than 4 calendar days prior to the start of construction will be covered or laid down until the time of construction. The covers must be approved by the Engineer prior to installation. The cost of materials, labor, and equipment necessary to complete this work will be incidental to other contract items. No separate payment will be made.

All fixed location signs, sign posts, and breakaway bases will be removed within 7 calendar days following pavement marking.

Signs will not be located such that they block the sidewalk.

All intersection that are not controlled by a temporary traffic signal will be twoway stops when the signals at the intersection are not operational.

TEMPORARY PEDESTRIAN ACCESS ROUTE

A Temporary Pedestrian Access Route (TPAR) will be provided when crosswalks, sidewalks, or other pedestrian facilities are blocked, closed, or relocated. A TPAR may consist of a combination of existing and/or temporary pedestrian facilities. The TPAR will be kept free of any obstructions and hazards, such as holes, debris, mud, snow, construction equipment, traffic control signing, stored materials, etc.

The Contractor will notify the Engineer at least 72 hours prior to start of any construction operation that will necessitate a change in pedestrian access. Pedestrian traffic signal displays controlling a crosswalk that is closed will be covered or removed.

TEMPORARY CURB RAMP

Temporary curb ramps should be firm, stable, and have a non-slip surface. They will not warp or buckle, and should be made of materials strong enough to support a weight of 800 pounds. Temporary curb ramps will be yellow or color contrasting and contain marked edges, so they are noticeable by pedestrians who have visual impairments. Lateral joints or gaps between surfaces will be a maximum of 0.5 inches in width. Temporary curb ramps will include detectable warning panels.

Temporary curb ramps will be the same width as the temporary pedestrian access route, with a recommended width of 60 inches and a minimum width of 48 inches. Temporary curb ramps will have a maximum slope of 8.3% and have free draining surfaces with a maximum cross slope of 2%. Handrails on temporary curb ramps are not required unless the curb ramp has a rise exceeding 6 inches and a length exceeding 72 inches.

All costs will be incidental to the contract unit price per each for "Temporary Curb Ramp".

LONGITUDINAL PEDESTRIAN BARRICADE

Longitudinal pedestrian barricades should not be used to provide positive protection for pedestrians.

To prevent any tripping hazard to pedestrians, ballast will be located behind or internal to the device.

When longitudinal pedestrian barricades are combined in a series, the maximum gap between devices that do not interlock will be one inch. Joints between devices that do interlock will be closed and flush to prevent canes or small wheels from being trapped and to facilitate safe hand trailing. When used as a sidewalk closure mechanism, longitudinal pedestrian barricade must run the entire width of the sidewalk. Longitudinal pedestrian barricade should provide a color contrasting pattern. Black should not be used to color any base on a device. The devices should comply with the general color and stripe pattern requirements of Section 6F.68 of the MUTCD.

Longitudinal pedestrian barricade will have continuous bottom and top surfaces. The top surface will be smooth to allow safe hand trailing. Both upper and lower surfaces will share a common vertical plane.

All costs will be incidental to the contract unit price per foot for "Longitudinal Pedestrian Barricade".

LONGITUDINAL PEDESTRIAN BARRIER

When used to separate pedestrians from vehicular traffic for TPARs in the roadway, longitudinal pedestrian barrier must meet or exceed the crashworthy requirements of NCHRP 350 or MASH Test Level 1. The bottom and top surfaces of the traffic side of devices will have retroreflective sheeting or delineation for improved nighttime visibility.

When longitudinal pedestrian barriers are combined in a series, the maximum gap between devices that do not interlock will be one inch. Joints between devices that do interlock should be closed and flush to prevent canes or small wheels from being trapped and to facilitate safe hand trailing. Channelizing devices should provide a color contrasting pattern. Black should not be used to color any base on a device. The devices should comply with the general color and stripe pattern requirements of Chapter 6F of the MUTCD.

Longitudinal pedestrian barriers will have continuous bottom and top surfaces. The top surface will be smooth to allow safe hand trailing.


All costs will be incidental to the contract unit price per foot for "Longitudinal Pedestrian Barrier".

Revised: 8/13/25 MD

,	STATE OF	PROJECT	SHEET	TOTAL SHEETS
)	SOUTH DAKOTA	NH 0012(323)298	5	92

Revised 06/11/2025 DLM

PEDESTRIAN CHANNELIZING DEVICE DETAILS



Longitudinal Pedestrian Barrier

Longitudinal Pedestrian Barricade

- 1. Barricade rail supports may not extend into the pedestrian walkway more than 4 inches from the face of the barricade.
- 2. The top edge of the bottom portion will be a minimum of 8 inches above the walkway.
- 3. Devices will not block water drainage from the walkway. A gap height or opening from the walkway surface up to a maximum of 2 inches in height is allowed for drainage purposes.
- 4. The top edge of the longitudinal pedestrian barricade is to be used as a guiderail to provide visual and tactile guidance to pedestrians along a designated route. The top surface should have a minimum width of 0.5 inches to allow the hand to feel the surface. The surface should be smooth and free of any sharp or abrasive elements to allow safe hand trailing.
- 5. Longitudinal pedestrian barrier used to provide positive protection from traffic to pedestrians should be crashworthy.

CONTROLLER PROGRAMMING


The existing controllers at US12 and Dakota St S, will be reprogrammed to use the patterns and timings specified on the Signal Timing Sheets by a qualified technician. Costs for reprogramming the controllers will be incidental to the contract lump sum price for "Miscellaneous, Electrical".

REMOVE SIGNAL AND LUMINAIRE POLES


Signal pole EE3. EE4 and pedestal pole EL3 are to be removed on this project and will become the property of the Contractor.

TEMPORARY CURB RAMP DETAILS

Temporary Curb Ramp - Parallel to Curb



Temporary Curb Ramp - Perpendicular to Curb



- 1. Curb ramps will be 48-inch minimum width with a firm, stable, and non-slip surface.
- 2. Protective edging with a 2-inch minimum height will be installed when the curb ramp or landing platform has a vertical drop of 6 inches or greater or has a side apron slope steeper than 33:1 (33%). Protective edging should be considered when curb ramps or landing platforms have a vertical drop of 3 inches or more.
- 3. Detectable edging with 6 inches minimum height and contrasting color will be installed on all curb ramp landings where the walkway changes direction (turns).
- 4. Curb ramps and landings should have a 50:1 (2%) maximum cross slope.
- 5. A minimum clear space of 48 inch x 48 inch minimum will be provided above and below the curb ramp, with a 60 inch x 60 inch clear space preferred.
- The curb ramp walkway edge will be marked with a contrasting color 2 to 4 inch wide marking. The marking is optional where color contrasting edging is used.
- 7. Water flow in the gutter system will have minimal restriction.
- 8. Lateral joints or gaps between surfaces will be less than 0.5 inches in width.
- Changes between surface heights should not exceed 0.5 inches. Lateral edges between 0.25 inches and 0.5 inches in height, should be vertical up to 0.25 inches in height and beveled at 2:1 between 0.25 inches and 0.5 inches in height.

PORTABLE TEMPORARY TRAFFIC CONTROL SIGNAL

The State will furnish, install, operate, and maintain a portable temporary traffic control signal during construction phases as determined by the Region Traffic Engineer.

The following intersection will have portable traffic signals when not operational:

- US12 and 5th St S
- US12 and 2nd St S
- US12 and State St S
- US12 and Dakota St S
- US12 and Roosevelt St S

Portable traffic signals will only be utilized at one intersection at a time.

The portable temporary traffic control signals will be set up and programmed by Aberdeen Region Traffic.

The Contractor will contact:

Matt Dorfschmidt, Aberdeen Traffic Engineer – 1 (605) 626-7879

Alyssa Taylor, Assistant Region Traffic Engineer – 1 (605) 626-2245

A minimum of one week prior to installation and programming of the signals

TRAFFIC SIGNAL PROGRAMMING:

The Contractor will initially program the controllers with the timings from the existing traffic signal programming existing at the intersections.

As project conditions and traffic needs change, the Contractor will adjust the traffic signal splits and offsets as directed by the Engineer after consultation with the Aberdeen Region Traffic Engineer. The Aberdeen Region Traffic Engineer will be the primary contact to approve any revision of the signal phasing or timing.

Emergency pre-emption will be provided and have priority.

Hardwire traffic signal interconnect will not be required during construction. The traffic signals will be coordinated using GPS clocks for time base coordinated. Controller time clocks will be kept in synchronization and adjusted as necessary to provide proper offsets and adequate coordination.

Emergency pre-emption will be installed for each approach controlled by a portable traffic signal system.

- The EVP heads will be Opticom or approved equal.
- One confirmation lights (socket and bulb) will be installed within each EVP head.

Costs to program and make adjustments to the traffic signal controllers will be incidental to the contract unit price per Hour for Maintenance of Traffic Signal(s).

Revised: 9/2/25 MD

STATE OF	PROJECT	SHEET	TOTAL SHEETS
SOUTH DAKOTA	NH 0012(323)298	6	92

Revised 06/11/2025 DLM

INSTALL STATE FURNISHED SIGNAL POLE:

Signal pole E3. will be furnished by the SDDOT and installed by the Contractor. The total cost of the furnished items for tax purposes is \$12,956.00

The pole will be installed by the Contractor as indicated on the Signal Layout and Conduit Layout Sheets. The signal pole, mast arms, and luminaire extensions are in the SDDOT Aberdeen Region Yard. The Contractor will be responsible for transporting the signal pole, mast arms, and luminaire extensions from the SDDOT Aberdeen Region Yard to the sites indicated on the Signal Layout and Conduit Layout Sheets. The Contractor may contact the Area Engineer for signal pole, mast arms, and luminaire extensions pick up information. The Area Engineer is Lane Goldsmith, (605) 626-7879. Anchor bolts will not be supplied by the DOT and the Contractor will need to provide them for the pole below.

Any poles damaged during pick-up, or delivery will be repaired or replaced by the Contractor at no cost to the State.

The signal pole to be installed is a Millerbernd Manufacturing signal pole Shop drawing number for the signal pole is Millerbernd Manufacturing SD 13-SIGONLY-1545.

Millerbernd Manufacturing P.O. Box 98 Winsted, MN 55395 Phone: (320) 485-2111

All work involved in furnishing anchor bolts, installing and transporting the state furnished signal poles will be incidental to the contract unit price per each for "Install Signal Pole with Mast Arm and Luminaire Arm"".

REMOVE SIGNAL POLE FOOTING

The footings of existing signal pole EE3 will be removed by the Contractor to a minimum of 2 feet below the ground surface. Restoration of the disturbed area will be to the satisfaction of the Engineer.

All costs for removing the footings of the existing signal poles will be incidental to the contract unit price per each for "Remove Signal Pole Footing".

REMOVE LUMINAIRE POLE FOOTING

The footings of existing luminaire pole EE4 will be removed by the Contractor to a minimum of 2 feet below the ground surface. Restoration of the disturbed area will be to the satisfaction of the Engineer.

All costs for removing the footings of the existing luminaire poles will be incidental to the contract unit price per each for "Remove Luminaire Pole Footing".

PEDESTAL SIGNAL POLES

Pedestal signal poles may be aluminum. Aluminum poles will conform to the following requirements:

Aluminum will conform to ASTM B221, Alloy 6061, and Temper T6.

Poles will be round with a minimum outside pole diameter of 4 inches, and the pole assembly will have a square, cast aluminum base with aluminum access door. The base will conform to the breakaway requirements of NCHRP 350 or MASH. A grounding lug will be provided in the base.

The pole to base connection will be a threaded connection; threads will be 8 TPI, NPT. A collar (integral or non-integral) to prevent wind-induced loosening of pole will be provided. All bolt and connection threads will be coated with a commercially available anti-seize compound intended for use in aluminum-to-aluminum and steel-to-aluminum connections.

The pole finish will either be brushed satin or spun. The top of the pole will be sealed by the traffic signal head mounting hardware or by an aluminum cap.

The existing bolt circle diameter of pedestal pole L3 is 13".

Measurement and payment for aluminum poles will be as specified in Specifications Section 635.

TABLE OF FOOTING DATA

Site	Footing	* Footing	**Spiral	**Spiral	Vertical
Designation	Diameter	Depth	Diameter	Length	Reinforcement
E3, L4	3' - 0"	12' - 0"	2' - 8"	120' - 9"	14-#8 x 11' -6"

^{*} Footing depth will be below ground level.

Soils at the footing location consist of approximately 5 feet of black silt clay overlying gravelly clay.

During construction of the cylindrical footings, concrete placement operations should closely follow excavation procedures. The longer the excavations are left open, the more likely caving will occur.

Concrete will not be dropped through standing water. If water is present in the excavation, it will be removed prior to concrete placement, or the concrete will be tremied.

TEMPORARY PEDESTRIAN SIDEWALK

Temporary pedestrian sidewalk will be a smooth, continuous, non-slip, hard surface. There should be no curbs or abrupt changes in grade or terrain that could cause tripping or be a barrier to wheelchair use.

Temporary pedestrian sidewalk will have a minimum width of 48 inches, with 60 inches recommended. The Contractor will try to provide boulevard sidewalk, whenever possible, for temporary pedestrian sidewalk that is 48 inches wide. Temporary pedestrian sidewalk less than 60 inches wide will provide for a 60-inch x 60-inch passing space at intervals not to exceed 200 feet. Temporary pedestrian sidewalk will have a maximum cross slope of 2%. The maximum grade will be 5% where the temporary pedestrian sidewalk does not follow the grade of the road.

All costs associated with installing and maintaining a temporary pedestrian access route, including temporary pedestrian sidewalk, will be incidental to the contract lump sum price for "Temporary Pedestrian Access Route".

TYPE 1 DETECTABLE WARNINGS

Detectable warnings will be in compliance with the Americans with Disabilities Act regulations.

The detectable warnings will be installed according to the manufacturer's installation instructions.

A concrete thickness equal to the adjacent concrete sidewalk thickness and 2 inches of granular cushion material will be placed below the Type 1 Detectable Warnings. When concrete is placed below the detectable warnings then the

concrete thickness will be transitioned at the rate of 1" per foot to match the adjacent concrete sidewalk thickness.

The detectable warnings will be cast iron plates may be a natural patina (weathered steel).

Type 1 Detectable Warning Panels will be one of the following products:

Type 1 Detectable Warnings

<u>Product</u>	<u>Manufacturer</u>
Detectable Warning Plate Cast Iron Plate	Neenah Foundry Company Neenah, WI 800-558-5075 http://www.neenahfoundry.com/
Detectable Warning Plate Cast Iron Plate	Deeter Foundry Lincoln, NE 800-234-7466 http://www.deeter.com/
Detectable Warning Plate Cast Iron Plate(No Coating)	East Jordan Iron Works, Inc. 301 Spring Street East Jordan, MI 49727 800-626-4653 http://www.ejiw.com

 Revised: 8/13/25 MD
 STATE OF SOUTH DAKOTA
 PROJECT
 SHEET
 TOTAL SHEETS

 NH 0012(323)298
 7
 92

Revised 06/11/2025 DLM

^{**} The size of all spirals will be #3.

`	STATE OF SOUTH	PROJECT	SHEET NO.	TOTAL SHEETS
J	DAKOTA	NH 0012(323)298	8	92

Plotting Date: 08/13/2025

ITEMIZED LIST FOR DETOUR SIGNING

			CONVENTIO	NAL ROAD	
SIGN CODE	SIGN DESCRIPTION	NUMBER	SIGN SIZE	SQFT PER SIGN	SQFT
R1-1	STOP	2	30"	5.2	10.4
R3-7R	RIGHT LANE MUST TURN RIGHT	1	30" x 30"	6.3	6.3
R3-7L	LEFT LANE MUST TURN LEFT	1	30" x 30"	6.3	6.3
R9-9	SIDEWALK CLOSED	1	24" x 12"	2.0	2.0
R9-10	SIDEWALK CLOSED (ARROW L or R) USE OTHER SIDE	4	24" x 12"	2.0	8.0
R9-11	SIDEWALK CLOSED AHEAD (ARROW L or R) CROSS HERE	1	24" x 18"	3.0	3.0
R9-11a	SIDEWALK CLOSED (ARROW L or R) CROSS HERE	1	24" x 12"	2.0	2.0
W4-2	LEFT or RIGHT LANE ENDS (symbol)	2	48" x 48"	16.0	32.0
W9-2	LANE ENDS MERGE LEFT	1	48" x 48"	16.0	16.0
W11-2	PEDESTRIAN (symbol)	4	36" x 36"	9.0	36.0
W16-9P	AHEAD (plaque)	2	30" x 18"	3.8	7.6
W20-1	ROAD WORK AHEAD	4	48" x 48"	16.0	64.0
W20-4	ONE LANE ROAD AHEAD	1	48" x 48"	16.0	16.0
W20-5	LEFT or RIGHT LANE CLOSED AHEAD	2	48" x 48"	16.0	32.0
W20-7	FLAGGER (symbol)	2	48" x 48"	16.0	32.0
W21-5	SHOULDER WORK	4	48" x 48"	16.0	64.0
G20-2	END ROAD WORK	2	36" x 18"	4.5	9.0
			VENTIONAL DUR SIGNING		346.6

Plotting Date: 06/11/2025

Revised 06/11/2025 DLM

	S	SIDEWALK QUA	ANTITIES REMOV	'AL AND REPLA	ACEMENT			
		REMOVE				INSTALL		
Intersection	Quadrant	Concrete Sidewalk (sqyd)	Remove Pedestrian Push Button Pole (Each) (110E1570)	4" Concrete Sidewalk (sqft)	Detectable Warning (sqft) (651E700)	Pedestrian Push Button Pole (Each) (635E5910)		
10 th St S	SW	8.6	1	77	15	1		
5 th St S	NW	8	1	72		1		
1st St S	NW	1.7		15				
Lincoln Ct C	SE	17.3	1	156	20	1		
Lincoln St S	NW	7	1	63	15	1		
Washington St S	SW	3.9		35				
Washington St S	NW	8.6	1	77	15	1		
	SE	11.7	1	105	10	1		
Kline St S	SW	11.7	1	105	15	1		
Killle 3t 3	NW	2.7	1	24		1		
	NE	2.7	1	24	30	1		
State St S	SE	11.7	1	105	10	1		
State St S	NW	2.7		24				
	SE	4.7		42				
Dakota St S	SW	4.7		42				
	NW	9		81				
	SE	3.1		28				
Harrison St S	SW	8	1	72	15	1		
	NW	8.9	1	80	15	1		
Lawson St S	SE	6.7	1	60	10	1		
Lawsull St 3	SW	8		72				
Total		151.4	13	1363	170	13		

LIVO

Revised: 8/13/25 MD

I SOUTH I	SHEETS
DAKOTA NH 0012(323)298 10	92

Plotti	ng	Date:	08/1	3/2025

	ESTIMATE OF CABLE QUANTITIES										
	US Hwy 12/6th Ave SW & 10th St S										
Bid	Item Number	635E9016	635E9502	635E9507	635E9524	635E9600	635E9800				
		1/C #6	2/C #14	7/C #14	24/C #14	#16 AWG	PREEMPTION				
		AWG	_	AWG IMSA	_	Twisted					
		Copper Cable	Copper Cable	Copper Cable	Copper Cable	Shielded Pair	CABLE				
1				_			_				
	on to Location	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)				
EJA1	Controller	420	280	70	140	70	70				
EJA1	Pole EA1	75		25	25		120				
EJA1	PA1		40								
EJA1	PA2		35								
EJA1	EJA2	240	160		80						
EJA1	EJA5					45					
EJA1	EJA4	630	420	105	210	105					
EJA2	Pole EA2	60			20						
EJA2	PA3		30								
EJA2	PA4		55								
EJA3	Pole EA3	60			20						
EJA3	EJA6					30					
EJA3	PA5		40								
EJA3	PA6		30								
EJA4	EJA3	255	130	65	65	65					
EJA4	Pole EA4	60		20	20						
EJA4	PA7		30								
EJA4	PA8		45								
EJA4	Power	1650									
Inters	ection Total	3450	1295	285	580	315	190				

ESTIMATE OF CABLE QUANTITIES US Hwy 12/6th Ave SW & 5th St S									
Bid	Item Number	635E9016	635E9502	635E9507	635E9524	635E9600	635E9800		
			2/C #14	7/C #14	24/C #14	#16 AWG	PREEMPTION		
		AWG Copper Cable	Copper Cable	AWG IMSA Copper Cable	Copper Cable	Twisted Shielded Pair	CABLE		
	on to Location	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)		
EJB1	Pole EB1	60		20	20		50		
EJB1	EJB5					70			
EJB1	PA1		20						
EJB1	PA2		25						
EJB1	EJB2	220	220	110	110	220	110		
EJB2	Pole EB2	60		20	20		50		
EJB2	PB3		25						
EJB2	PB4		20						
EJB2	EJB3	460	460	230	230	230	230		
EJB3	Pole EB3	60		20	20		50		
EJB3	PB5		20						
EJB3	PB7		35						
EJB3	EJB7	270				90			
EJB3	Controller	270	360	180	180	225	180		
EJB3	EJB6					80			
EJB3	EJB4		200	100	100	100	100		
EJB4	Pole EB4	60		40	40		70		
EJB4	PA7		25						
EJB4	PA8		35						
EJB4	EJB8					65			
EJB7	Power	990							
Inters	ection Total	2450	1445	720	720	1080	840		

200 t

Intersection Total

2220

855

260

1250

480

595

Revised: 8/13/25 MD

STATE OF	PROJECT	SHEET NO.	TOTAL SHEETS
SOUTH DAKOTA	NH 0012(323)298	11	92

	ESTIMATE OF CABLE QUANTITIES									
	ES	TIMAT	E OF	CABLE	QUAN	NTITIES				
		US F	lwy 12/6t	h Ave SW &	2nd St S					
Bid Iter	m Number	635E9016	335E9502	635E9507	635E9524	635E9600	635E9800			
		1/C #6 AWG	2/C #14 AWG IMSA	7/C #14 AWG IMSA	24/C #14 AWG IMSA	#16 AWG	PREEMPTION			
		Copper Cable	Copper Cable	Copper Cable	Copper Cable	Shielded Pair	CABLE			
Location t	to Location	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)			
EJC1	Pole EC1	60		20	20		50			
EJC1	PC1		20							
EJC1	PC2		30							
EJC1	EJC5					40				
EJC1	EJC2	360	180							
EJC1	EJC4	360	220	110	110	220	110			
EJC2	PC3		25							
EJC2	PC4		25							
EJC3	Pole EC3	60		20	20		45			
EJC3	PC5		30							
EJC3	PC6		25							
EJC3	EJC6				855		60			
EJC3	EJC7						30			
EJC3	Pole EC2	60			105		135			
EJC3	Controller	180	240	90	120	180	120			
EJC4	Pole EC4	60		20	20		45			
EJC4	PC7		30							
EJC4	PC8		30							
EJC4	EJC8					40				
EJC4	Power	1080								

ESTIMATE OF CABLE QUANTITIES US Hwy 12/6th Ave SW & 1st St S											
Bid Ite	m Number	635E9016		635E9507	635E9519		635E9600	635E9800			
		1/C #6 AWG	2/C #14 AWG IMSA	7/C #14 AWG IMSA	19/C #14 AWG IMSA		#16 AWG	PREEMPTION			
		Copper Cable	Copper Cable	Copper Cable	Copper Cable	Copper Cable	Shielded Pair	CABLE			
Location	to Location	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)			
EJD1	Controller	180	240	30	30	90	60	90			
EJD1	Pole ED1	60				30		60			
EJD1	PD1		35								
EJD1	PD2		35								
EJD1	EJA2	210	140		70						
EJD1	EJD5	630	420	105		210		105			
EJD1	EJD6						50				
EJD2	Pole ED2	60			20						
EJD2	PD3		25								
EJD2	PD4		25								
EJD3	Pole ED3	60		25		25		55			
EJD3	PD5		30								
EJD3	PD6		20								
EJD3	EJD4		110	55		55		55			
EJD3	Power	1110									
EJD4	Pole ED4	60				20		50			
EJD4	PD7		20								
EJD4	PA8		25								
Intersect	tion Total	2370	1125	215	120	430	110	415			

STATE OF	PROJECT	SHEET NO.	TOTAL SHEETS
SOUTH DAKOTA	NH 0012(323)298	12	92

ESTIMATE OF CABLE QUANTITIES US Hwy 12/6th Ave SW & Main St S										
Bid	Item Number	635E8120	635E9016	635E9502	635E9504	635E9507	635E9524	635E9600	635E9710	635E9800
		2" Schedule 40	1/C #6 AWG	2/C #14 AWG IMSA	4/C #14 AWG IMSA	7/C #14 AWG IMSA	24/C #14 AWG IMSA	#16 AWG	2/C #14 AWG Pole and	PREEMPTION
		Conduit	Copper Cable	Copper Cable	Copper Cable	Copper Cable	Copper Cable	Shielded Pair	Bracket Cable	CABLE
Locati	on to Location	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)
EJE1	Controller		180	240		30	180	150		90
EJE1	Pole EE1		60			20	20			70
EJE1	EJE5			40						
EJE1	EJE4									
EJE5	EJE2		300	150		75	75	75		75
EJE5	PE1			20						
EJE5	PE2			25						
EJE2	Pole EE2		60			20	20			60
EJE2	PE3			20						
EJE2	PE4			20						
EJE2	EJE6							40		
EJE3	Pole E3	30	60				40			60
EJE3	PE5		30							
EJE3	PE6		60							
EJE3	EJE4		320	160			80	240		80
EJE4	Pole E4		60				30			
EJE4	PE7			20						
EJE4	PE8			25						
EJE4	EJE7							20		
EJE4	Power		1020							
- 1	Pole E3				100	70			65	
	Pole E4				30	20			65	
Inters	ection Total	30	2150	720	130	235	445	525	130	435

ESTIMATE OF CABLE QUANTITIES US Hwy 12/6th Ave SW & Lincon St S										
Bid	Item Number	635E9016	635E9502	635E9507	635E9519	635E9524	635E9600	635E9800		
		1/C #6 AWG Copper Cable	2/C #14 AWG IMSA Copper Cable	7/C #14 AWG IMSA Copper Cable	19/C #14 AWG IMSA Copper Cable	24/C #14 AWG IMSA Copper Cable	#16 AWG Twisted Shielded Pair	PREEMPTION CABLE		
Location	on to Location	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)		
EJF1	Pole EF1	60				20		50		
EJF1	PF1		25							
EJJ1	PF2		20							
EJF1	EFJ5						60			
EJF1	EJF2		150			75	150	75		
EFF2	Pole EF2	60			20					
EJF2	PF3		15							
EFF2	PF4		25							
EJF2	EJF3		420		105	105	210	105		
EJF3	Pole EF3	60		20		20		50		
EJF3	PF5		30							
EJF3	PF6		20							
EJF3	Controller	180	240	30	30	90	60	90		
EJF3	EJF4	370	130			65		65		
EJF4	Pole EF4	60				20		50		
EJF2	PF7		25							
EJF4	PF8		30							
EJF4	Power	1080								
Inters	ection Total	1870	1130	50	155	395	480	485		

.

Revised: 8/13/25 MD

STATE OF	PROJECT	SHEET NO.	TOTAL SHEETS
SOUTH DAKOTA	NH 0012(323)298	13	92

Plotting	Date:	08/13/2025

	_						
	E	STIMA	ATE OF	CABL	E QUAI	NTITIES	S
		US Hv	vy 12/6th A	ve SW & Wa	ashington St	: S	
Bid Ite	m Number	635E9016	635E9502	635E9507	635E9524	635E9600	635E9800
		1/C #6	2/C #14	7/C #14	24/C #14	#16 AWG	PREEMPTION
			AWG	AWG	AWG		
		AWG	IMSA	IMSA	IMSA	Twisted	
		Copper	Copper	Copper	Copper	Shielded	
		Cable	Cable	Cable	Cable	Pair	CABLE
Location	to Location	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)
EJG1	Pole EG1	60		20	20		75
EJG1	PG1		35				
EJG1	PG2		20				
EJG1	EJG5					50	
EJG1	EJG2	300	150	75	75	150	75
EJG2	Pole EG2	60			20		55
EJG2	PG3		20				
EJG2	PG4		15				
EJG2	EJG3	220	220	105	110	110	110
ELG3	Controller	210	280	70	140	105	140
ELG3	Pole EG3	60		20	20		75
ELG3	PG5		20				
ELG3	PG6		35				
ELG3	EJG6		25				
ELG3	EJG4	180	120		60		60
EJG4	Pole EG4	60			20		55
EJG4	PG7		20				
EJG4	PJ8		35				
EJG4	Power	1080				_	
Intersect	tion Total	2230	995	290	465	415	645

	ESTIMATE OF CABLE QUANTITIES											
		US	6 Hwy 12/6t	h Ave SW &	Kline St S							
Bid Ite	m Number	635E9016	635E9502	635E9507	635E9524	635E9600	635E9800					
		1/C #6	2/C #14	7/C #14	24/C #14	#16 AWG	PREEMPTION					
			AWG	AWG	AWG							
		AWG	IMSA	IMSA	IMSA	Twisted						
		Copper	Copper	Copper	Copper	Shielded	04515					
		Cable	Cable	Cable	Cable	Pair	CABLE					
	to Location	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)					
EJH1	Pole EH1	60		20	20		55					
EJH1	PH1		30									
EJH1	PH2		20									
EJH1	EJH5					100						
EJH1	EJH2		140	70	70	140	70					
EJH2	Pole EH2	60			20		40					
EJH2	PH3		20									
EJH2	PH4		30									
EJH2	EJH3	420	420	105	210	210	210					
EJH3	Pole EH3	60		20	20		55					
EJH3	PH5		30									
EJH3	PH6		20									
EJH3	Controller	180	240	60	120	120	120					
EJH3	EJH6					50						
EJH3	EJH4	360	120		60		60					
EJH4	Pole EH4	60			15		50					
EJH4	PF7		20									
EJH4	PF8		30									
EJH4	Power	1050										
Intersect	ion Total	2250	1120	275	535	620	660					

) SOUTH	S1	SHEET TOTAL NO. SHEETS
DAKOTA NH 0012(323)298 14	L	

Plotting Date: 08/13/2025

	E	STIMA	TE OF	CABLE	OUA	NTITIES	<u> </u>
				h Ave SW &	•		
Bid Iter	m Number	635E9016	635E9502	635E9507	635E9524	635E9600	635E9800
		1/C #6	2/C #14	7/C #14	24/C #14	#16 AWG	PREEMPTION
			AWG	AWG	AWG		
		AWG	IMSA	IMSA	IMSA	Twisted	
		Copper Cable	Copper Cable	Copper	Copper	Shielded	CADLE
1	t. 1		_	Cable	Cable	Pair	CABLE
	to Location	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)
EJI1	Pole EI1	60		30	30		80
EJI1	PI1		35				
EJI1	PI2		20				
EJI1	EJI5					60	
EJI1	EJI2	340	170	85	85	170	85
EJI2	Pole El2	60		20	20		50
EJI2	PI3		15				
EJI2	PI4		20				
EJI2	EJI3	360	480	240	240	240	240
EJI2	Controller	75	200	100	100	150	100
ELI2	EJ16					40	
ELI3	Pole El3	60		20	20		50
ELI3	PI5		15				
ELI3	PI6		20				
ELI3	EJG7						60
ELI3	EJG4	180	180	90	90	90	90
EJI3	Power	1000					
EJI4	Pole El4	60		20	20		50
EJI4	PI7		25				
EJI4	PI8		20				
EJI4	EJG8					40	
Intersect	ion Total	2195	1200	605	605	790	805

	ESTI	MATE	OF CA	BLE Q	UANTI [*]	TIES				
	US Hwy 12/6th Ave SW & Dakota St S									
Bid Ite	m Number	635E9016		635E9507	635E9524	635E9800				
		1/C #6	2/C #14	7/C #14	24/C #14	PREEMPTION				
			AWG	AWG	AWG					
		AWG	IMSA	IMSA	IMSA					
		Copper Cable	Copper Cable	Copper Cable	Copper Cable	CABLE				
Location	to Location					_				
	to Location	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)				
EJJ1	Pole EJ1	60	00	20	20	70				
EJJ1	PJ1		20							
EJJ1	PJ2	460	25	400	400	400				
EJJ1	Controller	180	240	120	120	120				
EJJ1	EJJ2		230	115	115	115				
EJJ1	EJJ4	660	440	220	220	220				
EJJ2	Pole EJ2	60		20	20	80				
EJJ2	PJ3		30							
EJJ2	PI4		15							
EJJ3	Pole EJ3	60		20	20	55				
EJJ3	PJ5		20							
EJJ3	PJ6		30							
EJJ3	Power	210								
EJJ3	EJJ4									
EJH3	EJH4	510	170	85	85	85				
EJJ4	Pole EJ4	60		20	20	20				
EJJ4	PJ7		20							
EJJ4	PJ8		30							
Pole	EJ4			75						
Pole	EJ3			20						
Intersec	tion Total	1800	1270	710	620	765				

.

Revised: 8/13/25 MD

) SOUTH	STATE OF	PROJECT	SHEET NO.	TOTAL SHEETS
DAKUTA NH 0012(323)296 13 92) SOUTH DAKOTA	NH 0012(323)298	15	92

	E	STIMA	TE OF	CABLE	QUAI	NTITIES	S			
US Hwy 12/6th Ave SW & Harrison St S										
Bid Ite	m Number	635E9016			635E9524	635E9600	635E9800			
		1/C #6	2/C #14	7/C #14	24/C #14	#16 AWG	PREEMPTION			
			AWG	AWG	AWG					
		AWG	IMSA	IMSA	IMSA	Twisted				
		Copper	Copper	Copper	Copper	Shielded	0.451.5			
		Cable	Cable	Cable	Cable	Pair	CABLE			
	to Location	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)			
EJK1	Pole EK1	60		20	20		75			
EJK1	PKI1		20							
EJK1	PK2		30							
EJK1	EJK5	70								
EJK1	EJK2	195	130		65		65			
EJK1	EJK4	285	380	95	190	95	190			
EJK2	Pole EK2	60			15		50			
EJK2	PK3		20							
EJK2	PK4		30							
EJK3	Pole EK3	60			15		50			
EJK3	PK5		30							
EJK3	PK6		20							
EJK3	EJK4	390	130	65	65	65	65			
EJK3	Power	900								
EJK3	EJK6					25				
EJK4	Pole EK4	60		20	20		75			
EJK4	PK7		30							
EJK4	PK8		20							
EJK4	Controller		320	80	160	80	160			
Intersect	ion Total	2080	1160	280	550	265	730			

	ESTIMATE OF CABLE QUANTITIES											
	US Hwy 12/6th Ave SW & Lawson St S											
Bid Ite	m Number	635E9016			635E9507	635E9524	635E9600	635E9800				
		1/C #6 AWG	2/C #14 AWG IMSA	4/C #14 AWG IMSA	7/C #14 AWG IMSA	24/C #14 AWG IMSA	#16 AWG	PREEMPTION				
		Copper Cable	Copper Cable	Copper Cable	Copper Cable	Copper Cable	Shielded Pair	CABLE				
Location	to Location	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)	(Ft)				
EJL1	Pole L3	60				20						
EJL1	PL3		15									
EJL1	PL4		30									
EJL1	Controller	210	140		70	105	105	70				
EJL1	PL1		90									
EJL1	Pole EL1	255			85	85						
EJL1	EJL2	480	80		80	80	240	150				
EJL2	Pole EL2	60			20	20		65				
EJL2	PL2		15									
EJL2	EJL3						45					
EJL2	EJL4						60					
EJL2	Power	1500										
Dal	e L3			60								
POI	E LO			υU								
Intersect	tion Total	2565	370	60	255	310	450	285				

	STATE OF SOUTH	PROJECT	SHEET NO.	TOTAL SHEETS
,	DAKOTA	NH 0012(323)298	16	92

	ESTIMATE OF CABLE QUANTITIES										
US Hwy 12/6th Ave SW & Roosevelt St S											
Bid Ite	m Number	635E9014	635E9502	635E9507	635E9524	635E9800					
		1/C #6 AWG Copper	2/C #14 AWG IMSA Copper	7/C #14 AWG IMSA Copper	24/C #14 AWG IMSA Copper	PREEMPTION					
		Cable	Cable	Cable	Cable	CABLE					
Location to Location		(Ft)	(Ft)	(Ft)	(Ft)	(Ft)					
JM1	Power	540									
JM1	EJM2	1500	500	250	250						
JM1	EJM6		40	20	20						
JM1	EJM4		180	90	90						
EJM6	Pole EM1	60		20	20						
EJM6	PM1		20								
EJM6	PM2		25								
EJM2	Pole EM2	75		25	25	90					
EJM2	PM3		25								
EJM2	PM4		30								
EJM2	Controller	120	240	120	120	80					
EJM4	Pole EM4	60		45	45						
EJM4	PI7		35								
EJM4	PI8		45								
Intersect	tion Total	2355	1140	570	570	170					

OTTED FROM - TRAB17879B


EXISTING SIGNAL LAYOUT US HWY 12/6TH AVE SW & 10TH ST S

 Revised: 8/13/25 MD
 STATE OF SOUTH DAKOTA
 PROJECT NO.
 SHEET NO.
 STATE NO.
 SHEET SHEETS

 NH 0012(323)298
 17
 92


Plotting Date: 08/13/2025

Revised 06/01/2025 DLM



REMOVE SIGNAL EQUIPMENT						
KEY	ITEM	EST QUANT	UNIT			
PB	Accessible Pedestrian Signal PA1 - PA8	8	EACH			

	EXISTING ITEMS
KEY	ITEM
ф -	Signal Pole w/25' Mast Arm & 8' Lumin Arm (EA2, EA4)
ф -	Signal Pole w/40' Mast Arm & 8' Lumin Arm (EA1,EA3)
•	Roadway Luminaire, 400w with P.E. (EA1-EA4)
-[]>-	3 Section Vehicle Signal Head (1-15)
	Emergency Vehicle Preemption Unit (4-Channel)
P	Optical Detector
PB	Accessible Pedestrian Signal
-(Pedestrian Signal Head (16-23)
START CROSSING WATCH FOR WATCH FOR WEHCLES DOWN START INBUTIONS IN START CHARGE CROSSING CROSS TO CROSS PUSH SUTTON	Pedestrian Crossing Sign R10-3b (Left - 4/Right - 4)



EXISTING CONDUIT LAYOUT US HWY 12/6TH AVE SW & 10TH ST S

Revised: 8/13/25 MD

STATE OF	PROJECT	SHEET NO.	TOTAL SHEETS
SOUTH DAKOTA	NH 0012(323)298	18	92


Plotting Date: 08/13/2025

Revised 06/15/2025 DLM

	EXISTING ITEMS		
KEY	ITEM		
[]]	Detector Loop		
M	Meter Socket		
Ø	Wood Utility Pole		
	Electrical Service Cabinet		
0	Electrical Junction Box		
X	Traffic Signal Controller		
2" SCH 40	2" Rigid Conduit, Schedule 40		
4" SCH 40	4" Rigid Conduit, Schedule 40		
3" SCH 80	3" Rigid Conduit, Schedule 80		
2/C	2/C #14 AWG Copper Tray Cable, K2		
7/C	7/C #14 AWG Copper Tray Cable, K2		
24/C	24/C #14 AWG Copper Tray Cable, K2		
#4	1/C #4 AWG Copper Wire		
#6	1/C #6 AWG Copper Wire		
TSP	#16 AWG Copper Twisted Shielded Pair		
PC	PREEMPTION CABLE		

ESTIMATE OF QUANTITIES		
ITEM	QUANT	UNIT
Remove Signal Equipment	Lump Sum	LS

REMOVE SIGNAL EQUIPMENT			
KEY	ITEM	EST QUANT	UNIT
0	Electrical Junction Box (EJA3,EJA4)	2	EACH
2/C	2/C #14 AWG Copper Tray Cable, K2	1295	FT
7/C	7/C #14 AWG Copper Tray Cable, K2	285	FT
24/C	24/C #14 AWG Copper Tray Cable, K2	580	FT
#4	1/C #4 AWG Copper Wire	1350	FT
#6	1/C #6 AWG Copper Wire	1890	FT
TSP	#16 AWG Copper Twisted Shielded Pair	190	FT
PC	PREEMPTION CABLE	315	FT




STATE OF	PROJECT	SHEET NO.	TOTAL SHEETS
SOUTH DAKOTA	NH 0012(323)298	19	92

Plotting Date: 08/13/2025

Revised 06/01/2025 DLM

SIGNAL LAYOUT US HWY 12/6TH AVE SW & 10TH ST S

ESTIMATE OF QUANTITIES			
KEY	ITEM	EST QUANT	UNIT
PB	Accessible Pedestrian Signal (PA1-PA8)	8	EACH
0	Pedestrrian Push Button Pole (PA7)	1	EACH




STATE OF SOUTH DAKOTA	PROJECT	SHEET NO.	TOTAL SHEETS
	NH 0012(323)298	20	92

Plotting Date: 08/13/2025

Revised 06/16/2025 DLM

CONDUIT LAYOUT US HWY 12/6TH AVE SW & 10TH ST S

	ESTIMATE OF QUANTITIES		
KEY	ITEM	EST QUANT	UNIT
	Type 2 Electrical Junction Box (EJA3,EJA4)	2	EACH
2/C	2/C #14 AWG Copper Tray Cable, K2	1295	FT
7/C	7/C #14 AWG Copper Tray Cable, K2	285	FT
24/C	24/C #14 AWG Copper Tray Cable, K2	580	FT
#4	1/C #4 AWG Copper Wire	1350	FT
#6	1/C #6 AWG Copper Wire	1890	FT
PC	Preemption Cable	190	FT
TSP	#16 AWG Copper Twisted Shielded Pair	315	FT



EXISTING SIGNAL LAYOUT US HWY 12/6TH AVE SW & 5TH ST S




Revised 06/02/2025 DLM

ESTIMATE OF QUANTITIES		
ITEM	EST QUANT	UNIT
Remove Signal Equipment	Lump Sum	LS
Remove Pedesrian Push Button Pole	1	EACH

REMOVE SIGNAL EQUIPMENT			
KEY	ITEM	EST QUANT	UNIT
PB	Accessible Pedestrian Signal (PB1 - PB8)	8	EACH


	EXISTING ITEMS		
KEY	ITEM		
₩ =	Signal Pole w/40' Mast Arm & 8' Lumin Arm (EB2)		
₩	Signál Pole w/45' Mast Arm & 8' Lumin Arm (EB1,EB4)		
₩	Signal Pole w/50' Mast Arm & 8' Lumin Arm (EB3)		
•	Roadway Luminaire, 400w with P.E. (EB1-EB4)		
-[>-	3 Section Vehicle Signal Head (3, 4, 7-16)		
51	5 Section Vehicle Signal Head (1, 2, 5, 6)		
	Emergency Vehicle Preemption Unit (4-Channel)		
[>	Optical Detector		
PB	Accessible Pedestrian Signal		
	Blankout Sign		
0	Pedestrian Push Button Pole (EPB1-EPB4)		
-([]	Pedestrian Signal Head (17-24)		
START CROSSING VATCH FOR THE PROPERTY OF THE P	Pedestrian Crossing Sign R10-3b (Left - 4/Right - 4)		




EXISTING ITEMS			
ITEM			
WOOD UTILITY POLE			
Electrical Junction Box			
ELECTRICAL SERVICE CABINET			
TRAFFIC SIGNAL CONTROLLER			
METER SOCKET			
PREFORMED DETECTOR LOOP			
2" RIGID Steel CONDUIT			
2" RIGID CONDUIT, SCHEDULE 40			
2" RIGID CONDUIT, SCHEDULE 80			
3" RIGID CONDUIT, SCHEDULE 80			
1/C #4 AWG COPPER WIRE			
1/C #6 AWG COPPER WIRE			
2/C #14 AWG COPPER TRAY CABLE, K2			
7/C #14 AWG COPPER TRAY CABLE, K2			
24/C #14 AWG COPPER TRAY CABLE, K2			
#16 AWG COPPER TWISTED SHIELDED PAIR			
PREEMPTION CABLE			


ESTIMATE OF QUANTITIES			
ITEM	QUANT	UNIT	
Remove Signal Equipment	Lump Sum	LS	

REMOVE SIGNAL EQUIPMENT			
KEY	ITEM	UNIT	EST QUANT
	Electrical Junction Box (EJB1,EJB3)	EACH	2
#4	1/C #4 AWG COPPER WIRE	FT	765
2/c	2/C #14 AWG COPPER TRAY CABLE, K2	FT	1445
7/c	7/C #14 AWG COPPER TRAY CABLE, K2	FT	720
24/c	24/C #14 AWG COPPER TRAY CABLE, K2	FT	720
TSP	#16 AWG COPPER TWISTED SHIELDED PAIR	FT	1080
PC	PREEMPTION CABLE	FT	840












CONDUIT LAYOUT US HWY 12/6TH AVE SW & 5TH ST S



Revised 06/16/2025 DLM

Plotting Date: 08/13/2025





Revised: 8/13/25 MD


EXISTING SIGNAL LAYOUT US HWY 12/6TH AVE SW & 2ND ST S

 Revised: 8/13/25 MD
 STATE OF SOUTH DAKOTA
 PROJECT NO.
 SHEET NO.
 SHEET NO.
 SHEET SHEETS

 1
 NH 0012(323)298
 25
 92


Plotting Date: 08/13/2025

Revised 06/16/2025 DLM



REMOVE SIGNAL EQUIPMENT				
KEY	ITEM	EST QUANT	UNIT	
PB	Accessible Pedestrian Signal (PC1 - PC8)	8	EACH	

	EXISTING ITEMS		
KEY	ITEM		
#	Signal Pole w/25' Mast Arm & 8' Lumin Arm (EC2,EC4)		
#	Signal Pole w/40' Mast Arm & 8' Lumin Arm (EC1,EC3)		
•	Roadway Luminaire, 400w with P.E. (EC1-EC4)		
Ţ	3 Section Vehicle Signal Head(3, 4, 7-11, 13)		
(>	5 Section Vehicle Signal Head (1, 2, 5, 6, 12, 14)		
	Emergency Vehicle Preemption Unit (4-Channel)		
	Optical Detector		
PB	Accessible Pedestrian Signal		
-{/;	Pedestrian Signal Head (15-23)		
START CRUSSING WATCH FOR VEHICLES DESTRICT FRENCH CROSSING DONT CROSS TO CROSS PUSH BUTTON	Pedestrian Crossing Sign R10-3b (Left - 4/Right - 4)		




EXISTING ITEMS		
KEY	ITEM	
Ø	WOOD UTILITY POLE	
	Electrical Junction Box	
	ELECTRICAL SERVICE CABINET	
\square	TRAFFIC SIGNAL CONTROLLER	


EXISTING ITEMS		
KEY	ITEM	
Ø	WOOD UTILITY POLE	
	Electrical Junction Box	
	ELECTRICAL SERVICE CABINET	
	TRAFFIC SIGNAL CONTROLLER	
M	METER SOCKET	
	PREFORMED DETECTOR LOOP	
2" SCH 40	2" RIGID CONDUIT, SCHEDULE 40	
3" SCH 80	3" Rigid Conduit, Schedule 80	
4" SCH 40	4" Rigid Conduit, Schedule 40	
#4	1/C #4 AWG COPPER WIRE	
2/c	2/C #14 AWG COPPER TRAY CABLE, K2	
77/c	7/C #14 AWG COPPER TRAY CABLE, K2	
24/c	24/C #14 AWG COPPER TRAY CABLE, K2	
TSP	#16 AWG COPPER TWISTED SHIELDED PAIR	
PC	PREEMPTION CABLE	
3 #6	LUMINAIRE EXTENSION WIRING	


ESTIMATE OF QUANTITIES			
ITEM	QEST	UNIT	
Remove Signal Equipment	Lump Sum	LS	

REMOVE SIGNAL EQUIPMENT			
KEY	ITEM	UNIT	EST QUANT
(#4)	1/C #4 AWG COPPER WIRE	FT	630
(2/c)	2/C #14 AWG COPPER TRAY CABLE, K2	FT	855
(7/c)	7/C #14 AWG COPPER TRAY CABLE, K2	FT	260
24/c	24/C #14 AWG COPPER TRAY CABLE, K2	FT	1250
TSP	#16 AWG COPPER TWISTED SHIELDED PAIR	FT	480
(PC)	PREEMPTION CABLE	FT	595











Plotting Date: 08/13/2025

Revised: 8/13/25 MD

Revised 06/16/2025 DLM






EXISTING SIGNAL LAYOUT US HWY 12/6TH AVE SW & 1ST ST S


 Revised: 8/13/25 MD
 STATE OF SOUTH DAKOTA
 PROJECT NO. SHEET NO. SHEETS
 SHEET SHEETS

 NH 0012(323)298
 29
 92



	REMOVE SIGNAL EQUIPMENT				
KEY	ITEM	QUANT	UNIT		
PB	Accessible Pedestrian Signal PD1 - PD8	8	EACH		

	EVICTING ITEMS		
	EXISTING ITEMS		
KEY	ITEM		
*	Luminaire Pole with Mounted Signal Heads (ED2)		
₩ =	Signal Pole w/25' Mast Arm & 8' Lumin Arm (,ED4)		
‡	Signal Pole w/35' Mast Arm & 8' Lumin Arm (ED1,ED3)		
•	Roadway Luminaire, 400w with P.E. (ED1-ED4)		
-i>>	3 Section Vehicle Signal Head (1, 3-12)		
	Emergency Vehicle Preemption Unit (4-Channel)		
[>	Optical Detector		
PB	Accessible Pedestrian Signal		
-([]	Pedestrian Signal Head (13-20)		
START CROSSING WATCH FOR VEHICLES WATCH FOR VEHICLES FROM CROSSING E START CROSSING E START CROSSING E START CROSSING E START CROSS TO CROSS	Pedestrian Crossing Sign R10-3b (Left - 4/Right - 4)		




EXISTING CONDUIT LAYOUT US HWY 12/6TH AVE SW & 1ST ST S

Revised: 8/13/25 MD


STATE OF	PROJECT	SHEET NO.	TOTAL SHEETS
SOUTH DAKOTA	NH 0012(323)298	30	92

Revised	05/27/2025	DLM




ESTIMATE OF QUANTITIES			
ITEM	QEST	UNIT	
Remove Signal Equipment	Lump Sum	LS	


	REMOVE SIGNAL EQUIPMENT		
KEY	ITEM	UNIT	QUANT
_	Electrical Junstion Box (ED1)	EACH	1
#4	1/C #4 AWG COPPER WIRE	FT	960
2/c	2/C #14 AWG COPPER TRAY CABLE, K2	FT	1125
7/c	7/C #14 AWG COPPER TRAY CABLE, K2	FT	215
19/c	19/C #14 AWG COPPER TRAY CABLE, K2	FT	120
24/c	24/C #14 AWG COPPER TRAY CABLE, K2	FT	430
TSP	#16 AWG COPPER TWISTED SHIELDED PAIR	FT	110
PC	PREEMPTION CABLE	FT	415




PROJECT STATE OF SOUTH DAKOTA NH 0012(323)298 31 92

Plotting Date: 08/13/2025






EACH



s	STATE OF	PROJECT	SHEET NO.	TOTAL SHEETS
	SOUTH DAKOTA	NH 0012(323)298	32	92

Plotting Date: 08/13/2025




PD3 57+42.22-49.25' L PD4 57+46.73-40.33' L

PD1 56+83.24-39.70' L PD2 56+90.67-46.39' L

CONDUIT LAYOUT
US HWY 12/6TH AVE SW & 1ST ST S

	ESTIMATE OF QUANTITIES		
KEY	ITEM	QUANT	UNIT
	Type 4 Electrical Junction Box (EJD1)	1	EACH
#6	1/C #6 AWG COPPER WIRE	1225	FT
2/c	2/C #14 AWG COPPER TRAY CABLE, K2	1125	FT
7/c	7/C #14 AWG COPPER TRAY CABLE, K2	215	FT
19/c	19/C #14 AWG COPPER TRAY CABLE, K2	120	FT
24/c	24/C #14 AWG COPPER TRAY CABLE, K2	430	FT
TSP	#16 AWG COPPER TWISTED SHIELDED PAIR	110	FT
PC	PREEMPTION CABLE	415	FT



EXISTING SIGNAL LAYOUT US HWY 12/6TH AVE SW & MAIN ST S

 Revised: 8/13/25 MD
 STATE OF SOUTH DAKOTA
 PROJECT NO. SHEET NO. SHEETS
 TOTAL SHEETS

 NH 0012(323)298
 33
 92

Plotting Date: 08/13/2025


Revised 06/02/2025 DLM



ESTIMATE OF QUANTITIE	S	
ITEM	QUANT	UNIT
Remove Signal Equipment	Lump Sum	LS
Remove Signal Footing (EE3)	1	EACH
Remove Luminaire Pole	1	EACH
Remove luminaire pole Footing (EE4)	1	EACH

	REMOVE SIGNAL EQUIPMENT	
KEY	ITEM	EST QUANT
PB	Accessible Pedestrian Signal PE1 - PE8	8
₩-	Signal Pole w/35' Mast Arm (EE3)	1
	8' Luminaire Arm	1

	EXISTING ITEMS
KEY	ITEM
ф -	Signal Pole w/25' Mast Arm & 8' Lumin Arm (EE2)
₩ =	Signál Pole w/35' Mast Arm & 8' Lumin Arm (EE1, EE3)
•	Roadway Luminaire, 400w with P.E. (EE1-EE4)
-j>	3 Section Vehicle Signal Head (3, 4, 7-11)
47.5	5 Section Vehicle Signal Head (1, 2, 5, 6)
	Emergency Vehicle Preemption Unit (4-Channel)
[>	Optical Detector
PB	Accessible Pedestrian Signal
-(Pedestrian Signal Head (12-19)
START CROSSING WATCH FOR VAVICH FOR PENCIUS PONT START FRANCIO DON'T CROSS TO CROSS PUSH BUTTON	Pedestrian Crossing Sign R10-3b (Left - 4/Right - 4)



EX US


EXISTING CONDUIT LAYOUT US HWY 12/6TH AVE SW & MAIN ST S

Revised: 8/13/25 MD

	STATE OF	PROJECT	SHEET NO.	TOTAL SHEETS
)	SOUTH DAKOTA	NH 0012(323)298	34	92


Plotting Date: 08/13/2025

Revised 05/27/2025 DLM



ESTIMATE OF QUANTITIES	S	
ITEM	QUANT	UNIT
Remove Signal Equipment	Lump Sum	LS

	REMOVE SIGNAL EQUIPMENT		
KEY	ITEM	UNIT	EST QUANT
#4	1/C #4 AWG COPPER WIRE	FT	650
2/c	2/C #14 AWG COPPER TRAY CABLE, K2	FT	720
7/c	7/C #14 AWG COPPER TRAY CABLE, K2	FT	145
24/c	24/C #14 AWG COPPER TRAY CABLE, K2	FT	430
TSP	#16 AWG COPPER TWISTED SHIELDED PAIR	FT	525
PC)	PREEMPTION CABLE	FT	435



SIGNAL LAYOUT US HWY 12/6TH AVE SW & MAIN ST S

 Revised: 9/2/25
 MD
 STATE OF SOUTH DAKOTA
 PROJECT NO.
 SHEET NO.
 TOTAL SHEETS

 NH 0012(323)298
 35
 92

Plotting Date: 09/02/2025

Revised 06/02/2025


	ESTIMATE OF QUANTITIES		
KEY	ITEM	EST QUANT	UNIT
PB	Accessible Pedestrian Signal (PE1-PE8)	8	EACH
0	3" Diameter Footing (E3,E4)	24	FT
	Relocate Signal Equipment	LS	Lump Sum
0-	Install Signal Pole with Mast Arm and Luminaire Arm (E3)	1	EACH
	Signal Pole with 40' Mast Arm and 8' Luminaire Arm	1	EACH

^{*} Items are state furnished.

	RELOCATE SIGNAL EQUIPME	NT
KEY	ITEM	ODANT
<(]-	3 Section Vehicle Signal Head (7,8)	2
< 12	5 Section Vehicle Signal Head (1,6)	2
[]-	Pedestrian Signal Head with Count Down (14,15,18,19)	4
•	Roadway Luminaire (E3,E4)	2

Note:

The mast arm for signal pole E4 will not be installed at this time. The 40' mast arm will be delivered to the Aberdeen Region yard.



KEY

CONDUIT LAYOUT US HWY 12/6TH AVE SW & MAIN ST S

SHEET TOTAL NO. SHEETS PROJECT STATE OF Revised: 8/13/25 MD SOUTH DAKOTA NH 0012(323)298 36

Plotting Date: 08/13/2025



	QUANT	UNIT
	30	FT
	1750	FT
	720	FT
	145	FT
	445	FT
	525	FT
_		

FT

FT

525 435

130

ESTIMATE OF QUANTITIES

ITEM

2" SCHEDULE 40 CONDUIT

1/C #6 AWG COPPER WIRE


PREEMPTION CABLE

2/C #14 AWG COPPER TRAY CABLE, K2

7/C #14 AWG COPPER TRAY CABLE, K2

24/C #14 AWG COPPER TRAY CABLE, K2 #16 AWG COPPER TWISTED SHIELDED PAIR

2/C #10 AWG COPPER POLE AND BRACKET CABLE



PINT SCAIF - 1:40

EXISTING SIGNAL LAYOUT US HWY 12/6TH AVE SE & LINCOLN ST S

Revised: 8/13/25 MD

STATE OF	PROJECT	SHEET NO.	TOTAL SHEETS
SOUTH DAKOTA	NH 0012(323)298	37	92


Plotting Date: 08/13/2025

Revised 06/11/2025 DLM

ESTIMATE OF QUANTITIES			
ITEM	QUANT	UNIT	
Remove Signal Equipment	Lump Sum	LS	
Remove Pedesrian Push Button Pole (PF2.PF6)	2	EACH	

	REMOVE SIGNAL EQUIPMENT			
KEY	ITEM	QEST	UNIT	
PB	Accessible Pedestrian Signal PF1 - PF8	8	EACH	

	EXISTING ITEMS			
KEY	ITEM			
*	Luminaire Pole with Mounted Signal Heads (EF2)			
#	Signal Pole w/25' Mast Arm & 8' Lumin Arm (EF4)			
#	Signal Pole w/35' Mast Arm & 8' Lumin Arm (EF3)			
#	Signál Pole w/40' Mast Arm & 8' Lumin Arm (EF1)			
•	Roadway Luminaire, 400w with P.E. (EF1-EF4)			
-[>>	3 Section Vehicle Signal Head (1-11)			
	Emergency Vehicle Preemption Unit (4-Channel)			
[>	Optical Detector			
PB	Accessible Pedestrian Signal			
-([]	Pedestrian Signal Head (12-19)			
START CROSSING WATCH FOR WATCH FOR PHOLES ONT START HIMS CROSSING DON'T CROSS TO CROSS PUSH BUILTON	Pedestrian Crossing Sign R10-3b (Left - 4/Right - 4)			



EXISTING CONDUIT LAYOUT US HWY 12/6TH AVE SE & LINCOLN ST S


 Revised: 8/22/25 MD
 STATE OF SOUTH DAKOTA
 PROJECT NO.
 SHEET NO.
 SHEETS SHEETS

 NH 0012(323)298
 38
 92

	EXISTING ITEMS				
KEY	ITEM				
	Detector Loop				
	Meter Socket				
Ø	Wood Utility Pole				
M	Electrical Service Cabinet				
0	Electrical Junction Box				
×	Traffic Signal Controller				
2" SCH 40	2" Rigid Conduit, Schedule 40				
4" SCH 40	4" Rigid Conduit, Schedule 40				
3" SCH 80	3" Rigid Conduit, Schedule 80				
#4	1/C #4 AWG Copper Wire				
7/C	7/C #14 AWG Copper Tray Cable, K2				
19/C	19/C #14 AWG Copper Tray Cable, K2				
24/C	24/C #14 AWG Copper Tray Cable, K2				
TSP	#16 AWG Copper Twisted Shielded Pair				
PC	Preemption Cable				

ESTIMATE OF QUANTITIES			
ITEM	QEST	UNIT	
Remove Signal Equipment	Lump Sum	LS	

	REMOVE SIGNAL EQUIPMENT				
KEY	ITEM	EST QUANT	UNIT		
0	Electrical Junction Box (EJF1,EJF3)	2	EACH		
#4	1/C #4 AWG Copper Wire	815	EACH		
2/C	2/C #14 AWG Copper Tray Cable, K2	1130	FT		
7/C	7/C #14 AWG Copper Tray Cable, K2	50	FT		
19/C	19/C #14 AWG Copper Tray Cable, K2	155	FT		
24/C	24/C #14 AWG Copper Tray Cable, K2	395	FT		
TSP	#16 AWG Copper Twisted Shielded Pair	480	FT		
PC	Preemption Cable	485	FT		




SIGNAL LAYOUT US HWY 12/6TH AVE SE & LINCOLN ST S

Revised: 8/13/25 MD

Plotting Date: 08/13/2025

Revised 06/11/2025 DLM


	ESTIMATE OF QUANTITIES					
KEY	ITEM	EST QUANT	UNIT			
PB	Accessible Pedestrian Signal (PF1-PF8)	8	EACH			
0	Pedestrian Push Button Pole (PF2,PF6)	2	EACH			



STATE OF	PROJECT	SHEET NO.	TOTAL SHEETS
SOUTH DAKOTA	NH 0012(323)298	40	92

Plotting Date: 08/13/2025

CONDUIT LAYOUT US HWY 12/6TH AVE SE & LINCOLN ST S



	ESTIMATE OF QUANTITIES				
KEY	ITEM	EST QUANT	UNIT		
0	Type 3 Electrical Junction Box (EJF1)	1	EACH		
	Type 4 Electrical Junction Box (EJF3)	1	EACH		
#6	1/C #4 AWG Copper Wire	1650	EACH		
2/C	2/C #14 AWG Copper Tray Cable, K2	1130	FT		
7/C	7/C #14 AWG Copper Tray Cable, K2	50	FT		
19/C	19/C #14 AWG Copper Tray Cable, K2	155	FT		
24/C	24/C #14 AWG Copper Tray Cable, K2	395	FT		
TSP	#16 AWG Copper Twisted Shielded Pair	480	FT		
PC	Preemption Cable	485	FT		

EXISTING SIGNAL LAYOUT US HWY 12/6TH AVE SE & WASHINGTON ST S


Revised: 8/13/25 MD

| STATE OF SOUTH DAKOTA | NH 0012(323)298 | SHEET NO. SHEETS | SHEET NO. SH

ESTIMATE OF QUANTITIES			
ITEM	QUANT	UNIT	
Remove Signal Equipment	Lump Sum	LS	
Remove Pedesrian Push Button Pole (PG2)	1	EACH	

	REMOVE SIGNAL EQUIPMENT				
KEY	ITEM	EST QUANT	UNIT		
PB	Accessible Pedestrian Signal PG1 - PG8	8	EACH		


	EXISTING ITEMS			
KEY	ITEM			
#=	Signal Pole w/20' Mast Arm & 8' Lumin Arm (EG2,EG4)			
₩ •	Signal Polé w/35' Mast Arm & 8' Lumin Arm (EG3)			
#	Signal Pole w/40' Mast Arm & 8' Lumin Arm (EG1)			
•	Roadway Luminaire, 400w with P.E. (EG1-EG4)			
-i>	3 Section Vehicle Signal Head (1-14)			
	Emergency Vehicle Preemption Unit (4-Channel)			
[>	Optical Detector			
PB	Accessible Pedestrian Signal			
-([]	Pedestrian Signal Head (15-22)			
START CROSSING WATCH FOR VEHICLES DON'T START FRANCISCISTOR B STARTED DON'T CROSS TO CROSS PUSH BUTTON	Pedestrian Crossing Sign R10-3b (Left - 4/Right - 4)			



EXISTING ITEMS

ESTIMATE OF QUANTITIES		
ITEM	QUANT	UNIT
Remove Signal Equipment	Lump Sum	LS

	REMOVE SIGNAL EQUIPMENT				
KEY	ITEM	EST QUANT	UNIT		
0	Electrical Junction Box (EJG1,EJG3)	2	EACH		
#4	1/C #4 AWG Copper Wire	825	EACH		
2/C	2/C #14 AWG Copper Tray Cable, K2	995	FT		
7/C	7/C #14 AWG Copper Tray Cable, K2	290	FT		
24/C	24/C #14 AWG Copper Tray Cable, K2	465	FT		
TSP	#16 AWG Copper Twisted Shielded Pair	415	FT		
PC	Preemption Cable	645	FT		





PROJECT

STATE OF

Plotting Date: 08/13/2025


Revised 06/11/2025 DLM






PG1 67+87.04-39.43' L PG2 67+93.58-47.00' L Plotting Date: 08/13/2025

Revised 06/16/2025 DLM



PG3 68+49.65-47.17' L PG4 68+56.15-39.57' L

√ (sch) \ <u>40,</u> √	₩ SCH	
EQ EJO		
(2/C) (SCH) (40)	NIO S	D.O.W
R.O.W.	° 2/C 2	<u>R.O.W.</u>
	WPC (7/C) 2 (SCH) 3 (TSP) SCH) #6	
US Hwy 12/6th Ave SE	2 (24/0)	
67+00	68+00 PC 2/C 69+00	



ESTIMATE OF QUANTITIES				
KEY	ITEM	EST QUANT	UNIT	
0	Type 3 Electrical Junction Box (EJG1)	1	EACH	
	Type 4 Electrical Junction Box (EJG3)	1	EACH	
#6	1/C #6 AWG Copper Wire	1675	EACH	
2/C	2/C #14 AWG Copper Tray Cable, K2	995	FT	
(7/C)	7/C #14 AWG Copper Tray Cable, K2	290	FT	
24/0	24/C #14 AWG Copper Tray Cable, K2	465	FT	
TSP	#16 AWG Copper Twisted Shielded Pair	415	FT	
PC	Preemption Cable	645	FT	

EXISTING SIGNAL LAYOUT US HWY 12/6TH AVE SE & KLINE ST S

Revised: 8/13/25 MD


STATE OF	PROJECT	SHEET NO.	TOTAL SHEETS
SOUTH DAKOTA	NH 0012(323)298	45	92

Revised 06/16/2025 DLM

ESTIMATE OF QUANTITIES			
ITEM	EST QUANT	UNIT	
" " " " " " " " " " " " " " " " " " "	Lump Sum	LS	
Remove Pedesrian Push Button Pole (PH2.PH3.PH5.PH7)	4	EACH	

REMOVE SIGNAL EQUIPMENT				
KEY	ITEM	EST QUANT	UNIT	
PB	Accessible Pedestrian Signal PH1 - PH8	8	EACH	

	EXISTING ITEMS			
KEY	ITEM			
\$	Signal Pole w/20' Mast Arm & 8' Lumin Arm (EH4)			
ф=	Signal Pole w/25' Mast Arm & 8' Lumin Arm (EH2)			
☆	Signal Pole w/40' Mast Arm & 8' Lumin Arm (EH1,EH3)			
•	Roadway Luminaire, 400w with P.E. (EH1-EH4)			
-i>>	3 Section Vehicle Signal Head (1-14)			
	Emergency Vehicle Preemption Unit (4-Channel)			
[>	Optical Detector			
PB	Accessible Pedestrian Signal			
-([]	Pedestrian Signal Head (15-22)			
START CROSSING WATCH FOR WATCH FOR OCNTSTART HIGHIGES OCNTSTART DON'T CROSS TO CROSS PUSH BUTTON	Pedestrian Crossing Sign R10-3b (Left - 4/Right - 4)			




EXISTING CONDUIT LAYOUT US HWY 12/6TH AVE SE & KLINE ST S

PROJECT STATE OF Revised: 8/13/25 MD SOUTH DAKOTA NH 0012(323)298 46 92


Plotting Date: 08/13/2025

Revised 06/16/2025 DLM



ESTIMATE OF QUANTITIES			
item QEST uni			
Remove Signal Equipment	Lump Sum	LS	


REMOVE SIGNAL EQUIPMENT				
KEY	ITEM	EST QUANT	UNIT	
0	Electrical Junction Box (EJH1,EJH2,EJH3,EJH4)	4	EACH	
#4	1/C #4 AWG Copper Wire	795	EACH	
2/C	2/C #14 AWG Copper Tray Cable, K2	1120	FT	
7/C	7/C #14 AWG Copper Tray Cable, K2	275	FT	
24/C	24/C #14 AWG Copper Tray Cable, K2	535	FT	
TSP	#16 AWG Copper Twisted Shielded Pair	620	FT	
PC	Preemption Cable	660	FT	




SIGNAL LAYOUT
US HWY 12/6TH AVE SE & KLINE ST S

Revised: 8/13/25 MD

STATE OF	PROJECT	SHEET NO.	TOTAL SHEETS
SOUTH DAKOTA	NH 0012(323)298	47	92



	ESTIMATE OF QUANTITIES			
KEY	ITEM	EST QUANT	UNIT	
PB	Accessible Pedestrian Signal (PH1-PH8)	8	EACH	
v	Pedestrian Push Button Pole (PH2,PH3,PH5,PH7)	4	EACH	




STATE OF PROJECT SHEET TOTAL NO. SHEETS ABOUTH DAKOTA NH 0012(323)298 48 92

Plotting Date: 08/13/2025

Revised 06/16/2025 DLM







ESTIMATE OF QUANTITIES				
KEY	ITEM	QEST	UNIT	
0	Type 3 Electrical Junction Box (EJH1, EJH4)	2	EACH	
	Type 3A Electrical Junction Box (EJH2)	1	EACH	
	Type 4 Electrical Junction Box (EJH3)	1	EACH	
#6	1/C #6 AWG Copper Wire	1830	FT	
2/C	2/C #14 AWG Copper Tray Cable, K2	1120	FT	
<mark>7/C</mark>	7/C #14 AWG Copper Tray Cable, K2	275	FT	
24/0	24/C #14 AWG Copper Tray Cable, K2	535	FT	
(B)	#16 AWG Copper Twisted Shielded Pair	620	FT	
(S)	Preemption Cable	660	FT	

EXISTING SIGNAL LAYOUT US HWY 12/6TH AVE SE & STATE ST S

 Revised: 8/13/25 MD
 STATE OF SOUTH DAKOTA
 PROJECT
 SHEET NO.
 SHEETS SHEETS


 NH 0012(323)298
 49
 92





REMOVE SIGNAL EQUIPMENT			
KEY	ITEM	QUANT	
PB	Accessible Pedestrian Signal (PI1 - PI8)	8	


	EXISTING ITEMS
KEY	ITEM
☆	Signal Pole w/25' Mast Arm & 8' Lumin Arm (EI2,EI4)
☆	Signal Pole w/35' Mast Arm & 8' Lumin Arm (EI1,EI3)
•	Roadway Luminaire, 400w with P.E. (EI1-EI4)
-i>	3 Section Vehicle Signal Head (3, 4, 7, 8, 11, 12, 15, 16)
477	5 Section Vehicle Signal Head (1, 2, 5, 6, 9, 10, 13, 14)
	Emergency Vehicle Preemption Unit (4-Channel)
<u> </u>	Optical Detector
PB	Accessible Pedestrian Signal
-(Pedestrian Signal Head (17-23)
START CROSSING WATCH FOR VEHICLES DON'T START (HAWI CHOCKING F STARTE) DON'T CROSS FUSH BUTTON	Pedestrian Crossing Sign R10-3b (Left - 4/Right - 4)



EXISTING CONDUIT LAYOUT US HWY 12/6TH AVE SE & STATE ST S


 Revised: 8/13/25 MD
 STATE OF SOUTH DAKOTA
 PROJECT NO.
 SHEET NO.
 TOTAL SHEETS

 NH 0012(323)298
 50
 92





ESTIMATE OF QUANTIT	IES	
ITEM	EST QUANT	UNIT
Remove Signal Equipment	Lump Sum	LS

	REMOVE SIGNAL EQUIPMENT			
KEY	ITEM	EST QUANT	UNIT	
0	Electrical Junction Box (EJI1,EJI3)	2	EACH	
#4	1/C #4 AWG Copper Wire	935	EACH	
2/C 7/C	2/C #14 AWG Copper Tray Cable, K2	1200	FT	
7/C	7/C #14 AWG Copper Tray Cable, K2	605	FT	
24/C	24/C #14 AWG Copper Tray Cable, K2	605	FT	
TSP	#16 AWG Copper Twisted Shielded Pair	790	FT	
PC	Preemption Cable	805	FT	



PROJECT STATE OF SOUTH DAKOTA NH 0012(323)298 51 92






PROJECT NH 0012(323)298

52

92

Plotting Date: 08/13/2025



R.O.W.


85+00

R.O.W.

PI5 83+71.35-41.33' R PI6 83+63.04-47.97' R

120/240 v.a.c., 60 hz., 1 Phase, 3 Wire Service Existing (Northwestern Energy)

Pl1 82+93.59-40.86' L Pl2 83+02.32-48.13' L Pl4 83+75.81-44.05' L



PI7 83+02.16-51.09' R PI8 82+92.32-44.45' R

	ESTIMATE OF QUANTITIES				
KEY	ITEM	EST QUANT	UNIT		
0	Type 3 Electrical Junction Box (EJI1, EJI3)	2	EACH		
#6	1/C #6 AWG Copper Wire	2160	FT		
2/C	2/C #14 AWG Copper Tray Cable, K2	1200	FT		
7/C	7/C #14 AWG Copper Tray Cable, K2	605	FT		
24/0	24/C #14 AWG Copper Tray Cable, K2	605	FT		
TSP	#16 AWG Copper Twisted Shielded Pair	790	FT		
PC	Preemption Cable	805	FT		

EXISTING SIGNAL LAYOUT US HWY 12/6TH AVE SE & DAKOTA ST S

 Revised: 8/13/25 MD
 STATE OF SOUTH DAKOTA
 PROJECT NO.
 SHEET NO.
 SHEET NO.
 SHEET SHEETS


 53
 92

Revised	06/16/2025	DLM	

ESTIMATE OF QUANTITIES		
ITEM	EST QUANT	UNIT
Remove Signal Equipment	Lump Sum	LS

REMOVE SIGNAL EQUIPMENT			
KEY	ITEM	QUANT	
PB	Accessible Pedestrian Signal (PJ1 - PJ8)	8	
-[>	3 Section Vehicle Signal Head (13, 14)	2	

	EXISTING ITEMS
KEY	ITEM
₩=	Signal Pole w/35' Mast Arm & 8' Lumin Arm (EJ1,EJ3)
₩ •	Signal Pole w/40' Mast Arm & 8' Lumin Arm (EJ2)
₩ =	Signal Pole w/45' Mast Arm & 8' Lumin Arm (EJ4)
•	Roadway Luminaire, 400w with P.E. (EJ1-EJ4)
-j>	3 Section Vehicle Signal Head (3, 4, 7-16)
47.7	5 Section Vehicle Signal Head (1, 2, 5, 6)
	Emergency Vehicle Preemption Unit (4-Channel)
<u> </u>	Optical Detector
PB	Accessible Pedestrian Signal
-([]	Pedestrian Signal Head (17-24)
START CROSSING WATCH FOR VEHICLES DO DON'S TART FRIMI GROSSING IF STAMITED DON'T CROSS TO CROSS PUSH BUTTON	Pedestrian Crossing Sign R10-3b (Left - 4/Right - 4)



EXISTING CONDUIT LAYOUT US HWY 12/6TH AVE SE & DAKOTA ST S

 Revised: 8/13/25 MD
 STATE OF SOUTH DAKOTA
 PROJECT NO.
 SHEET NO.
 TOTAL SHEETS


 NH 0012(323)298
 54
 92

hosivos	06/16/2025	DΙ	N.

	EXISTING ITEMS		
KEY	ITEM		
[]]	Detector Loop		
	Meter Socket		
Ø	Wood Utility Pole		
M	Electrical Service Cabinet		
0	Electrical Junction Box		
X	Traffic Signal Controller		
2" SCH 40	2" Rigid Conduit, Schedule 40		
4" SCH 40	4" Rigid Conduit, Schedule 40		
3" SCH 80	3" Rigid Conduit, Schedule 80		
#4	1/C #4 AWG Copper Wire		
2/C	7/C #14 AWG Copper Tray Cable, K2		
7/C	7/C #14 AWG Copper Tray Cable, K2		
24/C	24/C #14 AWG Copper Tray Cable, K2		
TSP	#16 AWG Copper Twisted Shielded Pair		
(VC)	Video Cable		

ESTIMATE OF QUANTITIES		
ITEM	EST QUANT	UNIT
Remove Signal Equipment	Lump Sum	LS


REMOVE SIGNAL EQUIPMENT				
KEY	ITEM	EST QUANT	UNIT	
0	Electrical Junction Box (EJJ1,EJJ3,EJJ4)	3	EACH	
#4	1/C #4 AWG Copper Wire	780	EACH	
2/C	2/C #14 AWG Copper Tray Cable, K2	1270	FT	
7/C	7/C #14 AWG Copper Tray Cable, K2	620	FT	
24/C	24/C #14 AWG Copper Tray Cable, K2	620	FT	
TSP	#16 AWG Copper Twisted Shielded Pair	820	FT	
PC	Preemption Cable	765	FT	



Plotting Date: 08/13/2025

Revised 06/16/2025 DLM

ESTIMATE OF QUANTITIES			
KEY	ITEM	QUANT	UNIT
	5 section Vehicle Signal Head (13,14)	2	EACH
PB	Accessible Pedestrian Signal (PJ1-PJ8)	8	EACH




PROJECT NH 0012(323)298 56 92

Plotting Date: 08/13/2025

Revised 05/27/2025 DLM

CONDUIT LAYOUT US HWY 12/6TH AVE SE & DAKOTA ST S



	ESTIMATE OF QUANTITIES				
KEY	ITEM	QEST	UNIT		
0	Type 3 Electrical Junction Box (EJJ3, EJJ4)	2	EACH		
	Type 4 Electrical Junction Box (EJJ1)	1	EACH		
#6	1/C #6 AWG Copper Wire	1910	FT		
2/C	2/C #14 AWG Copper Tray Cable, K2	1270	FT		
7/C	7/C #14 AWG Copper Tray Cable, K2	710	FT		
24/0	24/C #14 AWG Copper Tray Cable, K2	620	FT		
PC	Preemption Cable	765	FT		

PLOT SCALE - 1:40

EXISTING SIGNAL LAYOUT US HWY 12/6TH AVE SE & HARRISON ST S

Revised: 8/13/25 MD

STATE OF	PROJECT	SHEET NO.	TOTAL SHEETS
SOUTH DAKOTA	NH 0012(323)298	57	92


Plotting Date: 08/13/2025

Rwvised 06/11/2025 DLM

ESTIMATE OF QUANTITIES			
ITEM	QUANT	UNIT	
Remove Signal Equipment	Lump Sum	LS	
Remove Pedesrian Push Button Pole (PK1,PK8)	2	EACH	

REMOVE SIGNAL EQUIPMENT			
KEY	ITEM	EST QUANT	
PB	Accessible Pedestrian Signal PK1 - PK8	8	

	EXISTING ITEMS
KEY	ITEM
ф	Signal Pole w/15' Mast Arm & 8' Lumin Arm (EK2)
☆	Signal Pole w/25' Mast Arm & 8' Lumin Arm (EK4)
₩ =	Signál Pole w/35' Mast Arm & 8' Lumin Arm (EK1)
₩	Signál Pole w/40' Mast Arm & 8' Lumin Arm (EK3)
•	Roadway Luminaire, 400w with P.E. (EK1-EK4)
-[]>	3 Section Vehicle Signal Head (1-14)
	Emergency Vehicle Preemption Unit (4-Channel)
[>	Optical Detector
PB	Accessible Pedestrian Signal
-([]	Pedestrian Signal Head (15-22)
START CROSSING WATCH FOR WEIGHTE WHITCHS WHITCHS WHITCHS WHITCHS WATCH FOR START WHITCHS WATCH W	Pedestrian Crossing Sign R10-3b (Left - 4/Right - 4)




EXISTING CONDUIT LAYOUT US HWY 12/6TH AVE SE & HARRISON ST S

 Revised: 8/13/25 MD
 STATE OF SOUTH DAKOTA
 PROJECT NO. SHEET NO. SHEETS
 SHEET SHEETS

 NH 0012(323)298
 58
 92


Plotting Date: 08/13/2025



ESTIMATE OF QUANTITIES		
ITEM	QUANT	UNIT
Remove Signal Equipment	Lump Sum	LS

Preemption Cable

REMOVE SIGNAL EQUIPMENT			
KEY	ITEM	EST QUANT	UNIT
0	Electrical Junction Box (EJK1,EJK3, EJK4)	3	EACH
#4	1/C #4 AWG Copper Wire	800	FT
#6	1/C #6 AWG Copper Wire	885	FT
2/C	2/C #14 AWG Copper Tray Cable, K2	1160	FT
7/C	7/C #14 AWG Copper Tray Cable, K2	280	FT
24/C	24/C #14 AWG Copper Tray Cable, K2	550	FT
TSP	#16 AWG Copper Twisted Shielded Pair	265	FT
PC	Preemption Cable	730	FT





SIGNAL LAYOUT US HWY 12/6TH AVE SE & HARRISON ST S Revised: 8/13/25 MD

STATE OF	PROJECT	SHEET NO.	TOTAL SHEETS
SOUTH DAKOTA	NH 0012(323)298	59	92


Plotting Date: 08/13/2025

Revised 06/11/2025 DLM






Revised: 8/13/25 MD | STATE OF SOUTH DAKOTA | NH 0012(323)298 | FROJECT | SHEET SHEETS | TOTAL NO. SHEETS | SHE



	\sim	
PK1 106+36.06-37.07' L		PK3 106+90.79 - 44.36' L
PK2 106+43,64-43,48' L	(PC)	PK4 106+99.27-36.58' L
FNZ 100143,04=43,40 L	\smile	FN4 100+33,27=30,30 L

	ESTIMATE OF QUANTITIES					
KEY	ITEM	ODANT	UNIT			
0	Type 3 Electrical Junction Box (EJK1, EJK3)	2	EACH			
	Type 4 Electrical Junction Box (EJK4)	1	EACH			
(#4)	1/C #6 AWG Copper Wire	1950	FT			
(2/C)	2/C #14 AWG Copper Tray Cable, K2	1160	FT			
(7/C)	7/C #14 AWG Copper Tray Cable, K2	280	FT			
24/0	24/C #14 AWG Copper Tray Cable, K2	550	FT			
TSP	#16 AWG Copper Twisted Sheielder Pair	265	FT			
PC	Preemption Cable	730	FT			



EXISTING SIGNAL LAYOUT US HWY 12/6TH AVE SE & LAWSON ST S

Revised: 8/13/25 MD


STATE OF	PROJECT	SHEET NO.	TOTAL SHEETS
SOUTH DAKOTA	NH 0012(323)298	61	92

Revised 06/16/2025 DLM

ESTIMATE OF QUANTITIES			
ITEM	QUANT	UNIT	
Remove Signal Equipment	Lump Sum	LS	
Remove Pedesrian Push Button Pole	1	EACH	

	REMOVE SIGNAL EQUIPMENT				
KEY ITEM QES					
PB	Accessible Pedestrian Signal (PL1 - PL4)	4			
0	Pedestal Signal Pole (EL3)	1			

	EXISTING ITEMS
KEY	ITEM
₩	Luminaire Pole with Mounted Signal Heads (EL3)
•	Signal Pole w/25' & 40' Mast Arms & 8' Lumin Arm (EL1)
***	Signal Pole w/15' & 25' Mast Arms & 8' Lumin Arm (EL2)
•	Roadway Luminaire, 400w with P.E. (EL1,EL2)
-i>>	3 Section Vehicle Signal Head (3-12)
	5 Section Vehicle Signal Head (1, 2)
	Emergency Vehicle Preemption Unit (4-Channel)
[>	Optical Detector
PB	Accessible Pedestrian Signal
-[[]	Pedestrian Signal Head (13-16)
START CRIDSING VATCH FOR VATCH FOR SHYCLES OWN START RIGHT CROSS TO CROSS PUSH BUTTON	Pedestrian Crossing Sign R10-3b (Left - 2/Right - 2)



KEY

0

Detector Loop

Meter Socket

Power Pole

Electrical Service Cabinet

Electrical Junction Box

KEY

Electrical Junction Box (EJL1,EJL2)

Preemption Cable

1/C #4 AWG Copper Wire

1/C #6 AWG Copper Wire

2/C #14 AWG Copper Tray Cable, K2

7/C #14 AWG Copper Tray Cable, K2

26/C #14 AWG Copper Tray Cable, K2

#16 AWG Copper Twisted Shielded Pair

Traffic Signal Controller 2" Rigid Conduit, Schedule 40 4" Rigid Conduit, Schedule 40 3" Rigid Conduit, Schedule 80 1/C #4 AWG Copper Wire 1/C #6 AWG Copper Wire 2/C #14 AWG Copper Tray Cable, K2 7/C #14 AWG Copper Tray Cable, K2 26/C #14 AWG Copper Tray Cable, K2 #16 AWG Copper Twisted Shielded Pair Preemption Cable **ESTIMATE OF QUANTITIES** OUANT ITEM UNIT Remove Signal Equipment Lump Sum

REMOVE SIGNAL EQUIPMENT

QUANT UNIT

1095

1470

370

255

310

450

285

EACH

FT

FT

FT

FT

FT

FT

EXISTING ITEMS

ITEM

EXISTING CONDUIT LAYOUT US HWY 12/6TH AVE SE & LAWSON ST S

Revised: 8/13/25 MD

STATE OF SOUTH DAKOTA

NH 0012(323)298

SHEET TOTAL SHEETS


NH 0012(323)298

62

92

Plotting Date: 08/13/2025

Revised 06/16/2025 DLM



s	TATE OF	PROJECT	SHEET NO.	TOTAL SHEETS
	SOUTH NH 0012(323)298	63	92	


Plotting Date: 08/13/2025

Revised 06/16/2025 DLM

SIGNAL LAYOUT US HWY 12/6TH AVE SE & LAWSON ST S

	ESTIMATE OF QUANTITIES				
KEY	ITEM	QEST	UNIT		
0	Pedestal Signal Pole (L3)	1	EACH		
PB	Accessible Pedestrian Signal (PL1-PL4)	4	EACH		
	RELOCATE SIGNAL EQUIPMENT	LUMP SUM	LS		
v	Pedestrian Push Button Pole (PL2)	2	EACH		

RELOCATE SIGNAL EQUIPMENT				
KEY	ITEM	EST QUANT		
<u> </u>	3 SECTION VEHICLE SIGNAL HEAD (12)	1		
(A)	5 SECTION VEHICLE SIGNAL HEAD (1)	1		
-([]	PEDESTRIAN SIGNAL HEAD WITH COUNTDOWN TIMER (14,15)	2		




D	STATE OF	PROJECT	SHEET	TOTAL SHEETS
	SOUTH DAKOTA	NH 0012(323)298	ю. 64	92

Plotting Date: 08/13/2025

Revised 06/16/2025 DLM





CONDUIT LAYOUT
US HWY 12/6TH AVE SE & LAWSON ST S

	ESTIMATE OF QUANTITIES				
KEY	KEY ITEM				
0	Type 3 Electrical Junction Box (EJL1, EJL2)	2	EACH		
(#6)	1/C #6 AWG Copper Wire	2230	FT		
(2/C)	2/C #14 AWG Copper Tray Cable, K2	370	FT		
(4/C)	4/C #14 AWG Copper Tray Cable, K2	45	FT		
7/C	7/C #14 AWG Copper Tray Cable, K2	255	FT		
24/0	24/C #14 AWG Copper Tray Cable, K2	310	FT		
TSP	Twisted Sheilded Pair	450	FT		
PC	Preemption Cable	285	FT		

EXISTING SIGNAL LAYOUT US HWY 12/6TH AVE SE & ROOSEVELT ST S

 Revised: 8/13/25 MD
 STATE OF SOUTH DAKOTA
 PROJECT NO.
 SHEET NO.
 SHEETS SHEETS

 NH 0012(323)298
 65
 92


Plotting Date: 08/13/2025

Revised 06/16/2025 DLM

ESTIMATE OF QUANTITIES		
ITEM	QUANT	UNIT
Remove Signal Equipment	Lump Sum	LS

REMOVE SIGNAL EQUIPMENT				
KEY	ITEM	QUANT		
PB	Accessible Pedestrian Signal (PM1 - PM8)	8		


	EXISTING ITEMS				
KEY	ITEM				
φ——	Signal Pole w/40' Mast Arm (EM1)				
\$===	Signal Pole w/45' Mast Arm (EM4)				
☆	Signal Pole w/40' Mast Arm & 8' Lumin Arm (EM3)				
ф -	Signal Pole w/50' Mast Arm & 8' Lumin Arm (EM2)				
•	Roadway Luminaire, 400w with P.E. (EM2,EM3)				
-i>>	3 Section Vehicle Signal Head (3, 4, 7, 8, 11, 12, 15, 16)				
	5 Section Vehicle Signal Head (1, 2, 5, 6, 9, 10, 13, 14)				
ĵ>	Optical Detector				
PB	Accessible Pedestrian Signal				
-([]	Pedestrian Signal Head w/Countdown Timer (17-24)				
START GROSSING WATCHERS WATCHERS DON'T START OF THE REMAINING TO THE REMAINING TO GROSS PUSH BUTTON	Pedestrian Crossing Sign R10-3e (Left - 4/Right - 4)				



EXISTING CONDUIT LAYOUT US HWY 12/6TH AVE SE & ROOSEVELT ST S

PROJECT STATE OF SOUTH DAKOTA NH 0012(323)298 66 92


Plotting Date: 08/13/2025 Revised 06/16/2025 DLM



	EXISTING ITEMS				
KEY	ITEM				
W	Meter Socket				
Ø	Wood Utility Pole				
	Electrical Service Cabinet				
0	Electrical Junction Box				
	Traffic Signal Controller				
2" SCH 40	2" Rigid Conduit, Schedule 40				
4" SCH 40	4" Rigid Conduit, Schedule 40				
3" SCH 80	3" Rigid Conduit, Schedule 80				
4" SCH 80	4" Rigid Conduit, Schedule 80				
(#6) (#6)	1/C #6 AWG Copper Wire				
(2/C) (2/C)	2/C #14 AWG Copper Tray Cable, K2				
30/C	30/C #14 AWG Copper Tray Cable, K2				
(PC) PC	Preemption Cable				
(VC)	Video Cable				

ESTIMATE OF QUANTITIES				
ITEM	QUANT	UNIT		
Remove Signal Equipment	Lump Sum	LS		

	REMOVE SIGNAL EQUIPMENT					
KEY	ITEM	EST QUANT	UNIT			
0	Electrical Junction Box (EJM1)	1	EACH			
#6	1/C #6 AWG Copper Wire	1215	FT			
2/C	2/C #14 AWG Copper Tray Cable, K2	1140	FT			
30/C	30/C #14 AWG Copper Tray Cable, K2	570	FT			
PC	Preemption Cable	170	FT			




Revised: 8/13/25 MD


STATE OF	PROJECT	SHEET NO.	TOTAL SHEETS
SOUTH DAKOTA	NH 0012(323)298	67	92

Plotting Date: 08/13/2025




Revised 06/16/2025 DLM





Plotting Date: 08/13/2025


Revised 06/16/2025 DLM



PM1 147+84.15 -41.17' L PM2 147+92.01 -48.98' L

CONDUIT LAYOUT
US HWY 12/6TH AVE SE & ROOSEVELT ST S

7' L
PM3 148+73.17 -50.95' L
PM4 148+81.04 -43.57' L



	ESTIMATE OF QUANTITIES					
KEY	ITEM	ODANT	UNIT			
0	Type 3 Electrical Junction Box (JM1)	1	EACH			
#6	1/C #6 AWG Copper Wire	1215	FT			
2/C	2/C #14 AWG Copper Tray Cable, K2	1140	FT			
7/C	7/C #14 AWG Copper Tray Cable, K2	570	FT			
24/0	24/C #14 AWG Copper Tray Cable, K2	570	FT			
PC	Preemption Cable	170	FT			

STATE OF PROJECT SHEET TOTAL NO. SHEETS SOUTH DAKOTA NH 0012(323)298 69 92

Plotting Date: 08/13/2025

WIRING DIAGRAM

US HWY 12/6TH AVE SW & 10TH ST S

POLE: EA1 CABLE SIZE: 24/C POLE: EA2 CABLE SIZE: 24/C POLE: EA3 CABLE SIZE: 24/C POLE: EA4 CABLE SIZE: 24/C

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Red	RED	R	2	6
6Y	Orange	ORANGE	Y	2	6
6G	Blue	BLUE	G	2	6
N	Black	BLACK	N	2	6
6R	Red/Black	RED	R	3	6
6Y	Orange/Black	ORANGE	Y	3	6
6G	Blue/Black	BLUE	G	3	6
N	Yellow/Black	BLACK	N	3	6
6R	Black/Red	RED	R	4	6
6Y	Orange/Red	ORANGE	Y	4	6
6G	Blue/Red	BLUE	G	4	6
N	Brown/Black	BLACK	N	4	6
N	Black/Blue	BLACK	N	16	6P
11R	Yellow/Red	RED	DW	16	6P
11G	Orange/Blue	BLUE	W	16	6P
N	Black/Orange	BLACK	N	21	4P
10R	Red/Orange	RED	DW	21	4P
10G	Blue/Orange	BLUE	W	21	4P
	Yellow				
	Brown				
	Brown/Red				
	Red/Blue				
	Yellow/Blue				
	Brown/Blue				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
2R	Black/Red	RED	R	5	2
2Y	Orange/Red	ORANGE	Y	5	2
2G	Blue/Red	BLUE	G	5	2
N	Brown/Black	BLAK	N	5	2
8R	Red	RED	R	10	4
8Y	Orange	ORANGE	Y	10	4
8G	Blue	BLUE	G	10	4
N	Black	BLACK	N	10	4
8R	Red/Black	RED	R	11	4
8Y	Orange/Black	ORANGE	Y	11	4
8G	Blue/Black	BLUE	G	11	4
N	Yellow/Black	BLACK	N	11	4
N	Black/Blue	BLACK	N	17	6P
11R	Brown/Red	RED	DW	17	6P
11G	Red/Blue	BLUE	W	17	6P
N	Black/Orange	BLACK	N	22	8P
12R	Red/Orange	RED	DW	22	8P
12G	Orange/Blue	BLUE	W	22	8P
	Yellow				
	Brown				
	Yellow/Red				
	Yellow/Blue				
	Brown/Blue				
	Blue/Orange				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
2R	Red	RED	R	6	2
2Y	Orange	ORANGE	Y	6	2
2G	Blue	BLUE	G	6	2
N	Black	BLACK	N	6	2
2R	Red/Black	RED	R	7	2
2Y	Orange/Black	ORANGE	Y	7	2
2G	Blue/Black	BLUE	G	7	2
N	Yellow/Black	BLACK	N	7	2
2R	Black/Red	RED	R	8	2
2Y	Orange/Red	ORANGE	Y	8	2
2G	Blue/Red	BLUE	G	8	2
N	Brown/Black	BLACK	N	8	2
4R	Yellow/Red	RED	R	13	4
4Y	Orange/Blue	ORANGE	Y	13	4
4G	Red/Blue	BLUE	G	13	4
N	Black/Blue	BLACK	N	13	4
N	Black/Orange	BLACK	N	18	2P
9R	Brown/Red	RED	DW	18	2P
9G	Yellow/Blue	BLUE	W	18	2P
	Yellow				
	Brown				
	Brown/Blue				
	Red/Orange				
	Blue/Orange	_			

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Black/Red	RED	R	1	6
6Y	Orange/Red	ORANGE	Y	1	6
6G	Blue/Red	BLUE	G	1	6
N	Brown/Black	BLACK	N	1	6
6R	Red	RED	R	14	4
6Y	Orange	ORANGE	Y	14	4
6G	Blue	BLUE	G	14	4
N	Black	BLACK	N	14	4
4R	Red/Black	RED	R	15	4
4Y	Orange/Black	ORANGE	Y	15	4
4G	Blue/Black	BLUE	G	15	4
N	Yellow/Black	BLACK	N	15	4
N	Black/Blue	BLACK	N	19	2P
9R	Red/Blue	RED	DW	19	2P
9G	Orange/Blue	BLUE	W	19	2P
N	Black/Orange	BLACK	N	20	4P
10R	Red/Orange	RED	DW	20	4P
10G	Blue/Orange	BLUE	W	20	4P
	Yellow				
	Brown				
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
_	Brown/Blue				

POLE:	EA1	CABLE SIZE:	7/C

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
8R	Red	RED	R	9	8
8Y	Orange	ORANGE	Y	9	8
8G	Blue	BLUE	G	9	8
N	Black	BLACK	N	9	8
	Yellow				
	Brown				
	Red/Black				

POLE:	EA3	CABLE SIZE:	7/C
		OADLE OILE.	.,.

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
N	Black	BLACK	N	23	8P
12R	Red	RED	DW	23	8P
12G	Blue	BLUE	W	23	8P
	Orange				
	Yellow				
	Brown				
	Red/Black				

24/C

24/C

CABLE SIZE:

Plotting Date: 08/13/2025

POLE:

POLE:

EB4

WIRING DIAGRAM

US HWY 12/6TH AVE SW & 5TH ST S

24/C

CABLE POLE **CABINET** HEAD | HEAD CONDUCTOR COND. TERM. TERM. NO. COLOR **COLOR** 6R Red RED R 2 6 2 6 **6Y** Y **ORANGE** Orange 6G Blue **BLUE** \mathbf{G} 2 6 N Black BLACK N 2 6 1Y Yellow YELLOW YA 2 1 1**G Brown BROWN** GA 2 1 6R Red/Black 3 6 RED **6Y** Orange/Black **ORANGE** Y 3 6 6G Blue/Black **BLUE** G 3 6 Yellow/Black BLACK 3 6 N 6R Black/Red RED R 4 6 **6Y** Y 4 6 Orange/Red **ORANGE** 6G 4 6 Blue/Red **BLUE** N Brown/Black BLACK N 4 6 Black/Blue 17 6P N BLACK N 11R 17 **6P** Yellow/Red RED **6P** 11G Red/Blue **BLUE** W 17 **6P** N Black/Orange BLACK N 22 Brown/Red RED 22 4P 10G Orange/Blue **BLUE** \mathbf{W} 22 4P Yellow/Blue Brown/Blue Red/Orange

CABLE SIZE:

24/C

POLE: EB1

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
2R	Black/Red	RED	R	5	2
2Y	Orange/Red	ORANGE	Y	5	2
2G	Blue/Red	BLUE	G	5	2
N	Brown/Black	BLACK	N	5	2
8R	Red	RED	R	10	8
8Y	Orange	ORANGE	Y	10	8
8G	Blue	BLUE	G	10	8
N	Black	BLACK	N	10	8
8R	Red/Black	RED	R	11	8
8Y	Orange/Black	ORANGE	Y	11	8
8G	Blue/Black	BLUE	G	11	8
N	Yellow/Black	BLACK	N	11	8
N	Black/Blue	BLACK	N	18	6P
11R	Yellow/Red	RED	DW	18	6P
11G	Red/Blue	BLUE	W	18	6P
N	Black/Orange	BLACK	N	23	8P
12R	Red/Orange	RED	DW	23	8P
12G	Blue/Orange	BLUE	W	23	8P
	Yellow				
	Brown				
	Brown/Red				
	Orange/Blue				
	Yellow/Blue				
	Brown/Blue				
	1	1			

POLE: EB2 CABLE SIZE:

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
2R	Red	RED	R	7	2
2Y	Orange	ORANGE	Y	7	2
2G	Blue	BLUE	G	7	2
N	Black	BLACK	N	7	2
2R	Red/Black	RED	R	8	2
2Y	Orange/Black	ORANGE	Y	8	2
2 G	Blue/Black	BLUE	G	8	2
N	Yellow/Black	BLACK	N	8	2
4R	Black/Red	RED	R	13	4
4Y	Orange/Red	ORANGE	Y	13	4
4G	Blue/Red	BLUE	G	13	4
N	Brown/Black	BLACK	N	13	4
N	Black/Blue	BLACK	N	19	2P
9R	Yellow/Red	RED	DW	19	2P
9G	Red/Blue	BLUE	W	19	2P
N	Black/Orange	BLACK	N	24	8P
12R	Red/Orange	RED	DW	24	8P
12G	Blue/Orange	BLUE	W	24	8P
	Yellow				
	Brown				
	Brown/Red				
	Orange/Blue				
	Yellow/Blue				
	Brown/Blue				

POLE: EB3 CABLE SIZE:

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
4R	Red	RED	R	14	4
4Y	Orange	ORANGE	Y	14	4
4G	Blue	BLUE	G	14	4
N	Black	BLACK	N	14	4
4R	Red/Black	RED	R	15	4
4Y	Orange/Black	ORANGE	Y	15	4
4G	Blue/Black	BLUE	G	15	4
N	Yellow/Black	BLACK	N	15	4
4R	Black/Red	RED	R	16	4
4Y	Orange/Red	ORANGE	Y	16	4
4G	Blue/Red	BLUE	G	16	4
N	Brown/Black	BLACK	N	16	4
N	Black/Orange	BLACK	N	20	2P
9R	Red/Orange	RED	DW	20	2P
9G	Blue/Orange	BLUE	W	20	2P
N	Black/Blue	BLACK	N	21	4P
10R	Red/Blue	RED	DW	21	4P
10G	Orange/Blue	BLUE	W	21	4P
	Yellow				
	Brown				
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	ø
6R	Red	RED	R	9	8
6Y	Orange	ORANGE	Y	9	8
6G	Blue	BLUE	G	9	8
N	Black	BLACK	N	9	8
	Yellow				
	Brown				
	Red/Black				

CABLE SIZE:

7/C__

POLE:

EB2

Blue/Orange

POLE: EB1

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
8R	Red	RED	R	12	8
8Y	Orange	ORANGE	Y	12	8
8G	Blue	BLUE	G	12	8
N	Black	BLACK	N	12	8
	Yellow				
	Brown				
	Red/Black				

CABLE SIZE:

7/C

POLE:

EB3

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
2R	Red	RED	R	6	2
2Y	Orange	ORANGE	Y	6	2
2G	Blue	BLUE	G	6	2
N	Black	N	N	6	2
5Y	Yellow	YELLOW	YA	6	5
5G	Brown	BROWN	GA	6	5
	Red/Black				

CABLE SIZE:

7/C

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	ø
6R	Red	RED	R	1	6
6Y	Orange	ORANGE	Y	1	6
6G	Blue	BLUE	G	1	6
N	Black	BLACK	N	1	6
1Y	Yellow	YELLOW	YA	1	1
1G	Brown	BROWN	GA	1	1
	Red/Black				

CABLE SIZE:

7/C

EB4

PLOTTED FROM - TRAB17879B

FILE - ... \PRJ\BRWNØ9V9\B

WIRING DIAGRAM

US HWY 12/6TH AVE SW & 2ND ST S

POLE: EC1 CABLE SIZE: 24/C POLE: EC2 CABLE SIZE: 24/C POLE: EC3 CABLE SIZE: 24/C POLE: EC4 CABLE SIZE: 24/C

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Red	RED	R	3	6
6Y	Orange	ORANGE	Y	3	6
6G	Blue	BLUE	G	3	6
N	Black	BLACK	N	3	6
6R	Red/Black	RED	R	4	6
6Y	Orange/Black	ORANGE	Y	4	6
6G	Blue/Black	BLUE	G	4	6
N	Yellow/Black	BLACK	N	4	6
8R	Black/Red	RED	R	9	8
8Y	Orange/Red	YELLOW	Y	9	8
8G	Blue/Red	BLUE	G	9	8
N	Brown/Black	BLACK	N	9	8
11R	Yellow/Red	RED	DW	15	6P
11G	Orange/Blue	BLUE	W	15	6P
N	Black/Blue	BLACK	N	15	6P
10R	Red/Orange	RED	DW	21	4P
10G	Blue/Orange	BLUE	W	21	4P
N	Black/Orange	BLACK	N	21	4P
	Yellow				
	Brown				
	Brown/Red				
	Red/Blue				
	Yellow/Blue				
	Brown/Blue				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
2R	Red	RED	R	5	2
2Y	Orange	ORANGE	Y	5	2
2G	Blue	BLUE	G	5	2
5Y	Yellow	YELLOW	YA	5	5
5G	Brown	BROWN	GA	5	5
N	Black	BLACK	N	5	2
8R	Red/Black	RED	R	10	8
8Y	Orange/Black	ORANGE	Y	10	8
8G	Blue/Black	BLUE	G	10	8
N	Yellow/Black	BLACK	N	10	8
8R	Black/Red	RED	R	11	8
8Y	Orange/Red	ORANGE	Y	11	8
8G	Blue/Red	BLUE	G	11	8
N	Brown/Black	BLACK	N	11	8
11R	Red/Orange	RED	DW	16	6P
11G	Blue/Orange	BLUE	W	16	6P
N	Black/Orange	BLACK	N	16	6P
12R	Brown/Red	RED	DW	22	8P
12G	Brown/Blue	BLUE	W	22	8P
N	Black/Blue	BLACK	N	22	8P
	Yellow/Red				
	Red/Blue				
	Orange/Blue				
	Yellow/Blue				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
2R	Red	RED	R	6	2
2Y	Orange	ORANGE	Y	6	2
2G	Blue	BLUE	G	6	2
5Y	Yellow	YELLOW	YA	6	5
5G	Brown	BROWN	GA	6	5
N	Black	BLACK	N	6	2
2R	Red/Black	RED	R	7	2
2Y	Orange/Black	ORANGE	Y	7	2
2G	Blue/Black	BLUE	G	7	2
N	Yellow/Black	BLACK	N	7	2
2R	Black/Red	RED	R	8	2
2Y	Orange/Red	ORANGE	Y	8	2
2G	Blue/Red	BLUE	G	8	2
N	Brown/Black	BLACK	N	8	2
9R	Red/Orange	RED	DW	17	2P
9G	Blue/Orange	BLUE	W	17	2P
N	Black/Orange	BLACK	N	17	2P
12R	Brown/Red	RED	DW	23	8P
12G	Brown/Blue	BLUE	W	23	8P
N	Black/Blue	BLACK	N	23	8P
	Yellow/Red				
	Red/Blue				
	Orange/Blue				
	Yellow/Blue				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
4R	Red/Black	RED	R	13	4
4Y	Orange/Black	ORANGE	Y	13	4
4G	Blue/Black	BLUE	G	13	4
7 Y	Yellow/Black	YELLOW	YA	13	7
7G	Brown/Black	BROWN	GA	13	7
N	Black/Red	BLACK	N	13	4
4R	Red	RED	R	14	4
4Y	Orange	ORANGE	Y	14	4
4G	Blue	BLUE	G	14	4
13Y	Yellow	YELLOW	YA	14	OLA
13G	Brown	BROWN	GA	14	OLA
N	Black	BLACK	N	14	4
9R	Red/Orange	RED	DW	18	2P
9G	Blue/Orange	BLUE	W	18	2P
N	Black/Orange	BLACK	N	18	2P
10R	Red/Blue	RED	DW	20	4P
10G	Orange/Blue	BLUE	W	20	4P
N	Black/Blue	BLACK	N	20	4P
	Blue/Red				
	Orange/Red				
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

POLE:	EC1	CABLE SIZE:	7/C

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Red	RED	R	2	6
6Y	Orange	ORANGE	Y	2	6
6G	Blue	BLUE	G	2	6
1Y	Yellow	YELLOW	YA	2	1
1R	Brown	BROWN	GA	2	1
N	Black	BLACK	N	2	6
	Red/Black				

OLE:	EC3	CABLE SIZE:	7/C

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
4R	Red	RED	R	12	4
4Y	Orange	ORANGE	Y	12	4
4G	Blue	BLUE	G	12	4
N	Black	BLACK	N	12	4
	Yellow				
	Brown				
	Red/Black				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Red	RED	R	1	6
6Y	Orange	ORANG	Y	1	6
6G	Blue	BLUE	G	1	6
1Y	Yellow	YELLOW	YA	1	1
1G	Brown	BROWN	GA	1	1
N	Black	BLACK	N	1	6
	Red/Black				

POLE: EC4 CABLE SIZE:

FILE\PRJ\BRWNØ9V9\BORDER.[

7/C

FROM - TRAB17879B

PROJECT STATE OF SOUTH NH 0012(323)298 72 92 DAKOTA Plotting Date: 08/13/2025

WIRING DIAGRAM

US HWY 12/6TH AVE SW & 1ST ST S

2

2

6P

6P

8P

8P

POLE: ED1 CABLE SIZE: 24/C

POLE

COND.

COLOR

RED

ORANGE

BLUE

BLACK

RED

ORANGE

BLUE

BLACK

RED

ORANGE

BLUE

BLACK

RED

BLUE

BLACK

RED

BLUE

BLACK

HEAD | HEAD

NO.

2

2

2

2

3

3

3

3

4

4

4

4

12

12

12

17 17

17

TERM.

R

Y

N

G

Y

G

 \mathbf{DW}

 \mathbf{DW}

CABLE

CONDUCTOR

COLOR

Red

Orange

Blue

Black

Red/Black

Orange/Black

Blue/Black

Yellow/Black

Black/Red

Orange/Red

Blue/Red

Brown/Black

Red/Orange

Blue/Orange

Black/Orange

Red/Blue

Orange/Blue

Black/Blue

Yellow Brown Yellow/Red Brown/Red Yellow/Blue Brown/Blue POLE: ED2 CABLE SIZE:

POLE: <u>ED3</u> CABLE SIZE:

24/C

POLE: ED4 CABLE SIZE:

24/C

19/C

6

6 6

6

6

6

6

6

6

6

6P

6P 6P

4P

4P

4P

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEA NO
2R	Red	RED	R	5
2Y	Orange	ORANGE	Y	5
2 G	Blue	BLUE	G	5
N	Black	BLACK	N	5
11R	Red/Blue	RED	DW	13
11G	Orange/Blue	BLUE	W	13
N	Black/Blue	BLACK	N	13
12R	Black/Red	RED	DW	18
12G	Blue/Red	BLUE	W	18
N	Brown/Black	BLACK	N	18
	Yellow			
	Brown			
	Red/Black			
	Blue/Black			
	Orange/Black			
	Yellow/Black			
	Orange/Red			
	Yellow/Red			
	Brown/Red			

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
2R	Red	RED	R	6	2
2Y	Orange	ORANGE	Y	6	2
2G	Blue	BLUE	G	6	2
N	Black	BLACK	N	6	2
2R	Red/Black	RED	R	7	2
2Y	Orange/Black	ORANGE	Y	7	2
2G	Blue/Black	BLUE	G	7	2
N	Yellow/Black	BLACK	N	7	2
2R	Black/Red	RED	R	8	2
2Y	Orange/Red	ORANGE	Y	8	2
2G	Blue/Red	BLUE	G	8	2
N	Brown/Black	BLACK	N	8	2
4R	Red/Blue	RED	R	9	4
4Y	Orange/Blue	ORANGE	Y	9	4
4G	Yellow/Blue	BLUE	G	9	4
N	Black/Blue	BLACK	N	9	4
9R	Red/Orange	RED	DW	14	2P
9G	Blue/Orange	BLUE	W	14	2P
N	Black/Orange	BLACK	N	14	2P
	Yellow				
	Brown				
	Yellow/Red				
	Brown/Red				
	Brown/Blue				

		1			
CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Red	RED	R	1	6
6Y	Orange	ORANGE	Y	1	6
6G	Blue	BLUE	G	1	6
N	Black	BLACK	N	1	6
4R	Red/Black	RED	R	10	4
4Y	Orange/Black	ORANGE	Y	10	4
4G	Blue/Black	BLUE	G	10	4
N	Yellow/Black	BLACK	N	10	4
4R	Black/Red	RED	R	11	4
4Y	Orange/Red	ORANGE	Y	11	4
4G	Blue/Red	BLUE	G	11	4
N	Brown/Black	BLACK	N	11	4
9R	Red/Orange	RED	DW	15	2P
9G	Blue/Orange	BLUE	W	15	2P
N	Black/Orange	BLACK	N	15	2P
10R	Red/Blue	RED	DW	16	4P
10G	Orange/Blue	BLUE	W	16	4P
N	Black/Blue	BLACK	N	16	4P
	Yellow				
	Brown				
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

POLE: ED3 **CABLE SIZE:** 7/C

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
12R	Red	RED	DW	18	8P
12G	Blue	BLUE	W	18	8P
N	Black	BLACK	N	18	8P
	Orange				
	Yellow				
	Brown				
	Red/Black				

CABINET

TERM.

6R

6Y

6G

N

6R

6Y

6G

N

6R

6Y

6G

N

11R

11G

N

10R

10G

N

	STATE OF	PROJECT	SHEET NO.	TOTAL SHEET
1	SOUTH DAKOTA	NH 0012(323)298	73	92
	Plotting (Date: 08/13/2025		

WIRING DIAGRAM

US HWY 12/6TH AVE SW & Main ST S

POLE: EE1 CABLE SIZE: 24/C POLE: <u>EE2</u> CABLE SIZE: POLE: EE3 CABLE SIZE: 24/C 24/C 24/C POLE: <u>EE4</u> CABLE SIZE:

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Red	RED	R	3	6
6Y	Orange	ORANGE	Y	3	6
6G	Blue	BLUE	G	3	6
N	Black	BLACK	N	3	6
6R	Red/Black	RED	R	4	6
6Y	Orange/Black	ORANGE	Y	4	6
6G	Blue/Black	BLUE	G	4	6
N	Yellow/Black	BLACK	N	4	6
8R	Black/Red	RED	R	9	8
8Y	Orange/Red	ORANGE	Y	9	8
8G	Blue/Red	BLUE	G	9	8
N	Brown/Black	BLACK	N	9	8
11R	Red/Orange	RED	DW	12	6P
11G	Blue/Orange	BLUE	W	12	6P
N	Black/Orange	BLACK	N	12	6P
10R	Red/Blue	RED	DW	16	4P
10G	Orange/Blue	BLUE	W	16	4P
N	Black/Blue	BLACK	N	16	4P
	Yellow				
	Brown				
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

	CABLE				
CABINET TERM.	CONDUCTOR	POLE COND. COLOR	HEAD TERM.	NO.	Ø
2R	Red	RED	R	5	2
2Y	Orange	ORANGE	Y	5	2
2G	Blue	BLUE	G	5	2
5Y	Yellow	YELLOW	YA	5	5
5G	Brown	BROWN	GA	5	5
N	Black	BLACK	N	5	2
8R	Red/Black	RED	R	10	8
8Y	Orange/Black	ORANGE	Y	10	8
8G	Blue/Black	BLUE	G	10	8
N	Yellow/Black	BLACK	N	10	8
8R	Black/Red	RED	R	11	8
8Y	Orange/Red	ORANGE	Y	11	8
8G	Blue/Red	BLUE	G	11	8
N	Brown/Black	BLACK	N	11	8
11R	Red/Orange	RED	DW	13	6P
11G	Blue/Orange	BLUE	W	13	6P
N	Black/Orange	BLACK	N	13	6P
12R	Red/Blue	RED	DW	17	8P
12G	Orange/Blue	BLUE	W	17	8P
N	Black/Blue	BLACK	N	17	8P
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	ø
2R	Red	RED	R	6	2
2Y	Orange	ORANGE	Y	6	2
2G	Blue	BLUE	G	6	2
5Y	Yellow	YELLOW	YA	6	5
5G	Brown	BROWN	GA	6	5
N	Black	BLACK	N	6	2
2R	Red/Black	RED	R	7	2
2Y	Orange/Black	ORANGE	Y	7	2
2G	Blue/Black	BLUE	G	7	2
N	Yellow/Black	BLACK	N	7	2
2R	Black/Red	RED	R	8	2
2Y	Orange/Red	ORANGE	Y	8	2
2G	Blue/Red	BLUE	G	8	2
N	Brown/Black	BLACK	N	8	2
9R	Red/Blue	RED	DW	14	2P
9G	Orange/Blue	BLUE	W	14	2P
N	Black/Blue	BLACK	N	14	2P
8R	Red/Orange	RED	DW	18	8P
8G	Blue/Orange	BLUE	W	18	8P
N	Black/Orange	BLACK	N	18	8P
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Red	RED	R	1	6
6Y	Orange	ORANGE	Y	1	6
6G	Blue	BLUE	G	1	6
1Y	Yellow	YELLOW	YA	1	1
1G	Brown	BROWN	GA	1	1
N	Black	BLACK	N	1	6
9R	Red/Orange	RED	DW	15	2P
9G	Blue/Orange	BLUE	W	15	2P
N	Black/Orange	BLACK	N	15	2P
4R	Black/Red	RED	DW	19	4P
4G	Blue/Red	BLUE	W	19	4P
N	Brown/Black	BLACK	N	19	4P
	Red/Black				
	Blue/Black				
	Orange/Black				
	Yellow/Black				
	Orange/Red				
	Yellow/Red				
	Brown/Red				
	Black/Blue				
	Red/Blue				
	Orange/Blue				
	Yellow/Blue				
	Brown/Blue				

POLE:	EE1	CABLE SIZE:	7/C

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Red	RED	R	2	6
6Y	Orange	ORANGE	Y	2	6
6G	Blue	BLUE	G	2	6
1 Y	Yellow	YELLOW	YA	2	1
1G	Brown	BROWN	GA	2	1
N	Black	BLACK	N	2	6
	Red/Black				

WIRING DIAGRAM

US HWY 12/6TH AVE SW & Lincoln ST S

POLE: EF1 CABLE SIZE: 24/C

POLE: <u>EF2</u> CABLE SIZE:

19/C

POLE: <u>EF3</u> CABLE SIZE:

24/C

POLE: <u>EF4</u> CABLE SIZE:

24/C

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Red	RED	R	2	6
6Y	Orange	ORANGE	Y	2	6
6G	Blue	BLUE	G	2	6
N	Black	BLACK	N	2	6
6R	Red/Black	RED	R	3	6
6Y	Orange/Black	ORANGE	Y	3	6
6G	Blue/Black	BLUE	G	3	6
N	Yellow/Black	BLACK	N	3	6
6R	Black/Red	RED	R	4	6
6Y	Orange/Red	ORANGE	Y	4	6
6G	Blue/Red	BLUE	G	4	6
N	Brown/Black	BLACK	N	4	6
11R	Red/Orange	RED	DW	12	6P
11G	Blue/Orange	BLUE	W	12	6P
N	Black/Orange	BLACK	N	12	6P
10R	Red/Blue	RED	DW	16	4P
10G	Orange/Blue	BLUE	W	16	4P
N	Black/Blue	BLACK	N	16	4P
	Yellow				
	Brown				
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	ø
2R	Red	RED	R	5	2
2Y	Orange	ORANGE	Y	5	2
2G	Blue	BLUE	G	5	2
N	Black	BLACK	N	5	2
11R	Red/Blue	RED	DW	13	6P
11G	Orange/Blue	BLUE	W	13	6P
N	Black/Blue	BLACK	N	13	6P
12R	Red/Black	RED	DW	17	8P
12G	Blue/Black	BLUE	W	17	8P
N	Orange/Black	BLACK	N	17	8P
	Yellow				
	Brown				
	Yellow/Black				
	Brown/Black				
	Black/Red				
	Blue/Red				
	Orange/Red				
	Yellow/Red				
	Brown/Red				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
2R	Red	RED	R	7	2
2Y	Orange	ORANGE	Y	7	2
2G	Blue	BLUE	G	7	2
N	Black	BLACK	N	7	2
2R	Red/Black	RED	R	8	2
2Y	Orange/Black	ORANGE	Y	8	2
2G	Blue/Black	BLUE	G	8	2
N	Yellow/Black	BLACK	N	8	2
4R	Black/Red	RED	R	9	4
4Y	Orange/Red	ORANGE	Y	9	4
4G	Blue/Red	BLUE	G	9	4
N	Brown/Black	BLACK	N	9	4
9R	Red/Orange	RED	DW	14	2P
9G	Blue/Orange	BLUE	W	14	2P
N	Black/Orange	BLACK	N	14	2P
12R	Red/Blue	RED	DW	18	8P
12G	Orange/Blue	BLUE	W	18	8P
N	Black/Blue	BLACK	N	18	8P
	Yellow				
	Brown				
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

		1			
CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Red	RED	R	1	6
6Y	Orange	ORANGE	Y	1	6
6G	Blue	BLUE	G	1	6
N	Black	BLACK	N	1	6
4R	Red/Black	RED	R	11	4
4Y	Orange/Black	ORANGE	Y	11	4
4G	Blue/Black	BLUE	G	11	4
N	Yellow/Black	BLACK	N	11	4
4R	Black/Red	RED	R	10	4
4Y	Orange/Red	ORANGE	Y	10	4
4G	Blue/Red	BLUE	G	10	4
N	Brown/Black	BLACK	N	10	4
9R	Red/Orange	RED	DW	15	2P
9G	Blue/Orange	BLUE	W	15	2P
N	Black/Orange	BLACK	N	15	2P
10R	Red/Blue	RED	DW	19	4P
10G	Orange/Blue	BLUE	W	19	4P
N	Black/Blue	BLACK	N	19	4P
	Yellow				
	Brown				
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

POLE: EF3 CABLE SIZE: 7/C

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
2R	Red	RED	R	6	2
2Y	Orange	ORANGE	Y	6	2
2G	Blue	BLUE	G	6	2
N	Black	BLACK	N	6	2
	Yellow				
	Brown				
	Red/Black				

WIRING DIAGRAM

US HWY 12/6TH AVE SW & Washington ST S

POLE: EG1 CABLE SIZE: 24/C POLE: EG2 CABLE SIZE: 24/C POLE: EG3 CABLE SIZE: 24/C POLE: EG4 CABLE SIZE: 24/C

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Red	RED	R	2	6
6Y	Orange	ORANGE	Y	2	6
6G	Blue	BLUE	G	2	6
N	Black	BLACK	N	2	6
6R	Red/Black	RED	R	3	6
6Y	Orange/Black	ORANGE	Y	3	6
6G	Blue/Black	BLUE	G	3	6
N	Yellow/Black	BLACK	N	3	6
6R	Black/Red	RED	R	4	6
6Y	Orange/Red	ORANGE	Y	4	6
6G	Blue/Red	BLUE	G	4	6
N	Brown/Black	BLACK	N	4	6
11R	Red/Orange	RED	DW	15	6P
11G	Blue/Orange	BLUE	W	15	6P
N	Black/Orange	BLACK	N	15	6P
10R	Red/Blue	RED	DW	20	4P
10G	Orange/Blue	BLUE	W	20	4P
N	Black/Blue	BLACK	N	20	4P
	Yellow				
	Brown				
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	ø
2R	Red	RED	R	5	2
2Y	Orange	ORANGE	Y	5	2
2G	Blue	BLUE	G	5	2
N	Black	BLACK	N	5	2
8R	Yellow/Red	RED	R	10	8
8Y	Orange/Red	ORANGLE	Y	10	8
8G	Blue/Red	BLUE	G	10	8
N	Black/Red	BLACK	N	10	8
8R	Red/Orange	RED	R	11	8
8Y	Black/Orange	ORANGE	Y	11	8
8G	Blue/Orange	BLUE	G	11	8
N	Brown/Black	BLACK	N	11	8
11R	Red/Blue	RED	DW	16	6P
11G	Orange/Blue	BLUE	W	16	6P
N	Black/Blue	BLACK	N	16	6P
12R	Red/Black	RED	DW	21	8P
12G	Blue/Black	BLUE	W	21	8P
N	Orange/Black	BLACK	N	21	8P
	Yellow/Black				
	Yellow				
	Brown				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
2R	Red	RED	R	7	2
2Y	Orange	ORANGE	Y	7	2
2G	Blue	BLUE	G	7	2
N	Black	BLACK	N	7	2
2R	Red/Black	RED	R	8	2
2Y	Orange/Black	ORANGE	Y	8	2
2G	Blue/Black	BLUE	G	8	2
N	Yellow/Black	BLACK	N	8	2
4R	Black/Red	RED	R	12	4
4Y	Orange/Red	ORANGE	Y	12	4
4G	Blue/Red	BLUE	G	12	4
N	Brown/Black	BLACK	N	12	4
9R	Red/Orange	RED	DW	17	2P
9G	Blue/Orange	BLUE	W	17	2P
N	Black/Orange	BLACK	N	17	2P
12R	Red/Blue	RED	DW	22	8P
12G	Orange/Blue	BLUE	W	22	8P
N	Black/Blue	BLACK	N	22	8P
	Yellow				
	Brown				
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Red	RED	R	1	6
6Y	Orange	ORANGE	Y	1	6
6G	Blue	BLUE	G	1	6
N	Black	BLACK	N	1	6
4R	Red/Black	RED	R	13	4
4Y	Orange/Black	ORANGE	Y	13	4
4G	Blue/Black	BLUE	G	13	4
N	Yellow/Black	BLACK	N	13	4
4R	Black/Red	RED	R	14	4
4Y	Orange/Red	ORANGE	Y	14	4
4G	Blue/Red	BLUE	G	14	4
N	Brown/Black	BLACK	N	14	4
9R	Red/Orange	RED	DW	18	2P
9G	Blue/Orange	BLUE	W	18	2P
N	Black/Orange	BLACK	N	18	2P
10R	Red/Blue	RED	DW	19	4P
10G	Orange/Blue	BLUE	W	19	4P
N	Black/Blue	BLACK	N	19	4P
	Yellow				
	Brown				
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

POLE:	EG1	CABLE SIZE:	7/C

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
8R	Red	RED	R	9	8
8Y	Orange	ORANGE	Y	9	8
8G	Blue	BLUE	G	9	8
N	Black	BLACK	N	9	8
	Yellow				
	Brown				
	Red/Black				

POLE:	EG3	CABLE SIZE:	7/C

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
2R	Red	RED	R	6	2
2Y	Orange	ORANGE	Y	6	2
2G	Blue	BLUE	G	6	2
N	Black	BLACK	N	6	2
	Yellow				
	Brown				
	Red/Black				

WIRING DIAGRAM

US HWY 12/6TH AVE SW & Kline ST S

POLE: EH1 CABLE SIZE: 24/C POLE: EH2 CABLE SIZE: 24/C POLE: 2H3 CABLE SIZE: 24/C POLE: 2H4 CABLE SIZE: 24/C

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	ø
6R	Red	RED	R	2	6
6Y	Orange	ORANGE	Y	2	6
6G	Blue	BLUE	G	2	6
N	Black	BLACK	N	2	6
6R	Red/Black	RED	R	3	6
6Y	Orange/Black	ORANGE	Y	3	6
6G	Blue/Black	BLUE	G	3	6
N	Yellow/Black	BLACK	N	3	6
6R	Black/Red	RED	R	4	6
6Y	Orange/Red	ORANGE	Y	4	6
6G	Blue/Red	BLUE	G	4	6
N	Brown/Black	BLACK	N	4	6
11R	Red/Orange	RED	DW	15	6P
11G	Blue/Orange	BLUE	W	15	6P
N	Black/Orange	BLACK	N	15	6P
10R	Red/Blue	RED	DW	20	4P
10G	Orange/Blue	BLUE	W	20	4P
N	Black/Blue	BLACK	N	20	4P
	Yellow				
	Brown				
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	ø
2R	Red	RED	R	5	2
2Y	Orange	ORANGE	Y	5	2
2G	Blue	BLUE	G	5	2
N	Black	BLACK	N	5	2
8R	Yellow/Red	RED	R	10	8
8Y	Orange/Red	ORANGLE	Y	10	8
8G	Blue/Red	BLUE	G	10	8
N	Black/Red	BLACK	N	10	8
8R	Red/Orange	RED	R	11	8
8Y	Black/Orange	ORANGE	Y	11	8
8G	Blue/Orange	BLUE	G	11	8
N	Brown/Black	BLACK	N	11	8
11R	Red/Blue	RED	DW	16	6P
11G	Orange/Blue	BLUE	W	16	6P
N	Black/Blue	BLACK	N	16	6P
12R	Red/Black	RED	DW	21	8P
12G	Blue/Black	BLUE	W	21	8P
N	Orange/Black	BLACK	N	21	8P
	Yellow/Black				
	Yellow				
	Brown				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
2R	Red	RED	R	7	2
2Y	Orange	ORANGE	Y	7	2
2G	Blue	BLUE	G	7	2
N	Black	BLACK	N	7	2
2R	Red/Black	RED	R	8	2
2Y	Orange/Black	ORANGE	Y	8	2
2G	Blue/Black	BLUE	G	8	2
N	Yellow/Black	BLACK	N	8	2
4R	Black/Red	RED	R	12	4
4Y	Orange/Red	ORANGE	Y	12	4
4G	Blue/Red	BLUE	G	12	4
N	Brown/Black	BLACK	N	12	4
9R	Red/Orange	RED	DW	17	2P
9G	Blue/Orange	BLUE	W	17	2P
N	Black/Orange	BLACK	N	17	2P
12R	Red/Blue	RED	DW	22	8P
12G	Orange/Blue	BLUE	W	22	8P
N	Black/Blue	BLACK	N	22	8P
	Yellow				
	Brown				
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Red	RED	R	1	6
6Y	Orange	ORANGE	Y	1	6
6G	Blue	BLUE	G	1	6
N	Black	BLACK	N	1	6
4R	Red/Black	RED	R	13	4
4Y	Orange/Black	ORANGE	Y	13	4
4G	Blue/Black	BLUE	G	13	4
N	Yellow/Black	BLACK	N	13	4
4R	Black/Red	RED	R	14	4
4Y	Orange/Red	ORANGE	Y	14	4
4G	Blue/Red	BLUE	G	14	4
N	Brown/Black	BLACK	N	14	4
9R	Red/Orange	RED	DW	18	2P
9G	Blue/Orange	BLUE	W	18	2P
N	Black/Orange	BLACK	N	18	2P
10R	Red/Blue	RED	DW	19	4P
10G	Orange/Blue	BLUE	W	19	4P
N	Black/Blue	BLACK	N	19	4P
	Yellow				
	Brown				
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

POLE: EH1 CABLE SIZE: 7/C

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
8R	Red	RED	R	9	8
8Y	Orange	ORANGE	Y	9	8
8G	Blue	BLUE	G	9	8
N	Black	BLACK	N	9	8
	Yellow		·		·
	Brown				·
	Red/Black				

POLE:	EH3	CABLE SIZE:	7/C

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
2R	Red	RED	R	6	2
2Y	Orange	ORANGE	Y	6	2
2G	Blue	BLUE	G	6	2
N	Black	BLACK	N	6	2
	Yellow				
	Brown				
	Red/Black				

TOTAL SHEETS PROJECT STATE OF SOUTH 77 NH 0012(323)298 92 DAKOTA Plotting Date: 08/13/2025

WIRING DIAGRAM

US HWY 12/6TH AVE SW & State ST S

POLE: EI1 **CABLE SIZE:** 24/C POLE: EI2 **CABLE SIZE:** 24/C POLE: EI3 **CABLE SIZE:** 24/C POLE: EI4 CABLE SIZE: 24/C CABLE POLE CABLE POLE CABLE POLE CABLE POLE HEAD HEAD CABINET HEAD **HEAD CABINET** HEAD HEAD **CABINET CABINET** HEAD HEAD CONDUCTOR COND. CONDUCTOR COND. CONDUCTOR COND. Ø CONDUCTOR COND. TERM. NO. TERM. TERM. NO. TERM. NO. TERM. NO. TERM. TERM. TERM. COLOR COLOR **COLOR COLOR** COLOR COLOR COLOR COLOR Red/Black Red/Black Red/Black 2 Red/Black 6R RED R 3 6 8R RED R 11 8 2R RED R 7 4R RED 15 4 3 6 8 2 4 6Y Orange/Black **ORANGE** Y **8**Y Orange/Black **ORANGE** Y 11 2Y Orange/Black ORANGE Y 7 4Y Orange/Black **ORANGE** Y 15 8 2 Blue/Black **BLUE** 3 Blue/Black 11 2GBlue/Black Blue/Black BLUE 15 N Yellow/Black BLACK 3 6 N Yellow/Black **BLACK** N 11 8 N Yellow/Black BLACK N 7 2 N Yellow/Black **BLACK** 15 4 Black/Red 4 6 Black/Red R 12 8 Black/Red 8 2 4R Black/Red 4 6R RED R 8R RED 2R RED R RED R 16 4 **ORANGE** Y 12 8 2 4 Orange/Red ORANGE Orange/Red Orange/Red **ORANGE** 4Y Orange/Red ORANGE 16 Blue/Red 6 8G 12 8 Blue/Red 2 4G Blue/Red 4 6G **BLUE** G 4 Blue/Red **BLUE** G 2G **BLUE** G 8 BLUE \mathbf{G} 16 Brown/Black 4 N Brown/Black BLACK N 4 N Brown/Black **BLACK** N 12 8 N Brown/Black **BLACK** N 8 2 N **BLACK** N 16 9 8 8 4 4 Red RED 8R Red RED R 10 Red RED 13 4R Red RED 14 Orange Orange **8Y** ORANGE 9 8 **8Y** Y 8 **4Y** Y 13 4 **4Y ORANGE** 4 Y Orange **ORANGE** 10 Orange **ORANGE** Y 14 **8G** Blue 9 8 **8G** G 8 4G 13 4 4G 4 **BLUE** \mathbf{G} Blue **BLUE** 10 Blue BLUE G Blue BLUE G 14 7 3Y Yellow YELLOW YA 9 3 3Y Yellow YELLOW YA 10 3 Yellow YELLOW YA 13 **7**Y Yellow YELLOW YA 14 **3**G Brown **BROWN** 9 3 **3G BROWN** 3 **7G BROWN** 13 7 **7G Brown BROWN** 14 7 GA Brown GA 10 **Brown** GA GA **Black** 9 8 8 13 Black 4 N N N Black N 10 N Black 4 N N 14 BLACK **BLACK BLACK** N BLACK \mathbf{DW} 17 **6P** 18 6P RED 19 2P 9R \mathbf{DW} 20 2P 11R Red/Orange RED 11R Red/Orange RED DW Red/Orange \mathbf{DW} Red/Orange RED Blue/Orange 11G **BLUE** W 17 6P 11G Blue/Orange **BLUE** 18 6P 9G Blue/Orange BLUE W 19 2P 9G Blue/Orange BLUE W 20 2P **6P** 18 6P 19 2P 20 2P N Black/Orange N 17 N Black/Orange BLACK N N Black/Orange BLACK N Black/Orange **BLACK** BLACK N N 22 4P 23 8P 8P 10R Red/Blue RED DW 12R Red/Blue RED \mathbf{DW} Red/Blue 24 10R Red/Blue RED \mathbf{DW} 21 4P 22 4P 8P 8P 4P 10G Orange/Blue **BLUE** W 12G Orange/Blue **BLUE** 23 12G Orange/Blue **BLUE** W 24 10G Orange/Blue **BLUE** 21 Black/Blue N BLACK N 22 4P N Black/Blue **BLACK** N 23 8P N Black/Blue **BLACK** N 24 8P N Black/Blue BLACK 21 4P Yellow/Red Yellow/Red Yellow/Red Yellow/Red Brown/Red Brown/Red Brown/Red Brown/Red Yellow/Blue Yellow/Blue Yellow/Blue Yellow/Blue Brown/Blue Brown/Blue Brown/Blue Brown/Blue

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Red	RED	R	2	6
6Y	Orange	ORANGE	Y	2	6
6 G	Blue	BLUE	G	2	6
1Y	Yellow	YELLOW	YA	2	1
1G	Brown	BROWN	GA	2	1
N	Black	BLACK	N	2	6
	Red/Black				

POLE: EI1 CABLE SIZE:

7/C___

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
2R	Red	RED	R	5	2
2Y	Orange	ORANGE	Y	5	2
2G	Blue	BLUE	G	5	2
5Y	Yellow	YELLOW	YA	5	5
5G	Brown	BROWN	GA	5	5
N	Black	BLACK	N	5	2
	Red/Black				

CABLE SIZE:

7/C

POLE: EI2

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
2R	Red	RED	R	6	2
2Y	Orange	ORANGE	Y	6	2
2G	Blue	BLUE	G	6	2
5Y	Yellow	YELLOW	YA	6	5
5G	Brown	BROWN	GA	6	5
N	Black	BLACK	N	6	2
	Red/Black				

CABLE SIZE:

7/C

POLE:

EI4

POLE: EI3

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Red	RED	R	1	6
6Y	Orange	ORANGE	Y	1	6
6G	Blue	BLUE	G	1	6
1Y	Yellow	YELLOW	YA	1	1
1G	Brown	BROWN	GA	1	1
N	Black	BLACK	N	1	6
	Red/Black				

CABLE SIZE:

7/C

WIRING DIAGRAM

US HWY 12/6TH AVE SW & Dakota ST S

POLE: EJ1 CABLE SIZE: 24/C POLE: EJ2 CABLE SIZE: 19/C POLE: EJ3 CABLE SIZE: 24/C POLE: EJ4 CABLE SIZE: 24/C

CABINET CABLE POLE HEAD HEAD CONDUCTOR CONDUCTO

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Red/Black	RED	R	3	6
6Y	Orange/Black	ORANGE	Y	3	6
6G	Blue/Black	BLUE	G	3	6
N	Yellow/Black	BLACK	N	3	6
6R	Black/Red	RED	R	4	6
6Y	Orange/Red	ORANGE	Y	4	6
6G	Blue/Red	BLUE	G	4	6
N	Brown/Black	BLACK	N	4	6
8R	Red	RED	R	9	8
8Y	Orange	ORANGE	Y	9	8
8G	Blue	BLUE	G	9	8
N	Black	BLACK	N	9	8
11R	Red/Orange	RED	DW	17	6P
11G	Blue/Orange	BLUE	W	17	6P
N	Black/Orange	BLACK	N	17	6P
10R	Red/Blue	RED	DW	22	4P
10G	Orange/Blue	BLUE	W	22	4P
N	Black/Blue	BLACK	N	22	4P
	Yellow				
	Brown				
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
8R	Red	RED	R	10	8
8Y	Orange	ORANGE	Y	10	8
8G	Blue	BLUE	G	10	8
N	Black	BLACK	N	10	8
8R	Red/Black	RED	R	11	8
8Y	Orange/Black	ORANGE	Y	11	8
8G	Blue/Black	BLUE	G	11	8
N	Yellow/Black	BLACK	N	11	8
8R	Black/Red	RED	R	12	8
8Y	Orange/Red	ORANGE	Y	12	8
8G	Blue/Red	BLUE	G	12	8
N	Brown/Black	BLACK	N	12	8
11R	Red/Orange	RED	DW	18	6P
11G	Blue/Orange	BLUE	W	18	6P
N	Black/Orange	BLACK	N	18	6P
12R	Red/Blue	RED	DW	23	8P
12G	Orange/Blue	BLUE	W	23	8P
N	Black/Blue	BLACK	N	23	8P
	Yellow				
	Brown				
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
2R	Red/Black	RED	R	7	2
2Y	Orange/Black	ORANGE	Y	7	2
2G	Blue/Black	BLUE	G	7	2
N	Yellow/Black	BLACK	N	7	2
2R	Black/Red	RED	R	8	2
2Y	Orange/Red	ORANGE	Y	8	2
2G	Blue/Red	BLUE	G	8	2
N	Brown/Black	BLACK	N	8	2
4R	Red	RED	R	13	4
4Y	Orange	ORANGE	Y	13	4
4G	Blue	BLUE	G	13	4
7Y	Yellow	YELLOW	YA	13	7
7G	Brown	BROWN	GA	13	7
N	Black	BLACK	N	13	4
9R	Red/Orange	RED	DW	19	2P
9G	Blue/Orange	BLUE	W	19	2P
N	Black/Orange	BLACK	N	19	2P
12R	Red/Blue	RED	DW	24	8P
12G	Orange/Blue	BLUE	W	24	8P
N	Black/Blue	BLACK	N	24	8P
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
4R	Red	RED	R	14	4
4Y	Orange	ORANGE	Y	14	4
4G	Blue	BLUE	G	14	4
7Y	Yellow	YELLOW	YA	14	7
7G	Brown	BROWN	GA	14	7
N	Black	BLACK	N	14	4
4R	Red/Black	RED	R	15	4
4Y	Orange/Black	ORANGE	Y	15	4
4G	Blue/Black	BLUE	G	15	4
N	Yellow/Black	BLACK	N	15	4
4R	Black/Red	RED	R	16	4
4Y	Orange/Red	ORANGE	Y	16	4
4G	Blue/Red	BLUE	G	16	4
N	Brown/Black	BLACK	N	16	4
9R	Red/Orange	RED	DW	20	2P
9G	Blue/Orange	BLUE	W	20	2P
N	Black/Orange	BLACK	N	20	2P
10R	Red/Blue	RED	DW	21	4P
10G	Orange/Blue	BLUE	W	21	4P
N	Black/Blue	BLACK	N	21	4P
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

POLE:	EJ1	CABLE SIZ
		ı

POLE

COND.

COLOR

RED

ORANGE

BLUE

YELLOW

BROWN

BLACK

CABLE

CONDUCTOR

COLOR

Red

Orange

Blue

Yellow

Brown

Black

Red/Black

7/C

HEAD

NO.

2

2

2

2

2

2

6

1

1

6

HEAD

TERM.

YA

GA

N

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
2R	Red	RED	R	5	2
2Y	Orange	ORANGE	Y	5	2
2G	Blue	BLUE	G	5	2
5Y	Yellow	YELLOW	YA	5	5
5G	Brown	BROWN	GA	5	5
N	Black	BLACK	N	5	2

POLE: <u>EJ2</u> CABLE SIZE:

Red/Black

7/C

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
2R	Red	RED	R	6	2
2Y	Orange	ORANGE	Y	6	2
2G	Blue	BLUE	G	6	2
5Y	Yellow	YELLOW	YA	6	5
5 G	Brown	BROWN	GA	6	5
N	Black	BLACK	N	6	2
	Red/Black				

7/C

POLE: <u>EJ3</u> CABLE SIZE:

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Red	RED	R	1	6
6Y	Orange	ORANGE	Y	1	6
6G	Blue	BLUE	G	1	6
1Y	Yellow	YELLOW	YA	1	1
1G	Brown	BROWN	GA	1	1
N	Black	BLACK	N	1	6
	Red/Black				

7/C

POLE: <u>EJ4</u> CABLE SIZE:

TIED FROM - TRAB17879B

CABINET

TERM.

6R

6G

1Y

1**G**

WIRING DIAGRAM

US HWY 12/6TH AVE SW & Harrison ST S

POLE: EK1 CABLE SIZE: 24/C POLE: EK2 CABLE SIZE: 24/C POLE: EK3 CABLE SIZE: 24/C POLE: EK4 CABLE SIZE: 24/C

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Red/Black	RED	R	3	6
6Y	Orange/Black	ORANGE	Y	3	6
6G	Blue/Black	BLUE	G	3	6
N	Yellow/Black	BLACK	N	3	6
6R	Black/Red	RED	R	4	6
6Y	Orange/Red	ORANGE	Y	4	6
6G	Blue/Red	BLUE	G	4	6
N	Brown/Black	BLACK	N	4	6
8R	Red	RED	R	9	8
8Y	Orange	ORANGE	Y	9	8
8G	Blue	BLUE	G	9	8
N	Black	BLACK	N	9	8
11R	Red/Orange	RED	DW	15	6P
11G	Blue/Orange	BLUE	W	15	6P
N	Black/Orange	BLACK	N	15	6P
10R	Red/Blue	RED	DW	20	4P
10G	Orange/Blue	BLUE	W	20	4P
N	Black/Blue	BLACK	N	20	4P
	Yellow				
	Brown				
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Black/Red	RED	R	5	6
6Y	Orange/Red	ORANGE	Y	5	6
6G	Blue/Red	BLUE	G	5	6
N	Brown/Black	BLACK	N	5	6
8R	Red	RED	R	10	8
8Y	Orange	ORANGE	Y	10	8
8G	Blue	BLUE	G	10	8
N	Black	BLACK	N	10	8
8R	Red/Black	RED	R	11	8
8Y	Orange/Black	ORANGE	Y	11	8
8G	Blue/Black	BLUE	G	11	8
N	Yellow/Black	BLACK	N	11	8
11R	Red/Orange	RED	DW	16	6P
11G	Blue/Orange	BLUE	W	16	6P
N	Black/Orange	BLACK	N	16	6P
12R	Red/Blue	RED	DW	21	8P
12G	Orange/Blue	BLUE	W	21	8P
N	Black/Blue	BLACK	N	21	8P
	Yellow				
	Brown				
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
2R	Red/Black	RED	R	7	2
2Y	Orange/Black	ORANGE	Y	7	2
2G	Blue/Black	BLUE	G	7	2
N	Yellow/Black	BLACK	N	7	2
2R	Black/Red	RED	R	8	2
2Y	Orange/Red	ORANGE	Y	8	2
2G	Blue/Red	BLUE	G	8	2
N	Brown/Black	BLACK	N	8	2
4R	Red	RED	R	13	4
4Y	Orange	ORANGE	Y	13	4
4G	Blue	BLUE	G	13	4
N	Black	BLACK	N	13	4
9R	Red/Orange	RED	DW	17	2P
9G	Blue/Orange	BLUE	W	17	2P
N	Black/Orange	BLACK	N	17	2P
12R	Red/Blue	RED	DW	22	8P
12G	Orange/Blue	BLUE	W	22	8P
N	Black/Blue	BLACK	N	22	8P
	Yellow				
	Brown				
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Black/Red	RED	R	1	6
6Y	Orange/Red	ORANGE	Y	1	6
6G	Blue/Red	BLUE	G	1	6
N	Brown/Black	BLACK	N	1	6
4R	Red	RED	R	13	4
4Y	Orange	ORANGE	Y	13	4
4G	Blue	BLUE	G	13	4
N	Black	BLACK	N	13	4
4R	Red/Black	RED	R	14	4
4Y	Orange/Black	ORANGE	Y	14	4
4G	Blue/Black	BLUE	G	14	4
N	Yellow/Black	BLACK	N	14	4
9R	Red/Orange	RED	DW	18	2P
9G	Blue/Orange	BLUE	W	18	2P
N	Black/Orange	BLACK	N	18	2P
10R	Red/Blue	RED	DW	19	4P
10G	Orange/Blue	BLUE	W	19	4P
N	Black/Blue	BLACK	N	19	4P
	Yellow				
	Brown				
	Yellow/Red				
_	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

POLE:	EK1	CABLE SIZE:	//C

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Red	RED	R	2	6
6Y	Orange	ORANGE	Y	2	6
6 G	Blue	BLUE	G	2	6
N	Black	BLACK	N	2	6
	Yellow				
	Brown				
	Red/Black				

POLE:	EK3	CABLE SIZE:	7/C
-------	-----	-------------	-----

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	ø
2R	Red	RED	R	6	2
2Y	Orange	ORANGE	Y	6	2
2G	Blue	BLUE	G	6	2
N	Black	BLACK	N	6	2
	Yellow				
	Brown				
	Red/Black				

	STATE OF SOUTH DAKOTA	PROJECT	SHEET NO.	TOTAL SHEETS
)		NH 0012(323)298	80	92

Plotting Date: 08/13/2025

WIRING DIAGRAM

US HWY 12/6TH AVE SW & Lawson ST S

POLE: EL1 CABLE SIZE: 24/C POLE: EL2 CABLE SIZE: 19/C POLE: EL3 CABLE SIZE: 24/C

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Red/Black	RED	R	3	6
6Y	Orange/Black	ORANGE	Y	3	6
6G	Blue/Black	BLUE	G	3	6
N	Yellow/Black	BLACK	N	3	6
6R	Black/Red	RED	R	4	6
6Y	Orange/Red	ORANGE	Y	4	6
6G	Blue/Red	BLUE	G	4	6
N	Brown/Black	BLACK	N	4	6
8R	Red/Orange	RED	R	8	8
8Y	Blue/Orange	ORANGE	Y	8	8
8G	Brown/Blue	BLUE	G	8	8
N	Black/Orange	BLACK	N	8	8
8R	Red	RED	R	9	8
8Y	Orange	ORANGE	Y	9	8
8G	Blue	BLUE	G	9	8
N	Black	BLACK	N	9	8
10R	Red/Blue	RED	DW	16	4P
10G	Orange/Blue	BLUE	W	16	4P
N	Black/Blue	BLACK	N	16	4P
	Yellow				
	Brown				
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
2R	Red/Black	RED	R	5	2
2Y	Orange/Black	ORANGE	Y	5	2
2G	Blue/Black	BLUE	G	5	2
N	Yellow/Black	BLACK	N	5	2
2R	Black/Red	RED	R	6	2
2Y	Orange/Red	ORANGE	Y	6	2
2G	Blue/Red	BLUE	G	6	2
N	Brown/Black	BLACK	N	6	2
2R	Red	RED	R	7	2
2Y	Orange	ORANGE	Y	7	2
2G	Blue	BLUE	G	7	2
N	Black	BLACK	N	7	2
4R	Red/Blue	RED	R	11	4
4Y	Orange/Blue	ORANGE	Y	11	4
4G	Yellow/Blue	BLUE	G	11	4
N	Black/Blue	BLACK	N	11	4
9R	Red/Orange	RED	DW	13	2P
9G	Blue/Orange	BLUE	W	13	2P
N	Black/Orange	BLACK	N	13	2P
	Brown/Blue				
	Yellow				
	Brown				
	Yellow/Red				
	Brown/Red				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Red	RED	R	1	6
6Y	Orange	ORANGE	Y	1	6
6G	Blue	BLUE	G	1	6
1Y	Yellow	YELLOW	YA	1	1
1G	Brown	BROWN	GA	1	1
N	Black	BLACK	N	1	6
4R	Red/Black	RED	R	12	4
4Y	Orange/Black	ORANGE	Y	12	4
4G	Blue/Black	BLUE	G	12	4
N	Yellow/Black	BLACK	N	12	4
9R	Red/Orange	RED	DW	14	2P
9G	Blue/Orange	BLUE	W	14	2P
N	Black/Orange	BLACK	N	14	2P
10R	Red/Blue	RED	DW	15	4P
10G	Orange/Blue	BLUE	W	15	4P
N	Black/Blue	BLACK	N	15	4P
	Black/Red				
	Orange/Red				
	Blue/Red				
	Brown/Black				
	Yellow/Blue				
	Brown/Blue				
	Yellow/Red				
	Brown/Red				

POLE:	EL1	CABLE SIZE:	7/C	POLE:	EL2	CABLE SIZE:	7/C
_				_			

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Red	RED	R	2	6
6Y	Orange	ORANGE	Y	2	6
6G	Blue	BLUE	G	2	6
1Y	Yellow	YELLOW	YA	2	1
1G	Brown	BROWN	GA	2	1
N	Black	BLACK	N	2	6
	Red/Black				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
4R	Red	RED	R	10	4
4Y	Orange	ORANGE	Y	10	4
4G	Blue	BLUE	G	10	4
N	Black	BLACK	N	10	4
	Yellow				
	Brown				
	Red/Black				

PROJECT STATE OF SOUTH DAKOTA NH 0012(323)298 Plotting Date: 08/13/2025

TOTAL SHEETS 81 92

WIRING DIAGRAM

US HWY 12/6TH AVE SW & Roosevelt ST S

POLE: EM1 CABLE SIZE: 24/C

POLE: EM2 CABLE SIZE: 24/C

POLE: EM3 CABLE SIZE:

24/C

POLE: EM4 CABLE SIZE:

24/C

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Red/Black	RED	R	3	6
6Y	Orange/Black	ORANGE	Y	3	6
6G	Blue/Black	BLUE	G	3	6
N	Yellow/Black	BLACK	N	3	6
6R	Black/Red	RED	R	4	6
6Y	Orange/Red	ORANGE	Y	4	6
6G	Blue/Red	BLUE	G	4	6
N	Brown/Black	BLACK	N	4	6
8R	Red	RED	R	9	8
8Y	Orange	ORANGE	Y	9	8
8G	Blue	BLUE	G	9	8
3Y	Yellow	YELLOW	YA	9	3
3G	Brown	BROWN	GA	9	3
N	Black	BLACK	N	9	8
11R	Red/Orange	RED	DW	17	6P
11G	Blue/Orange	BLUE	W	17	6P
N	Black/Orange	BLACK	N	17	6P
10R	Red/Blue	RED	DW	22	4P
10G	Orange/Blue	BLUE	W	22	4P
N	Black/Blue	BLACK	N	22	4P
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

	CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	ø
	8R	Red	RED	R	10	8
	8Y	Orange	ORANGE	Y	10	8
	8G	Blue	BLUE	G	10	8
	3Y	Yellow	YELLOW	YA	10	3
	3G	Brown	BROWN	GA	10	3
	N	Black	BLACK	N	10	8
	8R	Red/Black	RED	R	11	8
	8Y	Orange/Black	ORANGE	Y	11	8
	8G	Blue/Black	BLUE	G	11	8
	N	Yellow/Black	BLACK	N	11	8
	8R	Black/Red	RED	R	12	8
	8Y	Orange/Red	ORANGE	Y	12	8
	8G	Blue/Red	BLUE	G	12	8
	N	Brown/Black	BLACK	N	12	8
	11R	Red/Orange	RED	DW	18	6P
	11G	Blue/Orange	BLUE	W	18	6P
	N	Black/Orange	BLACK	N	18	6P
	12R	Red/Blue	RED	DW	23	8P
Ī	12G	Orange/Blue	BLUE	W	23	8P
Ī	N	Black/Blue	BLACK	N	23	8P
Ī		Yellow/Red				
Ī		Brown/Red				
ľ		Yellow/Blue				
Ī		Brown/Blue				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
2R	Red/Black	RED	R	7	2
2Y	Orange/Black	ORANGE	Y	7	2
2G	Blue/Black	BLUE	G	7	2
N	Yellow/Black	BLACK	N	7	2
2R	Black/Red	RED	R	8	2
2Y	Orange/Red	ORANGE	Y	8	2
2G	Blue/Red	BLUE	G	8	2
N	Brown/Black	BLACK	N	8	2
4R	Red	RED	R	13	4
4Y	Orange	ORANGE	Y	13	4
4G	Blue	BLUE	G	13	4
7 Y	Yellow	YELLOW	YA	13	7
7G	Brown	BROWN	GA	13	7
N	Black	BLACK	N	13	4
9R	Red/Orange	RED	DW	19	2P
9G	Blue/Orange	BLUE	W	19	2P
N	Black/Orange	BLACK	N	19	2P
12R	Red/Blue	RED	DW	24	8P
12G	Orange/Blue	BLUE	W	24	8P
N	Black/Blue	BLACK	N	24	8P
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
4R	Red	RED	R	14	4
4Y	Orange	ORANGE	Y	14	4
4G	Blue	BLUE	G	14	4
7Y	Yellow	YELLOW	YA	14	7
7 G	Brown	BROWN	GA	14	7
N	Black	BLACK	N	14	4
4R	Red/Black	RED	R	15	4
4Y	Orange/Black	ORANGE	Y	15	4
4G	Blue/Black	BLUE	G	15	4
N	Yellow/Black	BLACK	N	15	4
4R	Black/Red	RED	R	16	4
4Y	Orange/Red	ORANGE	Y	16	4
4G	Blue/Red	BLUE	G	16	4
N	Brown/Black	BLACK	N	16	4
9R	Red/Orange	RED	DW	20	2P
9G	Blue/Orange	BLUE	W	20	2P
N	Black/Orange	BLACK	N	20	2P
10R	Red/Blue	RED	DW	21	4P
10G	Orange/Blue	BLUE	W	21	4P
N	Black/Blue	BLACK	N	21	4P
	Yellow/Red				
	Brown/Red				
	Yellow/Blue				
	Brown/Blue				

POLE: EI1 CABLE SIZE:

7/C

POLE: El2 CABLE SIZE:

7/C

POLE: EI3 CABLE SIZE: 7/C POLE: EB4 CABLE SIZE:

7/C

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Red	RED	R	2	6
6Y	Orange	ORANGE	Y	2	6
6G	Blue	BLUE	G	2	6
1 Y	Yellow	YELLOW	YA	2	1
1G	Brown	BROWN	GA	2	1
N	Black	BLACK	N	2	6
	Red/Black				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
2R	Red	RED	R	5	2
2Y	Orange	ORANGE	Y	5	2
2G	Blue	BLUE	G	5	2
5 Y	Yellow	YELLOW	YA	5	5
5G	Brown	BROWN	GA	5	5
N	Black	BLACK	N	5	2
	Red/Black		_		

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
2R	Red	RED	R	6	2
2Y	Orange	ORANGE	Y	6	2
2G	Blue	BLUE	G	6	2
5Y	Yellow	YELLOW	YA	6	5
5 G	Brown	BROWN	GA	6	5
N	Black	BLACK	N	6	2
	Red/Black				

CABINET TERM.	CABLE CONDUCTOR COLOR	POLE COND. COLOR	HEAD TERM.	HEAD NO.	Ø
6R	Red	RED	R	1	6
6Y	Orange	ORANGE	Y	1	6
6G	Blue	BLUE	G	1	6
1Y	Yellow	YELLOW	YA	1	1
1G	Brown	BROWN	GA	1	1
N	Black	BLACK	N	1	6
	Red/Black				

SIGNAL TIMINGS

Revised: 8/13/25 MD

Plotting Date: 08/13/2025


US HWY NO 12 / 6TH AVENUE SE & DAKOTA STREET S


		BAS	IC INTE	ERVAL	S			
Phase	1	2	3	4	5	6	7	8
Movement	WBL	EB		SB	WBL	WB	SBL	NB
Min Green	5	12		10	5	12	5	10
Extension	3	3		4	3	3	3	4
Max 1	20	70		60	20	70	20	60
Max 2								
Time Before								
Time to Reduce								
Minimum Gap								
Yellow	3	3.5		4	3	3.5	3	4
All Red		2		2		2		2
Walk		4		4		4		4
Ped Clearance		19		18		19		18
Recall		Min				Min		
Prog Flash Display	Υ	Υ		R	Υ	Υ	R	R
Start Up Ø	·	Х				Х		

COORDINATION TIMING								
CYCLE I = 70 SEC						SP	LIT	ı
PHASE	1	2	3	4	5	6	7	8
MOVEMENT	<u>, </u>	-	٦	\	_	+		1
TIME	9	44		27	9	44	9	18
COORDINATED PHASE		Х				Х		


COORDINATION TIMING									
CYCLE I = 70 SEC						SP	LIT	ı	
PHASE	1	2	3	4	5	6	7	8	
MOVEMENT	-	-	٦	ļ		-		1	
TIME	9	49		27	9	49	9	18	
COORDINATED PHASE		Х				Х			


COORDINATION TIMING								
CYCLE 2 & 3 = 76 SEC								
PHASE	1	2	3	4	5	6	7	8
MOVEMENT	<u></u>	+	1	\	_	+		†
TIME - SPLIT I	9	40		27	9	40	9	18
COORDINATED PHASE		Х				Х		





Note: Use existing offsets






PROJECT TOTAL SHEETS STATE OF SOUTH 84 NH 0012(323)298 92 DAKOTA Plotting Date: 06/16/2025

Sheet I of 2

Revised 06/16/2025 DLM Optional concrete curb shown. ½" Preformed See Perspective View, Detail E, Expansion Joint Filler (Typ.) and Detail F on sheet 2 of 2 for other options. Width of PCC Approach Pavement ☑ Use only with Width of Driveway and Type P **|** *** *** optional curb. Concrete Gutter ☑ 5'-0" -Concrete Transition Sidewalk (Typ.) Contraction Joint -Concrete Curb Concrete Curb Type P Concrete Gutter and Gutter and Gutter Concrete Curb Transition **PLAN VIEW** Concrete Curb Transition (Optional Curb Shown) **5'-0" (Min.) See Detail C 10% (Max.) 1.5% (Design) 2.1% (Max.) PCC Approach Pavement - 4" Granular $\stackrel{\longleftarrow}{\mathsf{Type}}$ P Concrete Gutter Material **SECTION A-A** ½" Preformed Expansion - $-\frac{1}{2}$ " Preformed Expansion Joint Filler Joint Filler Width of Driveway and Type P Concrete--Concrete Concrete Gutter 4.5% (Design) Sidewalk Sidewalk 4.5% (Design) 5% (Max.) 5% (Max.) **PCC Approach Pavement** PCC Approach Pavement 4" Granular Material **SECTION B-B** * 8 inches at Commercial Approaches ** Sidewalk width is 5 feet unless specified otherwise in the plans. The cross slope of the sidewalk is designed at 1.5% and will not be steeper than 2.1% unless specified otherwise in the plans. *** The slope of the type B PCC approach pavement in these areas will match the slope of the concrete curb transition. The slope is designed at 4.5% and will not be steeper than 5% unless specified otherwise in the plans. April 8, 2025 S D PLATE NUMBER TYPE B 380.41 D PCC APPROACH PAVEMENT 0 Published Date: 2026



GENERAL NOTES:

Use the plan specified option for the pavement adjacent to the driveway and sidewalk. The options are shown above in the Perspective View, Detail E, and Detail F.

The concrete for the type B PCC approach pavement and adjacent driveway will comply with the requirements of the Specifications for class M6 concrete unless otherwise stated in the plans.

Contraction joints in the type B PCC approach pavement will be 1½ inches deep if formed in the fresh concrete using a suitable grooving tool. If a saw is used to cut the contraction joints, then the depth of the joint will be at least ¼ the thickness of the approach pavement. Additional contraction joints not shown in the Plan View will be spaced as follows:

> One joint at the center of the approach for driveways 16 feet to 24 feet wide. Two joints spaced at equal intervals for driveways greater than 24 feet to 40 feet wide.

All costs for furnishing and placing the type B PCC approach pavement and constructing the expansion and contraction joints including labor, equipment, excavation, and materials including the earthen backfill and granular material will be incidental to the contract unit price per square yard for the corresponding PCC Approach Pavement contract item.

April 8, 2025 PLATE NUMBER D D O T TYPE B 380.41 PCC APPROACH PAVEMENT Published Date: 2026 Sheet 2 of 2

STATE OF	PROJECT	SHEET NO.	TOTAL SHEETS
SOUTH DAKOTA	NH 0012(323)298	85	92

Plotting Date: 06/16/2025


Revised 06/16/2025 DLM


Published Date: 2026

14.9 Sq. Ft. 130 Lbs. (Typical) 9'-3" (Max.) 8'-0" (Min.) 4.3 Sq. Ft. 40 Lbs. (Typical) **VIEW A-A** Variable **GENERAL NOTE:** The signal heads are shown with backplates removed so that the mounting hardware is visible. November 19, 2022 S D D O T PLATE NUMBER 635.30 SIGNAL POLE (PEDESTAL)

Sheet I of I

PROJECT STATE OF SOUTH DAKOTA NH 0012(323)298 86 92





circular ties may be used in lieu of the spiral ties. The No. 3 ties will be spaced 12 inches apart except for the top two which will be spaced 6 inches apart. The ties will be lapped 18 inches and the laps will be staggered around the cage.

Spiral ties will have 1-1/2 extra turns at each end.

See Section 985 of the Specifications for footing materials.

Conduits and bushings may project 2½ inches to 6 inches above footing for fixed base poles but will not project above the slip plane or fracture plane for breakaway poles.

Conduits will be sealed water-tight during all phases of construction until poles are in place.

The anchor rods will fit inside the reinforcing steel cage. If the anchor rods designed by the Pole Manufacturer do not fit, contact the Office of Bridge Design for footing redesign. No additional payment will be made for the redesigned footing.


Costs of conduit and conduit bushings shown on footing detail will be incidental to the footing bid item(s).

The pole will not be installed until the concrete has attained design strength (4000 psi).

The contour of the area surrounding the breakaway pole will be flat, though not necessarily level for a distance of 5 feet in all directions. The Contractor may be required to provide finish grading at some breakaway pole locations.

			November 19, 2022
	S D D	POLE FOOTING	PLATE NUMBER 635.55
Published Date: 2026			Sheet I of I

STATE OF	PROJECT	SHEET NO.	TOTAL SHEETS	
SOUTH DAKOTA	NH 0012(323)298	87	92	
Plotting (



GENERAL NOTES:

The pedestrian push button pole will be as specified in the plans.

S D

D **O T**

The Contractor will install either the round or the square concrete footing. For informational purpose, the quantity of concrete for one footing is 0.14 cubic yards for the round footing and 0.17 cubic yards for the square footing.

The concrete for the footing will be class M6 concrete.

All costs for furnishing and installing the concrete footing will be incidental to the contract unit price per square foot for the corresponding concrete sidewalk bid item.


All costs for furnishing and installing the pedestrian push button pole including labor, equipment, and materials including the pole, cap, and the conduit in the footing will be incidental to the contract unit price per each for "Pedestrian Push Button Pole". April 8, 2025


> PLATE NUMBER *635.57*

> > Sheet I of 2

Published Date: 2026

PEDESTRIAN PUSH BUTTON POLE





S D D O T

PEDESTRIAN PUSH BUTTON POLE

April 8, 2025

PLATE NUMBER 635.57

Sheet 2 of 2

*Skid Resistant Surface **Appropriate Logo TOP VIEW (Cover)	
TOP VIEW (Box) [Box and Cover)	
(Box and Cover)	
Materials specified in plans. Portland Cement Concrete	
Base Course Conduit Base Course Base Course Base Course	
SIDE VIEW (Electrical Junction Box Installation Details)	
Published Date: 2026 Solution Published Date: 2026 Published No. 4 steel reinforcing bar not snown.) Published Pate: 1 Of 2 Published No. 4 steel reinforcing bar not snown.) Published Pate: 1 Of 2 Published No. 4 steel reinforcing bar not snown.) Published Pate: 1 Of 2 Published No. 4 steel reinforcing bar not snown.) Published Pate: 2026 Published Pate: 2026	

PROJECT

NH 0012(323)298

88

92

STATE OF SOUTH DAKOTA

Plotting Date: 06/16/2025

ά
1
Ξ
α
PAR
$\tilde{}$
щ
F
_
Σ
MUM
≍
щ
ш
_
\subset
Ē
_
i
5
c
δ

E	LECTRICAL	<u>. JUNCTION I</u>	вох
TYPE	DESCRIPTION		MINIMUM DEPTH (C)
1	Open Bottom with Gasket	11"x18"	18"
2	Open Bottom with Gasket	13"x24"	18"
3	Open Bottom with Gasket	17"x30"	18"
ЗА	Open Bottom with Gasket	24"x36" **	24"
4	Open Bottom with Gasket	30"x48" **	24"

GENERAL NOTES:

Published Date: 2026

The cover will be gasketed with a minimum of two stainless steel bolts and washers.

The cover will have a lifting eye.

- *The surface of the cover will have a minimum wet and dry coefficient of friction value of 0.5 as determined by ASTM F609.
- ** The cover of the junction box will have the appropriate logo in one inch size letters and will be recessed. When the junction box contains cables or wires for a traffic signal then the logo will be "Signal". When the junction box contains lighting conductors then the logo will be "Lighting".
- *** Two piece covers will be used for Type 3A and Type 4 junction boxes.

The electrical junction boxes will comply with the American National Standards Institute (ANSI)/Society of Cable Telecommunications Engineers (SCTE) 77 2007 Specification for Underground Enclosure Integrity. The loading requirement for all electrical junction boxes and covers will be Tier 22 of ANSI/SCTE 77 2007.

The electrical junction boxes will be UL listed.

For junction boxes located outside of pavement, a No. 4 steel reinforcing bar with a minimum length of 18" will be buried adjacent to the long side of the junction box. All costs associated with furnishing and placing the steel reinforcing bar will be incidental to the contract unit price per each for "Type" Electrical Junction Box".

November 19, 2020


D D O T

ELECTRICAL JUNCTION BOXES TYPE 1 THROUGH TYPE 4


PLATE NUMBER *635.65*

Sheet 2 of 2

	STATE OF SOUTH DAKOTA	PROJECT	SHEET NO.	TOTAL SHEETS
		NH 0012(323)298	89	92
	Plotting Date: 06/16/2025			



SECTION VIEW



GENERAL NOTE:

The Buried Cable Marker will be plastic, approximately 6" wide, and will be capable of sustaining a minimum of a 350% tolerance of elongation without tearing. The Buried Cable Marker will have a life expectancy approximately equal to that of the conductor(s) beneath it. A phrase indicating the presence of a buried electric circuit below will be printed in a contrasting color on the cable marker. The Buried Cable Marker will be subject to approval by the Engineer. All costs associated with furnishing and installing the Buried Cable Marker will be incidental to the contract unit price per foot for the bid item used for the electrical conductor.

November 19, 2022

PLATE NUMBER D D O *635.76* **CONDUIT INSTALLATION** Published Date: 2026 Sheet I of I

Published Date: 2026

-Transition from

concrete curb

edge to concrete

sidewalk edge.

Sawed or-

5' (Typ.)

-Back of Curb

ramp as shown in the plans.

Reference point for location of curb-

Tooled Joint

6" Curb

PLAN VIEW

(With Curved Curb and Gutter)

Transition from concrete

* Ramp

| |Slope |

★ Curb Transition

D D O

curb edge to concrete sidewalk edge.

**Ramp

|||||||dols***

****5'

Landing

⋖

Ramp

Opening

PLAN VIEW (With Straight Curb and Gutter)

Back of Curb

plate 651.75)

½" Preformed Expansion Joint Filler

(See specifications and standard

Detectable warnings as specified in the plans.

using type 2 detectable warnings.

Reference point for location of curb

Sawed or Tooled Joint

* Ramp

Slope

* Curb Transition

Detectable warnings as

specified in the plans.

ramp as shown in the plans.

The edge of the curb and gutter concrete adjacent to the type 1 detectable warnings

will be straight, but may be curved when

½" Preformed Expansion Joint —

Filler (See specifications and standard plate 651.75)


TYPE 3 CURB RAMP (PARALLEL CURB RAMP)

April 8, 2025 PLATE NUMBER 651.03

Sheet I of 3

PROJECT TOTAL SHEETS STATE OF SOUTH NH 0012(323)298 90 92 DAKOTA Plotting Date: 06/16/2025

- * The curb transition slope will match the curb ramp slope. Curb ramp slopes are designed at 7.5% unless stated otherwise in the plans. The curb ramp may have a maximum slope of 8.3% at any location of the curb ramp and will not exceed 15' in length unless stated otherwise in the plans. The curb transitions and curb ramp lengths will be adjusted as necessary to meet all slope and length requirements based on field geometrics.
- ** The cross slope of the ramp will not be steeper than 2.1% and the ramp width is 5' unless stated otherwise in the plans. Plans are designed using a 1.5% cross slope for the ramp unless stated otherwise in the plans.
- *** The slope in the landing will not be steeper than 2.1% in any direction of pedestrian travel. Plans are designed using a 1.5% slope unless stated otherwise in the plans.
- **** The landing is 5'x5' unless stated otherwise in the plans.



Sheet 2 of 3

SOUTH DAKOTA NH 0012(323)298 91 92	STATE OF	PROJECT	SHEET NO.	TOTAL SHEETS
		NH 0012(323)298		

Plotting Date: 06/16/2025

GENERAL NOTES:

For illustrative purpose only, type 1 detectable warnings are shown in the drawings.

For illustrative purpose only, a PCC fillet section is shown in one of the drawings. The curb ramp depicted on this standard plate may be used with a PCC fillet section or with curb and gutter.

The curb ramp will be placed at the location stated in the plans.

Sidewalk adjacent to the curb ramp will be as shown in the plans.

★ Care will be taken to ensure a uniform grade on the curb ramp, free of sags and short grade changes.

Surface texture of the curb ramp will be obtained by coarse brooming transverse to the slope of the curb ramp.

The normal gutter line profile will be maintained through the area of the ramp opening.

Joints will be sawed or tooled into the concrete adjacent to the detectable warnings to alleviate possible corner cracking (see plan view for joint location).

Care will be taken to ensure that the surface of the detectable warnings are clean and maintains a uniform color.

The detectable warnings will be cut as necessary to fit the plan specified limits of the detectable warnings. Cost for cutting the detectable warnings will be incidental to the corresponding detectable warning contract item.

When curb height is greater than 6" and less than 12", reinforcing steel is required in accordance with the detail on sheet 2 of 3. The reinforcing steel will conform to ASTM A615, Grade 60. Cost for furnishing and installing the reinforcing steel will be incidental to the contract unit price per square foot for the corresponding concrete sidewalk contract item.

There will be no separate payment for curb ramps. The curb ramp will be measured and paid for at the contract unit price per square foot for the corresponding concrete sidewalk contract item. The square foot area of the detectable warnings and the curb along the short radius will be included in the measured and paid for quantity of sidewalk.

The curb transitions and ramp opening will be measured and paid for at the contract unit price per foot for the corresponding curb and gutter contract item when curb and gutter is used. The curb transitions and ramp opening will be measured and paid for at the contract unit price per square yard for the corresponding PCC fillet section contract item when a PCC fillet section is used.

Type 1 detectable warnings will be measured to the nearest square foot. All costs for furnishing and installing type 1 detectable warnings including labor, equipment, materials, and incidentals will be paid for at the contract unit price per square foot for "Type 1 Detectable Warnings".

Type 2 detectable warnings will be measured to the nearest square foot. All costs for furnishing and installing type 2 detectable warnings including labor, equipment, and materials, including adhesive, necessary sealant or grout, and necessary grinding will be paid for at the contract unit price per square foot for "Type 2 Detectable Warnings".

April 8, 2025


D D O T

Published Date: 2026

TYPE 3 CURB RAMP (PARALLEL CURB RAMP) PLATE NUMBER *651.03*

Sheet 3 of 3





PROJECT STATE OF NH 0012(323)298 92 92 DAKOTA

