

SHEET

INDEX OF SHEETS

General Layout with Index Estimate with General Notes & Tables Location Map

ESTIMATE OF QUANTITIES

BID ITEM NUMBER	ITEM	QUANTITY	UNIT
009E0010	Mobilization	Lump Sum	LS
320E1200	Asphalt Concrete Composite	320	Ton
900E2490	Blading	10	Hour

SPECIFICATIONS

Standard Specifications for Roads and Bridges, 2015 Edition and Required Provisions, Supplemental Specifications and Special Provisions as included in the Proposal.

UTILITIES

The Contractor will contact the involved utility companies through South Dakota One Call (1-800-781-7474) prior to starting work. It will be the responsibility of the Contractor to coordinate work with the utility owners to avoid damage to existing facilities.

ASPHALT CONCRETE COMPOSITE

Mineral aggregate will be produced from a ledge rock source.

Mineral aggregate for the Asphalt Concrete Composite will conform to the requirements for Class E, Type 1.

The Asphalt Concrete Composite thickness will be 3".

Asphalt Concrete Composite will include MC-70 Asphalt for Prime placed at the rate of 0.30 gallons per square yard. The Asphalt for Prime will be applied to the existing base for the full width of the bottom layer of Asphalt Concrete Composite.

A flush seal will be required.

All other requirements in the Standard Specifications for Asphalt Concrete Composite will apply.

BLADING

The Contractor will grade the entire area to be covered by Asphalt Concrete Composite by Blading. After the Blading has been completed to the satisfaction of the Engineer, the Contractor will water and compact the entire area to the satisfaction of the Engineer.

All work related to this site preparation will be incidental to the contract unit price per hour for Blading.

STATE OF	PROJECT	SHEET	TOTAL SHEETS
SOUTH DAKOTA	410D409	2	3

Plotting Date:

Date: 02/13/2023

SDDOT RC REGION BUILDING "G" YARD PAVING



