

Plot Scale - 1:200

trc11951



Plotted From -

STATE OF SOUTH DAKOTA  
DEPARTMENT OF TRANSPORTATION  
PLANS FOR PROPOSED

PROJECTS  
000I-469, 000N-469, & 000P-469  
RAPID CITY REGION  
GUARDRAIL MAINTENANCE

GUARDRAIL REPAIR AT VARIOUS LOCATIONS  
ON A DEMAND BASIS

PCNs i3Lr, i3Lt, & i3Lu



STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	000I-469, 000N-469 & 000P-469	1	29

Plotting Date: 09/04/2014

INDEX OF SHEETS

- 1 Title Sheet
- 2-4 Estimate of Quantities and  
Plan Notes
- 5-30 Standard Plates

ESTIMATE OF QUANTITIES, 000I-469, PCN i3Lr, (Interstate)

Bid Item Number	Item	Quantity	Unit
009E0198	Mobilization 2	2	Each
110E0700	Remove 3 Cable Guardrail	25	Ft
110E0730	Remove Beam Guardrail	100.0	Ft
110E0770	Remove W Beam Guardrail Breakaway Cable Terminal	1	Each
110E0800	Remove W Beam Guardrail End Terminal	1	Each
110E6230	Remove W Beam Guardrail for Reset	25.0	Ft
629E0100	3 Cable Guardrail	100	Ft
629E0110	NCHRP 350 Test Level 3 High Tension Cable Guardrail	100	Ft
629E0290	NCHRP 350 Test Level 3 High Tension Cable Guardrail Anchor Assembly	1	Each
629E0300	3 Cable Guardrail Slip Base Anchor Assembly	1	Each
629E1000	Repair 3 Cable Guardrail	100	Ft
629E1100	3 Cable Guardrail End Post	3	Each
629E1102	3 Cable Guardrail Intermediate Post	10	Each
629E1104	3 Cable Guardrail Post, Winter	15	Each
629E1106	Drive Down 3 Cable Guardrail Post	10	Each
629E1110	Cable Anchor Bracket	1	Each
629E1112	Cable Splice	1	Each
629E1114	3 Cable Guardrail J Hook Bolt	100	Each
629E1116	Steel Turnbuckle Cable End Assembly	1	Each
629E1118	Spring Cable End Assembly with Turnbuckle	2	Each
629E1120	W Beam to 3 Cable Transition Bracket	1	Each
629E1122	3 Cable Guardrail End Post Cap	5	Each
630E0200	Straight Class A Thrie Beam Rail	12.5	Ft
630E0210	Straight Class B Thrie Beam Rail	12.5	Ft
630E1150	Straight Double Class B W Beam Guardrail with Wood Posts	12.5	Ft
630E1200	Straight Class A W Beam Rail	75.0	Ft
630E1210	Straight Class B W Beam Rail	25.0	Ft
630E2000	W Beam to Thrie Beam Guardrail Transition	1	Each
630E2015	W Beam Guardrail Flared End Terminal	1	Each
630E2020	W Beam Guardrail Tangent End Terminal	1	Each
630E2030	W Beam Guardrail Breakaway Cable Terminal	1	Each
630E2110	Beam Guardrail Post and Block	10	Each
630E2120	Beam Guardrail Post and Block, Winter	5	Each
630E2210	Breakaway Cable Terminal End Rail	1	Each
630E2215	W Beam Guardrail End Section Buffer	1	Each
630E5120	Reset Thrie Beam Rail	12.5	Ft
630E5160	Reset W Beam Rail	12.5	Ft
630E5170	Reset Double W Beam Rail	12.5	Ft
630E5520	Drive Down Beam Guardrail Post	3	Each
630E5550	Reset Beam Guardrail Post and Block	5	Each
634E0010	Flagging	3	Hour
634E0125	Traffic Control for Guardrail Repair	2	Site
634E0420	Type C Advance Warning Arrow Panel	1	Each

WORK DESCRIPTION

Work on the contract shall include the following:

- Repair of guardrail at various locations in the Rapid City Region on a demand basis.

SPECIFICATIONS

Standard Specifications for Roads & Bridges, 2004 Edition and Required Provisions, Supplemental Specifications and/or Special Provisions as included in the Proposal.

ESTIMATE OF QUANTITIES, 000N-469, PCN i3Lt, (Non-Priority)

Bid Item Number	Item	Quantity	Unit
009E0197	Mobilization 1	2	Each
009E0198	Mobilization 2	2	Each
009E0199	Mobilization 3	2	Each
110E0700	Remove 3 Cable Guardrail	25	Ft
110E0730	Remove Beam Guardrail	100.0	Ft
110E0770	Remove W Beam Guardrail Breakaway Cable Terminal	1	Each
110E0800	Remove W Beam Guardrail End Terminal	1	Each
110E6230	Remove W Beam Guardrail for Reset	25.0	Ft
629E0100	3 Cable Guardrail	100	Ft
629E0300	3 Cable Guardrail Slip Base Anchor Assembly	1	Each
629E1000	Repair 3 Cable Guardrail	100	Ft
629E1100	3 Cable Guardrail End Post	3	Each
629E1102	3 Cable Guardrail Intermediate Post	10	Each
629E1104	3 Cable Guardrail Post, Winter	15	Each
629E1106	Drive Down 3 Cable Guardrail Post	10	Each
629E1110	Cable Anchor Bracket	1	Each
629E1112	Cable Splice	1	Each
629E1114	3 Cable Guardrail J Hook Bolt	100	Each
629E1116	Steel Turnbuckle Cable End Assembly	1	Each
629E1118	Spring Cable End Assembly with Turnbuckle	2	Each
629E1120	W Beam to 3 Cable Transition Bracket	1	Each
629E1122	3 Cable Guardrail End Post Cap	5	Each
630E0200	Straight Class A Thrie Beam Rail	12.5	Ft
630E0210	Straight Class B Thrie Beam Rail	12.5	Ft
630E1150	Straight Double Class B W Beam Guardrail with Wood Posts	12.5	Ft
630E1200	Straight Class A W Beam Rail	75.0	Ft
630E1210	Straight Class B W Beam Rail	25.0	Ft
630E2000	W Beam to Thrie Beam Guardrail Transition	1	Each
630E2015	W Beam Guardrail Flared End Terminal	1	Each
630E2020	W Beam Guardrail Tangent End Terminal	1	Each
630E2030	W Beam Guardrail Breakaway Cable Terminal	1	Each
630E2110	Beam Guardrail Post and Block	10	Each
630E2120	Beam Guardrail Post and Block, Winter	5	Each
630E2210	Breakaway Cable Terminal End Rail	1	Each
630E2215	W Beam Guardrail End Section Buffer	1	Each
630E5120	Reset Thrie Beam Rail	12.5	Ft
630E5160	Reset W Beam Rail	12.5	Ft
630E5170	Reset Double W Beam Rail	12.5	Ft
630E5520	Drive Down Beam Guardrail Post	3	Each
630E5550	Reset Beam Guardrail Post and Block	5	Each
634E0010	Flagging	3	Hour
634E0125	Traffic Control for Guardrail Repair	6	Site
634E0420	Type C Advance Warning Arrow Panel	1	Each

CONTRACT TIME PROVISIONS

- The contract will expire on September 30, 2015.
- At such time as repairs are required, the Contractor will be notified. The Contractor will have 7 calendar days to complete the repairs.

ESTIMATE OF QUANTITIES, 000P-469, PCN i3Lu, (Priority)

Bid Item Number	Item	Quantity	Unit
009E0197	Mobilization 1	2	Each
009E0198	Mobilization 2	2	Each
009E0199	Mobilization 3	2	Each
110E0700	Remove 3 Cable Guardrail	25	Ft
110E0730	Remove Beam Guardrail	100.0	Ft
110E0770	Remove W Beam Guardrail Breakaway Cable Terminal	1	Each
110E0800	Remove W Beam Guardrail End Terminal	1	Each
110E6230	Remove W Beam Guardrail for Reset	25.0	Ft
629E0100	3 Cable Guardrail	100	Ft
629E0300	3 Cable Guardrail Slip Base Anchor Assembly	1	Each
629E1000	Repair 3 Cable Guardrail	100	Ft
629E1100	3 Cable Guardrail End Post	3	Each
629E1102	3 Cable Guardrail Intermediate Post	10	Each
629E1104	3 Cable Guardrail Post, Winter	15	Each
629E1106	Drive Down 3 Cable Guardrail Post	10	Each
629E1110	Cable Anchor Bracket	1	Each
629E1112	Cable Splice	1	Each
629E1114	3 Cable Guardrail J Hook Bolt	100	Each
629E1116	Steel Turnbuckle Cable End Assembly	1	Each
629E1118	Spring Cable End Assembly with Turnbuckle	2	Each
629E1120	W Beam to 3 Cable Transition Bracket	1	Each
629E1122	3 Cable Guardrail End Post Cap	5	Each
630E0200	Straight Class A Thrie Beam Rail	12.5	Ft
630E0210	Straight Class B Thrie Beam Rail	12.5	Ft
630E1150	Straight Double Class B W Beam Guardrail with Wood Posts	12.5	Ft
630E1200	Straight Class A W Beam Rail	75.0	Ft
630E1210	Straight Class B W Beam Rail	25.0	Ft
630E2000	W Beam to Thrie Beam Guardrail Transition	1	Each
630E2015	W Beam Guardrail Flared End Terminal	1	Each
630E2020	W Beam Guardrail Tangent End Terminal	1	Each
630E2030	W Beam Guardrail Breakaway Cable Terminal	1	Each
630E2110	Beam Guardrail Post and Block	10	Each
630E2120	Beam Guardrail Post and Block, Winter	5	Each
630E2210	Breakaway Cable Terminal End Rail	1	Each
630E2215	W Beam Guardrail End Section Buffer	1	Each
630E5120	Reset Thrie Beam Rail	12.5	Ft
630E5160	Reset W Beam Rail	12.5	Ft
630E5170	Reset Double W Beam Rail	12.5	Ft
630E5520	Drive Down Beam Guardrail Post	3	Each
630E5550	Reset Beam Guardrail Post and Block	5	Each
634E0010	Flagging	3	Hour
634E0125	Traffic Control for Guardrail Repair	6	Site
634E0420	Type C Advance Warning Arrow Panel	1	Each

UTILITIES

The Contractor shall contact the involved utility companies through South Dakota One Call (1-800-781-7474) prior to starting work. It shall be the responsibility of the Contractor to coordinate work with the utility owners to avoid damage to existing facilities.

Utilities are not planned to be affected on this project. If utilities are identified near the improvement area through the SD One Call Process as required by South Dakota Codified Law 49-7A and Administrative Rule Article 20:25, the Contractor shall contact the Project Engineer to determine modifications that will be necessary to avoid utility impacts.



**MOBILIZATION**

If more than one location within an area is to be repaired, the Contractor will be compensated for only one mobilization per area.

Mobilization 1 is the cost of mobilization per each time the Contractor is called in by the Belle Fourche Area Engineer, or his designated representative, to perform guardrail repair within the Belle Fourche Area.

Mobilization 2 is the cost of mobilization per each time the Contractor is called in by the Rapid City Area Engineer, or his designated representative, to perform guardrail repair within the Rapid City Area.

Mobilization 3 is the cost of mobilization per each time the Contractor is called in by the Custer Area Engineer, or his designated representative, to perform guardrail repair within the Custer Area

Mobilization will be paid once each time the Contractor is called to repair guardrail, regardless of the number of sites requiring repair within the project limits.

Guardrail repairs will be limited to all Interstate and State highways within the boundaries of the Rapid City Region. Maintenance maps for priority and non-priority routes are available at the Rapid City Region office.

**TRAFFIC CONTROL**

Traffic control shall at all times be maintained in accordance with applicable MUTCD Standards, Section 634 of the Standard Specifications and these plans.

The Contractor shall be required to have a person available 24 hour/day, 7 days/week to maintain traffic control devices. The name and cellular telephone number of this individual shall be given to the Engineer at the preconstruction meeting.

The bid item "Traffic Control for Guardrail Repair" shall include all necessary traffic control devices as required by these plans and shall be measured and paid and the contract unit price per "site". The Contractor shall be compensated each time they are required to mobilize to a "site" for guardrail repair. If the Contractor relocates the traffic control devices to a different location during the same mobilization, additional compensation will not be made and it shall be considered the same "site".

Construction vehicles shall exit or enter the construction work zone at locations identified by the Engineer. At no time shall construction vehicles utilize the maintenance crossovers or the I-90 median to exit or enter I-90 traffic.

Unless otherwise stated in these plans, no work will be allowed during hours of darkness. Hours of darkness are defined, as ½ hour after sunset until ½ hour before sunrise.

All materials and equipment shall be stored a minimum distance of 30' from the traveled way during nonworking hours.

Traffic shall be returned to the normal driving lanes during non-working hours.

**TRAFFIC CONTROL**

Storage of vehicles and equipment shall be as near the right-of-way as possible. Contractor's employees should mobilize at a location off the right-of-way and arrive at the work sites in a minimum number of vehicles necessary to perform the work. Indiscriminate driving and parking of vehicles within the right-of-way will not be permitted. Any damage of the vegetation, surfacing, embankment, delineators, and existing signs resulting from such indiscriminate use shall be repaired and/or restored by the Contractor, at no expense to the State, and to the satisfaction of the Engineer.

Vehicles working in traffic or alongside traffic shall be equipped with a flashing amber light visible from all directions. The amber light shall be mounted on the uppermost part of the contractor's vehicle. Lights must have peak intensity within the range of 40 to 400 candelas and must flash at 75 ± 15 flashes per minute. Vehicle flasher/hazard lights are not acceptable.

The Contractor shall provide documentation that all breakaway sign supports comply with FHWA NCHRP 350 or MASH crash-worthy requirements. The Contractor shall provide installation details at the preconstruction meeting for all breakaway sign support assemblies.

**RESTORATION OF DISTURBED AREAS**

Areas disturbed as a result of the work necessary to repair guardrail shall be reshaped and/or restored to the satisfaction of the Engineer. The disturbed areas shall be tilled to a minimum depth of three inches and seeded with the following seed mix rate:

Type F Permanent Seed Mixture shall consist of the following:

Grass Species	Variety	Pure Live Seed (PLS) (Pounds/Acre)
Western Wheatgrass	Flintlock, Rodan, Rosana	7
Green Needlegrass	Lodorm	4
Sideoats Grama	Butte, Killdeer, Pierre, Trailway	3
Blue Grama	Bad River, Willis	2
Oats or Spring Wheat: April through May; Winter Wheat: August through November		10
Total:		26

All costs for reshaping, leveling, tilling, and seeding disturbed areas shall be incidental to the various bid items on the project.

**GUARDRAIL**

When guardrail adjoining bridge ends is ordered to be repaired, the contractor shall replace with the same size and type as the existing guardrail.

When a W beam guardrail end terminal is replaced, the new end terminal shall be of the same type (flared or tangent) that was originally installed.

Beam Guardrail Post and Block, Winter - Includes the additional cost for removal and installation of a Beam Guardrail Wood Post and Block when there is at least one foot of solid frozen ground at the work site. This bid item shall be an additional payment. (i.e. the Contractor will be paid once for the respective Beam Guardrail Post and Block bid item and once for Beam Guardrail Post and Block, Winter for each post when the Engineer determines winter conditions apply).

Cable Guardrail Post, Winter - Includes the additional costs for removal and installation of a 3 Cable I Beam Steel and 3 Cable Flanged Channel Post when there is in excess of one foot of solid frozen ground at the work site. This bid item shall be an additional payment. (i.e. the Contractor will be paid once for the respective 3 Cable Guardrail Post bid item and once for 3 Cable Guardrail Post, Winter for each post when the Engineer determines winter conditions apply).

All reset portions of W Beam and Thrie Beam Guardrail sections shall include the removal of wood guardrail posts and resetting these posts to the proper alignment with the steel beam guardrail. Payment for this work will be the same for frozen or unfrozen ground.

Repair 3 Cable Guardrail – Includes all costs for replacing and repairing damaged cable, realigning posts, and the tensioning of the three cable guardrail. Payment for this item is applicable only when the cable is replaced, broken cable repaired, or the existing cable rail required realigning and retensioning.

"3 Cable Guardrail Intermediate Post" includes all costs to furnish and install either I Beam or Flanged type of posts. The post for this item shall be furnished and installed consistent with the type of posts presently in place at the proposed repair site.

"Beam Guardrail Post and Block" shall include all costs to furnish and install. 7' long posts shall be used when placed at the hinge point of the embankment

W Beam Guardrail Breakaway Cable Terminal will be repaired only when they are behind 3 Cable Guardrail. W Beam Guardrail Breakaway Cable Terminal - Includes the costs of removing damaged components of the BCT System, furnishing and installing new Wood Breakaway End Posts (2), W Beam End Section (Buffer) 11" + radius, related items and all hardware to attach same. Any other BCT items that are required will be paid for at invoice cost plus shipping, taxes and ten percent for profit.

**GUARDRAIL (CONTINUED)**

W Beam Guardrail BCT's or MELT's that are damaged and are not behind 3 Cable guardrail will be replaced with a new W Beam Guardrail End Terminal. Approved products are available at the following web address. <http://apps.sd.gov/Applications/HC54ApprovedProducts/main.asp>

The Contractor may be required to furnish some items that are not listed in the Contract Proposal. The Contractor shall furnish the invoice and will be paid invoice cost plus shipping, handling, taxes and 10 percent for profit. The Contractor is required to receive prior approval of the Engineer before making these purchases. Installation cost for these items shall be incidental to the contract unit prices for the various items.

The Contractor shall place "State Furnished Asphalt Concrete Cold Mix" around the posts to fill and level any voids created by the driving of the posts through the asphalt. This material will be available at the SDDOT maintenance in Rapid City. The material shall be placed ½" high around the post to force the water to drain away from the post. Cost for this work shall be incidental to the various bid items on the project.

All costs to furnish and install new bolts, nuts, washers, nails, misc. shall be incidental to the various bid items on the project. All removed guardrail items that are not reused shall become the property of the Contractor.

**NCHRP 350 TEST LEVEL 3 HIGH TENSION CABLE GUARDRAIL**

The Contractor shall furnish and install a 3 or 4 cable high tension guardrail system that meets the Test Level 3 crash testing requirements of National Cooperative Highway Research Program (NCHRP) 350 or Manual for Assessing Safety Hardware (MASH) 2009. The maximum dynamic deflection of the system shall be less than 8 feet and the maximum post spacing shall be 16 feet unless specified otherwise in the plans.

The high tension cable guardrail system shall be in compliance with Specifications Section 6.9 Buy America.

The Contractor shall install the system according to the manufacturer's installation recommendations except where stated otherwise in the plans. A copy of the detail drawings and installation instructions for the high tension cable guardrail and anchor assemblies shall be given to the Engineer a minimum of 4 weeks prior to installation of the high tension cable guardrail system.

All posts shall be galvanized and inserted into driven galvanized steel sleeves with soil plates.

Reflective sheeting shall be placed on the face of every other post cap or cable spacer and on the cable release post. The sheeting shall be in conformance with Section 982.2.1.2 of the Specifications. The color of the reflective sheeting shall be the same as the nearest pavement marking.

Reflective sheeting shall be placed along the guardrail at a minimum rate of 16 square inches of sheeting every 50'. The anchor assembly shall have a minimum of 256 square inches of object marker sheeting. The sheeting shall be fluorescent yellow super or very high intensity.

The cables provided shall be pre-stretched in the factory.

The Contractor shall check and adjust the tension of the cables a minimum of 3 weeks after installation and not longer than 6 weeks after installation. Cost for this work shall be incidental to the contract unit price per foot for "NCHRP 350 Test Level 3 High Tension Cable Guardrail".

The lengths of high tension cable guardrail stated in the plans were based on a non-effective length of 26' at each end of the "run" of guardrail. The length and location of the high tension cable guardrail at each site will need to be adjusted during construction as necessary if a system with a different non-effective length is used and it shall be approved by the Design Engineer before installation.

The Contractor shall provide a signed letter of compliance to the Engineer upon completion of the high tension cable guardrail installation(s) stating that the high tension cable barrier system has been installed in conformance to the installation instructions, specifications, and at a minimum meets the TL-3 crash test requirements of NCHRP 350 or MASH 2009.

The high tension cable guardrail shall be measured along the centerline of the cable guardrail from center of anchor assembly to center of anchor assembly to the nearest foot. Example: If the system utilizes 4 anchor footings in the anchor assembly, then the center of the anchor assembly would be centered between the 2<sup>nd</sup> and 3<sup>rd</sup> footing.

All costs for furnishing and installing the 3 or 4 cable high tension guardrail system including all labor, materials, and equipment shall be incidental to the contract unit price per foot for "NCHRP 350 Test Level 3 High Tension Cable Guardrail".

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	000I-469, 000N-469 & 000P-469	4	29

**HIGH TENSION CABLE GUARDRAIL ANCHOR ASSEMBLY**

The beginning and end of each "run" of high tension cable guardrail shall terminate with an anchor assembly that meets the Test Level 3 crash testing requirements of NCHRP 350 or MASH 2009.

The footing for the anchor assembly shall be designed to allow for 1 inch maximum of lateral deflection. The allowable design soil pressure shall be 1000 psf. The top 2 feet of soil pressure shall be neglected in the design of the footing. The footing shall be a minimum of 5' deep. The footing design shall be submitted through proper channels to the Office of Bridge Design for approval a minimum of 4 weeks prior to construction of the anchor footings.

All costs for furnishing and installing the High Tension Cable Guardrail Anchor Assembly including all labor, equipment, and materials which include the anchor footing, hardware, and all attachments to the anchor footing, shall be incidental to the contract unit price per each for "NCHRP 350 Test Level 3 High Tension Cable Guardrail Anchor Assembly".


Published Date: 3rd Qtr. 2014

STANDARD

3 CABLE GUARDRAIL

PLATE NUMBER  
629.01

Sheet 1 of 6



CABLE SPLICE

The following table and criteria shall apply to the arrangement of the Spring Cable End Assemblies (Compensation Devices) and Turnbuckle Cable End Assemblies:

LENGTH OF CABLE RUN	CRITERIA FOR ARRANGEMENT OF THE SPRING CABLE END ASSEMBLIES (COMPENSATION DEVICES) AND TURNBUCKLE CABLE END ASSEMBLIES
To 500'	Use turnbuckle on the approaching traffic end and compensating device on the other end of each individual cable, except in the W Beam to 3 Cable Transition where all compensating devices shall be provided at the bridge ends.
Greater than 500' to 1000'	Use compensating device on each end of each individual cable.
Greater than 1000'	Start new run by interlacing at last parallel post as shown above.

All Compensating Devices shall be attached to the cable anchor bracket when one end of the run is attached to a bridge. Compensating Devices must have a spring rate of 450 ± 50 Lbs. per inch and shall have a total available travel of 6" minimum.

The cable shall be retensioned after the initial 2 week pretension period in accordance with the following table:

Temperature Range (Deg.)	120 to 110	109 to 100	99 to 90	89 to 80	79 to 70	69 to 60	59 to 50	49 to 40	39 to 30	29 to 20	19 to 10	9 to 0	-1 to -10	-11 to -20
Spring Compression (In.)	1	1 1/4	1 1/2	1 3/4	2	2 1/4	2 1/2	2 3/4	3	3 1/4	3 1/2	3 3/4	4	4 1/4

December 23, 2010


Published Date: 3rd Qtr. 2014

STANDARD

3 CABLE GUARDRAIL

PLATE NUMBER  
629.01


Sheet 2 of 6



TYPICAL 3 CABLE GUARDRAIL ANCHOR SECTIONS




PLAN (FLARED ANCHOR SECTION)



PLAN (DOWNSTREAM ONE WAY ROADWAY ANCHOR SECTION)



PLAN (TANGENT ANCHOR SECTION)



December 23, 2010



Published Date: 3rd Qtr. 2014


DTSDS

3 CABLE GUARDRAIL

PLATE NUMBER  
629.01

Sheet 5 of 6

December 23, 2010



S3x5.7 STEEL I BEAM POST  
FOR 3 CABLE GUARDRAIL

Published Date: 3rd Qtr. 2014


DTSDS

3 CABLE GUARDRAIL

PLATE NUMBER  
629.01

Sheet 6 of 6


December 23, 2010



FLANGED CHANNEL STEEL POST  
FOR 3 CABLE GUARDRAIL

END POST CAP



**GENERAL NOTES:**  
Flanged channel steel posts shall be produced from high strength steel in accordance with ASTM A499 Grade 60.  
Anchor plate shall be carbon steel sheet.  
Alternate anchor plate shall be ASTM A36 steel.  
Bolt shall be in conformance with ASTM A354 Grade BD or BC. Nut shall be in conformance with ASTM A563 Grade DH.  
Bolt shall be Cadmium plated per ASTM A165-80 Type OS except using clear chromate.  
Finish for the post and anchor plate shall be a high quality dark green outdoor acrylic enamel.  
Alternate anchor plate may be unfinished.














**GENERAL NOTES:**

Asphalt concrete shall be the same type used elsewhere on the project or shall be as specified in the plans. If asphalt concrete is not specified in the plans, the asphalt concrete shall conform to the SD Standard Specifications for "Asphalt Concrete Composite." For informational purposes, the Rate of Materials for the 3.5' wide section of asphalt concrete as shown above shall be 4.80 Tons per Station.

Granular material shall be the same type used elsewhere on the project or shall be as specified in the plans. If granular material type is not specified in the plans, the material shall conform to the SD Standard Specifications for "Base Course". The granular material shall be placed the same thickness as the mainline surfacing or as specified in the plans.


Surfacing and embankment quantities will be paid for separately and will NOT be incidental to the "Thrie Beam Guardrail" bid item.

The cross slope for the surfacing and subgrade surface shall be as specified in the plans (See Typical Sections and/or Cross Sections).

The top of posts and top of block shall have a true square cut. The top of post and top of block shall be flush.

December 23, 2010

Published Date: 3rd Qtr. 2014	S D D O T	THRIE BEAM GUARDRAIL POST INSTALLATION	PLATE NUMBER 630.01
			Sheet 1 of 1



THRIE BEAM GUARDRAIL DEFLECTION CRITERIA	
POST SPACING	MAXIMUM DEFLECTION
6'-3"	2'-6"
3'-1 1/2"	1'-9"

For Informational Purposes Only

**GENERAL NOTES:**

All thrie beam rail shall be Type I.

There will be no separate payment for furnishing and installing Thrie Beam End Sections (Flared) and Thrie Beam Terminal Connectors. All costs for the Thrie Beam End Sections (Flared) and Thrie Beam Terminal Connectors shall be incidental to the contract unit price per foot for the respective "Thrie Beam Guardrail" bid item.

Thrie beam rail section lengths may be 12'-6" and/or 25'-0". The combination of section lengths used shall be compatible with the total length of rail per site as shown in the plans.

Thrie Beam End Sections (Flared) shall only be used in a one way traffic situation. See Standard Plate 630.80 for Thrie Beam End Section (Flared) in the Beam Guardrail Trailing End Terminal.

All costs for constructing thrie beam guardrail including labor, equipment, and materials including all posts, blocks, steel beam rail, and hardware shall be incidental to the contract unit price per foot for the respective "Thrie Beam Guardrail" bid item.


Surfacing and embankment quantities will be paid for separately and will NOT be incidental to the "Thrie Beam Guardrail" bid item.

December 23, 2010

Published Date: 3rd Qtr. 2014	S D D O T	THRIE BEAM GUARDRAIL INSTALLATION	PLATE NUMBER 630.02
			Sheet 1 of 1







POST SPACING ARRANGEMENT FOR THRIE BEAM GUARDRAIL AT BRIDGE END

December 23, 2002


Published Date: 3rd Qtr. 2014

SDOT

POST SPACING ARRANGEMENT FOR  
THRIE BEAM GUARDRAIL AT BRIDGE END

PLATE NUMBER  
630.15

Sheet 1 of 1



POST SPACING ARRANGEMENT FOR THRIE BEAM GUARDRAIL AT BRIDGE END

March 31, 2000


Published Date: 3rd Qtr. 2014

SDOT

POST SPACING ARRANGEMENT FOR  
THRIE BEAM GUARDRAIL AT BRIDGE END  
(BRIDGE GUARDRAIL DESIGN 1T)

PLATE NUMBER  
630.20

Sheet 1 of 1



\* 6" x 8" x 7' posts shall be used at these locations.

POST SPACING ARRANGEMENT FOR THRIE BEAM GUARDRAIL AT BRIDGE END

December 23, 2002


Published Date: 3rd Qtr. 2014

SD  
DOT

POST SPACING ARRANGEMENT FOR  
THRIE BEAM GUARDRAIL AT BRIDGE END  
(BRIDGE GUARDRAIL DESIGN 2T)

PLATE NUMBER  
630.21

Sheet 1 of 1



GENERAL NOTES:

Asphalt concrete shall be the same type used elsewhere on the project or shall be as specified in the plans. If asphalt concrete is not specified in the plans, the asphalt concrete shall conform to the SD Standard Specifications for "Asphalt Concrete Composite." For informational purposes, the Rate of Materials for the 3.5' wide section of asphalt concrete as shown above shall be 4.80 Tons per Station.

Granular material shall be the same type used elsewhere on the project or shall be as specified in the plans. If granular material type is not specified in the plans, the material shall conform to the SD Standard Specifications for "Base Course". The granular material shall be placed the same thickness as the mainline surfacing or as specified in the plans.

Surfacing and embankment quantities will be paid for separately and will NOT be incidental to the "W Beam Guardrail" bid item.

The cross slope for the surfacing and subgrade surface shall be as specified in the plans (See Typical Sections and/or Cross Sections).

The top of posts and top of block shall have a true square cut. The top of post and top of block shall be flush.

December 23, 2010


Published Date: 3rd Qtr. 2014

SD  
DOT


W BEAM GUARDRAIL POST INSTALLATION

PLATE NUMBER  
630.31

Sheet 1 of 1




SECTION THROUGH W BEAM RAIL ELEMENT



The Post Bolt is similar except the post bolt is 18" long.



SPLICE BOLT  
(5/8" BUTTON HEAD BOLT AND RECESS NUT)



Lap in direction of traffic.  
RAIL SPLICE

December 23, 2004

Published Date: 3rd Qtr. 2014	S D D O T	W BEAM RAIL, RAIL SPLICE, AND HARDWARE	PLATE NUMBER 630.33
			Sheet 1 of 1



#### GENERAL NOTES:

W Beam Terminal Connectors shall be 10 gauge.


When the W beam terminal connector is used to connect the rail to the bridge, 1" steel washers shall be used at the lap splice and the washers shall be in direct contact with the 3" slots of the W beam terminal connector. See the drawings above for the typical locations of the 1" steel washers.

There will be no separate payment for furnishing and installing the W Beam Terminal Connector. All costs for the W Beam Terminal Connector shall be incidental to the contract unit price per foot for the respective "W Beam Guardrail" bid item.

September 14, 2001

Published Date: 3rd Qtr. 2014	S D D O T	W BEAM TERMINAL CONNECTOR AND 1" STEEL WASHER	PLATE NUMBER 630.35
			Sheet 1 of 1





Offsets shall be measured from the installation line to the face of the W beam guardrail.

**GENERAL NOTES:**

The finished embankment surfacing cross slope shall match the roadway cross slope; however, if a steeper cross slope is necessary the steepest allowable cross slope is 10:1.

Asphalt concrete shall be the same type used elsewhere on the project or shall be as specified in the plans. If asphalt concrete is not specified in the plans, the asphalt concrete shall conform to the SD Standard Specifications for "Asphalt Concrete Composite."

Granular material shall be the same type used elsewhere on the project or shall be as specified in the plans. If granular material type is not specified in the plans, the material shall conform to the SD Standard Specifications for "Base Course". The granular material shall be placed the same thickness as the mainline surfacing or as specified in the plans.


\*\*\*An adhesive object marker shall be placed on the end section buffer after placement of the end section buffer. The adhesive object marker dimensions may be 16" x 16" or other variation due to the shape of the end section buffer. A minimum of 256 square inches of object marker reflective sheeting area is required. The reflective sheeting shall be fluorescent yellow super or very high intensity. All costs for furnishing and installing the adhesive object marker shall be incidental to various contract items.

Costs for constructing the W Beam Guardrail Breakaway Cable Terminal including labor, equipment, and materials including the anchor bracket, cable assembly, steel tubes, soil plates, bearing plate, pipe sleeve, W beam end section(buffer), modified W beam terminal connector, and all necessary hardware shall be incidental to the contract unit price per each for "W Beam Guardrail Breakaway Cable Terminal".

June 26, 2010

OFFSETS FOR BREAKAWAY CABLE TERMINAL	
POST	OFFSET
A	4.00'
B	2.79'
C	1.79'
D	1.01'
E	0.45'
F	0.11'

<b>1 GUARDRAIL CABLE TERMINAL</b>	<b>PLATE NUMBER</b> 630.47
	Sheet 1 of 3



GENERAL NOTES:

All hardware shall be galvanized in accordance with ASTM A153.

The steel tubes shall meet the requirements of ASTM Specification A500, Grade B, and shall be galvanized after fabrication in accordance with the requirements of AASHTO Specification M111.

The anchor bracket, soil plate, and bearing plate shall be fabricated from steel that meets ASTM A36 Specifications. They shall be galvanized after fabrication in accordance with ASTM A123.


The W Beam End Section (Buffer) shall be 12 gage galvanized steel.

The cable shall be  $\frac{3}{4}$ ", Type II, with Class A coating in conformance with AASHTO M30.

June 26, 2010


Published Date: 3rd Qtr. 2014	S D D O T	W BEAM GUARDRAIL BREAKAWAY CABLE TERMINAL	PLATE NUMBER 630.47
			Sheet 2 of 3





June 26, 2010

Published Date: 3rd Qtr. 2014	S D D O T	W BEAM GUARDRAIL BREAKAWAY CABLE TERMINAL	PLATE NUMBER 630.47
			Sheet 3 of 3




March 31, 2000

Published Date: 3rd Qtr. 2014	S D D O T	POST SPACING ARRANGEMENT FOR W BEAM GUARDRAIL AT BRIDGE END	PLATE NUMBER 630.50
			Sheet 1 of 1







POST SPACING ARRANGEMENT FOR W BEAM GUARDRAIL AT BRIDGE END  
(W BEAM RESET AND RETROFIT)

N = New post and block

March 31, 2000


Published Date: 3rd Qtr. 2014

SDOT

POST SPACING ARRANGEMENT FOR  
W BEAM GUARDRAIL AT BRIDGE END  
(W BEAM RESET AND RETROFIT)

PLATE NUMBER  
630.59

Sheet 1 of 1



DETAIL A  
(Post, Block, and Post Bolt not shown)

GENERAL NOTES:

The steel shall be in conformance with ASTM A 36 and shall be galvanized after fabrication in conformance with ASTM A 123. If pre-galvanized steel members are used, all cuts and welds shall be coated with an approved galvanizing paint.

Offset blocks shall be in conformance with section 630 of the Standard Specifications.  
All hardware shall be in conformance with the requirements of AASHTO M 180.

March 31, 2000


Published Date: 3rd Qtr. 2014

SDOT


RUBRAIL AT BRIDGE END  
(CAST IN INSERT)

PLATE NUMBER  
630.75


Sheet 1 of 2




SECTION A-A



RECTANGULAR PLATE WASHER




SECTION B-B



SECTION C-C


March 31, 2000

Published Date: 3rd Qtr. 2014	S D D O T	RUBRAIL AT BRIDGE END (CAST IN INSERT)	PLATE NUMBER 630.75
			Sheet 2 of 2



\* Rubrail does not have to be attached to these posts.

ELEVATION



DETAIL A

(Post, Block, and Post Bolt not shown)

GENERAL NOTES:

The steel shall be in conformance with ASTM A 36 and shall be galvanized after fabrication in conformance with ASTM A 123. If pre-galvanized steel members are used, all cuts and welds shall be coated with an approved galvanizing paint.

Offset blocks shall be in conformance with section 630 of the Standard Specifications.


All hardware shall be in conformance with the requirements of AASHTO M 180.

The wedge type anchor bolt, nut, and washer shall be hot dipped galvanized or made of a corrosion resistant material. The wedge type anchor shall be capable of sustaining an ultimate load in tension or shear of 17,000 pounds when the anchor is set in 4,500 psi compressive strength concrete. The anchor shall be installed according to the manufacturer's recommendations. The Contractor shall obtain certification from the manufacturer that the anchor meets the tensile and shear requirements and shall submit the certification to the Engineer. The cost for furnishing and installing the wedge type anchor, nut, and washer shall be incidental to the contract unit price per foot for "Rubrail".


March 31, 2000

Published Date: 3rd Qtr. 2014	S D D O T	RUBRAIL AT BRIDGE END (W BEAM RETROFIT AND DRILLED IN ANCHOR)	PLATE NUMBER 630.76
			Sheet 1 of 2







SECTION A-A



RECTANGULAR PLATE WASHER




SECTION B-B




SECTION C-C

March 31, 2000

Published Date: 3rd Qtr. 2014	S D D O T	RUBRAIL AT BRIDGE END (W BEAM RETROFIT AND DRILLED IN ANCHOR)	PLATE NUMBER 630.76
			Sheet 2 of 2




PLAN



\*Rubrail does not have to be attached to these posts.

ELEVATION



DETAIL A

(Post, Block, and Post Bolt not shown)


GENERAL NOTES:

The steel shall be in conformance with ASTM A 36 and shall be galvanized after fabrication in conformance with ASTM A 123. If pre-galvanized steel members are used, all cuts and welds shall be coated with an approved galvanizing paint.


Offset blocks shall be in conformance with section 630 of the Standard Specifications. All hardware shall be in conformance with the requirements of AASHTO M 180.

March 31, 2000


Published Date: 3rd Qtr. 2014	S D D O T	RUBRAIL AT BRIDGE END (W BEAM RETROFIT AND CAST IN INSERT)	PLATE NUMBER 630.77
			Sheet 1 of 2




SECTION A-A



RECTANGULAR PLATE WASHER




SECTION B-B




SECTION C-C

March 31, 2000

Published Date: 3rd Qtr. 2014	S D D O T	RUBRAIL AT BRIDGE END (W BEAM RETROFIT AND CAST IN INSERT)	PLATE NUMBER 630.77
			Sheet 2 of 2




PLAN



\*Rubrail does not have to be attached to these posts.

ELEVATION



DETAIL A

(Post, Block, and Post Bolt not shown)

GENERAL NOTES:



The steel shall be in conformance with ASTM A 36 and shall be galvanized after fabrication in conformance with ASTM A 123. If pre-galvanized steel members are used, all cuts and welds shall be coated with an approved galvanizing paint.

Offset blocks shall be in conformance with section 630 of the Standard Specifications.

All hardware shall be in conformance with the requirements of AASHTO M 180.


March 31, 2000

Published Date: 3rd Qtr. 2014	S D D O T	RUBRAIL AT BRIDGE END (W BEAM RETROFIT AND DRILLED IN ANCHOR)	PLATE NUMBER 630.78
			Sheet 1 of 2



Posted Speed Prior to Work (M.P.H.)	Spacing of Advance Warning Signs (Feet) (A)	Taper Length (Feet) (L)	Spacing of Channelizing Devices (Feet) (G)
0 - 30	100 - 200	180	25
35 - 40	350	320	25
45 - 50	500	600	50
55	750	660	50
60 - 65	1000	780	50

■ Channelizing Device




The channelizing devices shall be drums or 42" cones if traffic control must remain overnight or longer.

For short duration operations (1 hour or less) all signs and channelizing devices may be eliminated if a vehicle with an activated flashing or revolving yellow light is used.

Worker signs (W21-1 or W21-1a) may be used instead of SHOULDER WORK signs.


A SHOULDER WORK sign should be placed on the left side of a divided or one-way roadway only if the left shoulder is affected.

The SHOULDER WORK sign on an intersecting roadway is not required if drivers emerging from that roadway will encounter another advance warning sign before they reach a work activity area.



February 14, 2011

Published Date: 3rd Qtr. 2014	S D D O T	GUIDES FOR TRAFFIC CONTROL DEVICES WORK ON SHOULDERS	PLATE NUMBER 634.03
			Sheet 1 of 1



GENERAL NOTES:

In areas where the required guardrail wood post depth is not obtainable, shorter posts may be used and shall be anchored in concrete in accordance with the details shown on this standard plate.

A 20" x 20" square concrete anchor footing may be used in lieu of the 24" diameter round anchor footing.

Forms for the concrete anchor footing hole is not required.

Concrete for the concrete anchor footing shall be Class M6.

Three quarter inch polystyrene foam shall be attached to two sides of the posts. See details above for placement position of the polystyrene foam.

There will be no separate payment for furnishing and installing the concrete anchor footing for short guardrail post. All costs for concrete anchor footings shall be incidental to the contract unit price per foot for the respective "Thrie Beam or W Beam Guardrail" bid item.

March 31, 2000

Published Date: 3rd Qtr. 2014	S D D O T	CONCRETE ANCHOR FOOTING FOR SHORT GUARDRAIL POST	PLATE NUMBER 630.84
			Sheet 1 of 1

Posted Speed Prior to Work (M.P.H.)	Spacing of Advance Warning Signs (Feet) (A)	Spacing of Channelizing Devices (Feet) (G)
0 - 30	200	25
35 - 40	350	25
45 - 50	500	50
55	750	50
60 - 65	1000	50

- Flagger
- Channelizing Device

For low-volume traffic situations with short work zones on straight roadways where the flagger is visible to road users approaching from both directions, a single flagger may be used.

The ROAD WORK AHEAD and the END ROAD WORK signs may be omitted for short duration operations (1 hour or less).

For tack and/or flush seal operations, when flaggers are not being used, the FRESH OIL sign (W21-2) shall be displayed in advance of the liquid asphalt areas.

Flashing warning lights and/or flags may be used to call attention to the advance warning signs.

The channelizing devices shall be drums or 42" cones.


Channelizing devices are not required along the centerline adjacent to work area when pilot cars are utilized for escorting traffic through the work area.

2-029  
END  
ROAD WORK  
G20-2

Channelizing devices and flaggers shall be used at intersecting roads to control intersecting road traffic as required.

The buffer space should be extended so that the two-way traffic taper is placed before a horizontal or vertical curve to provide adequate sight distance for the flagger and queue of stopped vehicles.

Warning sign sequence in opposite direction same as below.



February 14, 2011

Published Date: 3rd Qtr. 2014

S  
D  
D  
O  
T

GUIDES FOR TRAFFIC CONTROL DEVICES  
LANE CLOSURE WITH FLAGGER PROVIDED

PLATE NUMBER  
634.23

Sheet 1 of 1

Posted Speed Prior to Work (M.P.H.)	Spacing of Advance Warning Signs (Feet) (A) (B) (C)	Taper Length (Feet) (L)	Spacing of Channelizing Devices (Feet) (G)
0 - 30	200	180	25
35 - 40	350	320	25
45 - 50	500	600	50 *
55	750	660	50 *
60 - 65	1000	780	50 *

\* Spacing to be every 40' for 42" cones.


⊙ Reflectorized Drum

■ Channelizing Device shall be 42" cones or drums

42" cones may be used in place of the drums shown in the taper if setup will not be used during any night time hours.

4" white temporary pavement marking shall be used for overnight and long term operations.

Longitudinal dimensions may be adjusted to fit project conditions such as horizontal curves, vertical curves, and other site restrictions.



December 23, 2012

Published Date: 3rd Qtr. 2014


S  
D  
D  
O  
T

GUIDES FOR TRAFFIC CONTROL DEVICES  
4-LANE UNDIVIDED, RIGHT LANE CLOSED

PLATE NUMBER  
634.47

Sheet 1 of 1





This procedure also applies when work is being performed in the lane adjacent to the median on a divided highway. Under these conditions, LEFT LANE CLOSED signs and the corresponding LANE REDUCTION symbol signs shall be used.

- ⊙ Reflectorized Drum
- Channelizing Device shall be 42" cones or drums

42" cones may be used in place of the drums shown in the taper if setup will not be used during any night time hours.

December 23, 2012

Published Date: 3rd Qtr. 2014

S  
D  
D  
O  
T

GUIDES FOR TRAFFIC CONTROL DEVICES  
LANE CLOSURE WITHOUT BARRIER

PLATE NUMBER  
634.64

Sheet 1 of 1