


Plot Scale - 1:200

Plotted From - trc12808



STATE OF SOUTH DAKOTA  
DEPARTMENT OF TRANSPORTATION

PLANS FOR PROPOSED  
**HIGHWAYS US 14A, SD 34,  
US 16, I-90, & SD 44**  
**PROJECTS**  
**014A-451, 034-451, 016 W-452,  
090 E-452, & 044-452**  
**PENNINGTON, LAWRENCE,  
& MEADE COUNTIES**  
**ASPHALT CONCRETE PAVEMENT REPAIR**  
**PCNs i4ua, i4uc, i4ud, i4ue, & i4uh**



STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	014A-451, etc.	1	19

Plotting Date: 07/17/2017

INDEX OF SHEETS

Sheet	1:	Title Sheet
Sheets	2-7:	Estimate of Quantities & Plan Notes
Sheets	9-11:	Special Details
Sheets	12-19:	Standard Plates

- ① US 14A  
MRM 49.570 to MRM 51.498,  
014A-451 PCN i4ua
- ② SD 34  
MRM 35.872 to MRM 36.360,  
034-451, PCN i4uc
- ③ US 16 W  
MRM 63.644 to MRM 64.127,  
016 W-452, PCN i4ud
- ④ I-90  
MRM 48.000,  
090 E-452, PCN i4ue
- ⑤ SD 44  
89.585 to MRM 103.955  
044-452, PCN i4uh



Storm Water Permit  
No Permit Required

ESTIMATE OF QUANTITIES

014A-451, PCN i4ua, US 14A

BID ITEM NUMBER	ITEM	QUANTITY	UNIT
009E0010	Mobilization	Lump Sum	LS
120E0100	Unclassified Excavation, Digouts	450	CuYd
260E1010	Base Course	600.0	Ton
320E1200	Asphalt Concrete Composite	365.1	Ton
332E0010	Cold Milling Asphalt Concrete	578	SqYd
633E1200	Waterborne Pavement Marking Paint with High Grade Polymer, White	3	Gal
633E1205	Waterborne Pavement Marking Paint with High Grade Polymer, Yellow	2	Gal
634E0010	Flagging	40.0	Hour
634E0020	Pilot Car	20.0	Hour
634E0110	Traffic Control Signs	201.0	SqFt
634E0120	Traffic Control, Miscellaneous	Lump Sum	LS
634E0640	Temporary Pavement Marking	200	Ft

034-451, PCN i4uc, SD 34

BID ITEM NUMBER	ITEM	QUANTITY	UNIT
009E0010	Mobilization	Lump Sum	LS
110E0300	Remove Concrete Curb and/or Gutter	22	Ft
120E0010	Unclassified Excavation	2	CuYd
120E0100	Unclassified Excavation, Digouts	2	CuYd
260E1010	Base Course	7.4	Ton
320E1200	Asphalt Concrete Composite	187.0	Ton
332E0010	Cold Milling Asphalt Concrete	1,619	SqYd
633E1200	Waterborne Pavement Marking Paint with High Grade Polymer, White	7	Gal
633E1205	Waterborne Pavement Marking Paint with High Grade Polymer, Yellow	7	Gal
634E0010	Flagging	30.0	Hour
634E0110	Traffic Control Signs	137.0	SqFt
634E0120	Traffic Control, Miscellaneous	Lump Sum	LS
634E0285	Type 3 Barricade, 8' Double Sided	2	Each
634E0420	Type C Advance Warning Arrow Board	2	Each
634E0640	Temporary Pavement Marking	617	Ft
650E0060	Type B66 Concrete Curb and Gutter	12	Ft
650E4660	Type P6 Concrete Gutter	10	Ft
734E0010	Erosion Control	Lump Sum	LS

016W-452, PCN i4ud, US 16 W

BID ITEM NUMBER	ITEM	QUANTITY	UNIT
009E0010	Mobilization	Lump Sum	LS
120E0100	Unclassified Excavation, Digouts	6	CuYd
260E1010	Base Course	8.0	Ton
320E1200	Asphalt Concrete Composite	35.9	Ton
332E0010	Cold Milling Asphalt Concrete	282	SqYd
633E1200	Waterborne Pavement Marking Paint with High Grade Polymer, White	1	Gal
634E0010	Flagging	40.0	Hour
634E0110	Traffic Control Signs	116.0	SqFt
634E0120	Traffic Control, Miscellaneous	Lump Sum	LS
634E0420	Type C Advance Warning Arrow Board	1	Each
634E0640	Temporary Pavement Marking	223	Ft

090 E-452, PCN i4ue, I-90 EB

BID ITEM NUMBER	ITEM	QUANTITY	UNIT
009E0010	Mobilization	Lump Sum	LS
320E1200	Asphalt Concrete Composite	239.0	Ton
332E0010	Cold Milling Asphalt Concrete	2,111	SqYd
633E1200	Waterborne Pavement Marking Paint with High Grade Polymer, White	5	Gal
633E1205	Waterborne Pavement Marking Paint with High Grade Polymer, Yellow	5	Gal
634E0010	Flagging	20.0	Hour
634E0110	Traffic Control Signs	488.0	SqFt
634E0120	Traffic Control, Miscellaneous	Lump Sum	LS
634E0285	Type 3 Barricade, 8' Double Sided	1	Each
634E0420	Type C Advance Warning Arrow Board	1	Each
634E0640	Temporary Pavement Marking	1,000	Ft
634E1215	Contractor Furnished Portable Changeable Message Sign	2	Each

044-452, PCN i4uh, SD 44

BID ITEM NUMBER	ITEM	QUANTITY	UNIT
009E0010	Mobilization	Lump Sum	LS
320E1200	Asphalt Concrete Composite	453.0	Ton
332E0010	Cold Milling Asphalt Concrete	4,000	SqYd
633E1200	Waterborne Pavement Marking Paint with High Grade Polymer, White	16	Gal
633E1205	Waterborne Pavement Marking Paint with High Grade Polymer, Yellow	16	Gal
634E0010	Flagging	80.0	Hour
634E0020	Pilot Car	40.0	Hour
634E0110	Traffic Control Signs	201.0	SqFt
634E0120	Traffic Control, Miscellaneous	Lump Sum	LS
634E0640	Temporary Pavement Marking	1,500	Ft

SPECIFICATIONS

Standard Specifications for Roads and Bridges, 2015 Edition and Required Provisions, Supplemental Specifications, and Special Provisions as included in the Proposal.

ENVIRONMENTAL COMMITMENTS

An Environmental Commitment is a measure that SDDOT commits to implement in order to avoid, minimize, and/or mitigate a real or potential environmental impact. Environmental commitments to various agencies and the public have been made to secure approval of this project. An agency mentioned below with permitting authority can influence a project if perceived environmental impacts have not been adequately addressed. Unless otherwise designated, the Contractor’s primary contact regarding matters associated with these commitments will be the Project Engineer. These environmental commitments are not subject to change without prior written approval from the SDDOT Environmental Office. The environmental commitments associated with this project are as follows:

COMMITMENT E: STORM WATER

Construction activities constitute less than 1 acre of disturbance.

Action Taken/Required:

At a minimum and regardless of project size, appropriate erosion and sediment control measures must be installed to control the discharge of pollutants from the construction site.

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	014A-451, etc.	2	19

COMMITMENT H: WASTE DISPOSAL SITE

The Contractor shall furnish a site(s) for the disposal of construction and/or demolition debris generated by this project.

Action Taken/Required:

Construction and/or demolition debris may not be disposed of within the Public ROW.

The waste disposal site(s) shall be managed and reclaimed in accordance with the following from the General Permit for Construction/Demolition Debris Disposal Under the South Dakota Waste Management Program issued by the Department of Environment and Natural Resources.

The waste disposal site(s) shall not be located in a wetland, within 200 feet of surface water, or in an area that adversely affects wildlife, recreation, aesthetic value of an area, or any threatened or endangered species, as approved by the Project Engineer.

If the waste disposal site(s) is located such that it is within view of any ROW, the following additional requirements shall apply:

1. Construction and/or demolition debris consisting of concrete, asphalt concrete, or other similar materials shall be buried in a trench completely separate from wood debris. The final cover over the construction and/or demolition debris shall consist of a minimum of 1 foot of soil capable of supporting vegetation. Waste disposal sites provided outside of the Public ROW shall be seeded in accordance with Natural Resources Conservation Service recommendations. The seeding recommendations may be obtained through the appropriate County NRCS Office. The Contractor shall control the access to waste disposal sites not within the Public ROW through the use of fences, gates, and placement of a sign or signs at the entrance to the site stating “No Dumping Allowed”.

2. Concrete and asphalt concrete debris may be stockpiled within view of the ROW for a period of time not to exceed the duration of the project. Prior to project completion, the waste shall be removed from view of the ROW or buried and the waste disposal site reclaimed as noted above.

The above requirements will not apply to waste disposal sites that are covered by an individual solid waste permit as specified in SDCL 34A-6-58, SDCL 34A-6-1.13, and ARSD 74:27:10:06.

Failure to comply with the requirements stated above may result in civil penalties in accordance with South Dakota Solid Waste Law, SDCL 34A-6-1.31.

All costs associated with furnishing waste disposal site(s), disposing of waste, maintaining control of access (fence, gates, and signs), and reclamation of the waste disposal site(s) shall be incidental to the various contract items.

COMMITMENT I: HISTORICAL PRESERVATION OFFICE CLEARANCES

The SDDOT has obtained concurrence with the State Historical Preservation Office (SHPO or THPO) for all work included within the project limits and all department designated sources and designated option material sources, stockpile sites, storage areas, and waste sites provided within the plans.

Action Taken/Required:

All earth disturbing activities not designated within the plans require review of cultural resources impacts. This work includes, but is not limited to: Contractor furnished material sources, material processing sites, stockpile sites, storage areas, plant sites, and waste areas.

The Contractor shall arrange and pay for a cultural resource survey and/or records search. The Contractor has the option to contact the state Archaeological Research Center (ARC) at 605-394-1936 or another qualified archaeologist, to obtain either a records search or a cultural resources survey. A record search might be sufficient for review; however, a cultural resources survey may need to be conducted by a qualified archaeologist.

The Contractor shall provide ARC with the following: a topographical map or aerial view on which the site is clearly outlined, site dimensions, project number, and PCN. If applicable, provide evidence that the site has been previously disturbed by farming, mining, or construction activities with a landowner statement that artifacts have not been found on the site.

The Contractor shall submit the records search or cultural resources survey report and if the location of the site is within the current geographical or historic boundaries of any South Dakota reservation to SDDOT Environmental Engineer, 700 East Broadway Avenue, Pierre, SD 57501-2586 (605-773-3180). SDDOT will submit the information to the appropriate SHPO/THPO. Allow **30 Days** from the date this information is submitted to the Environmental Engineer for SHPO/THPO review.

If evidence for cultural resources is uncovered during project construction activities, then such activities shall cease and the Project Engineer shall be immediately notified. The Project Engineer will contact the SDDOT Environmental Engineer in order to determine an appropriate course of action.

SHPO/THPO review does not relieve the Contractor of the responsibility for obtaining any additional permits and clearances for Contractor furnished material sources, material processing sites, stockpile sites, storage areas, plant sites, and waste areas that affect wetlands, threatened and endangered species, or waterways. The Contractor shall provide the required permits and clearances to the Project Engineer at the preconstruction meeting.

COMMITMENT K: RAPID CITY AREA AIR QUALITY CONTROL ZONE

Administrative Rule of South Dakota (ARSD) 74:36:18:03 states that "no state facility or state contractor may engage in any construction activity or continuous operation activity within the Rapid City air quality control zone which may cause fugitive emissions of particulate to be released into the ambient air without first obtaining a permit issued by the board or the secretary."

Construction activity is defined as any temporary activity at a state facility, which involves the removal or alteration of the natural or pre-existing cover of one acre or more of land. One acre of surface area is based on a cumulative area of disturbance to be completed for the entire project. Construction activity shall include, but not be limited to, stripping of topsoil, drilling, blasting, excavation, dredging, ditching, grading, street maintenance and repair, or earth moving. Construction activity is generally completed within one year. It also includes stockpiles, access roads, and disposal areas. An off-site disposal area of excess material will require an additional permit.

Action Taken/Required:

In order to be considered eligible for authorization to conduct a construction activity under the terms and conditions of this permit, the owner operator must submit a Notice of Intent (NOI) form. The form must be submitted to the address below at least seven business days prior to the anticipated date of beginning the construction activity.

South Dakota Department of Environment and Natural Resources Air Quality Program  
523 East Capitol, Joe Foss Building  
Pierre, SD 57501-3181  
Phone: 605-773-3151

The permit requires the Contractor to use reasonably available technology to control fugitive dust emissions. The Contractor is required to use control measures for track out, paved areas, unpaved roads, unpaved parking lots, disturbed areas, and for material handling and storage. The control measures that the Contractor is required to use are listed in the permit.

BASE COURSE

Base Course shall be placed and compacted according to Section 260.3 B. of the Specifications. At the time of compaction, the material placed on the shoulders shall have approximately 4 percent moisture uniformly blended throughout the depth of material. The percent moisture may be adjusted by the Engineer.

All remaining requirements of the Specifications for Base Course shall apply, except that in Section 260.3 A, the requirement for mixing the Base Course with water by a central plant and placed by an approved spreader shall be waived.

Water for Granular Material shall be applied at a rate of 20 gallons of water per cubic yard of Base Course and shall be incidental to the contract unit price per cubic yard for Base Course.

MAINTENANCE PATCHING

Maintenance Patching shall be in accordance with the requirements of Section 324 of the Standard Specifications, Asphalt Concrete Composite.

UNCLASSIFIED EXCAVATION DIGOUTS

Provided in the Estimate of Quantities is Unclassified Excavation-Digouts at the Maintenance Patching locations for the necessary removal of existing asphalt concrete and base material. The dimensions provided in these plans are subject to change in the field, at the discretion of the Engineer. Payment will be based on the actual quantities installed. Unclassified Excavation Digouts depth shall be 1 foot or as directed by the Engineer. Backfill shall be 6” of Base Course placed in 3” lifts and 6” of Asphalt Concrete Composite placed in 3” lifts.

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	014A-451, etc.	3	19

The existing asphalt concrete shall be sawed full depth with a vertical face to the removal limits established by the Engineer.

All costs associated with sawing, removal and disposal of existing asphalt and base material shall be incidental to the contract unit price per cubic yard Unclassified Excavation Digouts.

ASPHALT CONCRETE COMPOSITE

Asphalt Concrete Composite shall be furnished by the Contractor.

Mineral Aggregate for Asphalt Concrete Composite shall conform to the requirements of the Standard Specifications for Class E, Type 1 Asphalt Concrete Specifications.

SS-1h or CSS-1h Emulsified Asphalt for Tack shall be applied at the rate of 0.09 gallons per square yard.

The asphalt binder used in the mixture shall be PG 58-28, PG 64-22 or PG 64-28 Asphalt Binder.

A Flush Seal will not be required on the asphalt concrete patching.

Locations and quantities of asphalt repair are subject to change. The exact locations will be determined in the field by the Engineer. The Engineer reserves the right to adjust quantities and/or add locations at no additional cost to the state.

SURFACING THICKNESS DIMENSIONS

Plans tonnage will be applied even though the thickness may vary from that shown in the plans. At those locations where material must be placed to achieve a required elevation for smoothness, plans tonnage may be varied to achieve the required elevation.

COLD MILLING

The removed material from the Cold Milling operation shall be properly disposed of by the Contractor.

The Contractor shall provide temporary asphalt ramps with a 50:1 transition at all locations where traffic is transitioning from a milled to a paved surface and vice versa. All costs associated with this work shall be incidental to the various bid items on the project.

CURB OPENING

The curb and gutter quantities are provided in these plans to all water to drain off the pavement and soak into the grass boulevard along SD34. Currently water sits on the pavement on top of the joint between surfacing and curb and gutter.





TRAFFIC CONTROL – GENERAL NOTES

Requests to deviate from the sequence of operations shall be submitted in writing to the Engineer for review. Approval of an alternate sequence of operations will only be allowed when the proposed changes meet with the Department’s intent for traffic control and sequencing of the work. An alternate sequence shall be submitted for review a minimum of one week prior to potential implementation.

Unless otherwise stated in these plans, no work will be allowed during hours of darkness.

Existing guide, route, informational logo, regulatory, warning signs and delineation shall be temporarily reset and maintained during construction as directed by the Engineer. Removing, relocating, salvaging and resetting of the above items shall be the responsibility of the Contractor.

Non-applicable traffic control devices shall be completely covered or removed during periods of inactivity. Periods of inactivity shall be defined as no work taking place for a period of more than 2 calendar days.

All regulatory signs shall have a minimum mounting height of 5’ in rural locations, even when mounted on portable supports.

All materials and equipment shall be stored a minimum distance of 30’ from the traveled way during nonworking hours.

The Contractor shall provide installation details at the preconstruction meeting for all breakaway sign support assemblies.

All haul trucks shall be equipped with a second flashing amber light that is visible from the backside of the haul truck. The costs for the flashing amber lights shall be incidental to the various related contract bid items.

All construction operations shall be conducted in the general direction of traffic movement.

If there is a discrepancy between the traffic control plans, standard plates, and the MUTCD – whichever is more stringent shall be used, as determined by the Engineer.

Temporary Flexible Vertical Markers (Tabs) shall be used for lane closure tapers or lane shift tapers and shall be installed at 5’ spacing. Tabs used for tapers and shifts will not be measured for payment. All costs associated to furnish, install, maintain (including replacement as required by the Engineer at no added cost to the Department), and remove all markers will be incidental to the contract lump sum price for Traffic Control, Miscellaneous,

TRAFFIC CONTROL

i4ua

Work on bridge ends at MRM 49.57 shall be conducted using flagger and pilot car. See Special Provision for Contract Time regarding work restrictions on the bridge ends.

The Contractor shall conduct all work at MRM 51.498 off the traveled lanes.

i4uc

Utilize Standard Plate 634.47, 634.48, and 634.60 to complete work. See Special Provision for Contract Time regarding work restrictions.

i4ud

Utilize Standard Plate 634.64 and Ramp Entrance and Exit Signing Detail #1 to complete work at MRM’s 63.64 and 64.1. The southbound (westbound) Hwy 16 to westbound Catron Boulevard Right Turn Lane may be closed to complete work at MRM 64.1. See Special Provision for Contract Time regarding work restrictions.

i4ue

Utilize Standard Plate 634.63 to complete overlay of the Exit 48 On Ramp. The Exit 48 On-Ramp may be closed during milling and resurfacing operations. See Special Provision for Contract Time for work restrictions.

i4uh

Work shall be conducted using flagger and pilot car.

CONTRACTOR FURNISHED PORTABLE CHANGEABLE MESSAGE SIGN

Contractor Furnished Portable Changeable Message Signs shall be utilized on this project to advise the traveling public of project conditions. The Contractor shall furnish, position, and maintain the message signs at locations as directed by the Engineer.

Each message sign shall be in a new or nearly new condition and consist of a message board, power supply, and a message control system, all mounted on a heavy duty trailer. The message signs shall remain the property of the Contractor upon completion of the project.

Addco Manufacturing, Precision Solar Controls Inc., Winkomatic Signal Company, and American Signal Company are manufacturers of acceptable Solar Powered Portable Changeable Message Signs.

The overall dimensions of the message board shall be a minimum of 108” wide x 72” high. The message board shall be enclosed in a rigidly framed, weather tight housing.

The message board shall contain a minimum of three message lines. Each message line shall be capable of displaying a minimum of 8 characters. Each character shall be approximately 18” high and shall be formed by 35 dots in a 5 x 7 matrix. The message boards shall be capable of changing the entire message content in not more than 100 milliseconds. No more than 2 displays shall be used within any message cycle.

All costs associated with obtaining, positioning, re-positioning, programming, re-programming, maintaining, and removing the message signs shall be incidental to the contract unit price per each for Contractor Furnished Portable Changeable Message Sign.

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	014A-451, etc.	5	19

ITEMIZED LIST OF TRAFFIC CONTROL DEVICES

014A-451, PCN i4ua, US 14A

		CONVENTIONAL ROAD			
SIGN CODE	SIGN DESCRIPTION	NUMBER	SIGN SIZE	SQFT PER SIGN	SQFT
W3-4	BE PREPARED TO STOP	2	48" x 48"	16.0	32.0
W8-1	BUMP	2	48" x 48"	16.0	32.0
W8-15	GROOVED PAVEMENT	2	48" x 48"	16.0	32.0
W20-1	ROAD WORK AHEAD	2	48" x 48"	16.0	32.0
W20-4	ONE LANE ROAD AHEAD	2	48" x 48"	16.0	32.0
W20-7	FLAGGER (symbol)	2	48" x 48"	16.0	32.0
G20-2	END ROAD WORK	2	36" x 18"	4.5	9.0
		CONVENTIONAL ROAD TRAFFIC CONTROL SIGNS SQFT 201.0			

034-451, PCN i4uc, SD 34

		CONVENTIONAL ROAD			
SIGN CODE	SIGN DESCRIPTION	NUMBER	SIGN SIZE	SQFT PER SIGN	SQFT
W4-2	LEFT or RIGHT LANE ENDS (symbol)	3	48" x 48"	16.0	48.0
W20-1	ROAD WORK AHEAD	2	48" x 48"	16.0	32.0
W20-5	LEFT or RIGHT LANE CLOSED AHEAD	3	48" x 48"	16.0	48.0
G20-2	END ROAD WORK	2	36" x 18"	4.5	9.0
		CONVENTIONAL ROAD TRAFFIC CONTROL SIGNS SQFT 137.0			

TYPE 3 BARRICADES

ITEM DESCRIPTION	QUANTITY
Type 3 Barricade, 8' Double Sided	2 Each

ARROW BOARDS

ITEM DESCRIPTION	QUANTITY
Type C Advance Warning Arrow Board	2 Each

016E-452, PCN i4ud, US 16

		EXPRESSWAY / INTERSTATE			
SIGN CODE	SIGN DESCRIPTION	NUMBER	SIGN SIZE	SQFT PER SIGN	SQFT
R2-6aP	FINES DOUBLE (plaque)	2	36" x 24"	6.0	12.0
W4-2	LEFT or RIGHT LANE ENDS (symbol)	2	48" x 48"	16.0	32.0
W20-1	ROAD WORK AHEAD	2	48" x 48"	16.0	32.0
W20-5	LEFT or RIGHT LANE CLOSED AHEAD	2	48" x 48"	16.0	32.0
G20-2	END ROAD WORK	1	48" x 24"	8.0	8.0
		EXPRESSWAY / INTERSTATE TRAFFIC CONTROL SIGNS SQFT 116.0			

ARROW BOARDS

ITEM DESCRIPTION	QUANTITY
Type C Advance Warning Arrow Board	1 Each

ITEMIZED LIST OF TRAFFIC CONTROL DEVICES (CONTINUED)

090 E-452, PCN i4ue, I-90 EB

SIGN CODE	SIGN DESCRIPTION	EXPRESSWAY / INTERSTATE			
		NUMBER	SIGN SIZE	SQFT PER SIGN	SQFT
R1-2aP	TO ONCOMING TRAFFIC (plaque)	1	48" x 36"	12.0	12.0
R2-1	SPEED LIMIT	6	36" x 48"	12.0	72.0
R2-6aP	FINES DOUBLE (plaque)	2	36" x 24"	6.0	12.0
W3-2	YIELD AHEAD (symbol)	1	48" x 48"	16.0	16.0
W3-4	BE PREPARED TO STOP	1	48" x 48"	16.0	16.0
W3-5	SPEED REDUCTION AHEAD ( MPH)	4	48" x 48"	16.0	64.0
W4-1	MERGE (symbol)	1	48" x 48"	16.0	16.0
W4-2	LEFT or RIGHT LANE ENDS (symbol)	2	48" x 48"	16.0	32.0
W8-1	BUMP	2	48" x 48"	16.0	32.0
W8-7	LOOSE GRAVEL	2	48" x 48"	16.0	32.0
W8-15	GROOVED PAVEMENT	2	48" x 48"	16.0	32.0
W20-1	ROAD WORK AHEAD	4	48" x 48"	16.0	64.0
W20-5	LEFT or RIGHT LANE CLOSED AHEAD	2	48" x 48"	16.0	32.0
W20-7	FLAGGER (symbol)	2	48" x 48"	16.0	32.0
G20-2	END ROAD WORK	3	48" x 24"	8.0	24.0
		EXPRESSWAY / INTERSTATE TRAFFIC CONTROL SIGNS SQFT 488.0			

TYPE 3 BARRICADES

ITEM DESCRIPTION	QUANTITY
Type 3 Barricade, 8' Double Sided	1 Each

ARROW BOARDS

ITEM DESCRIPTION	QUANTITY
Type C Advance Warning Arrow Board	1 Each

044-452, PCN i4uh, SD 44

SIGN CODE	SIGN DESCRIPTION	CONVENTIONAL ROAD			
		NUMBER	SIGN SIZE	SQFT PER SIGN	SQFT
W3-4	BE PREPARED TO STOP	2	48" x 48"	16.0	32.0
W8-1	BUMP	2	48" x 48"	16.0	32.0
W8-15	GROOVED PAVEMENT	2	48" x 48"	16.0	32.0
W20-1	ROAD WORK AHEAD	2	48" x 48"	16.0	32.0
W20-4	ONE LANE ROAD AHEAD	2	48" x 48"	16.0	32.0
W20-7	FLAGGER (symbol)	2	48" x 48"	16.0	32.0
G20-2	END ROAD WORK	2	36" x 18"	4.5	9.0
		CONVENTIONAL ROAD TRAFFIC CONTROL SIGNS SQFT 201.0			

PERMANENT PAVEMENT MARKINGS

All surfaces have existing markings and the Contractor is encouraged to review prior to bidding.

The pavement marking paint and glass beads shall be furnished and applied by the Contractor. All materials shall be applied as per manufacturer's recommendations.

WATERBORNE PAVEMENT MARKING PAINT WITH HIGH GRADE POLYMER

All materials shall be applied as per manufacturer's recommendations.

This material shall consist of a durable high build, low VOC, fast drying, waterborne traffic paint with a 100% acrylic polymer (Dow DT-400 or Dow HD-21A or equivalent). The Contractor shall provide certification that the material is one of the following products or an equivalent as approved by the Operations Traffic Engineer:

Diamond Vogel's Waterborne High Build Polymer Marking Paint  
Ennis-Flint's High Build Polymer Marking Paint

No further testing of this material will be required. Reflective media consisting of glass beads as well as bonded core reflective elements shall be adhered to the paint.

The bonded core reflective elements shall contain either clear or yellow tinted microcrystalline ceramic beads bonded to the outer surface. All microcrystalline ceramic beads bonded to reflective elements shall have a minimum index of refraction of 1.8 when tested using the liquid oil immersion method.

RATES OF MATERIALS FOR WATERBORNE PAVEMENT MARKING PAINT WITH HIGH GRADE POLYMER

Solid 4" line = 27.8 Gals/Mile  
Glass Beads = 5.3 Lbs/Gal.  
Composite Reflective Elements = 2.1 Lbs/Gal.

All cost for materials, labor and equipment necessary to furnish and install the pavement markings shall be incidental to the contract unit price per gallon for "Waterborne Pavement Marking Paint with High Grade Polymer, White or Yellow".

EROSION CONTROL

All costs for the erosion control work for furnishing, placing, and maintaining erosion control including equipment, labor, seeding, fertilizing, and mulching shall be incidental to the contract lump sum price for "Erosion Control".

The limits of erosion control work will be determined by the Engineer during construction.

MYCORRHIZAL INOCULUM

Mycorrhizal inoculum shall consist of mycorrhizal fungi spores and mycorrhizal fungi-infected root fragments in a solid carrier. The carrier may include organic materials, calcinated clay, or other materials consistent with application and good plant growth. The supplier shall provide certification of the fungal species claimed and the live propagule count. The inoculum shall include the following fungal species:

Glomus intraradices 25%  
Glomus aggregatu 25%  
Glomus mosseae 25%  
Glomus etunicatum 25%

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	014A-451, etc.	6	19

All seed shall be inoculated by the seed supplier with a minimum of 100,000 live propagules of mycorrhizal fungi per acre. All costs of inoculating the seed shall be incidental to the contract unit price per lump sum for Erosion Control.

The mycorrhizal inoculum shall be as shown below or an approved equal:

Product

MycoApply

Manufacturer

Mycorrhizal Applications, Inc.  
Grants Pass, OR  
Phone: 1-866-476-7800  
[www.mycorrhizae.com](http://www.mycorrhizae.com)

FERTILIZING

The Contractor shall apply an all-natural slow release fertilizer prior to seeding or placing sod. The all-natural fertilizer shall have a minimum guaranteed analysis of 4-6-4 and be USDA Certified BioBased. It should provide a minimum of 4% (N) nitrogen with a minimum water insoluble nitrogen (WIN) fraction of 3.2%, a minimum of 6% (P2O5) available phosphate, a minimum of 4% (K2O) soluble potash, and a maximum carbon to nitrogen ratio (C:N ratio) of 5:1. The all-natural fertilizer shall be free of weed-seed and pathogens accomplished through thermophilic composting, and not mechanical or chemical sterilization, to assure presence of beneficial soil microbiology. The fertilizer shall have a near neutral pH, a low salt index, a low biological oxygen demand, contain organic humic and fulvic acids, and have high aerobic organism counts. The fertilizer shall also be stable, free of bad odors, and be unattractive as a food source for animals. It should also be in a granular form that is easily spread.

The fertilizer shall be applied at a rate of 1,500 pounds per acre in accordance with the manufacturer's recommended method of application.

The all-natural slow release fertilizer shall be as shown below or an approved equal:

Product

Sustane

Manufacturer

Sustane Corporate Headquarters  
Cannon Falls, Minnesota  
Phone: 1-800-352-9245  
[www.sustane.com](http://www.sustane.com)

**PERMANENT SEEDING**

The areas to be seeded consist of disturbed areas within the project limits.

Type F Permanent Seed Mixture shall consist of the following:

Grass Species	Variety	Pure Live Seed (PLS) (Pounds/Acre)
Western Wheatgrass	Arriba, Flintlock, Rodan, Rosana	7
Green Needlegrass	Lodorm	4
Sideoats Grama	Butte, Killdeer, Pierre, Trailway	3
Blue Grama	Bad River, Willis	2
Oats or Spring Wheat: April through May; Winter Wheat: August through November		10
Total:		26

**FIBER MULCHING**

Fiber mulch shall be applied in a separate operation following permanent seeding.

The Contractor shall allow the fiber mulch to cure a minimum of 18 hours prior to watering or any storm event to ensure proper cohesion between the soil and fiber particles.

The fiber mulch provided shall be from the approved product list. The approved product list for fiber mulch may be viewed at the following internet site:

<http://sddot.com/business/certification/products/Default.aspx>

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	014A-451, etc.	7	19


# SD 44 ASPHALT PATCHES

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	014A-451, etc.	8	19


Plotting Date: 07/17/2017

\* Lengths used for estimating purposes can be found in the Table of Material Quantities. These distances shall be adjusted in the field based upon in-place conditions between high points.

## LONGITUDINAL SECTION ALONG CENTERLINE (FULL ROADWAY WIDTH)



# Adjust milling depth as needed to achieve full smoothness between high points. A fixed stringline should be used to establish the elevation.



 Cold Milling Asphalt Concrete

 Asphalt Concrete Composite

Plot Scale - 1/4"

trc12808

Plotted From -

File - ...SD44 Milling.dgn




# TRAFFIC CONTROL

## RAMP ENTRANCE AND EXIT SIGNING DETAILS

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	014A-451, etc.	9	19

Plotting Date: 07/17/2017



 -- THE WARNING LIGHT SHALL BE A SHIELDED TYPE B, IN ACCORDANCE WITH THE MUTCD

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	014A-451, etc.	10	19

Plotting Date: 07/17/2017

Vehicle-mounted signs shall be mounted in a manner such that they are not obscured by equipment or supplies.

Sign legends on vehicle-mounted signs shall be covered or turned from view when work is not in progress.


Shadow and Work vehicles shall display high-intensity rotating, flashing, oscillating, or strobe lights, flags, signs, or arrow panels.

Vehicle hazard warning signals shall not be used instead of the vehicle's high-intensity rotating, flashing, oscillating, or strobe lights

Arrow panel shall be used in the caution mode.


Flashing

Arrow panels shall, as a minimum, be Type B, with a size of 60" x 30".



GUIDES FOR TRAFFIC CONTROL DEVICES  
MOBILE OPERATIONS ON 2-LANE ROAD

MOBILE: Intermittent & Continuous Moving



GUIDES FOR TRAFFIC CONTROL DEVICES  
MOBILE OPERATIONS ON 4-LANE DIVIDED


MOBILE: Intermittent & Continuous Moving

# TYPICAL PAVEMENT MARKING LAYOUT


STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	014A-451, etc.	11	19

Plotting Date: 07/17/2017

Plot Scale - 1:20



(B) End of Zone Marker





Centerline Detail




NOTE: A TWO "GUN" SYSTEM SHALL BE USED TO OBTAIN THIS PATTERN.

WHEN A SINGLE SKIP LINE EXISTS, THE SKIP SHALL BE PLACED TO THE SOUTH OR EAST OF THE CENTERLINE JOINT.

Centerline Detail



\* 8" WHITE - As per locations in plans with shoulders less than 2' width.



Plotted From - trc12808

File - ...PavementMarkingDetails.dgn

Posted Speed Prior to Work (M.P.H.)	Spacing of Advance Warning Signs (Feet) (A)	Spacing of Channelizing Devices (Feet) (G)
0 - 30	200	25
35 - 40	350	25
45	500	25
50	500	50
55	750	50
60 - 65	1000	50

- Flagger
- Channelizing Device

For low-volume traffic situations with short work zones on straight roadways where the flagger is visible to road users approaching from both directions, a single flagger may be used.

The ROAD WORK AHEAD and the END ROAD WORK signs may be omitted for short duration operations (1 hour or less).

For tack and/or flush seal operations, when flaggers are not being used, the FRESH OIL sign (W21-2) shall be displayed in advance of the liquid asphalt areas.

Flashing warning lights and/or flags may be used to call attention to the advance warning signs.

The channelizing devices shall be drums or 42" cones.


Channelizing devices are not required along the centerline adjacent to work area when pilot cars are utilized for escorting traffic through the work area.

Channelizing devices and flaggers shall be used at intersecting roads to control intersecting road traffic as required.

The buffer space should be extended so that the two-way traffic taper is placed before a horizontal or vertical curve to provide adequate sight distance for the flagger and queue of stopped vehicles.


The length of A may be adjusted to fit field conditions.

Warning sign sequence in opposite direction same as below.



June 3, 2016

Published Date: 3rd Qtr. 2017	S D D O T	GUIDES FOR TRAFFIC CONTROL DEVICES	PLATE NUMBER
		LANE CLOSURE WITH FLAGGER PROVIDED	634.23
			Sheet 1 of 1



September 6, 2015

Published Date: 3rd Qtr. 2017	S D D O T	GUIDES FOR TRAFFIC CONTROL DEVICES	PLATE NUMBER
		TEMPORARY ROAD WORK	634.30
			Sheet 1 of 1

Posted Speed Prior to Work (M.P.H.)	Spacing of Advance Warning Signs (Feet) (A)	Taper Length (Feet) (L)	Spacing of Channelizing Devices (Feet) (G)
0 - 30	200	180	25
35 - 40	350	320	25
45	500	600	25
50	500	600	50 *
55	750	660	50 *
60 - 65	1000	780	50 *

\* Spacing is 40' for 42" cones.

⊙ Reflectorized Drum

■ Channelizing Device


④ 4" White Temporary Pavement Marking

The channelizing devices shall be 42" cones or drums.

42" cones may be used in place of the drums shown in the taper if setup will not be used during night time hours.


Temporary pavement markings shall be used if traffic control must remain overnight.

The length of A and L may be adjusted to fit field conditions.



June 3, 2016


Published Date: 3rd Qtr. 2017	S D D O T	GUIDES FOR TRAFFIC CONTROL DEVICES 4-LANE UNDIVIDED, RIGHT LANE CLOSED	PLATE NUMBER 634.47
		Sheet 1 of 1	




June 3, 2016

Published Date: 3rd Qtr. 2017	S D D O T	GUIDES FOR TRAFFIC CONTROL DEVICES 4-LANE UNDIVIDED, LEFT LANE CLOSED	PLATE NUMBER 634.48
		Sheet 1 of 1	






Published Date: 3rd Qtr. 2017	S D D O T	GUIDES FOR TRAFFIC CONTROL DEVICES 5-LANE, OUTSIDE LANE CLOSED	PLATE NUMBER 634.60
		Sheet 1 of 1	



Published Date: 3rd Qtr. 2017	S D D O T	WORK ZONE SPEED REDUCTION FOR INTERSTATE AND HIGH SPEED MULTI-LANE HIGHWAYS	PLATE NUMBER 634.63
		Sheet 1 of 2	







Plot Scale - 1:200

Plotted From - ttrc12808

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	014A-451, etc.	16	19


Plotting Date: 07/17/2017





STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	014A-451, etc.	18	19

Plotting Date: 07/17/2017






\* Height of Curb

LONGITUDINAL SECTION OF CONCRETE CURB TAPER

September 14, 2005

Published Date: 3rd Qtr. 2017	S D D O T	CONCRETE CURB TAPER	PLATE NUMBER 650.35
			Sheet 1 of 1



\* The silicone sealant shall be placed such that it completely seals the joint and is bonded to the sides of the clean joint as approved by the Engineer.

September 6, 2013

Published Date: 3rd Qtr. 2017	S D D O T	JOINTS IN CONCRETE CURB AND GUTTER	PLATE NUMBER 650.90
			Sheet 1 of 2




1:200  
Plot Scale -

trc12808  
- Plotted From -

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	014A-451, etc.	19	19

Plotting Date: 07/17/2017



\* The silicone sealant shall be placed such that it completely seals the joint and is bonded to the sides of the clean joint as approved by the Engineer.

GENERAL NOTES:

For illustrative reason, only the type B curb and gutter is shown.

\*\* A 1/2" preformed expansion joint filler shall be placed transversely in the curb and gutter at the following locations:

1. At each junction between the radius return of curb and gutter and curb and gutter which is parallel to the project centerline.
2. At each junction between new curb and gutter and existing curb and gutter.

Transverse contraction joints shall be constructed at 10' intervals in the concrete curb and gutter except when the concrete curb and gutter is constructed adjacent to mainline PCC pavement. When concrete curb and gutter is constructed adjacent to mainline PCC pavement, a transverse contraction joint shall be constructed in the concrete curb and gutter at each mainline PCC pavement transverse contraction joint location.

When concrete curb and gutter is not placed monolithically with the mainline PCC pavement or when the adjacent mainline surfacing is not PCC concrete, the transverse contraction joints in the concrete curb and gutter shall be 1 1/2 inches deep if formed in the fresh concrete using a suitable grooving tool. If a saw is used to cut the contraction joints, then the depth of the joint shall be at least 1/4 the thickness of the concrete and the joint shall be sealed in accordance with the details shown above.

September 6, 2013

Published Date: 3rd Qtr. 2017	S D D O T	JOINTS IN CONCRETE CURB AND GUTTER	PLATE NUMBER 650.90
			Sheet 2 of 2

File - ...IRC Asphalt Patching1650\_3.dgn