


Plot Scale - 1:200

Plotted From - irrc11626



STATE OF SOUTH DAKOTA
DEPARTMENT OF TRANSPORTATION
PLANS FOR PROPOSED
PROJECT 190-452
INTERSTATE 190
PENNINGTON COUNTY
SIDEWALK
(CENTRAL HIGH SCHOOL TO RAPID CREEK BRIDGE)
PCN i4wv

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	190-452	1	26

Plotting Date: 08/23/2017


INDEX OF SHEETS

1	General Layout with Index
2-4	Estimate With General Notes & Tables
5	Typical Grading Section
6	Horizontal Alignment & Control Data
7	Legend
8-9	Plan and Profile Sheets
10	Sidewalk Removal Layout
11-12	Standard Plates
13-26	Cross Sections

DESIGN DESIGNATION

ADT (2016)	8670
ADT (2036)	11193
DHV	1153
D	50%
T DHV	1.0%
T ADT	2.1%
V	50 mph

STORM WATER PERMIT
(None Required)



Gross Length	826 Feet	0.1564 Miles
Length of Exceptions	Feet	Miles
Net Length	826 Feet	0.1564 Miles

File - ...title.dgn

ESTIMATE OF QUANTITIES

BID ITEM NUMBER	ITEM	QUANTITY	UNIT
009E0010	Mobilization	Lump Sum	LS
110E1140	Remove Concrete Sidewalk	99.1	SqYd
120E0600	Contractor Furnished Borrow Excavation	131	CuYd
230E0010	Placing Topsoil	43	CuYd
634E0110	Traffic Control Signs	4.0	SqFt
634E0120	Traffic Control, Miscellaneous	Lump Sum	LS
634E2000	Longitudinal Pedestrian Barricade	12	Ft
651E0050	5" Concrete Sidewalk	4,140	SqFt
734E0010	Erosion Control	Lump Sum	LS

SPECIFICATIONS

Standard Specifications for Roads and Bridges, 2015 Edition and Required Provisions, Supplemental Specifications, and Special Provisions as included in the Proposal.

ENVIRONMENTAL COMMITMENTS

An Environmental Commitment is a measure that SDDOT commits to implement in order to avoid, minimize, and/or mitigate a real or potential environmental impact. Environmental commitments to various agencies and the public have been made to secure approval of this project. An agency mentioned below with permitting authority can influence a project if perceived environmental impacts have not been adequately addressed. Unless otherwise designated, the Contractor's primary contact regarding matters associated with these commitments will be the Project Engineer. These environmental commitments are not subject to change without prior written approval from the SDDOT Environmental Office. The environmental commitments associated with this project are as follows:

COMMITMENT E: STORM WATER

Construction activities constitute less than 1 acre of disturbance.

Action Taken/Required:

At a minimum and regardless of project size, appropriate erosion and sediment control measures must be installed to control the discharge of pollutants from the construction site.

COMMITMENT H: WASTE DISPOSAL SITE

The Contractor shall furnish a site(s) for the disposal of construction and/or demolition debris generated by this project.

Action Taken/Required:

Construction and/or demolition debris may not be disposed of within the Public ROW.

The waste disposal site(s) shall be managed and reclaimed in accordance with the following from the General Permit for Construction/Demolition Debris Disposal Under the South Dakota Waste Management Program issued by the Department of Environment and Natural Resources.

The waste disposal site(s) shall not be located in a wetland, within 200 feet of surface water, or in an area that adversely affects wildlife, recreation, aesthetic value of an area, or any threatened or endangered species, as approved by the Project Engineer.

If the waste disposal site(s) is located such that it is within view of any ROW, the following additional requirements shall apply:

- Construction and/or demolition debris consisting of concrete, asphalt concrete, or other similar materials shall be buried in a trench completely separate from wood debris. The final cover over the construction and/or demolition debris shall consist of a minimum of 1 foot of soil capable of supporting vegetation. Waste disposal sites provided outside of the Public ROW shall be seeded in accordance with Natural Resources Conservation Service recommendations. The seeding recommendations may be obtained through the appropriate County NRCS Office. The Contractor shall control the access to waste disposal sites not within the Public ROW through the use of fences, gates, and placement of a sign or signs at the entrance to the site stating "No Dumping Allowed".
- Concrete and asphalt concrete debris may be stockpiled within view of the ROW for a period of time not to exceed the duration of the project. Prior to project completion, the waste shall be removed from view of the ROW or buried and the waste disposal site reclaimed as noted above.

The above requirements will not apply to waste disposal sites that are covered by an individual solid waste permit as specified in SDCL 34A-6-58, SDCL 34A-6-1.13, and ARSD 74:27:10:06.

Failure to comply with the requirements stated above may result in civil penalties in accordance with South Dakota Solid Waste Law, SDCL 34A-6-1.31.

All costs associated with furnishing waste disposal site(s), disposing of waste, maintaining control of access (fence, gates, and signs), and reclamation of the waste disposal site(s) shall be incidental to the various contract items.

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	190-452	2	26

COMMITMENT I: HISTORICAL PRESERVATION OFFICE CLEARANCES

The SDDOT has obtained concurrence with the State Historical Preservation Office (SHPO or THPO) for all work included within the project limits and all department designated sources and designated option material sources, stockpile sites, storage areas, and waste sites provided within the plans.

Action Taken/Required:

All earth disturbing activities not designated within the plans require review of cultural resources impacts. This work includes, but is not limited to: Contractor furnished material sources, material processing sites, stockpile sites, storage areas, plant sites, and waste areas.

The Contractor shall arrange and pay for a cultural resource survey and/or records search. The Contractor has the option to contact the state Archaeological Research Center (ARC) at 605-394-1936 or another qualified archaeologist, to obtain either a records search or a cultural resources survey. A record search might be sufficient for review; however, a cultural resources survey may need to be conducted by a qualified archaeologist.

The Contractor shall provide ARC with the following: a topographical map or aerial view on which the site is clearly outlined, site dimensions, project number, and PCN. If applicable, provide evidence that the site has been previously disturbed by farming, mining, or construction activities with a landowner statement that artifacts have not been found on the site.

The Contractor shall submit the records search or cultural resources survey report and if the location of the site is within the current geographical or historic boundaries of any South Dakota reservation to SDDOT Environmental Engineer, 700 East Broadway Avenue, Pierre, SD 57501-2586 (605-773-3180). SDDOT will submit the information to the appropriate SHPO/THPO. Allow **30 Days** from the date this information is submitted to the Environmental Engineer for SHPO/THPO review.

If evidence for cultural resources is uncovered during project construction activities, then such activities shall cease and the Project Engineer shall be immediately notified. The Project Engineer will contact the SDDOT Environmental Engineer in order to determine an appropriate course of action.

SHPO/THPO review does not relieve the Contractor of the responsibility for obtaining any additional permits and clearances for Contractor furnished material sources, material processing sites, stockpile sites, storage areas, plant sites, and waste areas that affect wetlands, threatened and endangered species, or waterways. The Contractor shall provide the required permits and clearances to the Project Engineer at the preconstruction meeting.

COORDINATION WITH INTERCHANGE REPLACEMENT PROJECT
IM 1902(61)0, PCN 1162

Roadway reconstruction near East North and Silver Streets on project IM 1902(61)0, PCN 1162, is currently in progress. The Contractor on this project shall coordinate with the Contractor on the reconstruction project so that work activities do no conflict. The Contractor for the project is Reede Construction, Inc. All costs associated with this coordination shall be incidental to the various bid items on the project.

UTILITIES

The Contractor shall contact the involved utility companies through South Dakota One Call (1-800-781-7474) prior to starting work. It shall be the responsibility of the Contractor to coordinate work with the utility owners to avoid damage to existing facilities.

Utilities are not planned to be affected on this project. If utilities are identified near the improvement area through the SD One Call Process as required by South Dakota Codified Law 49-7A and Administrative Rule Article 20:25, the Contractor shall contact the Project Engineer to determine modifications that will be necessary to avoid utility impacts.

CONTRACTOR FURNISHED BORROW

The Contractor shall provide a suitable site for Contractor furnished borrow excavation material. The Contractor is responsible for obtaining all required permits and clearances for the borrow site. The borrow material shall be approved by the Engineer. The plans quantity for “Contractor Furnished Borrow Excavation” as shown in the Estimate of Quantities will be the basis of payment for this item.

The Contractor shall place embankment material as necessary to construct the sidewalk berm. If sequencing allows, material from the removal of the existing sidewalk and temporary pedestrian path may be used as embankment material as approved by the Engineer. The removal of the temporary gravel pedestrian path shall be incidental to the contract bid item price for “Contractor Furnished Borrow Excavation”.

Restoration of the Contractor furnished borrow excavation site shall be the responsibility of the Contractor.

SIDEWALK JOINTS

The sidewalk shall be constructed according to the Specifications. However, the sidewalk contraction joints shall be saw cut in lieu of tooled joints.

TABLE OF QUANTITIES

Location	Contractor Furnished Borrow (CuYd)	Remove Concrete Sidewalk (SqYd)	5" Concrete Sidewalk (SqFt)	4" Topsoil (CuYd)
10+00 to 18+26	131	99.1	4140	43

TRAFFIC CONTROL – GENERAL NOTES

Unless otherwise stated in these plans, no work will be allowed during hours of darkness.

Non-applicable traffic control devices shall be completely covered or removed during periods of inactivity. Periods of inactivity shall be defined as no work taking place for a period of more than 48 hours.

All materials and equipment shall be stored a minimum distance of 30’ from the traveled way during nonworking hours.

The Contractor shall provide installation details at the preconstruction meeting for all breakaway sign support assemblies.

All haul trucks shall be equipped with a second flashing amber light that is visible from the backside of the haul truck. The costs for the flashing amber lights shall be incidental to the various related contract bid items.

All construction operations shall be conducted in the general direction of traffic movement.

If there is a discrepancy between the traffic control plans, standard plates, and the MUTCD – whichever is more stringent shall be used, as determined by the Engineer.

TABLE OF TRAFFIC CONTROL DEVICES

ITEMIZED LIST FOR TRAFFIC CONTROL SIGNS

SIGN CODE	SIGN DESCRIPTION	CONVENTIONAL ROAD			
		NUMBER	SIGN SIZE	SQFT PER SIGN	SQFT
R9-9	SIDEWALK CLOSED	2	24" x 12"	2.0	4.0
		CONVENTIONAL ROAD TRAFFIC CONTROL SIGNS SQFT			
		4.0			

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	190-452	3	26

LONGITUDINAL PEDESTRIAN BARRICADE

Longitudinal Pedestrian Barricades should not be used to provide positive protection for pedestrians.

Barricade rail supports may not project into pedestrian routes more than 4 inches from the face of the barricade. To prevent any tripping hazard to pedestrians, ballast shall be located behind or internal to the device.

When Longitudinal Pedestrian Barricades are combined in a series, the maximum gap between devices that do not interlock shall be one inch. Joints between devices that do interlock shall be closed and flush to prevent canes or small wheels from being trapped and to facilitate safe hand trailing. When used as a sidewalk closure mechanism, Longitudinal Pedestrian Barricade must run the entire width of the sidewalk. Longitudinal Pedestrian Barricade should provide a color contrasting pattern. Black should not be used to color any base on a device. The devices should comply with the general color and stripe pattern requirements of Section 6F.68 of the MUTCD.

Longitudinal Pedestrian Barricade shall have continuous bottom and top surfaces. A gap height or opening from the walkway surface up to a maximum of 2 inches is allowed for drainage purposes. The top edge of the bottom portion shall be a minimum of 8 inches above the walkway. The top of the top portion shall be between 34 and 38 inches above the walkway. The top surface shall be smooth to allow safe hand trailing. Both upper and lower surfaces shall share a common vertical plane.

All costs shall be incidental to the contract unit price per foot for LONGITUDINAL PEDESTRIAN BARRICADE.

SEQUENCE OF OPERATIONS

1. Install pedestrian traffic control.
2. Remove temporary pedestrian path and existing sidewalk.
3. Prepare and install sidewalk and embankment.
4. Place topsoil and seeding.
5. Remove pedestrian traffic control.

PLACING TOPSOIL

The thickness will be approximately 4 inches on the inslopes of the sidewalk and disturbed areas. The exact limits shall be determined by the Engineer during construction.

A topsoil windrow has been placed east of the proposed sidewalk location and contains approximately 43 cubic yards.

All costs to place the topsoil from the windrow shall be incidental to the contract unit price per cubic yard for “Placing Topsoil”.

EROSION CONTROL

The estimated area requiring erosion control is 3,556 square feet. All costs for the erosion control work for furnishing, placing, and maintain erosion control including equipment, labor, seeding, mycorrhizal inoculum, and fertilizing, shall be incidental to the contract lump sum price for “Erosion Control”.

The limits of erosion control work will be determined by the Engineer during construction.

Mycorrhizal Inoculum

Mycorrhizal inoculum shall consist of mycorrhizal fungi spores and mycorrhizal fungi-infected root fragments in a solid carrier. The carrier may include organic materials, calcinated clay, or other materials consistent with application and good plant growth. The supplier shall provide certification of the fungal species claimed and the live propagule count. The inoculum shall include the following fungal species:

<i>Glomus intraradices</i>	25%
<i>Glomus aggregatu</i>	25%
<i>Glomus mosseae</i>	25%
<i>Glomus etunicatum</i>	25%

All seed shall be inoculated with a minimum of 100,000 live propagules of mycorrhizal fungi per acre. All costs of inoculating the seed shall be incidental to the contract lump sum price for “Erosion Control”.

Fertilizing

The Contractor shall apply an all-natural slow release fertilizer prior to seeding or placing sod. The all-natural fertilizer shall have a minimum guaranteed analysis of 4-6-4 and be USDA Certified BioBased. It should provide a minimum of 4% (N) nitrogen with a minimum water insoluble nitrogen (WIN) fraction of 3.2%, a minimum of 6% (P2O5) available phosphate, a minimum of 4% (K2O) soluble potash, and a maximum carbon to nitrogen ratio (C:N ratio) of 5:1. The all-natural fertilizer shall be free of weed-seed and pathogens accomplished through thermophilic composting, and not mechanical or chemical sterilization, to assure presence of beneficial soil microbiology. The fertilizer shall have a near neutral pH, a low salt index, a low biological oxygen demand, contain organic humic and fulvic acids, and have high aerobic organism counts. The fertilizer shall also be stable, free of bad odors, and be unattractive as a food source for animals. It should also be in a granular form that is easily spread.

The application rate is 1500 pounds per acre.

The all-natural slow release fertilizer shall be from the list below or an approved equal:

<u>Product</u>	<u>Manufacturer</u>
Sustane	Sustane Corporate Headquarters Cannon Falls, Minnesota Phone: 1-800-352-9245 http://www.sustane.com/

Hydroseeding

The areas to be hydroseeded with Type F Permanent Seed Mixture shall comprise of all newly graded areas within the project limits.

Type F Permanent Seed Mixture shall consist of the following:

Grass Species	Variety	Pure Live Seed (PLS) (Pounds/Acre)
Western Wheatgrass	Flintlock, Rodan, Rosana	7
Green Needlegrass	Lodorm	4
Sideoats Grama	Butte, Killdeer, Pierre, Trailway	3
Blue Grama	Bad River, Willis	2
Oats or Spring Wheat: April through May; Winter Wheat: August through November		10
Total:		26

Hydroseeding shall be done by applying a mixture of water and seed at locations determined by the Engineer during construction.

The equipment used for hydroseeding shall be a mechanical agitation hydroseeding machine.


All costs for hydroseeding including equipment, labor, and materials which include the water and seed shall be incidental to the contract lump sum price for “Erosion Control”.

TYPICAL GRADING SECTION

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	190-452	5	26

Plotting Date: 08/07/2017

Sidewalk 10+00 to 18+26



Plot Scale - 1:133.333

Plotted From - trc11626

1:200
Plot Scale -
Plotted From -
Irrc11626

HORIZONTAL ALIGNMENT DATA

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	190-452	6	26

Plotting Date: 08/02/2017

SIDEWALK					
Type	Station			Northing	Easting
POB	10+00.00			652108.948	1206711.508
		TL= 26.86	N 46°19'10" E		
PC	10+26.86			652127.499	1206730.933
PI	10+55.48	R = 100.00	Delta = 31°56'46" L	652147.268	1206751.634
PT	10+82.62			652174.996	1206758.739
		TL= 66.85	N 14°22'24" E		
PC	11+49.47			652239.752	1206775.334
PI	11+55.43	R = 100.00	Delta = 6°49'47" R	652245.533	1206776.815
PT	11+61.39			652251.096	1206778.973
		TL= 173.65	N 21°12'11" E		
PC	13+35.03			652412.986	1206841.776
PI	13+40.08	R = 100.00	Delta = 5°46'32" L	652417.689	1206843.601
PT	13+45.11			652422.552	1206844.943
		TL= 311.18	N 15°25'39" E		
PI	16+56.29			652722.518	1206927.722
		TL= 170.06	N 14°30'01" E		
POE	18+26.36			652887.166	1206970.304

CONTROL DATA

Point #	Station / Offset (Alignment)	Description	Northing	Easting	Elevation
2035	122+58.91-2760.53' R (I-190 Mainline)	BNCHMK	654015.49	1206730.94	3259.31
CP01	212+19.20-1759.28' R (North Street)	REBAR	651651.13	1206634.85	3236.23
CP02	109+56.37-34.84' L (I-190 Mainline)	BAR WITH CAP	653044.73	1206803.78	3241.24
CP03	119+12.27-227.23' R (I-190 Mainline)	2 FT REBAR AND CAP 706 WEST BLVD NORTH	653963.94	1207174.56	3294.38
CP04	124+91.13-32.63' L (I-190 Mainline)	5 FT REBAR S BOUND OFF RAMP	654568.89	1206983.32	3287.71
CP05	138+44.64-104.91' R (I-190 Mainline)	5 FT REBAR AND CAP SW CORNER ANAMOSA AND WEST BLVD NORTH	655913.14	1207187.53	3310.79
CP06	208+22.47-1942.56' R (North Street)	COTTON GIN SPINDLE	651444.21	1205920.77	3240.85

The coordinates shown on this sheet are based on the South Dakota State Plane Coordinate System. South Zone (NAD 83/1996); Geoid 03; SF = 0.99978964601

Plot Scale - 1:200

Plotted From - Irrc11626

LEGEND

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	190-452	7	26

Plotting Date: 08/02/2017



Anchor		Hedge		Shrub Tree		State and National Line	
Antenna		Highway R.O.W. Marker		Sidewalk		County Line	
Approach		Interstate Close Gate		Sign Face		Section Line	
Assumed Corner		Iron Pin		Sign Post		Quarter Line	
Azimuth Marker		Irrigation Ditch		Slough Or Marsh		Sixteenth Line	
BBQ Grill/ Fireplace		Lake Edge		Spring		Property Line	
Bearing Tree		Lawn Sprinkler		Stream Gauge		Construction Line	
Bench Mark		Mailbox		Street Marker		R. O. W. Line	
Box Culvert		Manhole Electric		Subsurface Utility Exploration Test Hole		New R. O. W. Line	
Bridge		Manhole Gas		Telephone Fiber Optics		Cut and Fill Limits	
Brush		Manhole Misc		Telephone Junction Box		Control of Access	
Buildings		Manhole Sanitary Sewer		Telephone Pole		New Control of Access	
Bulk Tank		Manhole Storm Sewer		Television Cable Jct Box		Proposed ROW	
Cattle Guard		Manhole Telephone		Television Tower		(After Property Disposal)	
Cemetery		Manhole Water		Test Wells/Bore Holes			
Centerline		Merry-Go-Round		Traffic Signal			
Cistern		Microwave Radio Tower		Trash Barrel		Drainage Arrow	
Clothes Line		Misc. Line		Tree Belt			
Commercial Sign Double Face		Misc. Property Corner		Tree Coniferous			
Commercial Sign One Post		Misc. Post		Tree Deciduous		Remove Concrete Pavement	
Commercial Sign Overhead		Overhang Or Encroachment		Tree Stumps		Remove Concrete Driveway Pavement	
Commercial Sign Two Post		Overhead Utility Line		Triangulation Station		Remove Asphalt Concrete Pavement	
Concrete Symbol		Parking Meter		Underground Electric Line		Remove Concrete Sidewalk	
Creek Edge		Pipe With End Section		Underground Gas Line		Remove Concrete Approach Pavement	
Curb/Gutter		Pipe With Headwall		Underground High Pressure Gas Line		Remove Concrete Median Pavement	
Curb		Pipe Without End Section		Underground Sanitary Sewer		Remove Concrete Curb	
Dam Grade/Dike/Levee		Playground Slide		Underground Storm Sewer		Remove Concrete Curb and Gutter	
Deck Edge		Playground Swing		Underground Tank		Remove Concrete Gutter	
Ditch Block		Power And Light Pole		Underground Telephone Line			
Doorway Threshold		Power And Telephone Pole		Underground Television Cable			
Drainage Profile		Power Meter		Underground Water Line			
Drop Inlet		Power Pole		Warning Sign One Post			
Edge Of Asphalt		Power Pole And Transformer		Warning Sign Two Post			
Edge Of Concrete		Power Tower Structure		Water Fountain			
Edge Of Gravel		Propane Tank		Water Hydrant			
Edge Of Other		Property Pipe		Water Meter			
Edge Of Shoulder		Property Pipe With Cap		Water Tower			
Elec. Trans./Power Jct. Box		Property Stone		Water Valve			
Environmental Sensitive Site		Public Telephone		Water Well			
Fence Barbwire		Railroad Crossing Signal		Weir Rock			
Fence Chainlink		Railroad Milepost Marker		Windmill			
Fence Electric		Railroad Profile		Wingwall			
Fence Misc.		Railroad R.O.W. Marker		Witness Corner			
Fence Rock		Railroad Signs					
Fence Snow		Railroad Switch					
Fence Wood		Railroad Track					
Fence Woven		Railroad Trestle					
Fire Hydrant		Rebar					
Flag Pole		Rebar With Cap					
Flower Bed		Reference Mark					
Gas Valve Or Meter		Regulatory Sign One Post					
Gas Pump Island		Regulatory Sign Two Post					
Grain Bin		Retaining Wall					
Guardrail		Riprap					
Guide Sign One Post		River Edge					
Guide Sign Two Post		Rock And Wire Baskets					
Gutter		Rockpiles					
Guy Pole		Satellite Dish					
Haystack		Septic Tank					
						Detectable Warning	
						Pedestrian Push Button Pole	
						and 30" x 48" Clear Space	
						with 1.5% slope	

Plot Scale - 1:100.849


Plotted From - trrc11626

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	190-452	8	26

Plotting Date: 08/02/2017



PI 10+55.48 N 652147.27 E 1206751.63 Del 31°56'46" L Dc 57°17'45" T 28.62' L 55.76' R 100.00'	PI 11+55.43 N 652245.53 E 1206776.82 Del 6°49'47" R Dc 57°17'45" T 5.97' L 11.92' R 100.00'	PI 13+40.08 N 652417.69 E 1206843.60 Del 5°46'32" L Dc 57°17'45" T 5.04' L 10.08' R 100.00'	PI 16+56.29 N 652722.52 E 1206927.72 Del 0°55'38" L
--	--	--	--

 Topsoil Stockpile (43 CY)

File - ...plan.dgn

SIDEWALK PROFILE


STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	190-452	9	26

Plotting Date: 08/02/2017

Plot Scale - 1:100

Plotted From - Irrc11626

File - ...profile1.dgn



SIDEWALK REMOVAL LAYOUT


STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	190-452	10	26




Plotting Date: 08/02/2017


Plot Scale - 1"=40'





Plotted From - Irrc11626





File - ...lpavementremoval.dgn









-  Available Topsoil (43 CY)
-  Remove Concrete Sidewalk
-  Remove Temporary Pedestrian Access Route

















































Plotting Date: 08/02/2017


STATE OF SOUTH DAKOTA	PROJECT	SHEET NO.	TOTAL SHEETS
	190-452	21	26











STATE OF SOUTH DAKOTA	PROJECT	SHEET NO.	TOTAL SHEETS
	190-452	26	26