


Plot Scale - 1:200

TRRC12608

Plotted From -



PROJECT
US Highway 16A
MRM 57 - MRM 59.2

STATE OF SOUTH DAKOTA
DEPARTMENT OF TRANSPORTATION
PLANS FOR PROPOSED

PROJECT 16A-491
US HIGHWAY 16A
PENNINGTON COUNTY


CURB & GUTTER, DROP INLETS, AND EROSION CONTROL
PCN i5hr

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	16A-491	1	26

Plotting Date: 03/21/2019

INDEX OF SHEETS

Sheet No.	1:	Title and Index
Sheets No.	2 - 6:	Plan Estimate, Notes, and Tables
Sheet No.	7:	Typical Sections
Sheets No.	8 - 12:	Special Details
Sheets No.	13 - 26:	Standard Plates



DESIGN DESIGNATION

AADT (2017)	3654
AADT (2037)	5302
DHV	838
D	51%
DHV T%	1.1%
AADT T%	2.4%
V	45 mph

STORM WATER PERMIT

None Required

ESTIMATE OF QUANTITIES

BID ITEM NUMBER	ITEM	QUANTITY	UNIT
009E0010	Mobilization	Lump Sum	LS
110E0300	Remove Concrete Curb and/or Gutter	24	Ft
120E0010	Unclassified Excavation	685	CuYd
120E0600	Contractor Furnished Borrow Excavation	1,541	CuYd
230E0020	Contractor Furnished Topsoil	706	CuYd
260E1010	Base Course	5.0	Ton
380E3520	6" PCC Approach Pavement	28.9	SqYd
380E6110	Insert Steel Bar in PCC Pavement	1,171	Each
450E0122	18" RCP Class 2, Furnish	20	Ft
450E0130	18" RCP, Install	20	Ft
450E4759	18" CMP 16 Gauge, Furnish	180	Ft
450E4760	18" CMP, Install	180	Ft
450E5306	18" CMP Sloped End, Furnish	10	Each
450E5307	18" CMP Sloped End, Install	10	Each
462E0100	Class M6 Concrete	18.0	CuYd
480E0100	Reinforcing Steel	3,312	Lb
632E2510	Type 2 Object Marker Back to Back	10	Each
634E0010	Flagging	60.0	Hour
634E0110	Traffic Control Signs	331.0	SqFt
634E0120	Traffic Control, Miscellaneous	Lump Sum	LS
634E0275	Type 3 Barricade	2	Each
634E0420	Type C Advance Warning Arrow Board	1	Each
650E1079	Modified Type F68 Concrete Curb and Gutter	1,212	Ft
650E1080	Type F68 Concrete Curb and Gutter	1,870	Ft
650E4680	Type P8 Concrete Gutter	40	Ft
670E1010	2' x 3' Type B Drop Inlet	20	Each
670E5400	Precast Drop Inlet Collar	20	Each
720E1015	Bank and Channel Protection Gabion	45.0	CuYd
730E0210	Type F Permanent Seed Mixture	34	Lb
731E0100	Fertilizing	8	Lb
732E0200	Fiber Mulching	1.3	Ton
734E0154	12" Diameter Erosion Control Wattle	1,833	Ft
831E0110	Type B Drainage Fabric	153	SqYd
900E1310	Concrete Washout Facility	1	Each

SPECIFICATIONS

Standard Specifications for Roads and Bridges, 2015 Edition and Required Provisions, Supplemental Specifications, and Special Provisions as included in the Proposal.

ENVIRONMENTAL COMMITMENTS

The SDDOT is committed to protecting the environment and uses Section A Environmental Commitments as a communication tool for the Engineer and Contractor to ensure that attention is given to avoid, minimize, and/or mitigate an environmental impact. Environmental commitments to various agencies and the public have been made to secure approval of this project. An agency with permitting authority can delay a project if identified environmental impacts have not been adequately addressed. Unless otherwise designated, the Contractor's primary contact regarding matters associated with these commitments will be the Project Engineer. These environmental commitments are not subject to change without prior written approval from the SDDOT Environmental Office.

Additional guidance on SDDOT's Environmental Commitments can be accessed through the Environmental Procedures Manual found at: <http://www.sddot.com/resources/Manuals/EnvironProcManual.pdf>

For questions regarding change orders in the field that may have an effect on an Environmental Commitment, the Project Engineer will contact the Environmental Office at 605-773-3098 or 605-773-4336 to determine whether an environmental analysis and/or resource agency coordination is necessary.

COMMITMENT E: STORM WATER

Construction activities constitute less than 1 acre of disturbance.

Action Taken/Required:

At a minimum and regardless of project size, appropriate erosion and sediment control measures must be installed to control the discharge of pollutants from the construction site.

COMMITMENT H: WASTE DISPOSAL SITE

The Contractor will furnish a site(s) for the disposal of construction and/or demolition debris generated by this project.

Action Taken/Required:

Construction and/or demolition debris may not be disposed of within the Public ROW.

The waste disposal site(s) will be managed and reclaimed in accordance with the following from the General Permit for Construction/Demolition Debris Disposal Under the South Dakota Waste Management Program issued by the Department of Environment and Natural Resources.

The waste disposal site(s) will not be located in a wetland, within 200 feet of surface water, or in an area that adversely affects wildlife, recreation, aesthetic value of an area, or any threatened or endangered species, as approved by the Environmental Office and the Project Engineer.

If the waste disposal site(s) is located such that it is within view of any ROW, the following additional requirements will apply:

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	16A-491	2	26

1. Construction and/or demolition debris consisting of concrete, asphalt concrete, or other similar materials will be buried in a trench completely separate from wood debris. The final cover over the construction and/or demolition debris will consist of a minimum of 1 foot of soil capable of supporting vegetation. Waste disposal sites provided outside of the Public ROW will be seeded in accordance with Natural Resources Conservation Service recommendations. The seeding recommendations may be obtained through the appropriate County NRCS Office. The Contractor will control the access to waste disposal sites not within the Public ROW with fences, gates, and placement of a sign or signs at the entrance to the site stating "No Dumping Allowed".

2. Concrete and asphalt concrete debris may be stockpiled within view of the ROW for a period of time not to exceed the duration of the project. Prior to project completion, the waste shall be removed from view of the ROW or buried and the waste disposal site reclaimed as noted above.

The above requirements will not apply to waste disposal sites that are covered by an individual solid waste permit as specified in SDCL 34A-6-58, SDCL 34A-6-1.13, and ARSD 74:27:10:06.

Failure to comply with the requirements stated above may result in civil penalties in accordance with South Dakota Solid Waste Law, SDCL 34A-6-1.31.

All costs associated with furnishing waste disposal site(s), disposing of waste, maintaining control of access (fence, gates, and signs), and reclamation of the waste disposal site(s) will be incidental to the various contract items.

COMMITMENT I: HISTORICAL PRESERVATION OFFICE CLEARANCES

State Historical Preservation Office (SHPO or THPO) concurrence has not been obtained for this project.

Action Taken/Required:

All earth disturbing activities not designated within the plans require a cultural resource review prior to scheduling the pre-construction meeting. This work includes, but is not limited to: Contractor furnished material sources, material processing sites, stockpile sites, storage areas, plant sites, and waste areas.

The Contractor will arrange and pay for a record search and when necessary, a cultural resource survey. The Contractor has the option to contact the state Archaeological Research Center (ARC) at 605-394-1936 or another qualified archaeologist, to obtain either a records search or a cultural resources survey. A record search might be sufficient for review if the site was previously surveyed; however, a cultural resources survey may need to be conducted by a qualified archaeologist.

The Contractor will provide ARC with the following: a topographical map or aerial view of which the site is clearly outlined, site dimensions, project number, and PCN. If applicable, provide evidence that the site has been previously disturbed by farming, mining, or construction activities with a landowner statement that artifacts have not been found on the site.

The Contractor will submit the cultural resources survey report to SDDOT Environmental Office, 700 East Broadway Avenue, Pierre, SD 57501-2586. SDDOT will submit the information to the appropriate SHPO/THPO. Allow **30 Days** from the date this information is submitted to the Environmental Engineer for SHPO/THPO review.

In the event of an inadvertent discovery of human remains, funerary objects, or if evidence of cultural resources is identified during project construction activities, then such activities will immediately cease and the Project Engineer will be immediately notified. The Project Engineer will contact the SDDOT Environmental Office to determine an appropriate course of action.

SHPO/THPO review does not relieve the Contractor of the responsibility for obtaining any additional permits and clearances for Contractor furnished material sources, material processing sites, stockpile sites, storage areas, plant sites, and waste areas that affect wetlands, threatened and endangered species, or waterways. The Contractor will not utilize a site known or suspected of having contaminated soil or water. The Contractor will provide the required permits and clearances to the Project Engineer at the preconstruction meeting.

COMMITMENT S: FIRE PREVENTION IN THE BLACK HILLS AREA

This project is located within the Black Hills Forest Fire Protection Boundary.

Action Taken/Required:

The Contractor shall adhere to the “Special Provision for Fire Plan”.

UTILITIES

The Contractor shall contact the involved utility companies through South Dakota One Call 811 in State or (1-800-781-7474) prior to starting work. It shall be the responsibility of the Contractor to coordinate work with the utility owners to avoid damage to existing facilities.

Utilities are not planned to be affected on this project. If utilities are identified near the improvement area through the SD One Call Process as required by South Dakota Codified Law 49-7A and Administrative Rule Article 20:25, the Contractor shall contact the Project Engineer to determine modifications that will be necessary to avoid utility impacts.

WORK DESCRIPTION

Work on this project consists of installing curb and gutter, drop inlets, bank and channel protection gabions, and minor slope work on US Highway 16A from approximate MRM 56.88 to 59.22 (Keystone to the Keystone Wye.

UNCLASSIFIED EXCAVATION

Unclassified Excavation is provided on the project for removing excess material adjacent to the concrete surfacing, so that new curb and gutter can be installed in accordance with the typical sections. This excess material shall be installed behind the new curb and gutter and shall be graded to the satisfaction of the Engineer.

Plans quantity shall be the basis of payment for the Unclassified Excavation quantity. If changes are made in the field during construction, measurements shall be taken, and the quantity shall be adjusted accordingly.

DROP INLETS

The drop inlets shall be covered throughout construction operations as necessary with an Engineer approved cover to provide safe travel for motorists and to prevent materials from entering the storm sewer system. All costs involved with the coverings and removing debris from the drop inlets shall be incidental to the contract unit prices for the components of the drop inlets.

The plan shown quantities of the drop inlet components such as Class M6 Concrete, Reinforcing Steel, Collars, and Type B Frame and Grate Assembly will be the basis of payment for these items.

If additions or reductions to the number of drop inlets are ordered by the Engineer, payment for the components required to construct the drop inlets will be made at the contract unit prices for the components of the drop inlets.

CORRUGATED METAL PIPE

All corrugated metal pipes 36” and smaller shall have 2-2/3 X 1/2 corrugations unless otherwise noted in the plans.

BASE COURSE

Base Course shall be used as subgrade material under each drop inlet base. Included in the plan quantity is 12” of Base Course under each inlet location. All costs including furnishing, placing, and compacting the material shall be incidental to the contract unit price per ton for Base Course. Compaction shall be as directed by the Engineer.

Plans quantity shall be the basis of payment for the Base Course quantity. If changes are made in the field during construction, measurements shall be taken, and the quantity shall be adjusted accordingly.

INSERT STEEL BAR IN PCC PAVEMENT

Steel bars (No. 5 deformed epoxy bar) shall be installed as per Section 380.3 C.1

The steel bars shall be cut to the specified length by sawing and shall be free from burring or other deformations. Shearing will not be permitted.

A rigid frame or mechanical device will be required to guide the drill to ensure proper horizontal and vertical alignment of the steel bars in the drilled holes.

The No. 5 bars (to be inserted) shall be placed a minimum of 24” from the transverse contraction joints and on 48” centers. The No. 5 bars shall be placed on 30” centers for the F68 Modified Curb and Gutter or F68 Curb and Gutter.

The Contractor shall not place concrete until the epoxy has set enough to prevent steel bar movement.

Cost for the epoxy resin adhesive, No. 5 deformed bars, drilling holes, installing the steel bars into the drilled holes and all other items shall be incidental to the contract unit price per each for Insert Steel Bar in PCC Pavement.

MODIFIED TYPE F68 CONCRETE CURB AND GUTTER

There will be no distinction between straight or curved curb & gutter for bidding purposes.

The Contractor should note the Size and Increased Quantity of concrete that will be required to construct the Modified Type F68 curb and gutter. Reference the detail.

Sealing the joints as required per the Standard Plate shall be incidental to the contract unit price per foot for the Modified Type F68 Concrete Curb & Gutter.

All costs for Modified Type F68 Concrete Curb and Gutter shall be incidental to the contract unit price per foot for FL68 Concrete Curb and Gutter.

TYPE 2 OBJECT MARKERS

All Type 2 Object Markers listed in these plans shall be used to mark new pipe throughout this project. All costs for materials, labor, and equipment necessary to furnish and install object markers shall be incidental to the contract unit price per each for Type 2 Object Marker Back to Back.

TRAFFIC CONTROL – GENERAL NOTES

Unless otherwise stated in these plans, no work will be allowed during hours of darkness.

Work shall only be allowed on one side of the road at a time.

Non-applicable traffic control devices shall be completely covered or removed during periods of inactivity. Periods of inactivity shall be defined as no work taking place for a period of more than 48 hours.

All materials and equipment shall be stored a minimum distance of 30’ from the traveled way during nonworking hours.

The Contractor shall provide installation details at the preconstruction meeting for all breakaway sign support assemblies.

All haul trucks shall be equipped with a second flashing amber light that is visible from the backside of the haul truck. The costs for the flashing amber lights shall be incidental to the various related contract bid items.

All construction operations shall be conducted in the general direction of traffic movement.

If there is a discrepancy between the traffic control plans, standard plates, and the MUTCD – whichever is more stringent shall be used, as determined by the Engineer.

Removing, relocating, covering, salvaging and resetting of permanent traffic control devices, including delineation shall be the responsibility of the Contractor. Any delineators and signs damaged or lost shall be replaced by the Contractor at no cost to the State.

One lane of traffic shall be maintained each direction of travel throughout the project construction.

Work during non-daylight hours shall be subject to prior approval.

SHEETING FOR TRAFFIC CONTROL SIGNS

All fluorescent orange background material on traffic control signs, all temporary delineators, and all temporary STOP (R1-1), YIELD (R1-2), DO NOT ENTER (R5-1), and WRONG WAY (R5-1a) signs will conform to the requirements of ASTM D4956 Type IX or XI. All other traffic control signs and background colors will conform to the requirements of ASTM D4956 Type IV.

INVENTORY OF TRAFFIC CONTROL DEVICES

		CONVENTIONAL ROAD			
SIGN CODE	SIGN DESCRIPTION	NUMBER	SIGN SIZE	SQFT PER SIGN	SQFT
W1-4	REVERSE CURVE (L or R)	2	48" x 48"	16.0	32.0
W9-3	CENTER LANE CLOSED AHEAD	1	48" x 48"	16.0	16.0
W20-1	ROAD WORK AHEAD	6	48" x 48"	16.0	96.0
W20-4	ONE LANE ROAD AHEAD	2	48" x 48"	16.0	32.0
W20-7	FLAGGER (symbol)	2	48" x 48"	16.0	32.0
W21-5	SHOULDER WORK	2	48" x 48"	16.0	32.0
W21-5a	LEFT or RIGHT SHOULDER CLOSED	2	48" x 48"	16.0	32.0
W21-5b	LEFT or RIGHT SHOULDER CLOSED AHEAD	2	48" x 48"	16.0	32.0
G20-2	END ROAD WORK	6	36" x 18"	4.5	27.0
		CONVENTIONAL ROAD TRAFFIC CONTROL SIGNS SQFT			
		331.0			

PERMANENT SEEDING

The areas to be seeded consist of all newly graded areas within the project limits except for the top of roadways, temporary easements under cultivation, and areas designated to be sod.

Type F Permanent Seed Mixture shall consist of the Following:

Grass Species	Variety	Pure Live Seed (PLS) (Pounds/Acre)
Western Wheatgrass	Arriba, Flintlock, Rodan, Rosana, Walsh	7
Green Needlegrass	Lodorm, AC Mallard Ecovar	4
Sideoats Grama	Butte, Pierre	3
Blue Grama	Bad River	2
Oats or Spring Wheat: April through May; Winter Wheat: August through November		10
Total:		26

MYCORRHIZAL INOCULUM

Mycorrhizal inoculum shall consist of mycorrhizal fungi spores and mycorrhizal fungi-infected root fragments in a solid carrier. The carrier may include organic materials, calcinated clay, or other materials consistent with application and good plant growth. The supplier shall provide certification of the fungal species claimed and the live propagule count. The inoculum shall include the following fungal species:

<i>Glomus intraradices</i>	25%
<i>Glomus aggregatu</i>	25%
<i>Glomus mosseae</i>	25%
<i>Glomus etunicatum</i>	25%

All seed shall be inoculated with a minimum of 100,000 live propagules of mycorrhizal fungi per acre. All costs of inoculating the seed shall be incidental to the contract unit price per pound for Type F Permanent Seed Mixture.

The mycorrhizal inoculum will be as shown below or an approved equal:

Product	Manufacturer
MycoApply	Mycorrhizal Applications, Inc. Grants Pass, OR Phone: 1-866-476-7800 www.mycorrhizae.com
AM 120 Multi Species Blend	Reforestation Technologies Int. Gilroy, CA Phone: 1-800-784-4769 www.reforest.com

FERTILIZING

The Contractor will apply an all-natural slow release fertilizer prior to seeding or placing sod. The all-natural fertilizer will have a minimum guaranteed analysis of 4-4-4 and be USDA Certified BioBased. It should provide a minimum of 4% (N) nitrogen with a minimum water insoluble nitrogen (WIN) fraction of 2.07%, a minimum of 4% (P2O5) available phosphate, a minimum of 4% (K2O) soluble potash, and a maximum carbon to nitrogen ratio (C:N ratio) of 5:1. The all-natural fertilizer will be free of weed-seed and pathogens accomplished through thermophilic composting, and not mechanical or chemical sterilization, to assure presence of beneficial soil microbiology. The fertilizer will have a near neutral pH, a low salt index, a low biological oxygen demand, contain organic humic and fulvic acids, and have high aerobic organism counts. The fertilizer will also be stable, free of bad odors, and be unattractive as a food source for animals. It should also be in a granular form that is easily spread.

The fertilizer will be applied at a rate of 1,500 pounds per acre in accordance with the manufacturer's recommended method of application.

The all-natural slow release fertilizer will be as shown below or an approved equal:

Product	Manufacturer
Sustane	Sustane Corporate Headquarters Cannon Falls, Minnesota Phone: 1-800-352-9245 www.sustane.com
Perfect Blend	Perfect Blend, LLC Bellevue, WA Phone: 1-866-456-8890 www.perfect-blend.com

PLACING CONTRACTOR FURNISHED TOPSOIL

It is anticipated that a larger volume of topsoil will be needed for the new grade than can be salvaged from the existing grade. The Contractor will be required to furnish and place topsoil on areas as determined by the Engineer during construction.

All costs to furnish and place the topsoil shall be incidental to the contract unit price per cubic yard for Placing Contractor Furnished Topsoil.

EROSION CONTROL WATTLE

Erosion control wattles for restraining the flow of runoff and sediment will be installed at locations noted in the table and at locations determined by the Engineer during construction. Refer to Standard Plate 734.06 for details.

The Contractor will provide certification that the erosion control wattles do not contain noxious weed seeds.

Erosion control wattles will remain on the project to decompose.


The erosion control wattle provided will be from the approved product list. The approved product list for erosion control wattle may be viewed at the following internet site:

<http://sddot.com/business/certification/products/Default.aspx>


STATE OF SOUTH DAKOTA	PROJECT	SHEET NO.	TOTAL SHEETS
	16A-491	7	26
Plotting Date: 03/18/2019			
Revise Date: - -			
Initials:			

Typical Section

Typical Section - Left Side



Typical Section - Right Side



STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	16A-491	8	26

Plotting Date: 03/18/2019

Legend

MRM

Keystone




STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	16A-491	9	26

Plotting Date: 03/18/2019

Legend

MRM


Keystone



CROSS-SECTION DETAIL

STATE OF SOUTH DAKOTA	PROJECT	SHEET NO.	TOTAL SHEETS
	16A-491	10	26
Plotting Date: 03/18/2019			
Revise Date: - -			
Initials:			


MRM 59.00-0.780 - L
MRM 59.00-0.727 - L
MRM 58.00-0.101 - L
MRM 58.00-0.333 - L
MRM 58.00-0.906 - L
MRM 58.00-0.842 - L
MRM 56.88+0.309 - R
MRM 56.88+0.359 - R
MRM 56.88+0.409 - R
MRM 58.00+0.044 - R



All Locations:
Install 2 Drop Inlets
Furnish and install 2 Type B Frame & Grate
Install 2' - 18" CMP to connect the two drop inlets
Furnish and install one outlet pipe of 18' - 18" CMP
Furnish and install Bank and Channel Protection Gabions - 4.5 Cubic Yards
Culverts shall have a minimum of 6" drop in elevation.
Culverts may be skewed to fit drainage and/or to provide the desired drop in elevation as directed by the Engineer.

SPECIAL DETAIL FOR TYPE F MODIFIED
CONCRETE CURB AND GUTTER

STATE OF SOUTH DAKOTA	PROJECT	SHEET NO.	TOTAL SHEETS
	16A-491	11	26
Plotting Date: 03/18/2019			
Revise Date: - -			
Initials:			



Type	T ₁ (Inches)	T ₂ (Inches)	Cu. Yd. Per Lin. Ft.	Lin. Ft. Per Cu. Yd.
F68 (mod)	8	7.5	0.130	7.7


GENERAL NOTES:

- When concrete curb and gutter longitudinally adjoins new concrete pavement, the method of attachment shall be by one of the methods shown on Plate No. 380.11.
- 1/2" preformed expansion joint fillers shall be placed transversely in the curb and gutter as follows:
- At each junction of radius return curb and gutter and curb and gutter which is parallel to the project centerline.
 - At each junction with existing concrete curb or concrete curb and gutter.
 - At each junction with existing concrete sidewalk, to the depth of the sidewalk.
- When backface of curb and gutter is adjacent to concrete pavement or concrete sidewalk, 1/2" preformed expansion joint filler shall be placed longitudinally along the backface of the curb. The 1/2" preformed expansion joint filler shall be placed to the depth of the adjoining concrete.
- Weakened plane joints shall be constructed at 10' intervals except when curb and gutter is constructed adjacent to mainline PCC pavement. When curb and gutter is constructed adjacent to mainline PCC pavement the joints shall coincide with the mainline PCC pavement's transverse joints. The joints shall be constructed to a minimum depth of one inch by scoring with a tool which will leave the corners rounded and provide free movement of concrete at the joint.

FIXED LOCATION SIGNS

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	16A-491	12	26

Plotting Date: 03/18/2019




STATE OF SOUTH DAKOTA	PROJECT	SHEET NO.	TOTAL SHEETS
	16A-491	13	26

Plotting Date: 03/18/2019

LONGITUDINAL CONSTRUCTION JOINT WITH TIE BARS


(DRILLED IN BARS)



T = Pavement Thickness
The tie bars shall be embedded a minimum depth of 9 inches into the in place PCC pavement and anchored with an epoxy resin adhesive.

LONGITUDINAL CONSTRUCTION JOINT WITH TIE BARS

(INSERTED OR FORMED IN BARS)



GENERAL NOTES (For the details above):

The epoxy coated deformed tie bars shall be spaced in accordance with the following tables:

Tie Bar Spacing 48" Maximum	
Transverse Contraction Joint Spacing	Number of Tie Bars
6.5' to 10'	2
10.5' to 14'	3
14.5' to 18'	4
18.5' to 22'	5

Tie Bar Spacing 30" Maximum	
Transverse Contraction Joint Spacing	Number of Tie Bars
5' to 7'	2
7.5' to 9.5'	3
10' to 12'	4
12.5' to 14.5'	5
15' to 17'	6
17.5' to 19.5'	7
20' to 22'	8

The tie bars shall be placed a minimum of 15 inches from transverse contraction joints.

The required number of tie bars as shown in the table shall be uniformly spaced within each panel. The uniformly spaced tie bars shall be spaced a maximum of 48 inches center to center for a female keyway and shall be spaced a maximum of 30 inches center to center for a vertical face and male keyway. The maximum tie bar spacing shall apply to tie bars within each panel.

The keyway illustrated in the above details depict a female keyway.


The keyway is optional and is not required. When concrete pavement is formed and a keyway is provided, a metal recess strip shall be used. When concrete pavement is slip formed, a metal recess strip is not required.

August 31, 2013

Published Date: 1st Qtr. 2019	S D D O T	PCC PAVEMENT LONGITUDINAL JOINTS WITH TIE BARS	PLATE NUMBER 380.10
			Sheet 1 of 2

SAWED LONGITUDINAL JOINT WITH TIE BARS

(POURED MONOLITHICALLY)



T = Pavement Thickness

GENERAL NOTES (For the detail above):

The epoxy coated deformed tie bars shall be spaced in accordance with the following table:

Tie Bar Spacing 48" Maximum	
Transverse Contraction Joint Spacing	Number of Tie Bars
6.5' to 10'	2
10.5' to 14'	3
14.5' to 18'	4
18.5' to 22'	5

The tie bars shall be placed a minimum of 15 inches from the transverse contraction joints.

The required number of tie bars as shown in the table shall be uniformly spaced within each panel with a maximum space of 48 inches center to center. The maximum tie bar spacing shall apply to tie bars within each panel.


The first saw cut to control cracking shall be a minimum of 1/3 the thickness of the pavement. Additional sawing for widening the saw cut to provide the width for the installation of the hot poured elastic joint sealer is necessary.

August 31, 2013


Published Date: 1st Qtr. 2019	S D D O T	PCC PAVEMENT LONGITUDINAL JOINTS WITH TIE BARS	PLATE NUMBER 380.10
			Sheet 2 of 2

STATE OF SOUTH DAKOTA	PROJECT	SHEET NO.	TOTAL SHEETS
	16A-491	14	26

Plotting Date: 03/18/2019



- * 8" at Commercial Approaches
- ** Width for 6" high curb is 6' (See Standard Plate 650.35)
- *** Within these areas, the surface of the type A PCC approach pavement shall be sloped transitionally as approved by the Engineer.



GENERAL NOTES:

The concrete for the type A PCC approach pavement and adjacent driveway shall comply with the requirements of the Specifications for class M6 concrete unless otherwise stated in the plans.


Contraction joints in the type A PCC approach pavement shall be 1 1/2 inches deep if formed in the fresh concrete using a suitable grooving tool. If a saw is used to cut the contraction joints, then the depth of the joint shall be at least 1/4 the thickness of the approach pavement. Additional contraction joints not shown in the Plan View shall be spaced as follows:

- One joint at the center of the approach for driveways 16' to 24' wide.
- Two joints spaced at equal intervals for driveways greater than 24' to 40' wide.

All costs for furnishing and placing the type A PCC approach pavement and constructing the expansion and contraction joints including labor, equipment, excavation, and materials including the earthen backfill and granular material, shall be incidental to the contract unit price per square yard for the corresponding PCC Approach Pavement bid item.

September 14, 2017

Published Date: 1st Qtr. 2019	S D D O T	TYPE A PCC APPROACH PAVEMENT	PLATE NUMBER 380.40
			Sheet 1 of 1



ARCH C.M.P. SLOPED ENDS										
Equiv. Dia. (Inch)	(Inches)		Min. Thick.		Dimensions (Inches)			L Dimensions		
	Span	Rise	Inch	Gage	A	H	W	Overall Width	Slope	Length (Inch)
18	21	15	.064	16	8	6	27	43	4:1	20
21	24	18	.064	16	8	6	30	46	4:1	32
24	28	20	.064	16	8	6	34	50	4:1	40
30	35	24	.079	14	12	9	41	65	4:1	56
36	42	29	.109	12	12	9	48	72	4:1	76
42	49	33	.109	12	16	12	55	87	4:1	92
48	57	38	.109	12	16	12	63	95	4:1	112
54	64	43	.109	12	16	12	70	102	4:1	132
60	71	47	.109	12	16	12	77	109	4:1	148
72	83	57	.109	12	16	12	89	121	4:1	188

CIRCULAR C.M.P. SLOPED ENDS								
Pipe Dia. (Inch)	Min. Thick.		Dimensions (Inches)				L Dimensions	
	Inch	Gage	A	H	W	Overall Width	Slope	Length (Inch)
15	.064	16	8	6	21	37	4:1	20
18	.064	16	8	6	24	40	4:1	32
21	.064	16	8	6	27	43	4:1	44
24	.064	16	8	6	30	46	4:1	56
30	.109	12	12	9	36	60	4:1	80
36	.109	12	12	9	42	66	4:1	104
42	.109	12	16	12	48	80	4:1	128
48	.109	12	16	12	54	86	4:1	152
54	.109	12	16	12	60	92	4:1	176
60	.109	12	16	12	66	98	4:1	200

GENERAL NOTES:

Safety bars shall be attached to sloped ends over 30" in diameter only when specified in the plans.

Sloped ends shall be fabricated from galvanized steel and shall conform to the requirements of the Specifications.

Safety bars shall be fabricated from steel schedule 40 pipe in conformance with ASTM A53, grade B or HSS 3.5X.216 in conformance with ASTM A500, grade B.

Slotted holes for safety bar attachment shall be provided for all end sections.

Attachment to circular pipes 15" through 24" diameter shall be made with Type #1 straps. All other sizes shall be attached with Type #2 rods and lugs.

When stated in the plans, optional toe plate extension shall be punched and bolted to end section apron lip with 3/8" diameter galvanized bolts. Steel for toe plate extension shall be same gauge as end section. Dimensions shall be overall width less 6" by 8" high.

Installation shall be performed in accordance with the Specifications.

Cost of all work and materials required for fabrication and installation of sloped ends shall be incidental to the bid items for the various sizes of sloped ends.



February 10, 2014

S D D O T	C. M. P. SLOPED ENDS	PLATE NUMBER 450.37
		Sheet 2 of 2

Published Date: 1st Qtr. 2019

STATE OF SOUTH DAKOTA	PROJECT	SHEET NO.	TOTAL SHEETS
	16A-491	16	26

Plotting Date: 03/18/2019



The signs illustrated are not required if the work space is behind a barrier, more than 2 feet behind the curb, or 15 feet or more from the edge of any roadway.

The signs illustrated shall be used where there are distracting situations; such as: vehicles parked on shoulder, vehicles accessing the work site via the highway, and equipment traveling on or crossing the roadway to perform work operations.

The ROAD WORK AHEAD sign may be replaced with other appropriate signs, such as the SHOULDER WORK sign. The SHOULDER WORK sign may be used for work adjacent to the shoulder.

* If the work space is on a divided highway, an advance warning sign should also be placed on the left side of the directional roadway.

For short term, short duration, or mobile operations, all signs and channelizing devices may be eliminated if a vehicle with an activated flashing or revolving yellow light is used.

Posted Speed Prior to Work (M.P.H.)	Spacing of Advance Warning Signs (Feet) (A)
0 - 30	200
35 - 40	350
45 - 50	500
55	750
60 - 80	1000



April 15, 2015


S
D
D
O
T

GUIDES FOR TRAFFIC CONTROL DEVICES
WORK BEYOND THE SHOULDER

PLATE NUMBER
634.01


Sheet 1 Of 1

Published Date: 1st Qtr. 2019



Posted Speed Prior to Work (M.P.H.)	Spacing of Advance Warning Signs (Feet) (A)	Taper Length (Feet) (L)	Spacing of Channelizing Devices (Feet) (G)
0 - 30	200	180	25
35 - 40	350	320	25
45	500	600	25
50	500	600	50
55	750	660	50
60 - 65	1000	780	50

■ Channelizing Device



The channelizing devices shall be drums or 42" cones if traffic control must remain overnight.

For short duration operations (1 hour or less) all channelizing devices may be eliminated if a vehicle with an activated flashing or revolving yellow light is used.

Worker signs (W21-1 or W21-1a) may be used instead of SHOULDER WORK signs.

A SHOULDER WORK sign should be placed on the left side of a divided or one-way roadway only if the left shoulder is affected.

The SHOULDER WORK sign on an intersecting roadway is not required if drivers emerging from that roadway will encounter another advance warning sign before they reach a work activity area.

WORK SPACE

June 3, 2016

S
D
D
O
T

GUIDES FOR TRAFFIC CONTROL DEVICES
WORK ON SHOULDERS

PLATE NUMBER
634.03

Sheet 1 Of 1

Published Date: 1st Qtr. 2019

STATE OF SOUTH DAKOTA	PROJECT	SHEET NO.	TOTAL SHEETS
	16A-491	18	26

Plotting Date: 03/18/2019

Posted Speed Prior to Work (M.P.H.)	Spacing of Advance Warning Signs (Feet) (A)	Spacing of Channelizing Devices (Feet) (G)
0 - 30	200	25
35 - 40	350	25
45	500	25
50	500	50
55	750	50
60 - 65	1000	50

Warning sign sequence —
in opposite direction same
as below.

- —● Flagger
- Channelizing Device

For low-volume traffic situations with short work zones on straight roadways where the flagger is visible to road users approaching from both directions, a single flagger may be used.

The ROAD WORK AHEAD and the END ROAD WORK signs may be omitted for short duration operations (1 hour or less).

For tack and/or flush seal operations, when flaggers are not being used, the FRESH OIL sign (W21-2) shall be displayed in advance of the liquid asphalt areas.

Flashing warning lights and/or flags may be used to call attention to the advance warning signs.

The channelizing devices shall be drums or 42" cones.


Channelizing devices are not required along the centerline adjacent to work area when pilot cars are utilized for escorting traffic through the work area.

END
ROAD WORK
G20-2

Channelizing devices and flaggers shall be used at intersecting roads to control intersecting road traffic as required.

The buffer space should be extended so that the two-way traffic taper is placed before a horizontal or vertical curve to provide adequate sight distance for the flagger and queue of stopped vehicles.

The length of A may be adjusted to fit field conditions.



June 3, 2016


**S
D
D
O
T**

GUIDES FOR TRAFFIC CONTROL DEVICES LANE CLOSURE WITH FLAGGER PROVIDED

PLATE NUMBER
634.23

Sheet 1 of 1

Published Date: 1st Qtr. 2019



September 14, 2017



**S
D
D
O
T**


GUIDES FOR TRAFFIC CONTROL DEVICES 3-LANE, OUTSIDE LANE CLOSED

PLATE NUMBER
634.53

Sheet 1 of 1

Published Date: 1st Qtr. 2019





Type	T ₁ (Inches)	T ₂ (Inches)	Cu. Yd. Per Lin. Ft.	Lin. Ft. Per Cu. Yd.
F66	6	5 1/16	0.057	17.6
F67	7	6 1/16	0.065	15.4
F68	8	7 1/16	0.073	13.6
F68.5	8.5	7 9/16	0.077	12.9
F69	9	8 1/16	0.082	12.3
F69.5	9.5	8 9/16	0.086	11.7
F610	10	9 1/16	0.090	11.1
F610.5	10.5	9 9/16	0.094	10.7
F611	11	10 1/16	0.098	10.2
F611.5	11.5	10 9/16	0.102	9.8
F612	12	11 1/16	0.106	9.4


GENERAL NOTES:

When concrete curb and gutter longitudinally adjoins new concrete pavement, the method of attachment shall be by one of the methods shown on Standard Plate 380.11.

See Standard Plate 650.90 for expansion and contraction joints in the curb and gutter.

September 6, 2008

Published Date: 1st Qtr. 2019	S D D O T	TYPE F CONCRETE CURB AND GUTTER	PLATE NUMBER 650.20
			Sheet 1 of 1



Type	T ₁ (Inches)	T ₂ (Inches)	Cu. Yd. Per Lin. Ft.	Lin. Ft. Per Cu. Yd.
P6	6	6 3/8	0.047	21.2
P7	7	7 3/8	0.055	18.1
P8	8	8 3/8	0.064	15.7
P8.5	8.5	8 7/8	0.068	14.8
P9	9	9 3/8	0.072	13.9
P9.5	9.5	9 7/8	0.076	13.2
P10	10	10 3/8	0.080	12.5
P10.5	10.5	10 7/8	0.084	11.9
P11	11	11 3/8	0.088	11.3
P11.5	11.5	11 7/8	0.092	10.8
P12	12	12 3/8	0.096	10.4

* Joint will not be needed if concrete curb and gutter and type P concrete gutter is placed at the same time. If the 1/2 inch Preformed Expansion Joint Filler is provided, then the joint shall be sealed in accordance with Standard Plate 650.90.

GENERAL NOTES:

The concrete for the Type P Concrete Gutter shall comply with the requirements of the Specifications for Class M6 Concrete.

When concrete gutter longitudinally adjoins new concrete pavement, the method of attachment shall be by one of the methods shown on Standard Plate 380.11.

Transverse contraction joints shall be constructed at 10' intervals in the concrete gutter except when concrete gutter is constructed adjacent to mainline PCC pavement. When concrete gutter is constructed adjacent to mainline PCC pavement, a transverse contraction joint shall be constructed in the concrete gutter at each mainline PCC pavement transverse contraction joint location.


When concrete gutter is placed monolithically with mainline PCC pavement, the transverse contraction joints in the concrete gutter shall be sawed and sealed the same as the transverse contraction joints in the mainline PCC pavement.

When concrete gutter is not placed monolithically with the mainline PCC pavement and when the adjacent mainline surfacing is not PCC concrete, the transverse contraction joints in the concrete gutter shall be 1 1/2 inches deep if formed in the fresh concrete using a suitable grooving tool. If a saw is used to cut the contraction joints, then the depth of the joint shall be at least 1/4 the thickness of the concrete.

June 26, 2015

Published Date: 1st Qtr. 2019	S D D O T	TYPE P CONCRETE GUTTER	PLATE NUMBER 650.30
			Sheet 1 of 1


STATE OF SOUTH DAKOTA	PROJECT	SHEET NO.	TOTAL SHEETS
	16A-491	21	26
Plotting Date: 03/18/2019			



LONGITUDINAL SECTION OF CONCRETE CURB TAPER

September 14, 2005

<i>Published Date: 1st Qtr. 2019</i>	S D D O T	CONCRETE CURB TAPER	PLATE NUMBER 650.35
			Sheet 1 of 1



ESTIMATED QUANTITIES			
ITEM	UNIT	CONSTANT QUANTITY	VARIABLE QUANTITY
* Class M6 Concrete	Cu. Yd.	0.26	0.22H
Reinforcing Steel	Lb.	83.03	28.97H
Frame and Grate Assembly	Each	1	

DROP INLETS FOR 12" TO 24" DIAMETER PIPE

SPECIFICATIONS

Design Specifications: AASHTO LRFD Bridge Design Specifications, 2012 Edition.

Construction Specifications: South Dakota Standard Specifications for Roads and Bridges, Current Edition and required Provisions, Supplemental Specifications, and Special Provisions as included in the Proposal.

GENERAL NOTES:

Design Live Load: HL-93. No construction loading in excess of legal load was considered.

Reinforcing steel shall conform to ASTM A615 grade 60. The d bars shall be lapped 12 inches with the b and c bars. Cut and bend reinforcing steel as required to place pipe(s) through the drop inlet wall.

Drop inlet may be precast. If precast drop inlet details differ from this standard plate, submit a checked design done by a SD registered P.E. and shop plans to the Office of Bridge Design for approval.

* Reduce total quantities of concrete by the amount of concrete displaced by the pipe(s). The total quantity of concrete shall be computed to the nearest hundredth of a cubic yard. The total quantity of reinforcing steel shall be computed to the nearest pound.


Drop inlet shown may be modified by the addition or omission of connecting pipes as noted elsewhere in the plans. All pipes entering drop inlet must fit between the inside face of walls and shall not enter through the corners.

Maximum R.C.P. diameter shall not exceed 18 inches on the 2-foot wide side and shall not exceed 24 inches (24 inches for R.C. arch) on the 3-foot wide side of the drop inlet.

The dimension of H is in feet. Maximum H is 10 feet.

December 16, 2015

Published Date: 1st Qtr. 2019	S D D O T	2' X 3' TYPE B REINFORCED CONCRETE DROP INLET	PLATE NUMBER 670.01
			Sheet 1 of 2



REINFORCING SCHEDULE				
Mk.	No.	Size	Length	Type
a	2.67H	4	8' - 0"	17
b	5	5	6' - 3"	17
c	6	4	5' - 3"	17
d	22	4	H - 2"	Str.

NOTE:
All dimensions are out to out of bars.

Type 17

2' - 7 1/2"
3' - 7 1/2"
3' - 6 1/2"

a 2' - 2 1/2"
b 1' - 3 1/2"
c 1' - 3 1/2"

December 16, 2015


Published Date: 1st Qtr. 2019	S D D O T	2' X 3' TYPE B REINFORCED CONCRETE DROP INLET	PLATE NUMBER 670.01
			Sheet 2 of 2

STATE OF SOUTH DAKOTA	PROJECT	SHEET NO.	TOTAL SHEETS
	16A-491	23	26

Plotting Date: 03/18/2019

GENERAL NOTE:

Top of grate elevation shall be 0.04' below theoretical elevation of gutter.



June 26, 2011









Published Date: 1st Qtr. 2019

**S
D
D
O
T**

INSTALLATION OF TYPE B DROP INLET

PLATE NUMBER
670.75

Sheet 1 of 1



GENERAL NOTE:

Total weight of the assembly shall be 490 Lbs. minimum and the curb box shall be adjustable 6" to 9".

March 31, 2000


Published Date: 1st Qtr. 2019

**S
D
D
O
T**

TYPE B FRAME AND GRATE ASSEMBLY

PLATE NUMBER
670.80

Sheet 1 of 1



GABION DETAILS
STANDARD SIZES

SIZE	LENGTH	WIDTH	HEIGHT	NUMBER OF CELLS	CAPACITY, Cu. Yd.
A	6'-0"	3'-0"	3'-0"	2	2.0
B	9'-0"	3'-0"	3'-0"	3	3.0
C	12'-0"	3'-0"	3'-0"	4	4.0
D	6'-0"	3'-0"	1'-6"	2	1.0
E	9'-0"	3'-0"	1'-6"	3	1.5
F	12'-0"	3'-0"	1'-6"	4	2.0
G	6'-0"	3'-0"	1'-0"	2	0.7
H	9'-0"	3'-0"	1'-0"	3	1.0
I	12'-0"	3'-0"	1'-0"	4	1.3

Above Dimensions subject to mill tolerances.

GENERAL NOTES:

Lacing and internal connecting wire shall be 0.0866 inch diameter steel wire ASTM A641 Class 3 soft temper measured after galvanizing and for PVC coated gabions shall be 0.0866 inch diameter steel wire measured after galvanizing but before PVC coating.

The lacing procedure is as follows:


1. Cut a length of lacing wire approximately 1 1/2 times the distance to be laced but not exceeding 5 feet.
2. Secure the wire terminal at the corner by looping and twisting.
3. Proceed lacing with alternating single and double loops at a spacing not to exceed 6 inches.
4. Securely fasten the other lacing wire terminal.

Wire lacing or interlocking type fasteners shall be used for gabion assembly and final construction of gabion structures. Interlocking fasteners for galvanized gabions shall be high tensile 0.120 inch diameter galvanized steel wire measured after galvanizing. The galvanizing shall conform to ASTM A641-92 Class 3 coating. Fasteners shall also be in accordance with ASTM A764, Class II, Type III.

Interlocking fasteners for PVC coated gabions shall be high tensile 0.120 inch diameter stainless steel wire conforming to ASTM A313, Type 302, Class I. The spacing of the interlocking fasteners during all phases of assembly and construction shall not exceed 6 inches. All fasteners shall be placed where the mesh weaves around the selvage wire at the vertical and horizontal joints.

June 26, 2001

Published Date: 1st Qtr. 2019	S D D O T	BANK AND CHANNEL PROTECTION GABIONS	PLATE NUMBER
			720.01
			Sheet 1 of 1



June 26, 2016

Published Date: 1st Qtr. 2019	S D D O T	BANK AND CHANNEL PROTECTION GABION PLACEMENT UNDER PIPE END SECTIONS	PLATE NUMBER
			720.03
			Sheet 1 of 2

STATE OF SOUTH DAKOTA	PROJECT	SHEET NO.	TOTAL SHEETS
	16A-491	25	26

Plotting Date: 03/18/2019

ESTIMATED QUANTITIES *				
RCP, RCP Arch, CMP, and CMP Arch	Detail	Pipe Diameter (Inches)	Gabion (Cu. Yd.)	Type B Drainage Fabric (Sq. Yd.)
	1	12, 18, and 24	4.5	15
	2	30 and 36	6.0	19
	3	42	10.0	29
	4	48 and 54	12.0	34
	5	60	15.5	43
	6	66	17.0	47
	7	72	21.5	57
	8	78	26.0	68
	9	84	27.0	70

GENERAL NOTES:

Gabions at outlets of CMP and RCP shall be placed under the end section a distance of 2' from the outlet end. For CMP end section installations, the upper fabric of the gabions shall be modified to accommodate the metal end section as approved by the Engineer.

* Gabion and type B drainage fabric quantities on this standard plate are based on standard gabion sizes D, E, and F as depicted on Standard Plate 720.01.


Type B drainage fabric shall be placed under the gabions and around the exterior sides (perimeter) of the gabions as approved by the Engineer. The type B drainage fabric shall be in conformance with Section 831 of the Specifications. Measurement and payment of the type B drainage fabric shall be in conformance with Section 720 of the Specifications.

June 26, 2016

Published Date: 1st Qtr. 2019	S D D O T	BANK AND CHANNEL PROTECTION GABION PLACEMENT UNDER PIPE END SECTIONS	PLATE NUMBER 720.03
			Sheet 2 of 2

STATE OF SOUTH DAKOTA	PROJECT	SHEET NO.	TOTAL SHEETS
	16A-491	26	26

Plotting Date: 03/18/2019



December 23, 2004

Published Date: 1st Qtr. 2019	S D D O T	EROSION CONTROL WATTLE	PLATE NUMBER 734.06
			Sheet 1 of 2

GENERAL NOTES:

At cut or fill slope installations, wattles shall be installed along the contour and perpendicular to the water flow.

At ditch installations, point A must be higher than point B to ensure that water flows over the wattle and not around the ends.

The Contractor shall dig a 3" to 5" trench, install the wattle tightly in the trench so that daylight can not be seen under the wattle, and then compact the soil excavated from the trench against the wattle on the uphill side. See Detail B.

The stakes shall be 1"x2" or 2"x2" wood stakes, however, other types of stakes such as rebar may be used only if approved by the Engineer. The stakes shall be placed 6" from the ends of the wattles and the spacing of the stakes along the wattles shall be 3' to 4'.

Where installing running lengths of wattles, the Contractor shall butt the second wattle tightly against the first and shall not overlap the ends. See Detail C.

The Contractor and Engineer shall inspect the erosion control wattles once every week and within 24 hours after every rainfall event greater than 1/2". The Contractor shall remove, dispose, or reshape the accumulated sediment when necessary as determined by the Engineer.

Sediment removal, disposal, or necessary shaping shall be as directed by the Engineer. All costs for removing accumulated sediment, disposal of sediment, and necessary shaping shall be incidental to the contract unit price per cubic yard for "Remove Sediment".

All costs for furnishing and installing the erosion control wattles including labor, equipment, and materials shall be incidental to the contract unit price per foot for the corresponding erosion control wattle bid item.

All costs for removing the erosion control wattle from the project including labor, equipment, and materials shall be incidental to the contract unit price per foot for "Remove Erosion Control Wattle".

December 23, 2004

Published Date: 1st Qtr. 2019	S D D O T	EROSION CONTROL WATTLE	PLATE NUMBER 734.06
			Sheet 2 of 2