


Plot Scale - 1:200

Plotted From - TRR014610



STATE OF SOUTH DAKOTA  
DEPARTMENT OF TRANSPORTATION  
PLANS FOR PROPOSED  
**PROJECT  
085-451  
US HWY 85  
LAWRENCE COUNTY**  
RETAINING WALL BACKFILL REPAIR  
PCN i62e

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	085-451	1	10

Plotting Date: 04/26/2021

INDEX OF SHEETS


1	General Layout with Index
2-5	Estimate with General Notes & Tables
6	Legend
7	Plan Sheet
8	Traffic Control Layout
9-11	Standard Plates

PROJECT 085-451  
MRM 24.23

DESIGN DESIGNATION	
AADT (2020)	4222
AADT (2040)	5712
DHV	936
D	51%
DHV T%	5.3%
AADT T%	11.6%

STORM WATER PERMIT	
NO PERMIT REQUIRED	



ESTIMATE OF QUANTITIES

BID ITEM NUMBER	ITEM	QUANTITY	UNIT
009E0010	Mobilization	Lump Sum	LS
110E1140	Remove Concrete Sidewalk	4.7	SqYd
110E7802	Remove Fence for Reset	8	Ft
250E0010	Incidental Work	Lump Sum	LS
464E0100	Controlled Density Fill	1.0	CuYd
620E4100	Reset Fence	8	Ft
634E0110	Traffic Control Signs	83.0	SqFt
634E0120	Traffic Control, Miscellaneous	Lump Sum	LS
634E2000	Longitudinal Pedestrian Barricade	20	Ft
651E0040	4" Concrete Sidewalk	42	SqFt

SPECIFICATIONS

Standard Specifications for Roads and Bridges, 2015 Edition and Required Provisions, Supplemental Specifications, and Special Provisions as included in the Proposal.

ENVIRONMENTAL COMMITMENTS

The SDDOT is committed to protecting the environment and uses Environmental Commitments as a communication tool for the Engineer and Contractor to ensure that attention is given to avoid, minimize, and/or mitigate an environmental impact. Environmental commitments to various agencies and the public have been made to secure approval of this project. An agency with permitting authority can delay a project if identified environmental impacts have not been adequately addressed. Unless otherwise designated, the Contractor's primary contact regarding matters associated with these commitments will be the Project Engineer. During construction, the Project Engineer will verify that the Contractor has met Environmental Commitment requirements. These environmental commitments are not subject to change without prior written approval from the SDDOT Environmental Office.

Additional guidance on SDDOT's Environmental Commitments can be accessed through the Environmental Procedures Manual found at: <<https://dot.sd.gov/media/documents/EnvironmentalProceduresManual.pdf> >

For questions regarding change orders in the field that may have an effect on an Environmental Commitment, the Project Engineer will contact the Environmental Engineer at 605-773-3180 or 605-773-4336 to determine whether an environmental analysis and/or resource agency coordination is necessary.

Once construction is complete, the Project Engineer will review all environmental commitments for the project and document their completion.

COMMITMENT E: STORM WATER

Construction activities constitute less than 1 acre of disturbance.

Action Taken/Required:

At a minimum and regardless of project size, appropriate erosion and sediment control measures must be installed to control the discharge of pollutants from the construction site.

COMMITMENT H: WASTE DISPOSAL SITE

The Contractor will furnish a site(s) for the disposal of construction and/or demolition debris generated by this project.

Action Taken/Required:

Construction and/or demolition debris may not be disposed of within the Public ROW.

The waste disposal site(s) will be managed and reclaimed in accordance with the following from the General Permit for Construction/Demolition Debris Disposal Under the South Dakota Waste Management Program issued by the Department of Environment and Natural Resources.

The waste disposal site(s) will not be located in a wetland, within 200 feet of surface water, or in an area that adversely affects wildlife, recreation, aesthetic value of an area, or any threatened or endangered species, as approved by the Environmental Office and the Project Engineer.

If the waste disposal site(s) is located such that it is within view of any ROW, the following additional requirements will apply:

1. Construction and/or demolition debris consisting of concrete, asphalt concrete, or other similar materials will be buried in a trench separate from wood debris. The final cover over the construction and/or demolition debris will consist of a minimum of 1 foot of soil capable of supporting vegetation. Waste disposal sites provided outside of the Public ROW will be seeded in accordance with Natural Resources Conservation Service recommendations. The seeding recommendations may be obtained through the appropriate County NRCS Office. The Contractor will control the access to waste disposal sites not within the Public ROW with fences, gates, and placement of a sign or signs at the entrance to the site stating, "No Dumping Allowed".

2. Concrete and asphalt concrete debris may be stockpiled within view of the ROW for a period not to exceed the duration of the project. Prior to project completion, the waste will be removed from view of the ROW or buried, and the waste disposal site reclaimed as noted above.

The above requirements will not apply to waste disposal sites that are covered by an individual solid waste permit as specified in SDCL 34A-6-58, SDCL 34A-6-1.13, and ARSD 74:27:10:06. Failure to comply with the requirements stated above may result in civil penalties in accordance with South Dakota Solid Waste Law, SDCL 34A-6-1.31.

All costs associated with furnishing waste disposal site(s), disposing of waste, maintaining control of access (fence, gates, and signs), and reclamation of the waste disposal site(s) will be incidental to the various contract items.



**COMMITMENT I: HISTORIC PRESERVATION OFFICE CLEARANCES**

State Historic Preservation Office (SHPO or THPO) concurrence has not been obtained for this project.

**Action Taken/Required:**

All earth disturbing activities require a cultural resource review prior to scheduling the pre-construction meeting. This work includes but is not limited to: Contractor furnished material sources, material processing sites, stockpile sites, storage areas, plant sites, and waste areas.

The Contractor will arrange and pay for a record search and when necessary, a cultural resource survey. The Contractor has the option to contact the state Archaeological Research Center (ARC) at 605-394-1936 or another qualified archaeologist, to obtain either a records search or a cultural resources survey. A record search might be sufficient for review if the site was previously surveyed; however, a cultural resources survey may need to be conducted by a qualified archaeologist.

The Contractor will provide ARC with the following: a topographical map or aerial view in which the site is clearly outlined, site dimensions, project number, and PCN. If applicable, provide evidence that the site has been previously disturbed by farming, mining, or construction activities with a landowner statement that artifacts have not been found on the site.

The Contractor will submit the cultural resources survey report to SDDOT Environmental Office, 700 East Broadway Avenue, Pierre, SD 57501-2586. SDDOT will submit the information to the appropriate SHPO/THPO. Allow **30 Days** from the date this information is submitted to the Environmental Engineer for SHPO/THPO review.


In the event of an inadvertent discovery of human remains, funerary objects, or if evidence of cultural resources is identified during project construction activities, then such activities within 100 feet of the inadvertent discovery will immediately cease and the Project Engineer will be immediately notified. The Project Engineer will contact the SDDOT Environmental Office, who will contact the appropriate SHPO/THPO within 48 hours of the discovery to determine an appropriate course of action.

The Contractor is responsible for obtaining any additional permits and clearances for Contractor furnished material sources, material processing sites, stockpile sites, storage areas, plant sites, and waste areas that affect wetlands, threatened and endangered species, or waterways. The Contractor will not utilize a site known or suspected of having contaminated soil or water. The Contractor will provide the required permits and clearances to the Project Engineer at the preconstruction meeting.

**RETAINING WALL REPAIR AREA**



**ORIGINAL RETAINING WALL DETAIL**



UTILITIES

The Contractor will contact the involved utility companies through South Dakota One Call (1-800-781-7474) prior to starting work. It will be the responsibility of the Contractor to coordinate work with the utility owners to avoid damage to existing facilities.

If utilities are identified near the improvement area through the SD One Call Process as required by South Dakota Codified Law 49-7A and Administrative Rule Article 20:25, the Contractor will contact the Project Engineer to determine modifications that will be necessary to avoid utility impacts.

TABLE OF SIDEWALK REMOVAL

Station	to	Station	L/R	Quantity (SqYd)
16+94		17+04	R	4.7
Total:				4.7

INCIDENTAL WORK (Attach Timber to top of Concrete Wall)

The Contractor will attach the timber to the top of the concrete retaining wall with a new steel angle bracket. The new steel angle bracket will be placed on top of the wall and attached to the side of the timber.

The new steel angle bracket will match the existing steel brackets color, thickness, length, width, bolt pattern and shape. Lag Bolts, Bolts, Nuts, Washers, and Concrete Anchors will match existing for attachment of the new steel angle bracket.

All costs associated with this work will be incidental to the contract unit price per lump sum for “Incidental Work”.

CONTROLLED DENSITY FILL (RETAINING WALL BACKFILL REPAIR)

The Contractor will provide a means of containing the Controlled Density Fill at the base of the timber, where the granular backfill material is spilling out of the gaps between the timber and concrete walls. Aggregate larger than the gap at the base of the timber may need to be added to plug and keep the controlled density fill contained behind the timber during placement.

Controlled Density Fill will be done to fill voids behind the wall due to loss of granular backfill material through the gap between the concrete walls and the timber. Placement of Controlled Density Fill should start at or near the bottom and proceed upward to fill the void.

All costs associated with this work will be incidental to the contract unit price per cubic yard for “Controlled Density Fill”.

TABLE OF 4” CONCRETE SIDEWALK

Station	to	Station	L/R	Quantity (SqFt)
16+94		17+04	R	42.4
Total:				42.4



SEQUENCE OF OPERATIONS

Contractor requests to deviate from the sequence of operations will be submitted in writing to the Engineer for review. Approval of an alternate sequence of operations will only be allowed when the proposed changes meet with the Department’s intent for traffic control and sequencing of the work. An alternate sequence will be submitted for review a minimum of one week prior to potential implementation.

RETAINING WALL REPAIR

- 1. Install temporary pedestrian detour.
- 2. Remove existing fence for reset.
- 3. Remove sidewalk.
- 4. Install new steel bracket to connect the timber to the top of the wall.
- 5. Fill void behind timber with Controlled Density Fill
- 6. Place concrete sidewalk.
- 7. Reset fence.
- 8. Remove temporary pedestrian detour

GENERAL TRAFFIC CONTROL

Existing guide, route, informational logo, regulatory, and warning signs will be temporarily reset and maintained during construction. Removing, relocating, covering, salvaging, and resetting of existing traffic control devices, including delineation, will be the responsibility of the Contractor. Cost for this work will be incidental to the contract unit prices for the various items unless otherwise specified in the plans. Any delineators and signs damaged or lost will be replaced by the Contractor at no cost to the State.

All temporary traffic control sign locations will be set in the field by the Contractor and verified by the Engineer prior to installation.

Portable sign supports will not be located on sidewalks, bicycle facilities, or other areas designated for pedestrian or bicycle traffic.

All construction operations will be conducted in the general direction of traffic movement.

If there is a discrepancy between the traffic control plans, standard plates, and the MUTCD, whichever is more stringent will be used, as determined by the Engineer.

Unless otherwise stated in these plans, work will not be allowed during hours of darkness.

Fixed location signing placed more than 4 calendar days prior to the start of construction will be covered or laid down until the time of construction. The covers must be approved by the Engineer prior to installation. The cost of materials, labor, and equipment necessary to complete this work will be incidental to other contract items. No separate payment will be made.

All fixed location signs, sign posts, and breakaway bases will be removed within 7 calendar days following pavement marking.

The Contractor will notify businesses/homeowners a minimum of two weeks prior to construction to inform them of upcoming construction and again a minimum of 48 hours prior to any blocked access to make appropriate arrangements.

When blocking off 3 or more parking spaces on the road in order to provide a work area. The Contractor will need to work with City of Lead to let them know when this will happen. The Contractor will be limited to 5 parking stalls to be closed/used for work immediately adjacent to the work area.

TABLE OF TRAFFIC CONTROL DEVICES

ITEMIZED LIST FOR TRAFFIC CONTROL SIGNS

SIGN CODE	SIGN DESCRIPTION	CONVENTIONAL ROAD			
		NUMBER	SIGN SIZE	SQFT PER SIGN	SQFT
R9-9	SIDEWALK CLOSED	2	24" x 12"	2.0	4.0
R9-11	SIDEWALK CLOSED AHEAD (ARROW L or R) CROSS HERE	2	24" x 18"	3.0	6.0
W20-1	ROAD WORK AHEAD	2	48" x 48"	16.0	32.0
W21-5	SHOULDER WORK	2	48" x 48"	16.0	32.0
G20-2	END ROAD WORK	2	36" x 18"	4.5	9.0
		CONVENTIONAL ROAD TRAFFIC CONTROL SIGNS SQFT			
		83.0			

TEMPORARY PEDESTRIAN ACCESS ROUTE

A Temporary Pedestrian Access Route (TPAR) will be provided when crosswalks, sidewalks, or other pedestrian facilities are blocked, closed, or relocated. A TPAR may consist of a combination of existing and/or temporary pedestrian facilities. The TPAR will be kept free of any obstructions and hazards, such as holes, debris, mud, snow, construction equipment, traffic control signing, stored materials, etc.

The Contractor will notify the Engineer at least 72 hours prior to start of any construction operation that will necessitate a change in pedestrian access. Pedestrian traffic signal displays controlling a crosswalk that is closed will be covered or removed.

LONGITUDINAL PEDESTRIAN BARRICADE

Longitudinal pedestrian barricades should not be used to provide positive protection for pedestrians.


To prevent any tripping hazard to pedestrians, ballast will be located behind or internal to the device.

When longitudinal pedestrian barricades are combined in a series, the maximum gap between devices that do not interlock will be one inch. Joints between devices that do interlock will be closed and flush to prevent canes or small wheels from being trapped and to facilitate safe hand trailing. When used as a sidewalk closure mechanism, longitudinal pedestrian barricade must run the entire width of the sidewalk. Longitudinal pedestrian barricade should provide a color contrasting pattern. Black should not be used to color any base on a device. The devices should comply with the general color and stripe pattern requirements of Section 6F.68 of the MUTCD.

Longitudinal pedestrian barricade will have continuous bottom and top surfaces. The top surface will be smooth to allow safe hand trailing. Both upper and lower surfaces will share a common vertical plane.

All costs will be incidental to the contract unit price per foot for “Longitudinal Pedestrian Barricade”.

PEDESTRIAN CHANNELIZING DEVICE DETAILS



- 1. Barricade rail supports may not extend into the pedestrian walkway more than 4 inches from the face of the barricade.
- 2. The top edge of the bottom portion will be a minimum of 8 inches above the walkway.
- 3. Devices will not block water drainage from the walkway. A gap height or opening from the walkway surface up to a maximum of 2 inches in height is allowed for drainage purposes.
- 4. The top edge of the longitudinal pedestrian barricade is to be used as a guiderail to provide visual and tactile guidance to pedestrians along a designated route. The top surface should have a minimum width of 0.5 inches to allow the hand to feel the surface. The surface should be smooth and free of any sharp or abrasive elements to allow safe hand trailing.
- 5. Longitudinal pedestrian barrier used to provide positive protection from traffic to pedestrians should be crashworthy.

Plot Scale - 1"=40'

Plotted From - TRR011951

File - ...plan.dgn

16+94 to 17+04 R  
Remove sidewalk

16+96 R to 17+04 R  
Remove Fence for Reset - 8'  
Reset Fence - 8'


16+94 R  
Attach Timber to Top of Concrete Retaining Wall  
with New Steel Bracket  
Incidental Work

16+94 R  
Install cellular grout to  
plug and fill void between  
timber and concrete retaining  
wall

16+94 to 17+04 R  
Install 4" concrete sidewalk

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	085-451	6	10

Plotting Date: 06/16/2021



Remove and Replace Concrete Sidewalk



# TRAFFIC CONTROL LAYOUT

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	085-451	7	10

Plotting Date: 04/26/2021



 - WORK AREA


Plot Scale - 1:40


Plotted From - TRR014610

File - ...lto plan.dgn







 Longitudinal Pedestrian Barricade





STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	085-451	9	10

Plotting Date: 04/26/2021





Plot Scale - 1:200

Plotted From - TRRC-1610

STATE OF SOUTH DAKOTA	PROJECT	SHEET	TOTAL SHEETS
	085-451	10	10

Plotting Date: 04/26/2021



File - ...162e Stdplates.dgn