

| TYPE B CONCRETE CURB | | | | | | |
|----------------------|---------------|---------------|----------------------------|----------------------------|--|--|
| Туре | H (Inches) | W (Inches) | Cu. Yd. Per Lin. Ft. | Lin. Ft. Per Cu. Yd. | | |
| B6 | 6 | 8 | 0.0353 | 28.4 | | |
| B7 | 7 | 8 % | 0.0383 | 26.1 | | |
| B8 | 8 | 8% | 0.0414 | 24.1 | | |
| B9 | 9 | 9 | 0.0449 | 22.3 | | |
| B10 | 10 | 9 % | 0.0485 | 20.6 | | |

GENERAL NOTES:

The concrete for the type B concrete curb will comply with the requirements of the specifications for class M6 concrete.

A $\frac{1}{2}$ " preformed expansion joint filler will be placed transversely in the curb at the following locations:

- 1. At each junction between the radius return of curb and curb which is parallel to the project centerline.
- 2. At each junction between the existing curb and new curb or curb and gutter.
- 3. At each junction between the curb and existing sidewalk to the depth of the sidewalk.

See standard plate 650.90 for contraction joints in the curb.

| | | | December 23, 2019 |
|----------------------|-------------|----------------------|------------------------|
| | S D D | TYPE B CONCRETE CURB | plate number 650.02 |
| Published Date: 2024 | 0 T | | Sheet I of I |