

# WOLMANIZED® WOOD END CUT SOLUTION

With Brown Color Additive  
For Exterior Use Only



Wood Treated Right™

From the  
Wolmanized®  
wood family  
of products



EPA Reg. No. 1022-518-75506  
IBD-PL-302

EPA Est. No. 1022-TN-1  
3/07

1 Gallon (3.785 liters)

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

**KEEP OUT OF REACH OF CHILDREN  
DANGER**

#### FIRST AID

<b>IF IN EYES:</b>	<ul style="list-style-type: none"> <li>• Hold eye open and rinse slowly and gently with water for 15-20 minutes.</li> <li>• Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.</li> <li>• Call a Poison Control Center or doctor for treatment advice.</li> </ul>
<b>IF INHALED:</b>	<ul style="list-style-type: none"> <li>• Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.</li> <li>• Call a Poison Control Center or doctor for treatment advice.</li> </ul>

In case of emergency, call Arch Chemical Emergency Action Network at 1-800-654-6911.  
Have the product container or label with you when calling a Poison Control Center or doctor, or going for treatment.


## DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Use only the application method specified for a particular use.

Wolmanized End Cut Solution is a multi-purpose, water-based exterior wood preservative and insecticide pre-treatment for below ground, ground contact, fresh water contact and above ground applications where either pressure-treated or non-pressure-treated wood has been used. When applied as directed, this product provides protection against attack from termites and other wood boring insects and decay fungi, including mildew, mold, rot and decay organisms. It also controls warping, swelling and end checking due to its anti-wicking property, which resists moisture absorption and movement from end to end. This preservative will impart a color to wood that will fade over time, but if undesirable, can be top-coated with paint or stain.

Wolmanized End Cut Solution requires no dilution before use. Use as received, following label directions.

Wood treated with this preservative should not be used where it may come in contact with food, feed or potable water.



**RECOMMENDED USES:** Landscape timbers, railroad ties, fence posts, poles, pickets and rails, construction posts, foundation sills, steps, stairs, porches, siding, millwork, shakes, shingles, roofs, windows, window frames, doors, docks, piers, boats or other non-pressure-treated exterior wood exposed to moisture, weather or wood destroying insects. Also recommended for pressure-treated wood end cut protection, especially on decks. Since Wolmanized End Cut Solution has very low phytotoxicity, it can be used to treat wood for greenhouses, nursery flats, etc. Pretreatment only. Do not apply at sites on or near water or wetlands.

Powder post beetles which invade structural lumber are killed by application of this preservative. These insects will not attack the treated wood. Wood to be protected against subterranean termites should be treated before use in construction. Termites will not attack wood treated with this preservative.

In addition to preventing decay, blue stain, and insect attack on wood, Wolmanized End Cut Solution controls warping, swelling, shrinking and end-checking caused by changes in moisture content of lumber and plywood products.

**BEFORE YOU START:** Make sure wood is dry and free of dust, dirt and debris. Stir or shake well before using. **IMPORTANT:** This product has a color that slowly fades with time, but can be stained or painted after 24 hours, or re-applied at any time. Always test in an inconspicuous area for color satisfaction.

**APPLICATION PROCEDURES:** For best results, apply when outside temperatures are between 50°F and 90°F, and when 24 hours of precipitation-free weather is expected. Apply by dip treatment, brush, roller or pump sprayer.

**Below Ground, Ground or Fresh Water Contact:**

Seasoned (weathered) or green (new) wood may be treated. Make certain the wood is free of bark, then immerse in Wolmanized End Cut Solution for 12 to 48 hours or until the sapwood is completely penetrated. If dipping is not possible, 2 brush coats, roller or spray applications should be applied. Allow at least 1 hour between applications. Make certain all areas are fully treated to get the maximum benefits. Allow wood to dry for 24 hours before installation.

**Above Ground Contact:**

The best results will be obtained if wood to be treated is immersed for 3 minutes or longer. If dipping is not possible, 2 brush coats, roller or spray applications should be applied. Allow at least 1 hour between applications. Make certain all areas are fully treated to get the maximum benefits. Allow 24 hours or longer after application of the preservative prior to installation, painting and/or staining.

**COVERAGE:** One gallon covers 100 – 300 sq ft (9 – 28 m<sup>2</sup>), depending upon the wood age and species, surface porosity and method of application. One quart covers 40 – 50 sq. ft. (4 – 5 m<sup>2</sup>).

**CLEAN-UP:** Clean tools and equipment after use with soap and water.

**Brush-on preservative especially formulated for the coating of freshly sawn ends of pressure-treated Outdoor® Wood.**

### STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

**PESTICIDE STORAGE:** Store in a secure, well-ventilated area protected from extreme temperatures. Do not transfer to unmarked containers. Keep container closed when not in use.

**DISPOSAL: If Empty:** Do not reuse this container. Place in trash or offer for recycling if available. **If Partially Filled:** Call your local solid waste agency or 1-800-CLEANUP for disposal instructions. Never place unused product down any indoor or outdoor drain.

**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

**DANGER**

Causes irreversible eye damage. Do not get in eyes, on skin or on clothing. Wear goggles or face shield.

Harmful if inhaled. Avoid breathing spray mist.


Wash thoroughly with soap and water after handling.

Remove contaminated clothing and wash before reuse.

Do not breathe vapors or mist during brush, roll, spray, and dip applications. Wear a NIOSH/MSHA-approved mist/vapor respirator when spraying for continued or prolonged use of this product or for frequent use of the product.

In case of medical questions, emergencies, or accidents involving this product, call Arch Chemical Emergency Action Network at 1-800-654-6911.

Application of this product may produce strong, lingering, unpleasant odor.



**ENVIRONMENTAL HAZARDS**

This product is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or public waters unless in accordance with the requirements of a National Pollutant Discharge Elimination system (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

**PHYSICAL AND CHEMICAL HAZARDS**

Do not use or store near heat or open flame.

**Ingredient Statement**

ACTIVE INGREDIENT:	
Copper Naphthenate .....	9.08%*
INERT INGREDIENTS: .....	90.92%
TOTAL: .....	100.00%

\*Equivalent to 1% metallic copper.

This product weighs approximately 8.5 lbs. per gallon.

**Volatile Organic Compounds <350 gm/liter  
VOS (excluding water) <0.35 kg/liter**

**LIMITED WARRANTY:** Arch Treatment Technologies, Inc. will refund the purchase price to the original consumer if within one year this product is shown to be defective. Notify Arch Treatment Technologies, Inc., 1955 Lake Park Drive, Suite 100, Smyrna, GA 30080, within sixty (60) days of learning of defect. ARCH TREATMENT TECHNOLOGIES, INC. MAKES NO FURTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY WHICH EXTEND BEYOND THE DURATION OF THIS WRITTEN WARRANTY. Arch Treatment Technologies, Inc. shall not be liable for any incidental or consequential damages. Some states do not allow limitations on how long any implied warranty lasts and/or limitation of incidental or consequential damages, so the above limitation and exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

DISTRIBUTED BY:

**Arch Treatment Technologies, Inc.**  
1955 Lake Park Drive, Suite 100 • Smyrna, GA 30080  
770-801-6600