

airkem
brand

SANI-TEX®

Carpet Sanitizing Cleaner

ACTIVE INGREDIENTS:
 Octyl decyl dimethyl ammonium chloride 0.60%
 Dioctyl dimethyl ammonium chloride 0.24%
 Didecyl dimethyl ammonium chloride 0.36%
 Alkyl (C₁₄, 50%; C₁₂, 40%; C₁₆, 10%)
 dimethyl benzyl ammonium chloride 0.80%
INERT INGREDIENTS: 98.00%

**KEEP OUT OF REACH OF CHILDREN
DANGER**

See side panel for additional precautionary statements.

ECOLAB® *Net Contents:
1 U.S. gal/3.78 L*

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER
 Keep out of reach of children. Corrosive. Causes eye and skin damage. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed or absorbed through skin. Avoid contamination of food.

STATEMENT OF PRACTICAL TREATMENT
 In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse.

If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution; or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measure against circulatory shock, respiratory depression, and convulsion may be needed.

STORAGE AND DISPOSAL
 Do not contaminate water, food, or feed by storage or disposal. Do not store on side. Avoid creasing or impacting of side walls.

CONTAINER DISPOSAL: Do not reuse empty container. Wrap container and put in trash.

EPA Registration No. 6836-108-42964
 EPA Est. 303-IN-1 (L), 1677-IL-2 (J), 1677-MN-1 (P), 1677-CA-1 (S), 1677-NJ-1 (W),
 1677-PR-1 (B), 1677-TX-1 (D), 1677-OH-1 (H), 1677-GA-1 (M), 1677-CA-2 (R),
 1677-WV-1 (V).
 Superscript refers to first letter of date code.

airkem
brand

SANI-TEX®

Carpet Sanitizing Cleaner

ACTIVE INGREDIENTS:
 Octyl decyl dimethyl ammonium chloride 0.60%
 Dioctyl dimethyl ammonium chloride 0.24%
 Didecyl dimethyl ammonium chloride 0.36%
 Alkyl (C₁₄, 50%; C₁₂, 40%; C₁₆, 10%)
 dimethyl benzyl ammonium chloride 0.80%
INERT INGREDIENTS: 98.00%

**KEEP OUT OF REACH OF CHILDREN
DANGER**

See side panel for additional precautionary statements.

ECOLAB® *Net Contents:
1 U.S. gal/3.78 L*

FOR HOSPITAL, INSTITUTIONAL AND INDUSTRIAL USE

Sani-Tex should be an integral part of any carpet maintenance system. Routine application will not only clean the carpets, but sanitize and deodorize for a cleaner, longer lasting carpet. *Sani-Tex* is a low foaming carpet shampoo formulated for use with extraction and carpet steam cleaning equipment. *Sani-Tex* contains "twin chain" quaternary ammonium compounds to reduce and control the growth of gram negative and gram positive odor causing bacteria. *Sani-Tex* is fortified with odor counteractants to neutralize malodors. Optimized for use on commercial washable synthetic fibers, but not recommended for use on wool carpets. *Sani-Tex* effectively and economically lifts and removes greasy soil, resists resoling and utilizes "built-in" defoamers for more productive use.

DIRECTIONS FOR USE:
 It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

To Clean, Sanitize, and Deodorize Carpets:
Steam Extraction: Vacuum carpet thoroughly. Mix two (2) ounces of *Sani-Tex* per gallon of water. Inject and extract as you would any steam cleaning shampoo.

Spin Bonnet (Bonnet Buff) Cleaning: Vacuum carpet thoroughly. Mix four (4) ounces of *Sani-Tex* per gallon of water. Bonnet on carpet at rate of 200-300 sq. ft. per gallon.

Heavy Duty Spin Bonnet (Bonnet Buff) Cleaning: Vacuum carpet thoroughly. Mix sixteen (16) ounces of *Sani-Tex* per gallon of water. Spray on carpet at rate of 200-300 sq. ft. per gallon. NOTE: Test color fastness of carpet before use. Apply diluted cleaner to a small concealed spot, then rub with clean white cloth. If color transfers to cloth or changes, a water-based product should not be used.

NOTE: Not recommended for use on Stain-Resistant Nylon Carpets. Consult carpet manufacturer's warranty and maintenance instructions for proper use.

After cleaning, set carpet pile in one direction with a stiff brush (carpet pilator). Place aluminum foil under legs of furniture while carpet is drying. Over-wetting can cause shrinkage of carpet. Manufacturer assumes no responsibility for over-wetting or misuse.

Distributed by:
 Airkem Professional Products, Division of Ecolab Inc.
 370 Wabasha Street N., St. Paul, MN 55102
 © 2002 Ecolab Inc. Made in U.S.A. 784272/8906/1202
 All Rights Reserved.

1 gallon sleeve dieline/Gen Spec #570705

master: ppd #570705 784272/89 colors: pms 227 red, black
 label type: poly sleeve